


True Vertical Depth Log


Longtom-4 P LWD RM 500TVD

ECO6 id13_0c_02

Format: EcoScope RM Log TVD Vertical Scale: 1:500 Graphics File Created: 26-Jul-2008 20:14

Rate of Penetration, Averaged over Last 5ft (ROP5_RM) 200 (M/HR) 0	ARC Phase Shift Resistivity 40 inch at 2 MHz (P40H) 0.2 (OHMM) 2000	
Ultrasonic Caliper, Vertical Diameter (UCVE) 6 (IN) 16	ARC Phase Shift Resistivity 34 inch at 2 MHz (P34H) 0.2 (OHMM) 2000	Photoelectric Factor, Bottom (PEB) 0 (----) 10
Ultrasonic Caliper, Horizontal Diameter (UCHO) 6 (IN) 16	ARC Phase Shift Resistivity 28 inch at 2 MHz (P28H) 0.2 (OHMM) 2000	Bulk Density Correction, Bottom (DRHB) -0.25 (G/C3) 0.25
Time after BIT (between drilling and measurement) (TAB_DEN) 0 (HR) 10	ARC Phase Shift Resistivity 22 inch at 2 MHz (P22H) 0.2 (OHMM) 2000	Thermal Neutron Porosity (Ratio Method) in Selected Lithology (TNPH) 45 (PU) -15
Gamma Ray, Average (GRMA) 0 (GAPI) 200	ARC Phase Shift Resistivity 16 inch at 2 MHz (P16H) 0.2 (OHMM) 2000	Bulk Density, Bottom (ROBB) 1.85 (G/C3) 2.85
	Collar Rotational Speed (CRPM) (RPM) 0 200	





IDEAL Version: ID13_OC_08
IDF

ECO6

id13_oc_02

True Vertical Depth Log

