

True Vertical Depth Log

Longtom-4 H LWD RM 500TVD

FIELD PRINT

Format: EcoScope RM Log TVD

Vertical Scale: 1:500

Graphics File Created: 06-Aug-2008 17:14

Rate of Penetration, Averaged over Last
5ft (ROP5_RM)

200 (M/HR) 0

Ultrasonic Caliper, Vertical Diameter
(UCVE)
6 (IN) 16

Ultrasonic Caliper, Horizontal Diameter
(UCHO)
6 (IN) 16

Time after BIT (between drilling and
measurement) (TAB_DEN)
0 (HR) 10

Gamma Ray, Average (GRMA)
0 (GAPI) 200

Collar
Rotational
Speed
(CRPM)
(RPM)
0 200

ARC Phase Shift Resistivity 40 inch at 2
MHz (P40H)

0.2 (OHMM) 2000

ARC Phase Shift Resistivity 34 inch at 2
MHz (P34H)

0.2 (OHMM) 2000

ARC Phase Shift Resistivity 28 inch at 2
MHz (P28H)

0.2 (OHMM) 2000

ARC Phase Shift Resistivity 22 inch at 2
MHz (P22H)

0.2 (OHMM) 2000

ARC Phase Shift Resistivity 16 inch at 2
MHz (P16H)

0.2 (OHMM) 2000

Photoelectric Factor, Bottom (PEB)
0 (----) 10

Bulk Density Correction, Bottom
(DRHB)
-0.25 (G/C3) 0.25

Thermal Neutron Porosity (Ratio
Method) in Selected Lithology (TNPH)
45 (PU) -15

Bulk Density, Bottom (ROBB)
1.85 (G/C3) 2.85





