



**CORE LABORATORIES
AUSTRALIA PTY LTD**

***Routine Core Analysis
Well Pecten East - 1***

Australia

Prepared for
Santos Ltd.

April 2009

File: PRP-08055

Rock Properties
Core Laboratories
Perth
Australia



CORE LABORATORIES AUSTRALIA PTY LTD

6th April 2009

Santos Ltd.

Level 3
60 Flinders Street.
Adelaide, SA 5000

Attention : David Schubert

Subject : Routine Core Analysis
Well : Pecten East - 1
File : PRP-08055

Dear David,

Presented herein is the final report of a routine core analysis study conducted on selected MSCT samples from the above well that arrived at our laboratory in September 2008.

We appreciate the opportunity to present this service to Santos Ltd. Please contact us should you require any further information or assistance.

Yours sincerely,

Core Laboratories Australia Pty Ltd

James Brown
Senior Core Analyst

TABLE OF CONTENTS

Introduction	Page 1
Summary	Page 2
Laboratory Procedures	
Initial Inventory	Page 3
Sample Preparation	Page 3
Grain Volume and Grain Density	Page 3
Porosity and Permeability	Page 3
Tabular Data	
MSCT Porosity, Permeability and Grain Density	Page 4

INTRODUCTION

The MSCT samples arrived at our laboratory in September 2008.

Services performed and presented in the report include:

- Horizontal permeability, porosity, (ambient) and grain density measurements on MSCT samples
- Photography

The reported data for the above services are presented digitally on a CD-Rom, with the exception of the photography which was sent under a separate cover.

SUMMARY

Porosity and permeability measurements on nine samples, were determined at a net confining stress of 800 psi (Ambient). Grain density was also measured on the samples.

	<u>Minimum</u>	<u>Maximum</u>	<u>Average</u>
<u>MSCT</u>			
<u>Net Confining Pressure of 800psig.</u>			
Porosity (%)	14.6	23.2	18.9
Permeability, Kair, (md)	0.656	160	34.7
Grain Density (g/cc)	2.623	2.667	2.647

LABORATORY PROCEDURES

Initial Inventory:

All sample bottles were laid out in order, and an in-house inventory was made of the nine samples. Each sample was examined for their suitability for analysis. Initially the samples were photographed under white light, then prepared for porosity, permeability and grain density measurements.

Sample Preparation:

The selected samples were cleaned to remove mud solids, trimmed using a 2% potassium chloride brine, then cleaned of residual salts by using cool methanol. After cleaning, the samples were dried in a controlled humidity oven.

Grain Volume and Grain Density:

The weight, diameter and length of all samples were measured before they were processed through the Ultrapore™ porosimeter to determine grain volume. As a standard quality control measure, a calibration check plug was run with the samples. Grain density data was calculated from grain volume and sample weight data.

Porosity and Permeability:

The samples were run at the confining stress of 800psi (ambient) while determining porosity and permeability. A standard check plug was run with every set of samples. Klinkenberg permeability (K_{inf}) values are obtained directly from the CMS™300, since it operates by unsteady-state principles. Porosity data was obtained by combining pore volumes from the CMS™300 data with grain volumes from the Ultrapore porosimeter.

MSCT POROSITY, PERMEABILITY AND GRAIN DENSITY

SAMPLE NUMBER	DEPTH (m)	CMS 300 CONFINING STRESS 800psi.			GRAIN DENSITY (g/cc)	COMMENTS
		PERMEABILITY		POROSITY		
		Kinf (md)	Kair (md)	(%)		
4	1929.50	42.4	49.5	19.0	2.635	
5	1925.25	102	160	22.2	2.623	
6	1920.50	0.763	1.07	16.0	2.633	
7	1917.50	16.4	18.8	18.7	2.649	
8	1913.00	0.862	1.20	16.9	2.655	
10	1906.50	2.19	2.78	17.5	2.642	
11	1903.00	34.1	37.4	23.2	2.654	
13	1899.00	0.456	0.656	14.6	2.667	
14	1895.50	37.3	40.7	22.0	2.665	