

EXPLORATION LOGGING DRILLING RATE AND DATA <input checked="" type="checkbox"/> FT/HR <input type="checkbox"/> MIN/FT VISUAL POROSITY CORE TEST GO. FAIR TR.	DEPTH TEST	LITHOLOGY	OIL TRACE GD. TRACE FAIR GOOD V. GOOD	DRILLING MUD				CUTTINGS		REMARKS AND LITHOLOGY DESCRIPTION
				CONTINUOUS DITCH GAS		CHROMATOGRAPHIC ANALYSIS		GAS		
				OIL IN MUD TR. X FAIR XX GD. XXX	TOTAL GAS (BACKUP SCALE - 10X) PETROL VAP	METHANE ETHANE PROPANE	BUTANES PENTANES M-1000	TOTAL GAS (BACKUP SCALE - 10X) PETROL VAP SHALE DENSITY	DENSITY	
200 150 100 50 	9200	SANDSTONE, CLEAR TO CLOUDY, COARSE GRAIN, PYRITIC; SMALL AMOUNT SHALE, LIGHT GREY, FIRM, GLAUCONITIC						2.2 2.8	W 9.7 V 32 FL 10.2 FC 2/32 PH 9.5 CL- 1100PPM DEPT. NAT. RES & ENV PE603702	
	9300	SANDSTONE, AS ABOVE AND INTERBEDDED LIGHT GREY, MEDIUM GRAIN, FRIABLE SANDSTONE							W 9.9 V 40	
	9400	SANDSTONE, COARSE GRAIN LOOSE, AS ABOVE & SANDSTONE, MEDIUM GRAIN & FRIABLE, AS ABOVE							V 40	
NB# 8 HIC HMG 227FT 11MR	9500	SHALE, LIGHT GREY, FIRM CALCAREOUS, INTERBED W/MEDIUM GRAIN, PYRITE GLAUCONITIC, GREENISH SANDSTONE, & COARSE, CLEAR-FROSTED QUARTZ SAND.								
	9600	SANDSTONE, MEDIUM TO COARSE, SUB-ROUNDED, QUARTZ, WELL SORTED, FINE-MEDIUM GRAIN GREEN SANDSTONE, GLAUCONITIC, FRIABLE, PYRITIC.							W 9.7 V 37 C = 21U AT 37V	