WOODSIDE (LAKES ENTRANCE) OIL COMPANY N.L.

PROGRESS WELL LOG — LITHOLOGIC DESCRIPTION

ELEV. K. B. + 16 FT. DATE 15th March LOGGED BY A.A.M. D.G.L.

WELL: DUTSON DOWNS No 1
SHEET No.: SEVEN
INTERVAL FROM 2180
TO 2540

DEPT. NAT. RES & ENV
PE604397

BIT CHANGES | DIP DATA | TESTS | CASINGS-PERFS PLUGS | SW CORES CORES | GRAPHIC LOG DEPTH SCALE 1 : 600 | DESCRIPTION OF SHOWS AND MUD LOSSES: OIL SHOW RATING, GAS SHOW, FLUORESCENCE, CUT, STAIN, EST. POROSITY | % LITHOLOGY: LIMESTONE, DOLOMITE, SANDSTONE, SHALE, CLAY (MARL), ANHYDRITE, COAL | LITHOLOGIC DESCRIPTION | FORMATION | AGE

DRILLING RATE (MIN/FT) 0 — 7

Bit No 5 Reed YT3A 8½"

2200 2250 2300 2350 2400 2450 2500

2294 2310 2354

Bit No 5 R.R

Coal

LIMESTONE	DOLOMITE	SANDSTONE	SHALE	CLAY (MARL)	ANHYDRITE	COAL
				100		
				100		
				100		
				100		
				100		
				100		
				100		
				100		
				100		
				100		
				100		
				100		
				100		
		80		20		
		100				
		100				
		100				
		100				
		100				
		100				
		20				80
		30				70
		20			30	50
		50			30	20
		100				
		100				
		100				
		100				
		100				
		100				
		100				
		20				80
						100
						100

2315–2395
SANDSTONE fine and medium sub rounded to rounded moderately well sorted slightly clayey quartz grains

2395–2900
SANDSTONE WITH INTERBEDDED BROWN COAL AND CLAY
SANDSTONE as above and becoming coarser grained in part. Also contain fine angular grains of clear quartz
CLAY brown, carbonaceous argillaceous

FORMATION: LAKES ENTRANCE FORM. / LATROBE VALLEY COAL MEASURES
AGE: OLIGOCENE / EOCENE