

WELL ELEMENTARY
REPORT

MIDFIELD-2

W413

MIDFIELD-2

ELEMENTARY
REPORT

W413

PE904152

This is an enclosure indicator page.
The enclosure PE904152 is enclosed within the
container PE906521 at this location in this
document.

The enclosure PE904152 has the following characteristics:

ITEM_BARCODE = PE904152
CONTAINER_BARCODE = PE906521
NAME = well card
BASIN = GIPPSLAND
PERMIT =
TYPE = WELL
SUBTYPE = WELL_CARD
DESCRIPTION = well card Midfield 2
REMARKS =
DATE_CREATED =
DATE_RECEIVED =
W_NO = W413
WELL_NAME = Midfield-2
CONTRACTOR = Midfield Co
CLIENT_OP_CO = Midfield Co

(Inserted by DNRE - Vic Govt Mines Dept)

Elevation 192'.

Surface to 15' - white sand

15' to 87' - conglomerate, yellowish gravel and clay

Casing 8" set at 87'

87' to 334' - bluish grey marl

334' " 406' - polyzoal lime

406' " 790' - marl, blue grey, very strong sticky

790' " 840' - marl, lighter blue grey, more pliable

Gas show.

840' to 1030' - micaceous clay

Gas very strong

1030' to 1100' - micaceous clay

1100' " 1101' - hard band 12"

1101' " 1113' - micaceous clay

1113' " 1114' - hard band 12"

1114' " 1123' - micaceous clay

1123' " 1124' - hard band 12"

1124' " 1140' - micaceous clay

1140' " 1141' - hard band 12"

1141' " 1166' - micaceous clay

1166' " 1167' - hard band

1167' " 1175' - micaceous clay

1175' " 1176' - hard band

1176' " 1210' - micaceous clay

1210' " 1211' - hard band

1211' " 1223' - micaceous clay

1223' " 1254' - hard band

Drilled to 1300 feet - water.

Abandoned.

Production nil.

Company	Well No.	Parish	Fluorite	Bedrock
Trujil No. S. Co.	1	Calypson	71' at 1290'	Granite at 1360'. About 10 gall. per day. Abandoned.
do.	2	do.	30' at 1280'	Bottomed at 1310'. About 10 gall. per day. Abandoned.
Midfield Co. or Glenwood South	1	do.	33' at 1272'	Bottomed at 1305'. Small quantity of oil. Abandoned
do.	2	do.	28' at 1280'	Bottomed at 1308'. Small quantity oil. Abandoned.
Mid West	1	do.	40' at 1280'	Granite at 1320'. Small quantity oil. Abandoned.
do.	2	do.		In progress
Lake View	1	do.	37' at 1170'	Metamorphic at 1207'. About 20 gall. per day. Abandoned.
do.	2	do.	39' at 1302'	Bottomed at 1341'. About 20 gall. per day. Abandoned.
do.	3	do.	30' at 1255'	Bottomed at 1285'. 20 gall. per day. Abandoned.
Oil Search	1	do.	25' at 1160'	About 20 gall. per day. No pump installed.
do.	2	do.	27' at 1155'	About 30 gall. per day. No pump installed.
Carpenter's	1	do.	36' at 1165'	No pump installed.
Texland	1	do.	29' at 1245'	No pump installed.

NOTE: Quantity of oil given by company;

Amount of water present in emulsion not given.

COPY

Midfield No 1/1
No 2

PARTICULARS TO 30/3/1931

	Expenditure in Victoria	Production in Barrels
	£	(Companies' figures)
South Aus. Oil Wells	50,000	10,000
Point Addis	10,000	500
Midfield	5,000	50
Tanjil and Tanjil No. 2	12,000	1,500
Lake View	6,000	50
Kalimna	7,000	50
Boola Boola	30,000	-
South Victoria (Lake Boga)	21,000	-
Mersey Valley	12,000	-
Torquay Oil Wells	5,000	-
Leongatha	2,500	-
Moutajup	2,000	-
Lakes Entrance Dev. Co.	5,000	-