

CHECKSHOT SURVEY STACK SUMMARY LISTING

Gun and Hydrophone Coordinates:

Gun Azimuth 115.0 DEG
 Gun Offset 45.0 M
 Gun Depth From Schlumberger Zero 30.0 M
 Hydrophone Depth From Schlumberger Zero 35.0 M
 SRD Depth From Schlumberger Zero 25.0 M

Other VSP constants:

True Vertical Time Correction YES
 Surface Velocity 1524.00 M/s

Stack number	Measured Depth (1) (M)	Measured Trans Time (MS)	True Vert. Depth from SRD (2) (M)	Corrected Trans Time (3) (MS)	Interval Velocity (4) (M/S)
32	781.5	345.33	756.3	351.55	1405.61
32	796.9	356.28	771.7	362.51	2840.64
31	881.6	386.07	856.4	392.32	2997.66
31	897.1	391.24	871.9	397.49	2722.76
29	981.5	422.22	956.3	428.49	3068.07
29	996.9	427.23	971.7	433.51	2951.39
28	1081.6	455.92	1056.4	462.20	3034.58
28	1097.0	460.99	1071.8	467.28	2378.50
30	1099.5	462.04	1074.3	468.33	3025.61
30	1114.9	467.13	1089.7	473.42	2994.02
27	1181.5	489.36	1156.3	495.66	2912.80
27	1196.9	494.65	1171.7	500.95	2798.72
26	1281.5	524.86	1256.3	531.17	3133.09
26	1297.0	529.81	1271.8	536.12	3093.13
25	1381.5	557.12	1356.2	563.43	2960.72
25	1396.9	562.32	1371.6	568.63	3072.79
24	1469.5	585.94	1444.2	592.26	2764.38
23	1481.5	590.28	1456.2	596.60	3565.21
24	1484.9	591.23	1459.6	597.55	2739.73
23	1496.9	595.61	1471.6	601.93	2865.01
22	1581.5	625.13	1556.2	631.46	3024.35
22	1597.0	630.26	1571.7	636.58	3040.17
21	1681.6	658.08	1656.3	664.41	3059.38
21	1697.0	663.11	1671.7	669.44	3034.86
20	1776.5	689.30	1751.2	695.63	3311.07
20	1791.9	693.95	1766.6	700.28	3387.08
19	1806.5	698.53	1781.2	704.59	2917.47
19	1821.9	703.99	1796.6	709.87	3107.68
18	1829.6	706.47	1804.3	712.35	3261.95
17	1836.5	708.59	1811.2	714.46	3178.85
18	1845.0	711.25	1819.7	717.13	3307.85
17	1851.9	713.32	1826.6	719.22	3322.63
16	1866.5	717.71	1841.2	723.61	3729.61
16	1881.9	721.83	1856.6	727.74	3435.49
15	1896.5	726.07	1871.2	731.99	3944.32
15	1911.9	729.97	1886.6	735.89	3550.37
14	1926.6	734.10	1901.3	740.03	3666.35
14	1942.0	738.30	1916.7	744.23	3724.42
13	1956.5	742.18	1931.1	748.12	3841.99
13	1972.0	746.21	1946.6	752.16	3722.62
12	1986.5	750.10	1961.1	756.05	3895.52
12	2001.8	754.02	1976.4	759.98	3573.81
11	2016.6	758.15	1991.2	764.12	3989.64
11	2032.0	762.00	2006.6	767.98	3252.21
10	2046.5	766.46	2021.1	772.44	4011.52
10	2061.9	770.29	2036.5	776.28	3984.87
9	2076.5	773.94	2051.1	779.94	3483.04
8	2091.4	778.22	2066.0	784.22	-2122.55
9	2091.9	777.98	2066.5	783.98	3375.65
7	2106.5	782.30	2081.1	788.31	-1069.19
8	2106.9	781.93	2081.5	787.93	3750.64
6	2121.5	785.81	2096.1	791.83	695.24
7	2121.9	786.39	2096.5	792.40	4967.52
5	2134.8	788.98	2109.4	795.00	2241.99
6	2136.9	789.91	2111.5	795.93	4111.61
5	2150.2	793.14	2124.8	799.17	0.00

- (1) Measured Depth is Cable Depth Referenced to Schlumberger Zero.
- (2) TVD is referenced to SRD (5)
- (3) Transit time with respect to SRD(5) corrected for Deviation.
- (4) Interval Velocity corrected for Deviation.
- (5) SRD is Seismic Reference Depth.