



Perch

11

Rm = 1.12 @ 68°
0.37 @ 208 = 2800 ppm

PERCH A-1
RUN - 3

INTERVAL	SP	R _{IL} "	R _{IL}	GR	CALIPER	DEN	DIN φ	Sonic	Sonic	Ave. φ	F	R _{wa}	R _o	R _o /R _o	Sw	Sol. in PPM
5652-75	36	5	5	56	15"	2.35	26%	86	25.5	26	11	.45	5	1	100	2250
5725-5802	20	8	12	52	17"	2.4	23	80	21.0	22	14	.75	12	1	100	
5862-5835	34	8	10	56	18"	2.35	24	82	22.5	24	13	.77	10	1	100	
6693-6210	16	9	12	52	17 1/2"	2.38	23.5	80	21.0	22.5	15	.86	12	1	100	
6348-6363	22	10	13	56	15 1/2"	2.37	25	78	17.5	22	16	.81	13	1	100	
6382-6430	16	12	14	48	16 1/2"	2.325	28	80	21	24.5	13	1.2	14	1	100	900
6430-6455	16	12	12	48	16 1/2"	2.4	23	8	21	22	16	.75	12	1	100	
6460-6515	16	10	15	48		2.45	20.5	8	21	21	17.5	.85	12	1	100	
6580-6638	14	15	25	44	16	2.38	23.5	76	18	21	17.5	1.43	25	1	100	700
6638-6762	12	12	15	44	15-17	2.33	27	76	18	22.5	15	1.0	15	1	100	
7306-7422	16	15	28	50	17	2.48	18	74	16	17	28	1.0	22	1	100	
7558-7612	14	13	27	54	18	2.44	17	75	17	17	28	.97	27	1	100	
7706-7770	14	20	35	54	18	2.48	18	70	13	15.5	34	1.03	35	1	100	
7770-7850	14	22	50	56	16	2.525	15	68	12	13.5	46	1.09	50	1	100	
7880-7890	6	23	45	64	15 3/4	2.5	16.6	73	16	16	32	1.4	45	1	100	
7920-7937	8	12	25	64	16 1/4	2.53	14.5	77	17	16	32	.78	25	1	100	
7942-8072	10	25	50	56	15	2.56	13	68	12.5	13	48	1.04	50	1	100	
8165-8135	6	20	45	50	15 1/2	2.53	14.5	70	16.5	15.5	34	1.47	45	1	100	675
8162-8182	4	15	35	52	15 1/2	2.52	15	74	16	15.5	34	1.03	35	1	100	
8225-8235	2	14	20	52	15 1/4	2.55	13.5	68	12.5	13	48	.42	20	1	100	
8252-8268	4	23	50	56	14	2.55	13.5	68	12.5	13	48	1.04	50	1	100	
8278-8312	6	25	50	56	14	2.56	13	67	11	12	58	.86	50	1	100	

= .225 = R_w (SP)