


Depth logged:	778.5 m To 3910.6 m	Mag decl:	10.27°	Other services: Dir. Surveys & Perf. Drilling
Date logged:	18-Oct-04 To 04-Nov-04	Mag dip:	-69.95°	

Bit Run Summary

Potassium	%	4.2	4.2	4.2	4.2						
Environmental data											
GR											
Mud weight	ppg	8.8	9.1	9.1	12.9						
Bit size	in	12.25	12.25	8.5	8.5						
Resistivity											
Neutron porosity											
Hole Size	in	12.25	12.25	8.5	8.5						
Mud weight	ppg	8.8	9.1	9.1	12.9						
Downhole Temperature	°C	43.0	57.0	61.0	104.0						
Mud salinity	ppm	42000	46000	42000	51000						
Formation salinity	ppm	N/A	N/A	N/A	N/A						
Recording rate 1	SEC	6	6	10	10	GR-APWD RES					
Recording rate 2	SEC	6	6	10	10						
Filtering GR		3-Point	3-point	3-point	3-point						
Filtering density		N/A	N/A	N/A	N/A						
Filtering Neutron		N/A	N/A	N/A	N/A						
Company representative		B. Houston	P. King	J.Young	R.Subramanian						
Anadrill personnel		A. DeCastro	D. Hastie	A. Ahmad	B. Manjenic						

DISCLAIMER THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.											
OTHER SERVICES FOR RUN1 Directional Surveys Performance Drilling Annular Pressure, ECD & Temperature Multi- Vibrational Chassis (MVC)			OTHER SERVICES FOR RUN2 Directional Surveys Performance Drilling Annular Pressure, ECD & Temperature Multi- Vibrational Chassis (MVC)			OTHER SERVICES FOR RUN3 Directional Surveys Annular Pressure, ECD & Temperature Multi- Vibrational Chassis (MVC)					
REMARKS: RUN NUMBER 1 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Drill 12-1/4" section to section TD. POOH: Change bit. Note: Excessive shocks affected resistivity and ECD measurements from 840-987m MD.			REMARKS: RUN NUMBER 2 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Continue drilling 12-1/4" section to section TD. POOH: Section TD.			REMARKS: RUN NUMBER 3 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Drill 8-1/2" section to well TD. POOH: Change bit.					

EQUIPMENT DESCRIPTION											
RUN1			RUN2			RUN3					
DOWNHOLE F			DOWNHOLE F			DOWNHOLE F					



DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN4 Directional Surveys Annular Pressure, ECD & Temperature Multi- Vibrational Chassis (MVC)	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 4 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Drill 8-1/2" section to well TD. POOH: Well TD. Zoned Parameters: 2662 - 3016 : Mud Weight 9.51 ppg. 3016 - 3318 : Mud Weight 10.52 ppg. 3318 - 3450 : Mud Weight 11.60 ppg. 3450 - 3652 : Mud Weight 12.10 ppg. 3652 - 3864 : Mud Weight 12.94 ppg. 3864 - 3914 : Mud Weight 13.94 ppg.	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

EQUIPMENT DESCRIPTION

RUN4	RUN	RUN
DOWNHOLE E PowerP s/n V8 software ver: D&I — 13.8 18.1		

RWA_RES_RM	Rwa computation resistivity input	1.000000	1.000000	1.000000	1.000000
RWS_RM	Resistivity of Connate Water (RM)	69.799980	69.799980	69.799980	69.799980
SHT_RM	Surface Hole Temperature (RM)	3248.031250	8366.141602	8733.595703	12841.207031
TD_RM	Total Measured Depth (RM)	75.000000	75.000000	75.000000	75.000000
TWS_RM	Temperature of Connate Water (RM)	0.500000	0.500000	0.500000	0.500000
VF_ILLI	Fraction of illite in shales	0.500000	0.500000	0.500000	0.500000
VF_KAOL	Fraction of kaolinite in shales	0.000000	0.000000	0.000000	0.000000
VF_MONT	Fraction of montmorillonite in shales	0.675000	0.675000	0.675000	0.675000
XPDM_RM	Cross plot density porosity multiplier	0.325000	0.325000	0.325000	0.325000
XPNM_RM	Cross plot neutron porosity multiplier	BS	BS	BS	BS
LWD_RM/STATION_FILE/	PARAMETERStation Time-frame file name	BS	BS	BS	BS
CDR					
CDR/ENV_SELECT/	PARAMETERCDR: Res. Env. Corr. selection	BS	BS	BS	BS
CDR/TF_FILE/	PARAMETERCDR: Time-frame file name	BS	BS	BS	BS
CDR/TF_TIME_OFFSET/	PARAMETERCDR Time-frame file time offset	-86400.000000	-86400.000000	0.000000	0.000000
COLS	Gamma Ray Collar thickness	CDR_9_50	CDR_9_50	CDR_6_75	CDR_6_75
DIRES_RM	CDR: Compute Dielectric Resistivity ?	NO	NO	NO	NO
FLBS	Fraction of Levels Less Than Bit Size	0.000000	0.000000	0.000000	0.000000
G3_OFF	CDR GRW3 offset	2.000000	2.000000	2.000000	2.000000
G4_OFF	CDR GRW4 offset	1.000000	1.000000	1.000000	1.000000
GTIK_SEL	CDR Generate Tick Channels	YES	YES	YES	YES
JSD_CDR	CDR Acquisition start date	YES	YES	YES	YES
NGT_RM	CDR: Compute NGT ?	NO	NO	NO	NO
PLATEAU	CDR: Plateau GR sensor	YES	YES	YES	YES
POCS_RM	CDR: Phase Offset Calculation	NO	NO	NO	NO
POMW_RM	CDR: Phase Offset at Start Depth	NO WRAP	NO WRAP	NO WRAP	NO WRAP
PUDT_RM	CDR: Phase Unwrapping Lower Threshold	-180.000000	-180.000000	-180.000000	-180.000000
PUUT_RM	CDR: Phase Unwrapping Upper Threshold	180.000000	180.000000	180.000000	180.000000
QRO_RM	Compute Qualitative Resistivity Overlay (QRO) for CDR?	NO	NO	NO	NO
START_MD	Starting measured depth	2583.661377	3248.031250	8366.141602	8733.595703
STOP_MD	Stopping measured depth	3248.031250	8366.141602	8733.595703	12841.207031
TSIZ_CDR	CDR Tool Diameter	9.500000	9.500000	6.750000	6.750000
VERS_CDR	CDR Downhole Software Version	6.000000	6.000000	6.000000	6.000000

Schlumberger Drilling & Measurements

Parameter Insert Header Software version 2.0c

IDEAL Version: ID9_1C_01

IDF

CDR id9_1c_01 MWD_10 id9_1c_01

Format: CDRRM_1:200MD Vertical Scale: 1:200


Graphics File Created: 09-Nov-2004 17:36


Parameters

DLIS Name	Description	Value
DO	Depth Offset	0.0 m
MW_RM	Mud Weight (RM)	12.852 lbm/gal
PLATEAU	CDR: Plateau GR sensor	YES

PIP SUMMARY


- Gamma Ray samples
- Resistivity samples









800



825



See Remarks









Run 1
Run 2


1000



1025


1050











1075



1100
































1525

1550











1700

1725




PSR



ATR







1750



1775




















2025

2050













2200

2225











2300

2325

2350









2425


2450






2475


2500



PSR

ATR








2575



2600



2625
















2875


2900






2925

2950






2975

3000

TAB_CDR_RES



GR_CDR



ROP5_RM




PSR

ATR











3150

3175









3250

3275


3300






3325


3350






3375


3400






3425

3450






3475

3500

TAB_CDR_RES


GR_CDR

ROP5_RM



PSR

ATR



3525


3550

3575

TAB_CDR_RES


GR_CDR

ROP5_RM




ATR

PSR





3600


3625



TAP_CDD_REF


CDD








3700

3725










3825

3850





PIP SUMMARY Gamma Ray samples Resistivity samples			
IDEAL Version: ID9_1C_01 IDF			
CDR	id9_1c_01	MWD_10	id9_1c_01

Master: Calibration out of date 5-Jul-2004 7:27											
9.50-in. Compensated Dual Resistivity Calibration											
Resistivity: Air											
Phase	Attenuation down DB		Value	Phase	Attenuation up DB		Value	Phase	BHC attenuation DB		Value
Master			3.696	Master			4.069	Master			3.883
	3.290 (Minimum)	3.890 (Nominal)	4.490 (Maximum)		3.290 (Minimum)	3.890 (Nominal)	4.490 (Maximum)		3.790 (Minimum)	3.890 (Nominal)	3.990 (Maximum)

Master: Calibration out of date 5-Jul-2004 7:27														
9.50-in. Compensated Dual Resistivity Calibration														
Resistivity: Air														
Phase	Phase shift down DEG			Value	Phase	Phase shift up DEG			Value	Phase	BHC phase shift DEG			Value
Master				0.4900	Master				-0.3346	Master				0.07771
	-2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)			-2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)			-0.9000 (Minimum)	0.1000 (Nominal)	1.100 (Maximum)	

Master: Calibration out of date 8-Jul-2004 2:56			
9.50-in. Compensated Dual Resistivity Calibration			
Gamma Ray: Blanket			
Phase	Gain		Value
Master			1.036
	0.8000 (Minimum)	1.000 (Nominal)	1.200 (Maximum)

6.75-in. Compensated Dual Resistivity / Equipment Identification			
Primary Equipment:			
Tool Name and Serial Number	CDR6 – AA	552	
Gamma Ray Type	Plat – GR		
Calibration Status	–		

Master: 7-Sep-2004 5:24

Resistivity: Air				Resistivity: Air				Resistivity: Air			
Phase	Attenuation down DB		Value	Phase	Attenuation up DB		Value	Phase	BHC attenuation DB		Value
Master			5.102	Master			4.999	Master			5.050
	4.420 (Minimum)	5.020 (Nominal)	5.620 (Maximum)		4.420 (Minimum)	5.020 (Nominal)	5.620 (Maximum)		4.920 (Minimum)	5.020 (Nominal)	5.120 (Maximum)

Master: 7-Sep-2004 5:24

6.75-in. Compensated Dual Resistivity Calibration

Resistivity: Air				Resistivity: Air				Resistivity: Air			
Phase	Phase shift down DEG		Value	Phase	Phase shift up DEG		Value	Phase	BHC phase shift DEG		Value
Master			0.1451	Master			0.1541	Master			0.1496
	-2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)		-2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)		-0.9000 (Minimum)	0.1000 (Nominal)	1.100 (Maximum)

Master: 7-Sep-2004 6:17

6.75-in. Compensated Dual Resistivity Calibration

Gamma Ray: Blanket				Gamma Ray: Blanket				Gamma Ray: Blanket			
Phase	Gain		Value	Phase	Gain		Value	Phase	Gain		Value
Master			1.060	Master			1.060	Master			1.060
	0.8000 (Minimum)	1.000 (Nominal)	1.200 (Maximum)		0.8000 (Minimum)	1.000 (Nominal)	1.200 (Maximum)		0.8000 (Minimum)	1.000 (Nominal)	1.200 (Maximum)

SCHLUMBERGER

Survey report

4-Nov-2004 08:10:53

Page 1 of 4

Client..... SANTOS Ltd.
Field..... Callister

Well..... Callister-1
API number.....
Engineer..... A. DeCastro/D. Hastie/A. Ahmad

RIG:..... Jack Bates
STATE:..... Victoria

Spud date..... 13-Oct-2004
Last survey date..... 04-Nov-04
Total accepted surveys... 76
MD of first survey..... 0.00 m
MD of last survey..... 3914.50 m

----- Survey calculation methods-----
Method for positions..... Minimum curvature
Method for DLS..... Mason & Taylor

----- Depth reference -----
Permanent datum..... LEAST ASTRONOMICAL TIDE
Depth reference..... Driller's Depth
GL above permanent..... -129.42 m
KB above permanent..... -15240.00 m
DF above permanent..... 29.00 m

----- Vertical section origin-----
Latitude (+N/S-)..... 0.00 m
Departure (+E/W-)..... 0.00 m

----- Platform reference point-----
Latitude (+N/S-)..... 0.00 m
Departure (+E/W-)..... 0.00 m

Azimuth from Vsect Origin to target: 0.00 degrees

----- Geomagnetic data -----
Magnetic model..... BGGM version 2004
Magnetic date..... 15-Oct-2004
Magnetic field strength.. 1218.81 HCNT
Magnetic dec (+E/W-)..... 10.27 degrees
Magnetic dip..... -69.95 degrees

----- MWD survey Reference Criteria -----
Reference G..... 1000.05 mGal
Reference H..... 1218.81 HCNT
Reference Dip..... -69.95 degrees
Tolerance of G..... (+/-) 2.50 mGal
Tolerance of H..... (+/-) 6.00 HCNT
Tolerance of Dip..... (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-)..... 10.27 degrees
Grid convergence (+E/W-).. -0.29 degrees
Total az corr (+E/W-)..... 10.56 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

[(c)2004 IDEAL ID9_1C_01]
SCHLUMBERGER Survey Report

4-Nov-2004 08:10:53

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	TIP	None
2	299.00	0.50	0.00	299.00	299.00	1.30	1.30	0.00	1.30	0.00	0.05	MWD_M	None
3	385.00	1.00	0.00	86.00	384.99	2.43	2.43	0.00	2.43	0.00	0.18	MWD_M	None
4	414.00	1.00	0.00	29.00	413.98	2.94	2.94	0.00	2.94	0.00	0.00	MWD_M	None
5	446.00	1.00	0.00	32.00	445.98	3.49	3.49	0.00	3.49	0.00	0.00	MWD_M	None
6	471.00	1.50	0.00	25.00	470.97	4.04	4.04	0.00	4.04	0.00	0.61	MWD_M	None
7	557.00	1.00	0.00	86.00	556.95	5.92	5.92	0.00	5.92	0.00	0.18	MWD_M	None
8	615.00	0.50	0.00	58.00	614.95	6.68	6.68	0.00	6.68	0.00	0.26	MWD_M	None
9	643.00	0.50	0.00	28.00	642.95	6.92	6.92	0.00	6.92	0.00	0.00	MWD_M	None
10	672.00	1.00	0.00	29.00	671.94	7.30	7.30	0.00	7.30	0.00	0.53	MWD_M	None
11	701.00	1.00	0.00	29.00	700.94	7.81	7.81	0.00	7.81	0.00	0.00	MWD_M	None
12	728.00	0.50	0.00	27.00	727.94	8.16	8.16	0.00	8.16	0.00	0.56	MWD_M	None
12	756.00	1.00	0.00	29.00	755.94	8.52	8.52	0.00	8.52	0.00	0.54	MWD_M	None

13	756.00	1.00	0.00	28.00	755.93	8.53	8.53	0.00	8.53	0.00	0.54	MWD	None
14	787.50	1.00	0.00	31.50	787.43	9.08	9.08	0.00	9.08	0.00	0.00	MWD	None
15	790.06	0.45	331.69	2.56	789.99	9.11	9.11	-0.00	9.11	359.97	7.63	MWD	None
16	817.91	0.45	330.23	27.85	817.84	9.30	9.30	-0.11	9.30	359.32	0.01	MWD	None
17	847.21	0.69	337.63	29.30	847.14	9.56	9.56	-0.24	9.56	358.59	0.26	MWD	None
18	874.56	1.05	344.29	27.35	874.48	9.95	9.95	-0.37	9.96	357.90	0.42	MWD	None
19	903.94	1.25	333.65	29.38	903.86	10.50	10.50	-0.58	10.52	356.83	0.30	MWD	None
20	931.51	1.37	331.34	27.57	931.42	11.06	11.06	-0.87	11.09	355.49	0.14	MWD	None
21	959.28	0.22	170.41	27.77	959.19	11.30	11.30	-1.02	11.34	354.83	1.73	MWD	None
22	990.11	1.04	330.11	30.83	990.02	11.48	11.48	-1.15	11.54	354.27	1.23	MWD	None
23	1016.77	1.00	334.61	26.66	1016.67	11.90	11.90	-1.37	11.98	353.42	0.10	MWD	None
24	1037.31	1.03	330.72	20.54	1037.21	12.23	12.23	-1.54	12.32	352.82	0.11	MWD	None
25	1073.31	0.97	332.91	36.00	1073.20	12.78	12.78	-1.84	12.91	351.82	0.06	MWD	None
26	1101.55	1.29	326.69	28.24	1101.44	13.26	13.26	-2.12	13.43	350.91	0.37	MWD	None
27	1130.35	1.38	328.84	28.80	1130.23	13.82	13.82	-2.48	14.05	349.84	0.11	MWD	None
28	1159.59	1.19	326.05	29.24	1159.46	14.38	14.38	-2.83	14.65	348.87	0.21	MWD	None
29	1188.36	1.09	328.96	28.77	1188.23	14.86	14.86	-3.14	15.19	348.08	0.12	MWD	None
30	1216.58	1.00	326.02	28.22	1216.44	15.29	15.29	-3.41	15.67	347.42	0.11	MWD	None
[[c)2004 IDEAL ID9_1C_01]													
SCHLUMBERGER Survey Report													
4-Nov-2004 08:10:53													
Page 3 of 4													
===	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
Seq	Measured	Incl	Azimuth	Course	TVD	Vertical	Displ	Displ	Total	At	DLS	Srvy	Tool
#	depth	angle	angle	length	depth	section	+N/S-	+E/W-	displ	Azim	(deg/	tool	Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(m)	(deg)	100f)	type	(deg)
===	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
31	1245.42	1.04	326.14	28.84	1245.28	15.72	15.72	-3.70	16.15	346.76	0.04	MWD	None
32	1274.17	1.16	320.05	28.75	1274.02	16.16	16.16	-4.03	16.66	345.99	0.18	MWD	None
33	1303.61	0.91	307.43	29.44	1303.46	16.53	16.53	-4.41	17.11	345.07	0.35	MWD	None
34	1332.69	0.59	319.05	29.08	1332.54	16.78	16.78	-4.69	17.43	344.39	0.37	MWD	None
35	1361.48	0.51	310.54	28.79	1361.32	16.98	16.98	-4.89	17.67	343.95	0.12	MWD	None
36	1390.36	0.53	314.61	28.88	1390.20	17.16	17.16	-5.08	17.89	343.51	0.04	MWD	None
37	1417.46	0.62	318.06	27.10	1417.30	17.35	17.35	-5.27	18.13	343.12	0.11	MWD	None
38	1447.76	0.51	316.13	30.30	1447.60	17.57	17.57	-5.47	18.40	342.72	0.11	MWD	None
39	1476.30	0.56	320.25	28.54	1476.14	17.77	17.77	-5.65	18.65	342.38	0.07	MWD	None
40	1503.90	0.49	302.77	27.60	1503.74	17.94	17.94	-5.83	18.86	341.99	0.19	MWD	None
41	1532.52	0.49	296.48	28.62	1532.36	18.06	18.06	-6.04	19.04	341.50	0.06	MWD	None
42	1560.05	0.41	312.01	27.53	1559.89	18.18	18.18	-6.22	19.21	341.11	0.16	MWD	None
43	1588.76	0.41	306.97	28.71	1588.60	18.31	18.31	-6.38	19.39	340.79	0.04	MWD	None
44	1674.20	0.58	302.18	85.44	1674.03	18.72	18.72	-6.99	19.99	339.53	0.06	MWD	None
45	1759.79	0.77	300.09	85.59	1759.62	19.24	19.24	-7.85	20.78	337.79	0.07	MWD	None
46	1847.14	0.95	294.58	87.35	1846.96	19.84	19.84	-9.02	21.79	335.55	0.07	MWD	None
47	1930.43	0.89	302.24	83.29	1930.24	20.47	20.47	-10.20	22.87	333.52	0.05	MWD	None
48	2017.36	0.91	307.00	86.93	2017.15	21.25	21.25	-11.32	24.07	331.95	0.03	MWD	None
49	2103.93	0.96	309.22	86.57	2103.71	22.12	22.12	-12.43	25.37	330.67	0.02	MWD	None
50	2187.51	0.94	306.90	83.58	2187.28	22.97	22.97	-13.52	26.66	329.52	0.02	MWD	None
51	2273.18	1.01	323.23	85.67	2272.94	24.00	24.00	-14.53	28.06	328.80	0.10	MWD	None
52	2358.91	0.97	322.75	85.73	2358.66	25.18	25.18	-15.43	29.53	328.51	0.01	MWD	None
53	2445.35	0.96	329.95	86.44	2445.08	26.39	26.39	-16.23	30.98	328.41	0.04	MWD	None
54	2524.68	1.01	330.09	79.33	2524.40	27.57	27.57	-16.91	32.35	328.48	0.02	MWD	None
55	2559.17	0.98	331.10	34.49	2558.89	28.09	28.09	-17.21	32.94	328.51	0.03	MWD	None
56	2616.28	1.09	335.82	57.11	2615.99	29.02	29.02	-17.67	33.97	328.67	0.07	MWD	None
57	2701.32	1.08	328.22	85.04	2701.01	30.44	30.44	-18.42	35.58	328.82	0.05	MWD	None
58	2786.73	0.87	334.96	85.41	2786.41	31.71	31.71	-19.12	37.03	328.91	0.09	MWD	None
59	2873.56	0.47	315.46	86.83	2873.24	32.56	32.56	-19.65	38.03	328.89	0.16	MWD	None
60	2960.21	0.37	282.26	86.65	2959.88	32.87	32.87	-20.17	38.57	328.47	0.09	MWD	None
[[c)2004 IDEAL ID9_1C_01]													
SCHLUMBERGER Survey Report													
4-Nov-2004 08:10:53													
Page 4 of 4													
===	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
Seq	Measured	Incl	Azimuth	Course	TVD	Vertical	Displ	Displ	Total	At	DLS	Srvy	Tool
#	depth	angle	angle	length	depth	section	+N/S-	+E/W-	displ	Azim	(deg/	tool	Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(m)	(deg)	100f)	type	(deg)
===	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
61	3045.67	0.47	240.13	85.46	3045.34	32.76	32.76	-20.74	38.77	327.66	0.11	MWD	None
62	3129.38	0.54	224.15	83.71	3129.05	32.30	32.30	-21.31	38.70	326.58	0.06	MWD	None
63	3215.10	0.92	224.41	85.72	3214.76	31.52	31.52	-22.08	38.48	324.99	0.14	MWD	None
64	3303.12	1.31	213.64	88.02	3302.76	30.18	30.18	-23.13	38.02	322.53	0.15	MWD	None
65	3330.63	1.43	212.93	27.51	3330.27	29.63	29.63	-23.49	37.81	321.59	0.13	MWD	None
66	3358.35	1.62	214.79	27.72	3357.98	29.02	29.02	-23.90	37.59	320.52	0.22	MWD	None
67	3386.78	1.69	213.08	28.43	3386.39	28.33	28.33	-24.36	37.37	319.31	0.09	MWD	None
68	3414.60	1.67	214.65	27.82	3414.20	27.66	27.66	-24.81	37.16	318.10	0.05	MWD	None
69	3473.12	2.20	213.29	58.52	3472.69	26.02	26.02	-25.92	36.72	315.11	0.28	MWD	None
70	3528.68	2.23	216.78	55.56	3528.21	24.26	24.26	-27.15	36.41	311.78	0.08	MWD	None
71	3557.20	2.26	215.08	28.52	3556.71	23.36	23.36	-27.80	36.31	310.03	0.08	MWD	None
72	3586.67	2.18	216.17	29.47	3586.15	22.43	22.43	-28.47	36.24	308.23	0.09	MWD	None
73	3700.75	2.17	212.69	114.08	3700.15	18.86	18.86	-30.92	36.21	301.38	0.04	MWD	None
74	3787.16	2.50	209.01	86.41	3786.49	15.83	15.83	-32.71	36.34	295.83	0.13	MWD	None
75	3898.83	2.70	196.27	111.67	3898.05	11.18	11.18	-34.63	36.39	287.89	0.17	MWD	None
76	3914.50	2.70	196.27	15.67	3913.70	10.47	10.47	-34.84	36.38	286.73	0.00	Proj	to TD
[[c)2004 IDEAL ID9_1C_01]													

Well: **Callister-1**
Field: **Exploration**
Rig: **Jack Bates**
State: **Victoria**

VIC-P-51

CDR – Resistivity
1:200 Measured Depth
Recorded Mode