

17 MAR 1986

COMPOSITE WELL LOG WOODSIDE OIL N.L. WELLINGTON PARK No. 2



LOCATION: Lat 38° 08' 08" S
Long 147° 20' 55" E
(Australian Geodetic Datum)

ELEVATION: Ground Level: 4-95'
Rotary Table: 16-68'
Kelly Bushing: 18-01' (well datum)
(Williamstown Datum)

Date Spudded: March 16, 1970
Date Drilling Stopped: April 1, 1970
Date Rig Released: April 7, 1970

Total Depth: 4127'

RUN NUMBER	INDUCTION ELECTRIC LOGS		BOREHOLE COMPENSATED SONIC LOGS	
	ONE	TWO	ONE	TWO
Date	24-3-70	2-4-70	24-3-70	2-4-70
Depth - Driller	1802'	4127'	1802'	4127'
Depth - Logger	1802'	4127'	1802'	4127'
Bit Log Interval	1802'	4127'	1802'	4127'
Top Log Interval	232'	1802'	232'	1802'
Casing - Driller	13 7/8 to 230'	9 7/8 to 1804'	13 7/8 to 230'	9 7/8 to 1804'
Casing - Logger	232'	1802'	232'	1802'
Bit Size	12 1/2"	8 1/2"	12 1/2"	8 1/2"
Type Fluid in Hole	Gel	Gel	Gel	Bentonite
Density / Viscosity	9.7 / 6.0	10.0 / 5.0	9.7 / 6.0	10.0 / 5.0
pH / Fluid Loss	8.7 / 10 ml	9.3 / 70 ml	8.7 / 10 ml	9.5 / 70 ml
Source of Sample	Circ	Flowline	Circ	Flowline
Run at Max. Temp.	0.320 @ 147°	0.47 @ 169°	0.320 @ 147°	0.47 @ 169°
Run at Min. Temp.	0.240 @ 65°	0.36 @ 60°	0.240 @ 65°	0.36 @ 60°
Run at Mean Temp.	0.280 @ 62°	0.41 @ 62°	0.280 @ 62°	0.41 @ 62°
Time Since Circ	2 hours	12 hours	2 hours	12 hours
Max. Run Temp.	92°	172°	92°	172°
Equip. / Licenses	4522 / Sole	4522 / Sole	4522 / Sole	4522 / Sole
Recorded by	Bradley	Murdoch	Bradley	Schan
Witnessed by	Murphy	Wilkinson	Murphy	Wilkinson

PETROLEUM TENEMENT: P.E.P. 72
STATE: VICTORIA
4-MILE SHEET: SALE
BASIN: GIPPSLAND
WELL STATUS: PLUGGED & ABANDONED
COMPANY: WOODSIDE OIL N.L. et al.

Drilled by: Woodside Oil N.L. (Crew supplied by Richter Bowden Drilling Pty. Ltd.)
Drilling Method: Rotary
Cemented by: Halliburton Limited
Logged by: Schlumberger SEACO Inc.
Mud Logging: Data Analysis Pty. Ltd.
Mud Logging Interpretation: Data Analysis Pty. Ltd.
Lithology: M. Wilshire, A. Morimathu and V. Dent
Drafted by: Geodrafting Services Pty. Ltd.

Hole Size	Inches	From	To
12 1/2"	26'	13'	50'
12 1/4"	17 1/2"	30'	240'
12 1/8"	12 1/4"	240'	1805'
8 1/2"	8 1/4"	1805'	4127'

Casing	Inches	WT	Gr	Depth	Cmt	Cmt to Surface
20	13'	48 lbs <td>H-40</td> <td>230'</td> <td>227 sk</td> <td>Surface</td>	H-40	230'	227 sk	Surface
15 1/2	15 1/2"	36 lbs	J-55	1804'	350 sk	Surface

Cement Plugs	From	To
	13'	65'
	1750'	1850'
	2250'	2350'
	3650'	3750'

LITHOLOGIC REFERENCE

	Sandstone		Limestone		Feldspar		Fossiliferous
	Siltstone		Calcareous		Calcareous		Carbonaceous
	Clay		Mudstone		Mica		
	Mudstone		Dolomite		Glaucous		
	Shale		Coal		Pyritic		

WELL SYMBOLS

- ◊ Fluorescence
- ▶ Sidewall core, number - recovered
- ◻ Sidewall core, number - not recovered
- Drill stem test showing interval and number
- ▲ Casing shoe
- ⊗ Plugged interval

