DEPT. NAT. RES & ENV
PE601164

EXLOG | COMPANY: BEACH PETROLEUM N.L. | WELL: FAHLEY No. 1 SIDETRACK | SHEET NO. 1

FORMATION EVALUATION LOG

FAHLEY-1. W.C.R.

RATE OF PENETRATION — K METRE/HR — VISUAL POROSITY

CUTTINGS LITHOLOGY

HYDROCARBON ANALYSIS — CONTINUOUS TOTAL GAS — CUTTINGS GAS — CHROMATOGRAPH — METHANE, ETHANE, PROPANE, BUTANES, PENTANES — GAS PERCENT — GAS UNITS — PPM

CUTTINGS GAS

LITHOLOGY DESCRIPTION AND REMARKS

DEPTH

FAHLEY No. 1 WAS CEMENTED BACK TO 2079M DUE TO EXCESSIVE HOLE DEVIATION. AFTER SIDETRACK WAS ACHIEVED, SIDETRACK SAMPLING WAS COMMENCED AT 2181 METERS AFTER CEMENT CONTAMINATION AND DRILLED CEMENT SUFFICIENTLY SUBSIDED.

FAHLEY No. 1 SIDETRACK

TO 2/TR U

DEV: 5½°

NOTE: SAMPLES BADLY CONTAMINATED BY GREASE.

W 9.6, V 40, PV 20, YP 15, GEL 2/4, F 7.8, FC 1, SOL 4, 3d TR, pH 12, CL 39000

DEV: 5°

SANDSTONE, VERY LIGHT GREY TO VERY LIGHT BROWN GREY CLEAR, FRIABLE TO HARD VERY FINE TO OCC COARSE DOM VERY FINE TO FINE, SUB ANGULAR TO SUBROUND, MOD SORTED, TRACE TO OCC COMMON GREY TO BROWN ARGILACEOUS MATRIX, COMMON SILICEOUS CEMENT, TRACE DOLOMITE CMT IN PART, RARE PYRITE CMT TRACE DARK GREY LITHICS TRACE TO COMMON LIGHT YELLOW STAINING ON QUARTZ GRAINS, RARE CARBONACEOUS DETRITUS, POOR TO FAIR VISUAL POROSITY.
CLAYSTONE, LIGHT-DARK GREY, FIRM, VERY DISPERSIVE, SUB FISSILE, VERY SILTY IN PART, COMMON ARENACEOUS MATERIAL, TRACE MICROMICA & CARBONACEOUS FLECKS, TRACE PYRITE.

DEV: 4½°

C = 40u AT 42V

W 9.5, V 42, PV 22, YP 19, GEL 2/4, F 7.6, FC 1, SOL 4, 3d TR, pH 11.5, CL 39000

SANDSTONE, AS ABOVE.

DEV: 4½°

CLAYSTONE, FROM 2295M, VERY DARK BROWN GREY-VERY DARK GREY, FIRM, MOD DISPERSIVE, SUBFIS, TR-COM MICROMICA, VERY SILTY IN PART, VERY CARBONACEOUS, TR VERY FINE SAND, TR PYRITE, TR QUARTZ SAND LAMINAE.

SANDSTONE, FROM 2315M, AS ABOVE, INTERBEDDED WITH SANDSTONE, OFF WHITE, LIGHT-MEDIUM GREY, VERY HARD, FRI IN PART, VERY FINE TO MED, DOM FINE QUARTZ AGG SBANG-SBRND, FAIR-MOD WELL CMTED, TRACE-COM WH-LT GY ARG MATRIX, ABUNDANT GY ARG MATRIX IN PART, STRONG SILICA CMT, TRACE MED BRN CRYPTXL DOL, TRACE-COM PART ALTERED FELDS, TRACE GREEN RED, GY, BRN, BLK LITHICS TRACE YEL STAINED QTZ AGG TRACE CARB FLECKS, TRACE MAS & INTERGRANULAR PYR POOR VISUAL POROSITY

DEV: 3¾°

W 9.6, V 45, PV 27, YP 27, GEL 2/4, F 6.4, FC 1, SOL 4½, 3d TR, pH 11, CL 38000

SANDSTONE, FROM 2374M, AS ABOVE, INTERBEDDED WITH: SANDSTONE, LIGHT GREY, HARD FRIABLE, FINE-VERY COARSE, DOM MED-COARSE, ANG-SUBRND DOM SUBANG, POOR-MOD SRTD, COM PALE GREEN, RED AND YELLOW LITHICS, STRONG SILICA CEMENT, TRACE PYRITE POOR-FAIR VISUAL POROSITY
CLAYSTONE, FROM 2381M, MED-DARK GREY, FIRM, SUBFIS, MOD DISPERSIVE, VERY SILTY AND VERY FINELY ARENACEOUS IN PART, MOD-VERY CARBONACEOUS WITH COM BLACK COALLY FLECKS, RARE GLAUCONITE & MED BROWN CRYPTOXLN DOLO.

DEV: 2½°

SANDSTONE, FROM 2405M, OFF WHITE-LIGHT BROWN, VERY FINE-VERY COARSE, DOM VERY FINE, SBANG, VERY POORLY SORTED, QTZ GRAINS SET IN AN ABUNDANT WHITE CLAY MATRIX, COM BROWN DOLOMITE CEMENT. IN PART, NO VISUAL POROSITY, NO FLUOR OR CUT.

W 9.6, V 50, PV 29, YP 27, GEL 2/4, F 7.2, FC 1, SOL 5, 3d TR, pH 11, CL 39000

THE DRILL PIPE BECAME STUCK AT 2433 METERS. THE PIPE WAS THEN BACKED OFF AT 2220 METERS. THE WELL WAS CEMENTED BACK TO 2051 METERS. THE CEMENT WAS DRESSED OFF TO 2088 METERS AND SIDETRACKING ATTEMPTED WITH A DYNA-DRIL AND A 1½° BENT SUB.