

(PAGE 1 OF 71)


~~909080 001~~

909080 001

Santos
SANTOS LTD A.B.N. 80 007 550 923

NAYLOR 1
GAS EXPLORATION WELL
WELL PROPOSAL

DRILLING PROGRAM
COMPLETING & TESTING
PROGRAM



P.E.P. 154, OTWAY BASIN

South Australian Business Unit
Exploration & Development

Santos (BOL) Ltd
(A.C.N. 000 670 575)

EXPLORATION & DEVELOPMENT - SA

NAYLOR 1
WELL PROPOSAL

G Parsons / M Majedi
January 2001

CONTENTS

1. WELL DATA SUMMARY

2. EXECUTIVE SUMMARY

3. GEOLOGICAL RISK ASSESSMENT

3.1 Play Analysis

3.2 Trap

3.3 Reservoir

3.4 Seal

3.5 Charge

4. RESOURCE DISTRIBUTION AND ECONOMIC EVALUATION

4.1 Resource Distribution

4.1.1 Area

4.1.2 Porosity

4.1.3 Hydrocarbon Saturation

4.1.4 Net Pay

4.1.5 Recovery Factor

4.1.6 Gas Composition

4.1.7 Flow Rate

4.2 Location

FIGURES, ENCLOSURES AND ATTACHMENTS**FIGURES**

1. Location Map
2. Otway Basin - Stratigraphic Column
3. Proposed Naylor 1 - Stratigraphic Column
4. Diagrammatic Structural Cross-Section – Proposed Naylor 1
5. Log Display – Boggy Creek 1
6. Log Display - Curdie 1
7. Log Display – Flaxmans 1
8. Log Display – Howmains 1
9. Composite Seismic Line - Curdievale 3D – Proposed Naylor – Curdie 1 Prospect Overview Dip Line
10. Composite Seismic Line - Curdievale 3D – Proposed Naylor – Curdie 1 Prospect Strike Line
11. Composite Seismic Line - Curdievale 3D – Proposed Naylor – Curdie 1 Prospect Detailed Dip Line
12. Near Top Waarre Sand Time Map - Naylor Prospect
13. Top Waarre Sandstone Amplitudes (Near and Far Offsets)
14. Curdievale 3D – Average Amplitude – Near Offset Stack
15. Curdievale 3D – Average Amplitude – Far Offset Stack
16. Curdievale 3D – Average Amplitude – Far - Near Offset Stack
17. Port Campbell Embayment – Waarre Depositional Model

TABLES

1. Resource Computation

ENCLOSURES

1. Near top Waarre Sand Time Map - Overview
2. Stratigraphic Cross Section Howmains 1 - Flaxmans 1 – Curdie 1 – Boggy Creek 1

ATTACHMENTS

1. Geophysical Prognosis
2. Drilling Program
3. Completion and Testing Program

1. WELL DATA SUMMARY

WELL NAME: Naylor 1			WELL TYPE: Gas Exploration																																									
LICENCE: PEP 154 EQUITY: <table border="0"> <tr> <td colspan="2">Voting (%)</td> <td colspan="2">BUDGET STATUS: 2001 Budget Item</td> <td colspan="2"></td> </tr> <tr> <td colspan="2"></td> <td colspan="2">Investment (\$mm)</td> <td colspan="2"></td> </tr> <tr> <td>Santos</td> <td>90%</td> <td>Santos</td> <td>\$1.094mm</td> <td colspan="2"></td> </tr> <tr> <td>Beach Petroleum</td> <td>10%</td> <td>Beach Petroleum</td> <td>\$0.122mm</td> <td colspan="2"></td> </tr> <tr> <td colspan="2">TOTAL</td> <td colspan="2">TOTAL</td> <td colspan="2">\$1.216 mm (P&A) **</td> </tr> </table>			Voting (%)		BUDGET STATUS: 2001 Budget Item						Investment (\$mm)				Santos	90%	Santos	\$1.094mm			Beach Petroleum	10%	Beach Petroleum	\$0.122mm			TOTAL		TOTAL		\$1.216 mm (P&A) **		Latitude: 38° 31' 56.77" S Longitude: 142° 48' 29.29" E Seismic Reference: Inline 2200 Curdievale 3D CDP 10225 Ground Level: 46.0m (Preliminary) Rotary Table: 50.7m (Preliminary) Proposed Total Depth: 2191m RT (-2140m) Rig: OD&E 30 Nearby Facilities: Heytesbury (12km)											
Voting (%)		BUDGET STATUS: 2001 Budget Item																																										
		Investment (\$mm)																																										
Santos	90%	Santos	\$1.094mm																																									
Beach Petroleum	10%	Beach Petroleum	\$0.122mm																																									
TOTAL		TOTAL		\$1.216 mm (P&A) **																																								
Resource Estimate (Recoverable)			Cost Estimates																																									
Mean Success Volume: 5.9 BCF Mean Expected Volume: 2.5 BCF			P&A: \$1.216 mm C&S: \$1.466 mm Cost Code: 8EE-84D894																																									
Objectives/Fluid Contacts			Stratigraphic Prognosis																																									
Primary		Secondary																																										
Waarre Sandstone (gas)																																												
			<table border="1"> <thead> <tr> <th>Formation</th> <th>Depth (m-KB)</th> <th>Depth (m-SS)</th> </tr> </thead> <tbody> <tr><td>Clifton</td><td>457</td><td>-406</td></tr> <tr><td>Mepunga</td><td>520</td><td>-469*</td></tr> <tr><td>Dilwyn</td><td>560</td><td>-509*</td></tr> <tr><td>Pember</td><td>830</td><td>-779*</td></tr> <tr><td>Pebble Pt</td><td>956</td><td>-905</td></tr> <tr><td>Paaratte</td><td>1039</td><td>-988</td></tr> <tr><td>Skull Ck</td><td>1534</td><td>-1483</td></tr> <tr><td>Belfast</td><td>1729</td><td>-1678</td></tr> <tr><td>Flaxmans</td><td>2000</td><td>-1949*</td></tr> <tr><td>WAARRE</td><td>2059</td><td>-2008</td></tr> <tr><td>Eumeralla</td><td>2157</td><td>-2106</td></tr> <tr><td>TD</td><td>2192</td><td>-2141</td></tr> </tbody> </table>			Formation	Depth (m-KB)	Depth (m-SS)	Clifton	457	-406	Mepunga	520	-469*	Dilwyn	560	-509*	Pember	830	-779*	Pebble Pt	956	-905	Paaratte	1039	-988	Skull Ck	1534	-1483	Belfast	1729	-1678	Flaxmans	2000	-1949*	WAARRE	2059	-2008	Eumeralla	2157	-2106	TD	2192	-2141
Formation	Depth (m-KB)	Depth (m-SS)																																										
Clifton	457	-406																																										
Mepunga	520	-469*																																										
Dilwyn	560	-509*																																										
Pember	830	-779*																																										
Pebble Pt	956	-905																																										
Paaratte	1039	-988																																										
Skull Ck	1534	-1483																																										
Belfast	1729	-1678																																										
Flaxmans	2000	-1949*																																										
WAARRE	2059	-2008																																										
Eumeralla	2157	-2106																																										
TD	2192	-2141																																										
			*Geological Picks																																									
Formation Evaluation			Hole Design/Drilling Issues																																									
Wireline Logging: PEX-HRS TD to Surface Casing to Surface SDT (WFT) TD to Surface Casing (WFT across Waarre Sst) MCFL-CALI TD to 10 m above top Pember PEX-LDL-CNL TD to 100' above Waarre Sst (dependent on shows and reservoir development) SWC's: 20 programmed MDT's / RFT's : 20 point pressure survey Velocity Survey: No Mudlogging: 10m Samples from Surface Casing to approx 1000m 3m samples thereafter to TD Samples as per well programme Formation Testing: None programmed Coring: None programmed REMARKS/RECOMMENDATIONS: South & West deviation is critical. Directional surveys to be taken every 150 m. Steering required			Well Class: Down size monobore/Exploration Hole Type: Down size monobore Hole Size Casing Depth 9 7/8" 7 5/8" Surface to 475m 6 3/4" 3 1/2" Surface to TD Drill Fluid: KCII/PHPA/Polymer Deviation Sub-Surface Targets: Naylor 1 is a vertical well. An accuracy of 25m radius from seismic reference at TD has been requested. The critical structural direction is to the south and west of the wellsite. Other Information/Hazards: No hazardous zones in offset wells No shallow gas expected Waarre Sandstone has excellent reservoir properties (porosity 20%, permeability up to 20 darcies) Nearby Wells and Duration: Flaxmans 189 days (TD 3514m) Curdie 40 days (TD 2596m) Penryn 10 days (TD 1823m)																																									
Approved by:		Project Leader:	Team Leader:	Operations Geology																																								
				Drilling Engineer:																																								

ALL COORDINATES WITHIN THIS DOCUMENT USE AN AGD84 DATUM

2. EXECUTIVE SUMMARY

Naylor 1 is proposed as an Otway Basin gas exploration well to be located in the PEP 154 licence, approximately 10 km north west of the town of Peterborough, 1.6 km south west of the Boggy Creek CO₂ field and 9.8 km west of the Wallaby Creek gas field. The Naylor structure is situated within the Port Campbell Embayment and the productive Waarre Sandstone play fairway, (Figure 1).

The PEP 154 Licence is held 90% Santos (operator) and 10% Beach Petroleum N.L. The Naylor Structure is a tilted-fault block closure defined by the Curdievale 3D seismic. The well is expected to intersect a Waarre Sandstone reservoir with mean average net pay of 39.4 m.

The prognosed stratigraphic succession for the Otway Basin and Naylor 1 are summarised in Figures 2 & 3 respectively.

Naylor 1 is contingent on the results of Croft 1. Given success at Croft 1, Naylor 1 is an attractive project with a mean prognosed success case of 5.86 BCF sales gas (13.78 BCF OGIP) and a current Pc (probability of commercial success) of 42%, resulting in expected mean reserves of 2.5 BCF sales gas. Pc would increase significantly if hydrocarbons are discovered at Croft 1.

3. GEOLOGICAL RISK ASSESSMENT

3.1 Play Analysis

The Naylor Prospect is mapped as a tilted-fault block closure with the primary reservoir being the Waarre Sandstone; both vertical and cross-fault seal are provided by a thick Belfast Mudstone (Figure 4). Structures are charged from mature source beds located within the underlying Eumeralla and / or Crayfish Group, with migration directly into the reservoir or via fault conduits. The play has proven successful in the nearby Mylor, Fenton Creek, North Paaratte, Wallaby Creek and Iona gas fields as well as the Boggy Creek CO₂ field. Naylor as with each of these fields exhibits a strong amplitude anomaly at the Waarre Sandstone horizon, which is interpreted as being indicative of a well-developed, gas saturated reservoir.

3.2 Trap (Pcl = 95%)

Interpretation and mapping of the Naylor prospect was based on the Curdievale 3D survey, which was recorded in early 2000. The Curdievale 3D data quality is good over the Naylor structure.

Several migrated volumes including migrated stacks with and without spectral whitening and both near and far offset migrated stacks were generated and used for interpretation. Due to better horizon continuity and amplitude preservation the migrated stack volume without spectral whitening was used for horizon interpretation. Far and near offset volumes were used for amplitude extraction and AVO analysis.

A coherency cube (similarity volume) was also generated and used in conjunction with other volumes for fault interpretation.

Well ties were performed for Boggy Creek 1 (Figure 5), Callista 1 and Curdie 1 (Figure 6). The Curdie 1 ties however may not be valid for the Waarre, as the well appears to have penetrated a fault plane at this level.

Figure 9 shows an arbitrary line through Boggy Creek 1 to the proposed Naylor 1 and Croft 1 locations. Figures 10 and 11 are strike and dip lines respectively through the proposed Naylor 1 location.

Main mapping was carried out at near top Waarre Sandstone, which is the primary target reservoir (Enclosure 1 & Figure 12). The Waarre sand package has a distinctive characteristic and therefore a high degree of consistency was maintained on mapping this unit.

The top Belfast Mudstone was interpreted on a selected grid in order to evaluate adequately its seal efficiency over the Naylor structure.

The Naylor structure is a relatively complex tilted fault block structure located between Boggy Creek 1, Curdie 1 and the proposed Croft 1 (Figure 12 and Enclosure 1). The extended Naylor structural closure area partially relies on downthrown side fault seal where Waarre reservoir juxtaposes the Eumerella Formation. Similar seal potential has already proven to be efficient at Boggy Creek. A strong amplitude event is prominent within the Waarre sand unit over the Naylor prospect. Similar events over all gas fields within the Port Campbell region suggest that the amplitude anomaly is likely related to the presence of gas in these structures. Furthermore, near and far-offset volumes were also used to evaluate the AVO response over the Naylor structure. Figure 12 is a line over the Naylor structure from the near and far offset volume. It clearly shows that the amplitude within the Waarre sand unit is much brighter in the far offset compared to the near offset. Figures 14, 15 and 16 are displays of amplitudes extracted from within the Waarre sand unit. Figure 16 is particularly encouraging as amplitudes from far offset minus near offset clearly indicate an AVO anomaly coincident with the Naylor structure.

The location for the proposed Naylor 1 well was selected on inline 2200 CDP 10225. This location is at a near crestal position, and about 50 metres away from the main fault at the Waarre sand level.

Depth conversion for the prognosis was performed using Curdie 1 velocities. The results of this conversion are presented in Attachment 1.

3.3 Reservoir (Prs = 95%)

The Waarre Sandstone reservoir was deposited as the initial post-rift sequence at the commencement of the Turonian time under non-marine to marginal marine conditions. The section is sub-divided into three sub-units – Waarre “A”, “B” & “C”. The lower A unit represents a basal transgressive systems tract (TST) characterised by flooding of an incised valley with sediments deposited under marginal marine / estuarine conditions. The basal portion of Unit A is represented by either sand (as in Curdie 1) or shale (Boggy Creek 1 and Callista 1). This section is overlain by the widespread predominantly argillaceous Unit B, which was deposited under estuarine conditions. Unit C followed and is characterised by initial estuarine / deltaic conditions succeeded by high-energy sands. As the transgression develops the valley system is flooded with the Flaxmans Formation and Belfast Mudstone. Figure 17 illustrates this model.

The Waarre Sandstone thickens to the south in the Port Campbell Embayment. The proximity to the Boggy Creek Field where good reservoir is encountered provides high confidence that similar good reservoir will be found in Naylor 1. Nearby in the water-

wet Curdie 1, the Waarre Sandstone has an average porosity of 12% and a maximum porosity of 17% from logs. This reduced porosity could be a result of the Waarre sands not having early hydrocarbon emplacement, and thus being subject to increased diagenesis from the nearby fault and greater depth of burial. The strong amplitude anomaly associated with the Naylor prospect is likely to be an indication of good porosity.

A review of the local wells shows some variability in Waarre sand quality. In Boggy Creek 1 a maximum core permeability of 10.1 Darcies and average core permeabilities of 4.5 Darcies were measured. Drill stem tests confirmed the potential of the reservoir with test rates of 4.5 MMCFD. Howmains 1 represents an interfluvial environment where the Waarre sand appears to be shalier and did not develop the same reservoir quality as at many adjacent locations. No log porosity estimate can be generated for Flaxmans 1, due to the poor Waarre coverage by the sonic log and its spurious nature. Log displays for Boggy Creek 1, Curdie 1, Flaxmans 1 and Howmains 1 are presented in Figures 5, 6, 7 & 8 and as a stratigraphic cross section (Enclosure 2).

3.4 Seal (Psi = 95%)

All Otway Basin successes in the Port Campbell Embayment area have been from high-side, tilted fault or horst blocks. The ultimate top seal to Waarre reservoirs is the marine Belfast Mudstone. While a potential waste or "thief" zone (the Flaxmans Formation) exists between the Waarre sands and the Belfast seal, the unit was deposited under transitional marine conditions and generally acts as a seal.

A review of the cross-fault seal in proposed Naylor 1 suggests that leakage will not occur as the bounding fault displacement (~160ms) is considerably less than the thickness of the Belfast Mudstone (+260ms).

3.5 Charge (Pch = 50%)

Hydrocarbons are produced in the Port Campbell Embayment with the Eumeralla Formation and/or the Crayfish Group being the source beds. Analysis of the condensates and oils from the area suggest a non-marine origin with both algal and higher land plant components (Type III Kerogen). Maturation studies indicate that the top of the hydrocarbon window lies at about 2500m (SS). Thus mature Eumeralla source units which underlie the local gas fields are most likely to charge directly into the overlying structures through source-reservoir juxtaposition or via fault conduits. This model is proposed for Naylor 1, which is positioned in a similar setting to the nearby existing gas fields.

With many of the structures being present prior to the Belfast deposition, the timing of generation and migration does not appear to be a major issue. The charge risk incorporates the risk of CO₂ displacement (see discussion below).

3.5 CO₂ Issues

The distribution of CO₂ within the Port Campbell area appears to be related to the introduction of a restricted CO₂ volume at a number of locations and its subsequent migration. The CO₂ is considered to be from a mantle source and is likely to have occurred in conjunction with the emplacement of an igneous body during the Miocene.

A review of the high-resolution aeromagnetic data has been undertaken in an effort to understand the distribution of deep-seated faulting, believed to be the conduit for CO₂ migration and the emplacement of igneous bodies. The results of the study indicate

the presence of an intrusive marginal to the coast and proximal to a major NNE-SSW lineament. This lineament appears to be coincident with major

faulting identified on the seismic and is seen as a likely conduit for the Langley and Grumby CO₂. While an intrusive is not identified at nearby Boggy Creek, a similar trending lineament is mapped through the Boggy Creek well location.

Given the location of Naylor with respect to Boggy Creek (1.6km to NE) and the imprecision of the aeromagnetic tool, it is difficult to accurately predict whether CO₂ poses a major risk to the prospect. A factor (50%) has been included in the charge risk for the prospect with respect to CO₂. The drilling of Naylor 1 is contingent upon the success Croft 1 which would see considerably reduced the risk if CO₂ is present.

4. RESOURCE DISTRIBUTION AND ECONOMIC EVALUATION

4.1 Resource Distribution

Distributions for local gas field parameters are estimated primarily from those at Boggy Creek 1, Curdie 1 and Flaxmans 1 with data from other nearby wells reviewed to provide details of the upper and lower limits. These results are set forth in Table 1 and are used in the resource calculation sheets.

4.1.1 Area

The seismic mapping shows an independent closure of 340 acres (Enclosure 1) and this is used as the P1 area. A low side 75-acre area forms the basis of the P99 estimation and corresponds to the extent of the high amplitude anomaly associated with the prospect. The resultant mean area corresponds to the area covered by the strongest amplitude anomaly.

4.1.2 Porosity

In the adjacent Curdie and Boggy Creek wells, average porosity of about 12% and 17% are calculated from the respective logs. Spot core porosities of over 27% were measured in Boggy Creek 1. A range of 12% to 22% average porosity for P99 & P1 respectively calculates a mean porosity of 16.4% for the proposed Naylor 1.

4.1.3 Gas Saturation

A gas saturation distribution of 60-90% (min/max) captures all of the discoveries in the Port Campbell Embayment. Based on a lognormal distribution this calculates a mean of 73.8%, which approximates the Boggy Creek 1 gas average of 71.5%.

4.1.4 Net Pay

Boggy Creek 1 has net CO₂ pay of 28m (93 ft) from a gross 45m (146ft) section. At Curdie 1 net sand was 63m (208ft) from a gross interval of 81m (265ft). The proposed Naylor lies on depositional strike with Curdie 1 and a gross Waarre section of 98m (322ft) is predicted. Net / Gross ratios of 68% & 78% are recorded in Boggy Creek 1 and Curdie 1 respectively with a range from 60% (P99) and 90% (P1) providing an 73.8% N/G for the proposed Naylor 1. The mean net pay estimate for Naylor 1 is 39m (129 ft).

4.1.5 Recovery Factor

The recovery factor for Santos' Mylor and Fenton Creek fields is estimated to be about 50%. The mean recovery factor of 49.6% is calculated for Naylor based on 40% and 60% P90 and P10 respectively. The mean RF reflects the best estimate from reservoir engineering. It is believed that gas production could be influenced by a strong aquifer and hence the low assigned recovery factor.

4.1.6 Gas Composition

The ranges of gas compositions utilised for Naylor are relatively narrow and reflect the variation between the Mylor 1 and Fenton Creek 1 gas compositions. No detailed information from other nearby fields is available although there is potential for the gas to be drier. The main risk in Naylor regarding this issue is the percentage of CO₂ and this is incorporated in the shrinkage factor low side of 80% and a charge factor of 50%.


4.1.7 Flow Rate

Flow rates used range between 3 MMCFD and 30 MMCFD. These estimates are based on the results of the Mylor and Fenton Creek extended production tests. Mylor 1 flowed at 25mmcf on a ¾" choke, Fenton Creek 1 flowed 17mmcf on a ½" choke and Boggy Creek 1 flowed at 4.5 MMCFD on a ½" choke on open hole DST. The 4.5mmcf flow from the DST at Boggy Creek 1 doesn't reflect the multidarcy permeability of the reservoir.

4.2 Location

The proposed Naylor 1 is located about 10km north west of the town of Peterborough. The site is located in intensive farming land (dairy cattle / sheep) as well as remnant native bushland and utmost attention needs to be given to environmental and landholder issues.


Santos



Proposed Naylor 1

Heytesbury Gas Facility

SABU - Otway Basin, Victoria
 PEP 154
Proposed Naylor 1
 Well Location



909080 011

PE909080-color-001

Figure 1

OTWAY BASIN STRATIGRAPHIC COLUMN




Figure 2

Santos Ltd ACN 007 550 923, 9/10/97, Revised 27 July 1999, File No. OTWAY 274

NAYLOR 1 STRATIGRAPHIC COLUMN

Santos Ltd ABN 80 007 550 923, Sept 2000, File No. OTWAY 379

Lat.: 38° 31' 52.61"S (ANS) Long.: 142° 48' 25.57"E (ANS)

Seismic : Curdievale 3D Inline 2206, CDP 10222

G.L.: 46.0m(prelim)

R.T.: 50.7m (prelim)

AGE	FORMATION	ELEV.(m) SUBSEA PROGN.	LITHOLOGY	COMMENTS	CASING	CORING	TESTING	LOGGING	MONITORING		ANALYSIS											
									GAS	CUTTING												
TERTIARY	MIOCENE																					
												OLIGOCENE	HEYTESBURY GROUP (INCLUDING CLINTON FM)									
	EOCENE	NIRRANDA GROUP (INCLUDING MEPUNGA FM)	-494																			
			500mSS									-859										
	PALEO.	PEMBER	-905																			
		PEBBLE PT	-988										1000mSS									
CRETACEOUS	LATE	PAARATTE																				
												SKULL CREEK	-1483									
													1500mSS									
												BELFAST	-1949									
												FLAXMANS	2000mSS									
WAARRE	-2106																					
EARLY	EUMERELLA										-2140											

75/8" @ 475m

3 1/2" @ T.D. if required

NO CONVENTIONAL CORES
1 GUN (20 SIDEWALL CORES)

20 MDT POINTS

GR-DLL : T.D. TO SURFACE
SDT : T.D. TO SURFACE CASING
MSFL-CALI : T.D. TO 10m ABOVE TOP PEMBER
LDL/LDS-CNL : T.D. TO 100m ABOVE EUMERELLA FORMATION (DEPENDENT ON SHOWS AND RESERVOIR DEVELOPMENT)

GAS DETECTOR AND GAS CHROMATOGRAPH FROM SURFACE TO T.D.

3m INTERVALS
10m INTERVALS to 905m (SS)

PALYNOLOGY : SANTOS, ADELAIDE

PRIMARY OBJECTIVE
T.D.

Figure 3

Otway Basin, Victoria - PEP 154 A

Santos

Proposed Naylor I Diagrammatic Structural Cross Section

approx
vertical
scale
0
100
200m

W

E

proposed Naylor I

amplitude anomaly
coincident with
structural closure

*Belfast Mudstone (Seal)
(including Flaxmans)*

*Waarre Sandstone
(Reservoir)*

Proposed T.D.
-2140m (2191m RT)

Eumeralla Formation (Source)

Figure 4

PEP 154 A - color 014

Santos

SANTOS LIMITED

Santos

BOGGY_CREEK_1

RIG RELEASED : 12 JAN 1992

KB RT : 35.0
(METRES)

TOTAL DRILLED DEPTH : 1900.0
(METRES)

Vertical Units METRES




FIGURE 5

Santos

SANTOS LIMITED

Santos

CURDIE_1

RIG RELEASED : 27 MAR 1982

KB RT (METRES) : 43.0

TOTAL DRILLED DEPTH (METRES) : 2600.0

Vertical Units METRES




FIGURE 6

Santos

SANTOS LIMITED

Santos

FLAXMANS_1

RIG RELEASED 08-NOV-1961

K3/R1
METRES 67.36

TOTAL DRILLED DEPTH
METRES 3513.73

Vertical Units METRES




FIGURE 7

Santos

SANTOS LIMITED

Santos

HOWMAINS_1

RIG RELEASED 22-JUL-1994

KB/RT : 49.0
METRES)

TOTAL DRILLED DEPTH : 2150.0
METRES)

Vertical Units METRES




FIGURE 8





FIGURE 9


909080 019

PE999080-color08



909080 020

PE909080-color 009



PE909080 - color 00
909080 021

PE909010 - color 010


NAYLOR

909080 022



Santos

Near Top Waarre Sand
 Nov. 2000
 M. Majedi
 (Horizon : cv_war_pk)



UNIVERSAL TRANSVERSE MERCATOR PROJECTION
 AUSTRALIAN NATIONAL SPHEROID
 CENTRAL MERIDIAN 141 00 00 E
 Mapsheet datum: "Unknown"

Date : December 18, 2000	Author :	HNCL
Contour Interval : 10	Drafted :	
Datum : AUSTRALIAN NATIONAL	File No. :	

FIGURE 12




FIGURE 13

PE90948φ - color φ11
909080 023




FIGURE 14

Define trav path

Map: cv_pk_near_5-5 CDP: SP: Ln:
 Svy: H: HZ:

909030 024

PE900088 - color 12




FIGURE 15


Define trav path

Map: cv	CDP:	SP:	Ln:
Svy:	H:	HZ:	

909080 025

PE909080-color 013

Waarre Sandstone Depositional Model



- Bay head delta
- Barrier shoreface, & flood tidal delta
- Alluvial deposits
- Central basin
- Inner shelf
- Low stand wedge

Figure 17

PE909080 - color-014
 909080 026

ATTACHMENT 1

GEOPHYSICAL PROGNOSIS

ATTACHMENT 1
NAYLOR 1

GEOPHYSICAL PROGNOSIS

Latitude 38° 31' 56"S Longitude 142° 48' 27"E

	CURDIE 1						PROP.NAYLOR 1						BOGGY CK 1					
	TWT (ms)	DEPTH (m-ss)	Isopach (m)	VAV (m/s)	VINT* (m/s)		TWT (ms)	DEPTH (m-ss)	ERROR (+/-m)	Isopach (m)	VAV (m/s)	VINT* (m/s)		TWT (ms)	DEPTH (m-ss)	Isopach (m)	VAV (m/s)	VINT* (m/s)
CLIFF	458	428		1869			434	406			1869			435	406		1867	
PEB.P	860	959	531	2230	2642		818	905		499	2212	2600		802	870	464	2170	
PAAR	968	1095	136	2262	2519		881	988		83	2243	2650		872	968	98	2220	2800
SKUL	1300	1672	577	2572	3476		1190	1483		494	2492	3200		1200	1448	480	2413	2927
BELF	1410	1852	180	2627	3273		1305	1678		196	2572	3400		1246	1531	83	2457	3609
WAAR	1745	2410	558	2762	3331		1508	2008	+/- 20m	330	2663	3250		1313	1638	107	2495	3194
EUME	1800	2513	103	2792	3745		1573	2106		98	2677	3000		1373	1715	77	2498	2567
(TD)		2557	44					2141		35					1865	150		

ATTACHMENT 2

DRILLING PROGRAM

TABLE OF CONTENTS

1. GENERAL DRILLING PROCEDURES	
1.1 Introduction	3
1.2 Sequence of Operations	3
1.3 Sectional Summary	4
2. BITS AND HYDRAULICS	8
3. BOTTOM HOLE ASSEMBLIES	9
4. SURVEYING PROGRAMME	9
5. CASING CEMENTING AND WELLHEAD	
5.1 Casing Design Summary	10
5.2 Centraliser & Marker Joint Programme	10
6. WELLHEAD DETAILS	12
7. PRESSURE TESTING SCHEDULE	12
8. ABANDONMENT PLUG PROGRAMME	13
APPENDICIES	14
1. Montage	

1. GENERAL DRILLING PROCEDURES

1.1 INTRODUCTION

This document outlines the various steps in the drilling operation. A separate document, the "Santos DQMS Drilling Operations Manual", summarises the Santos General Operating and Well Control Procedures, 'drilling equipment and other procedures. This 'Drilling Program' is to be read in conjunction with the above 'Drilling Operations Manual'.

Naylor #1 is a gas exploration well drilled in PEP154 in the Victorian Otway Basin. The primary target is the Waarre Sandstone for gas. Anticipated spud date is May10, 2001.

1.2 SEQUENCE OF OPERATIONS

- Rig up, drill mousehole & rathole (Note 20" conductor pre-installed)
- Drill 9 7/8" hole to approx 480m (1575 ft).
- Wiper trip and laydown 6 1/2" drill collars
- Run & cement 7 5/8" casing leaving 2m rathole
- NU & test Bradenhead & BOP's
- RIH PU 6 3/4" drilling assembly
- Drill out shoetrack & 3m (10') of new formation
Perform LOT to fracture propagation
- Drill 6 3/4" hole to 35 m into Eumeralla (approx 2192 m TVD)
Wireline log – 3 runs. GR-LCS-MRS-DLS-CAL. Run 2 CDS-CNS. Run 3 RFS (20 points)
- Run and cement 3 1/2" tubing or P&A. Install seal adaptor flange and Xmas tree if C&S and pressure test.
- Release rig.

1.3 SECTIONAL SUMMARY

Pre-Spud

- A 20" conductor has been pre-installed by the lease preparation contractor
- Drill rat hole and mouse hole. Inspect rig and complete prespud rig inspection form.
- Hold pre-spud safety meeting.

9 7/8" Surface Hole

Hazards & General Notes

- Mud rings may be encountered on this well in the Gellibrand Marl. The section is to be drilled with a caustic spud mud system.
- Potential total lost circulation at very shallow depths.

Operation

- Spud well with 9 7/8" bit with spud mud.
- Drill with reduced flow rate (under 300 gpm) and parameters until 6 1/2" drill collars buried. Then increase to full drilling flowrate and drilling parameters for optimum ROP. Ensure vis at least 50 sec/qrt in the surface limestone prior to reaching the marl formations. If mud rings become a problem in the clay-rich formations then dilute with drill water as a first recourse.
- Take a MSS survey at approx 30m (100ft).
- Drill ahead surveying with MSS every 150m (500ft) to approximately 480m. Allow for approximately 2m of rathole.
- Check bottoms up sample to confirm competent seat.
- Wiper trip back to old hole if required. Increase mud weight only if dictated by hole conditions.
- POOH. Laydown 6 1/2" Drill Collars.

Surface Hole Shallow Lost Circulation Contingency

On the recent "Wild Dog Road 1" well drilled by OCA/Boral nearby, total lost circulation was experienced from 14m to 16m below ground level. If uncontrollable losses are encountered on "Naylor #1", then a 13 3/8" second conductor string will be set to case off the entire limestone section. The decision to proceed with this plan will be at the discretion of the Santos representative, depending on the severity of losses experienced.

Contingency Operation

- Continue drilling 9 7/8" hole blind or with limited returns to 50m below RT.
- POOH and change bit out to 17 1/2" mill tooth with open jets
- Open 9 7/8" hole to 17 1/2" to up to 160m below RT
- Set LCM pill on bottom or pump LCM sweep if partial returns and POOH, layout 17 1/2" bit.
- Run 13 3/8" STC casing with float shoe, 2 x centralisers and landing joint, tag bottom, pick up 3m and attempt to circulate
- Rig up STC cement head with top plug installed, pump 5 bbls water spacer then pump neat cement with 2% CaCl₂. Pump as slow as practical.
- Land casing on bottom
- Drop top plug and displace plug with mud to 5m above the float shoe. Pump as slow as practical.
- If no cement returns are observed, perform top up job with neat cement with 2% CaCl with 1" cement stinger.
- Remove cement head, cut casing and weld on flow-riser sleeve and fit flowline riser
- MU 9 7/8" bit and BHA and RIH. Drill out shoe and continue drilling 9 7/8" surface hole

7 5/8" Surface Casing

Hazards & General Notes

- No hazards are anticipated during this section

Operation

- Rig up and run 7 5/8" surface casing. Thread lock shoe track. Run 3m (10') BTC pup above float collar and thread lock to float collar.
- Run casing.
- Wash last joint to bottom and cement casing.
- Soft break collar on last joint below landing joint.
- Displace cement with old mud. Do not displace more than theoretical casing volume plus half the shoetrack volume. If bump observed, increase pressure to 2600 psi for 10 mins to test casing.
- Space out to set top flange of Bradenhead 4-6" above ground level (check space underneath rig floor. If not possible to set 4-6" above ground level, then set as high as possible).
- Perform 20m top-up job while WOC regardless of cement returns.
- WOC until surface samples have set (minimum of 4hrs).
- Nipple up 5k wellhead and BOP's and pressure test BOP's with rig pumps. Pressure test casing to 2600 psi for 10 mins with rig pumps **if plug did not bump**.
- Run wear bushing.
- RIH picking up 6 3/4" drilling assembly.
- Drill shoe track & 3m (10') of new formation.
- Perform leak-off test with pressure test unit (A 15.5 ppg leak off is expected, which would give the well a 14 bbl kick tolerance. Minimum required leakoff for 10 bbls kick tolerance is 14.4 ppg EMW. Notify the drilling engineer immediately if less than 14.4 ppg leakoff is achieved). Pump to fracture propagation or max allowable surface pressure.

6 ¾" Production Hole

Hazards & General Notes

- Differential sticking has been observed in the Paaratte Formation, and the Eumeralla Formation.
- Swelling clays in the Skull Creek and Belfast mudstones and filter cake build-up in the Nullawarre greensand may cause tight hole.

Operation

- Drill 6-3/4" hole with MSS surveys every 150 m (500 ft). The target tolerance is a 50 m radius around the surface location at the Waarre formation top.
- Drill in rotary as long as possible, but if the well trajectory indicates the target may be missed, drill no further than will allow for a correction run of no more than 30 degrees maximum inclination and no more than 8 degrees / 30m dogleg. If there is need for a correction run, use a rockbit and survey with MWD as necessary.
- Drill TD at 50m into Eumeralla (at approx 2192 m TVD).
- Make wiper trips as required.
- After TD, make a wiper trip back to old hole, take final survey and POOH to run logs.
- Rig up & run wireline logs: Run 1: GR-LCS-MRS-DLS-CAL, Run 2: CDS-CNS Run 3: RFS (20 points)
- Avoid a wiper trip between run 2 and 3 unless absolutely necessary. This is to avoid super charging of the formation.

3 ½" Production Casing

Hazards & General Notes

- The casing will require drifting with a 2.867" drift.
- Differential sticking of 7" casing in 8.5" hole has been observed in the Eumeralla in offset wells
- The slips will be set with buoyed casing string weight plus 40klbs against the **tail cement ONLY** WOC until tail cement sample set – lead cement samples should not have set.
- Once slip and seal assembly is in place, the annulus valve is to remain open while cement sets. Ensure this valve is closed once the lead surface cement samples have set.
- Mud left between 3-1/2" & 7-5/8" casing after cementing will contain biocide and the pH will be increased to more than 10 using caustic.

Operation

- If casing is to be run, RIH with bit (open nozzles and no stabilisers required).
- Condition hole and POOH laying down drill pipe and BHA.
- Rig up and run 3½" tubing. Threadlock the two joint shoe track. Monitor torque vs turns with JAM system provided by casing running contractor.
- Wash last joint to bottom and cement casing.
- Displace cement with 2% KCl brine. Ensure surface lines flushed from cement unit all the way to the cement head prior to displacing with the cementing unit. Use a ball below the top plug. Every attempt to bump the plug should be made. Do not displace more than 3 bbls over theoretical with the planned shoe depths and formation tops. This will be confirmed by the DE prior to the job. Pressure test casing to 2600 psi for 10 mins.
- Record string weight prior to cementing, at end of cement job and again prior to landing tubing.
- WOC until **tail cement surface samples have set**. Record string weight at start and then every 30 min. while WOC. Record these values on the Casing and Cementing report.
- Run slip and seal assembly. Set 3½" casing in tension with 40 klb overpull above buoyed string weight.
- Nipple down BOP's, install seal adaptor flange & 5k 3 1/8" Xmas Tree and pressure test (as per Section 7).
- Release rig.

Abandonment

Hazards & General Notes

- All plugs to be set on a 30 m (100ft) hi-vis pill (Min YP=50).
- Min plug length 60 m (30m above & 30m below formation top).
- Shoe plug to be 120 m (60m above and 60m below the shoe)
- All plugs 10% over calliper or 20% over gauge hole.
- Mud left in the surface casing will contain corrosion inhibitor and biocide.
- DE will confirm final depths from wireline logs.

Operation

- RIH 6 3/4" BHA and POOH laying down same.
- RIH with 2 7/8" EUE cement stinger and set balanced abandonment plugs as per program (Section 8).
- Tag shoe plug with 10klbs. Shut annular and pressure test to 500 psi above shoe leak-off pressure.
- POOH & LD DP.
- Pull wear bushing.
- Nipple down BOP's and remove Bradenhead.
- Set surface cement plug.
- Install identification plate and release rig.

2. PRELIMINARY BIT AND HYDRAULICS PROGRAMME

TBA

3. BOTTOM HOLE ASSEMBLIES

TBA

4. SURVEYING PROGRAMME

Hole section	9 7/8"	6 3/4"
Survey Type & frequency	MSS at 30m then every 150m	MWD or MSS surveys 150m minimum frequency

5. CASING PROGRAMME

5.1 CASING DESIGN SUMMARY

Casing String		Surface Casing	Production Casing
Casing size (in)		7-5/8	3 1/2"
Shoe depth (m MD/ft RT MD)		425 / 1395	1720 / 5643
Grade		L80	J55
Weight (lb/ft)		26.4	9.3
Burst rating (psi)		6020	6980
Collapse rating (psi)		3400	7400
Tensile rating (klb)		602	142
Connection		BTC	New NK3SB
Nominal Wall (in)		0.328	0.254
Inside diameter (in)		6.969	2.992
Drift Diameter (in)		6.844	2.867
Capacity (bbl/ft)		0.0472	.0087
Coupling OD (in)		8.5	4.25
Make-Up Torque (ft/lbs)	Minimum	To bottom	2160
	Optimum	Of triangle	2700
	Maximum		2970
FLOAT EQUIPMENT		Dowell	Dowell
Float Shoe		Non-Rotating	
Float Collar		Non-Rotating	
Shoe Track Length		2 Joints	1 Joint
Threadlock		Shoe Track	Shoe Track
Safety Factors			
Burst		3.0	3.5
Collapse		6.6	3.3
Tension - Running		5.2	1.9
- Pressure Test		5.6	2.3

Design based on deepest possible well depth of 1723m.

5.2 CENTRALISER & MARKER JOINT PROGRAMME

Casing Size	7 5/8"	3 1/2"
Centraliser Placement	Middle 1 st & 2 nd jts 3 rd , 5 th and 7 th coupling 1st coupling below cellar	3m above shoe Next 2 couplings Every 2 nd coupling from 15m above Flaxmans formation top to 15m below the Eumeralla formation top. 1 st & 3 rd coupling above 7 5/8" shoe
Centraliser Type	Bow spring	Bow spring
Marker Joints	Not req'd.	15m (50ft) above each pay zone separated by more than 60m 200ft Same weight & weight & grade as casing (higher grade is OK but not heavier weight).

NOTE:**7 5/8" Surface Casing**

- Drift every joint using the 6.84" drift.
- The two joint shoe-track will be made up and a 10' BTC pup joint will be run immediately above the float collar (Threadlock the float/pup joint connection). This will allow the shoe track to be stood back in the derrick if necessary.

3 1/2" Production Casing

- Drift every joint using the 2.867" drift.
- The two joint shoe-track will be made-up of a two 9.3 J55 New NK3SB.
- Dowell will provide the 3 1/2" circulating swedge.

6. WELLHEAD DETAILS

	Type	Flange size	Connection
Bradenhead	Wood 5k 7 5/8" BTC Box	11" 5000psi	7 5/8" BTC Box down
Slip & Seal Assy	Wood WG-22 11" x 3 1/2" S&S	NA	
Seal Adaptor Flange	Wood WG-A4-P 11" x 3 1/8" 5k	11" 5000psi x 3 1/8" 5000psi	
X Mas Tree	Wood	3 1/8" 5000psi Blind Flange, 1/2" NPT pressure gauge	

Santos Petroleum Engineering require that the Xmas tree (5k 3 1/8") be installed by the drilling rig and tested. Test the Xmas tree valves and the slip and seal packoff to 5000 psi. When testing the slip and seal packoff from above, ensure the bradenhead wing valve is open in case the slip and seal passes and exposes the surface casing to 5000 psi.

7. PRESSURE TESTING SCHEDULE

Component	Pressure Test
7 5/8" Surface casing	2600 psi
Pipe rams, K&C lines, choke manifold, Standpipe, kelly & safety valves	2600 psi
Annular	2000psi
Bradenhead – casing connection	2600psi
3 1/2" Production casing	2600psi
Packoff and Seal Assembly	5000 psi
7 5/8" x 3 1/2" annulus	2600 psi
Xmas tree valves	5000 psi
LOT	Minimum allowable 14.4ppg EMW (to fracture propagation or max allowable surface pressure)

NOTE:

Pressure tests will be a 10 minute low pressure test to 200psi and a 10 minute high pressure test as above. Pressure test BOPs, choke line and manifold, casing and conduct leak off test with rig pumps.

8. Abandonment Program for Naylor #1

If production casing is not run, the well will be abandoned with cement plugs and the wellhead removed.

Plug No	Depth (m RT MD / ft RT MD)	Purpose
1	2090 – 2030 m RT 6855 – 6655 ft RT	Waarre Isolation
2	1760 – 1700 m RT 5775 – 5575 ft RT	Belfast Isolation
3	1070 – 1010 m RT 3510 – 3310 ft RT	Paaratte Isolation
4	860 – 800 m RT 2820 – 2620 ft RT	Pember Isolation
5	510 – 450 m RT 1675 – 1475 ft RT	Surface casing shoe
6	0 – 15 m 0 – 50 ft RT	Surface plug

APPENDICIES

1. Directional Plots and Target Tolerance Description
2. Montage

WELL NAME: MAYLOR #1 WELL TYPE: GAS EXPLORATION WELL AREA: PEP 154 RIG CODE 3D		LATITUDE (SURFACE/TARGET): 38 deg 31' 56.77" S LONGITUDE (SURFACE/TARGET): 142 deg 48' 27.29" E SEISMIC REF TARGET: CDP-10225 INLINE 2200 ELEVATION (prelim): GL - 46.0 m (151 ft) RT - 50.7 m (166 ft)		SANTOS Limited	
TOPS & TARGETS TVD (m)	WELL SCHEMATIC	CASING WELLHEAD	CEMENTATION	DRILLING FLUID	EVALUATION
200 400 600 800 1000 1200 1400 1600 1800 2000 2200		SURFACE CASING 7.56" 28.4 pfl L80 B13C Run Down non rotating, float equipment, Connection to be torqued to triangle S41 Shoe @ 480 m (1575 ft) PRODUCTION CASING Lead: G 11.8 ppg w/ 8% Bentonite 0.07 gal/gal DO80 and 0.01 gal/gal DO47 Yield 2.22 cuft/gal Tail: G 15.0 ppg w/ 0.1 gal/gal DO80 and 0.04 gal/gal DO47 Yield 1.19 cuft/gal The top of lead cement to go a minimum of 500 ft (150 m) inside the surface casing shoe (approx. 1060 ft, 322m) Top of tail to go to 200' (60 m) above top Vshare (approx. 642 ft, 195 m) Use 10% excess over casing Condition the mud prior to cementing-etc. a min. 2 hole vols AV same as what drilling with low YP. Hold safety meeting and pressure tests etc. prior to circulation ie. minimise delays. Displace cement with 2% KCl brine. Pump to bump on production casing. (ensure top plug has fallen) A 3 1/2" top plug above the ball is to be run following the cement in the production casing Reciprocate the production casing string during job.	SURFACE HOLE Spot Mud MW: ALAP Treated viscosity 45 - 50 sec/cp YP 20 - 25 Use 84/110 mesh shaker screens Use plenty of fresh water for dilution and SAAP if mud rings noted	SURFACE HOLE Assumed Temp Grad 1.47 degrees / 100 ft Boggy Creek #1: 1.55deg/100ft Faxmans #1: 1.38deg/100ft Survey every 150 m, 500 ft (MSS) Offsets include: Boggy Creek #1: 1.6 km Curdie #1: 2.7 km Faxmans #1: 3.0 km Potential lost circulation in surface limestones and mud rings in deeper mats	WELL DATA 20" Conductor set at 5 m below G.L. Survey every 150 m, 500 ft (MSS)
800 830 866 1039 1534 1729 2000 2059 2157 2192 2200		PRODUCTION CASING 8-3/4" J55 New NCSB Run Downwell float equipment. Make up a two joint shoe track Use Klepac type thread protectors and stabbing guide when handling premium threads. Run centralisers and marker joints as per programme Make up connections to optimum torque of 2,700 lbs (opt). Use dump valve on power tongs and monitor torque vs turns with JAM system.	MAIN HOLE 2% - 3% KCl 1600m - TD 3% KCl 1600m - TD Use finest possible shaker screens to 250 mesh Ensure mud weight 9.1 ppg prior to Vshare Weight up to 9.4 ppg if required in Eumerala (20 points)	MAIN HOLE Mudlogging - Samples every 15m to approx. 1000 m and NO BOPs run wear badging when rotating Pressure test BOPs to 200/2500 psi. Hydril to 200/2000 psi using rig pumps FIT 14.4 ppg EMM (min) to top Member CDS-CNS (TD to 20m above Faxmans) RFS (20 points) Service Company Revers	WELL COST CAS: \$ 1,468,000 P&A: \$ 1,216,000 Cost Code: TBA VERSION 0 REVISION 0
TARGETS: Primary ● No changes to the drilling programme can be made without the Programme Change Control form (DQMS-F207) first being signed and sent to the rig. Secondary ○ Any changes to the scope of the work (eg extra DST's or logging runs) must be accompanied by DQMS Forms-F208 (Change of Scope).		Prepared by: Geoff Coker	Checked by:	Date:	WELL COST CAS: \$ 1,468,000 P&A: \$ 1,216,000 Cost Code: TBA VERSION 0 REVISION 0
Time - Depth Curve All depths are in m RT		OPERATION Rig Move 4 (6) Surface Hole - DRB 9.70" Hole to 480 m (1575) Run 7.56" casing & cement to 480 m (1575) Muds up with 2% BOPS & Tail Same Main Hole - DRB to TD at 2192 m (7192) Logs, RFS 2.4 (15.2) P & A CAS 2.4 (17.9)	ACTUAL 4 (6) 1.0 (5.0) 1.3 (7.2) 5.6 (13.8) 2.4 (15.2) 2.4 (17.9)	Time (Days from Spud) 0 2 4 6 8 10 12 14	LOT DATA: Fenton Creek 3.6 ppg EMM at 40m near base Narraweet Natf Mylor 1 16.5 ppg EMM at 20m middle Cellarand Natf Penryn #1 15.9 ppg EMM at 070m in top Member Mudstone Survey Data: Fenton Creek 1 : 0.5 - 3.5 degrees Mylor #1 : 0.5 - 2.5 degrees Penryn #1 : 0.25 - 3.5 deg 0 - 1428 m 3.5 - 5.5 deg 1428 - 1813m Boggy Creek #1 : 4 deg max at 1595 m built to 3 1/4" degrees by 7200 ft Faxmans #1 : 2.5 deg max to 6800 ft Potential for 8.9 ppg reservoir pressure in Eumerala, may require weight up to 9.4 ppg Swelling clays in the Skull Creek and Bellair mudstones may cause tight hole Maximum possible surface pressure (gas filled popo) is 2600 psi.

ATTACHMENT 3

COMPLETION AND TESTING PROGRAM

Santos Ltd
A.C.N. 007 550 923

Santos

Cost Code: 8ED - 83D*** - 813

BCRs:

<u>Contractor</u>	<u>Contract Number</u>	<u>Release no.</u>	<u>Comment</u>
Ascots			
Slickline contractor			
Electric-line contractor			

Purpose of Program:

To complete and test Naylor #1 to determine well deliverability. The program has been split into two parts to enable review/revision of the testing activities based on the results of the perforating. The testing equipment will be mobilised after the perforating has been completed, at a time determined by the Project Leader.

Part A

drift and swab well
slickline perforate Waarre Unit "C" sandstone underbalance
clean up flow and wellhead samples

Part B

- 2 rate flow test complete with HP samples.

Current Well Status:

3-1/2" monobore cased and suspended as a future Waarre Unit "C" gas producer.

Block:

PEP 154, Onshore Otway Basin, Victoria.

Location:

Latitude 38° 31' 56.77" S
Longitude: 142° 48' 27.29" E
Seismic line CDP 10225 INLINE 2200

Elevation:

Ground Level 46.0m
Rotary Table: 50.7m
Elevations are Above Mean Sea Level.
All depths are m. RT unless otherwise noted.

Brief Well History:

Naylor #1 was drilled as a monobore in South Western Victoria in the Otway Basin. This well is planned to intersect high porosity, high permeability net pay in the Waarre Unit "C" formation. The 3-1/2" J55 production casing will be run (based on a well life of < 4 years) to 2192 m and the well suspended as a future Waarre Unit "C" gas producer.
The well is located approximately
1.6 km from Boggy Creek #1, 5.0 km from Flaxmans #1 and
2.7 km from Curdie #1

Wellhead Maintenance: A 3-1/8" x 5000# trim 2 wellhead installed & pressure tested.

Casing Details: Surface Casing:

Plan to run 39 Joints 9-5/8" casing to 480m (1575') RT as follows:

Refer to attachment #1 - Surface Casing & Cementing report

Production Casing:

6-3/4" hole drilled to 2192m.

Plan to run 228 Jts of 3-1/2" 9.3 #/ft New NK3SB tubing to 2192m RT.

Refer to attachment #2 - Production Casing & Cementing report

TD: planned 2192m RT (7192' RT)

PBTD: planned 2181.5m RT (7157' RT)

Perforations: yet to be perforated

Preliminary

Reservoir Pressure & Temperature:

<u>Formation</u>	<u>Pressure</u>	<u>Temperature</u>	<u>Source</u>
Waarre Unit "C"	3275 psia @ 2157m RT (7077' RT)	174 F	Naylor #1 montage Dec 2001

Wellhead Equipment:

See Proposed Wellhead Schematic (Attachment 3.)

Downhole Equipment:

See Proposed Wellbore Schematic (Attachment 4.)

Preliminary

CONTENTS

PROCEDURE

<u>1. INSTALL WELLHEAD & DRIFT WELL</u>	<u>8</u>
<u>2. CONDUCT SLICKLINE CORRELATION LOGS</u>	<u>8</u>
<u>3. SWAB WELL</u>	<u>9</u>
<u>4. RUN SLICKLINE PERFORATING SYSTEM</u>	<u>9</u>
<u>5. DEPTH CORRELATION</u>	<u>9</u>
<u>6. PREPARE GUN MODULE</u>	<u>9</u>
<u>7. RUN PERFORATING GUN MODULE & FIRING HEAD</u>	<u>10</u>
<u>8. DROP BAR AND FLOW</u>	<u>10</u>
<u>9. RETRIEVE PERFORATING ASSEMBLY</u>	<u>10</u>
<u>10. RIG IN TESTING EQUIPMENT</u>	<u>12</u>
<u>11. PRE-FLOW & RUN BOTTOMHOLE GAUGES</u>	<u>12</u>
<u>12. TWO RATE FLOW TEST & SAMPLING</u>	<u>12</u>
<u>13. STATIC GRADIENT & RIG DOWN</u>	<u>14</u>

Preliminary

ATTACHMENTS

1. Surface Casing & Cementing Report
2. Production Casing & Cementing Report
3. Proposed Wellhead Schematic
4. Proposed Downhole Schematic
5. Perforation Request Advice
6. Lease Layout
7. Equipment Requirements
8. Condensate Production
9. Emergency Contacts
10. CFA Fire Permits
11. Determination Of Cement Quality

KILL FLUID CALCULATION SHEET

Formation:	Waarre Unit "C"
Reservoir Depth (ft.)	7077
Reservoir Pressure (psi)	3275
Reservoir Temperature (°F)	174
Kill Fluid Weight :	$3275 + 150$
	7077×0.052
	9.31 lb/gal
Temperature Correction:	Average Downhole Temp.
	$= \frac{174 + 70}{2}$
	= 122 °F
	Density Correction:
	$= 0.003 (122 - 70) \text{ lb/gal}$
	= 0.156 lb/gal
	Kill Fluid Weight at 70°F
	= 9.47 lb/gal

Preliminary

If required to kill well, then use 2% KCl fluid with a density of at least 9.47lb/gal

PROCEDURE

Note: Refer to the following SANPE procedures where necessary.

Note: Phone numbers for the site are 03 TBA & 03 TBA

Refer to the following SANPE procedures where necessary.

- 1-7 Wellsite Inspection for Downhole and Surface Completion Equipment.
- 1-10 Tubing Conveyed Perforating – Special Considerations.**
- 1-11 Well Control Equipment Testing
- 1-13 Well Maintenance-Top Up and Pressure Testing
- 1-14 Installation of Flarelines.
- 2-1 Coiled Tubing Operations
- 5-1 Slick line rig up
- 7-1 Work Place Hazard Inspections
- 7-2 Chemical Handling and Transport
- 7-3 Manual Handling Task Assessment

Preliminary

PART A - PERFORATING

1. INSTALL WELLHEAD & DRIFT WELL

- 1.1. Conduct wellsite safety meeting.
- 1.2. Install suitable flareline to flare up to 10 MMscf/d complete with 2-1/16" choke to wing valve (2-1/16") to existing flare pit.

Note: Ensure that the flare line is laid out taking into account the prevailing wind.

Rig up wing valve, variable choke and flowlines according to the normal procedures ensuring that an appropriate spacing is allowed between each major item of equipment. Refer to attachments #6 for lease layout, and #7 for equipment requirements.

Flare pit must be banded for flare containment.

- 1.3. Function test 3-1/8" 5000 psi Trim 2 wellhead.
- 1.4. Rig in slickline with 3000 psi lubricator and pressure test to 3000 psi for 10 mins. Pressure test wellhead to 3000 psi.
- 1.5. Pressure test surface casing string to 2000 then to 3000 and hold for minimum of 10 minutes. Record and report results of the pressure tests.

Note: The maximum expected shutin surface pressure (full column of gas) is approximately 2600 psi.

- 1.6. Make up and RIH 1.75" drift and tag PBTB @ 2181.5m RT.
- 1.7. Make up and RIH 2.867" API drift and tag PBTB.
- 1.8. Make up and RIH 2.80" x 20' dummy perforating drift and tag PBTB (for 2-1/8" perforating guns).
- 1.9. Break out toolstring and prepare to run Memory Production Logging Tool (MPLT).

2. CONDUCT SLICKLINE CORRELATION LOGS

Note: If the cementing is problematic, or a successful pressure test is not obtained on the surface casing, then a Program Change Request (PCR) will be issued to mobilise electric-line to conduct a Cement Bond Log (CBL/VDL/GR/CCL). Refer to Attachment #11.

- 2.1. Make up MPL toolstring to record Gamma Ray (GR), Casing Collar Locator (CCL) and Temperature (T).
- 2.2. RIH to PBTB and log up to at to approx. 2007m RT to record GR/CCL across the Waarre Unit "C" interval for correlation to open hole logs.

Note: The pup joint (marker joint) above the Waarre Unit "C" must be logged.

- 2.3. POOH to approx. 510m RT (30m below surface casing shoe).
- 2.4. Log across the surface casing shoe to 258m RT (70m above expected top of cement) to obtain a temperature pass.
Logging speed will be approximately 18m/min (60 ft/min).

**Naylor #1
Perforation & Flow Testing**

- 2.5. RIH and repeat log from 510 to 258m RT at a logging speed of approximately 36m/min (120 ft/min).
- 2.6. POOH and download data for depth correlation purposes. Correlate to open-hole log GR-LCS, MRS-DLS-CAL, CDS-CNS, dated not run yet as provided in PRA:yy/###/Rev. # (attachment #5 in the original program).

Note: If a suitable log has not been recorded, then the MPL will need to be re-run.

- 2.7. Prepare to swab well.

3. SWAB WELL

- 3.1. Rig in swabbing equipment.
- 3.2. RIH and swab well down to at least 400m. This will provide an underbalance of approx. 500 psi. Swabbed fluids must be directed to the flare pit.

Note: Brine in wellbore is 9.1 ppg.

A fluid head of at least 300 psi is required on top of the firing head.

- 3.3. Rig down swabbing equipment.

4. RUN SLICKLINE PERFORATING SYSTEM

- 4.1. Upon arrival at the wellsite, and prior to rigging up, conduct an onsite safety meeting and job review.

Note: Before commencing operations, report any wellhead pressures that may be present.

Ensure that the full details of the tubing stop and other downhole components are recorded.

- 4.2. RIH Slickline contractor with G type tubing stop assembly to approx. 2177m RT (20m below Waarre Unit "C" to minimise spacer requirements) and perform setting procedure in accordance with standard procedures.

Note: Ensure that the tubing stop setting depth does not interfere with the required perforation intervals given in PRA (Attachment #5).

The lowest perforation is at ****m RT - TO BE CONFIRMED

5. DEPTH CORRELATION

- 5.1. Connect memory CCL/GR gauges to Slickline contractor slickline.
- 5.2. RIH and tag tubing stop. Log off and up to at least 1524m (5000') RT (ie include marker joint at ****m RT). POOH.
- 5.3. The perforating engineer will download the data so that a hard copy of the depth correlation is available for reference. Correlate to the open hole depth reference log GR-LCS, MRS-DLS-CAL, CDS-CNS, dated not run yet, and cased hole GR/CCL run previously.

6. PREPARE GUN MODULE

- 6.1. Hold safety meeting to discuss operations with explosives. Conduct "Job Safety Analysis" and "Step Back" to review operations.
- 6.2. Load 2-1/8" Owen Raptor guns @ 6 spf 6.4g HMX charges, 60° phasing to perforate the Waarre Unit "C" sands as outlined in PRA:yy/###/Rev. # (Attachment #5). Determine spacer requirements taking into account the setting depth of the tubing stop.

7. RUN PERFORATING GUN MODULE & FIRING HEAD

- 7.1. RU Slickline contractor slickline unit and 3-1/2" lubricator.
- 7.2. Connect running tool to Slickline contractor slickline.
- 7.3. Connect spacer gun/perforating gun module to tool string and RIH.
- 7.4. RIH gun module and firing head.

Note: The Santos representative is to double check perforation interval as marked on gun module.

- 7.5. Rig down Slickline contractor.

8. DROP BAR AND FLOW

- 8.1. Conduct WSSM & OB and record on both Santos Daily Report and Slickline contractor Job Logs.

Note: Ensure that there are not any fire restrictions (ie. total fire ban), and that the appropriate authorities (CFA, Police etc.) and local residents have been notified.
Refer to attachment #9.

If fire restrictions are in place then do not proceed with perforating of the well.
Refer to attachment #10.

Ensure that the DNRE have been notified 24 hours prior to perforating the well.

Monitor annulus pressure during all of the following operations. Maximum Allowable Annulus Pressure (MAAP) is 200 psi.

- 8.2. Drop detonating bar **WITH THE WELL OPEN** to detonate the guns. It will be approximately 500 psi underbalance.
- 8.3. Flow to flare to unload water cushion and any perforating debris.
- 8.4. Report flare status, rates, FTHP, SIPCP and choke setting. Bleed down SIPCP as required.
- 8.5. Shut in well.
- 8.6. Report results to GWS-Adelaide immediately.

9. RETRIEVE PERFORATING ASSEMBLY

- 9.1. RU ET with 3-1/2" lubricator in preparation to fish perforating assembly. Ensure sufficient length of lubricator is available to fish gun hanger system components.

Note: Perforating specialist **MUST** be on location during slickline operations fishing gun modules.

- 9.2. Pressure test lubricator to 3000 psi for ten minutes

- 9.3. Conduct safety meeting and review JSA for pulling perforating guns.
- 9.4. RIH and retrieve bar, firing head and gun/spacer modules.
- 9.5. RIH and pull tubing stop.

Note: Advise GWS-Adelaide if any difficulties are encountered in recovering any of the perforating system components

- 9.6. RDMO Slickline contractor.
- 9.7. Flow well on cleanup for a minimum of 2 hours.
- 9.8. Report flare status, rates, FTHP, SIPCP and choke setting. Bleed down SIPCP as required.

Note: Obtain at least one hour of stable flowing tubing head pressure (1300 psi is the target).

Just prior to shutting in the well, obtain 2 HP gas samples from the wellhead.

Ensure that the samples are despatched to Adelaide ASAP via the Santos representative at the wellsite.

- 9.9. Shut in well and secure.
- 9.10. Report results to GWS-Adelaide.

Preliminary

PART B - TESTING

10. RIG IN TESTING EQUIPMENT

- 10.1. Ensure that the flare line is laid out taking into account the prevailing wind.
- 10.2. Rig up wing valve, variable choke, flowlines, separator, heater, gauge tank and frac tank according to the normal procedures ensuring that an appropriate spacing is allowed between each major item of equipment. Refer to attachments #6 for lease layout, and #7 for equipment requirements.

Note: Connect liquid flowlines to the riser of the test tank so that a constant head is maintained against the separator.

Piping should allow flow to tank and a loading point of tanker trucks to remove condensate produced.

Tank, lines and loadout pump are to be earthed to eliminate EMF differentials.

Refer to Slickline contractor Job Safety Analysis.

11. PRE-FLOW & RUN BOTTOMHOLE GAUGES

Note: Ensure that there are no fire restrictions (ie total fire ban), and that the appropriate authorities (CFA, Police etc.) and local residents have been notified. Refer to attachment #9.

If fire restrictions are in place then do not proceed with testing of the well.
Refer to attachment #10.

Ensure that the DNRE have been notified 24 hours prior to commencement of testing.

Do not run gauges until there is a clear indication that there will not be any fire bans for the next 2 days.

- 11.1. Pressure test all lines and equipment to full SITHP.
- 11.2. Open well to flare and determine appropriate choke settings. Warm separator and establish levels.
- 11.3. Shut in well to stabilise.
- 11.4. Rig up electronic gauge programmed as per Reservoir Development engineer's specifications. Connect battery, noting time and hang in lubricator. Pressure lubricator to full SITHP.

Note: The well must have a stable SITHP and have been shut in for at least 6 hours.

It is anticipated that the buildup will be less than 2 hours, so a high gauge rate of data sampling is required (refer to attachment #8).

- 11.5. After a 15 minute stop in the lubricator, RIH conducting a Static Gradient Survey with stops at each 305m (1000') (sufficient for gauge stabilisation). Hang gauges 15m (50') below the perforations at approximately 2157m RT (refer to attachment #4). Secure slickline and prepare for flow test.

12. TWO RATE FLOW TEST & SAMPLING

Naylor #1
Perforation & Flow Testing

- 12.1. Prepare to flow well at pressure of 1000 psi **OR** at a rate of approximately 10 MMscf/d. During the flow periods, monitor all separator parameters every 15 minutes and calculate all flow rates every 30 minutes for the first 2 hours, then hourly thereafter. During the shutin, also monitor pressures.

Note: Wellhead temperatures are important for flowline design.

- 12.2. Gradually bring the well on line and trim through the separator to flare.
- 12.3. Commence flowing the well through the separator. Adjust the choke to maintain a FTHP of approximately 1000 psi **OR** at a rate of approximately 10 MMscf/d. Flow well for 8 to 12 hours. The flow duration will be determined based on pressure/flow stability.

Note: Test gas for both H2S and CO2 by means of a Draeger test kit. If a positive H2S reading is registered, confirm and notify GWS Adelaide immediately. Full test equipment will then be mobilised in order to accurately ascertain the gas composition.

- 12.4. At the end of the first flow period, adjust choke setting to obtain a flowing pressure of 1350 psi (anticipated flowline pressure) **OR** at a rate of approximately 5 MMscf/d. Flow well for 8 to 12 hours. The flow duration will be determined based on pressure/flow stability.

Note: Refer to attachment #8 for approximate condensate (C5+) volumes expected to be produced. It is anticipated that the yield will be similar to nearby wells at approximately 12-18 bbls/MMscf. Condensate volumes will also depend on duration of the test.

Scotts Transport (Colin Richardson, 08 183473449) need to be advised on timing for pickup of condensate from location.

Western District Pumping Service (Peter Kavanagh, 018 528549, fax 03 55611337) will be mobilised to transfer the condensate.

- 12.5. Near the end of the second rate (after stable flow has been reached), take 2 sets of high pressure samples (gas & liquid), ensuring that the flow rates and pressures are stable. All separator functions are to be monitored and recorded. Also take 2 x 20L stock tank samples of the produced condensate.

Note: All samples should be taken under the same separator operating conditions and labelled accordingly.

LGR conditions **MUST** be stable.

Duplicate samples should be taken approximately one hour apart.

It is required to ensure stable conditions for sampling. If necessary, extend the flow period. Use evacuated cylinders for gas and acidified saturated brine solution for condensate sampling by displacement.

During the sampling monitor all the flow parameters.

Clearly label all samples and report sample container numbers in morning and final report.

- 12.6. Flow the well for a sufficient period (1-2 hours) after taking the duplicate set of samples to ensure that stabilised conditions have existed after sampling.
- 12.7. Shut well in on build up for approximately 24 hours, or 6 hours after the surface pressure stabilises. Notify the Project Leader if there are any problems with the test, or if the shutin monitoring can be curtailed earlier.

13. STATIC GRADIENT & RIG DOWN

13.1. At the end of the shutin period with the well still shutin, POOH with gauges conducting a Static Gradient Survey at 305m (1000') intervals (stop duration dependent on gauge stabilisation time) on the way out. Stop in lubricator for 15 minutes prior to isolating and bleeding down the lubricator and retrieving the gauges. Download the data and forward to the Project Leader as soon as is practically possible.

Note: The notice to end the test (or to rerun gauges) will be given by the on-site Reservoir Engineer.

Rig down separator and all associated equipment and demobilise from location.

- 13.2. RDMO slickline equipment and secure the well. Wellhead valves are to be chained and padlocked, as is the cage surrounding the wellhead. One set of padlock keys are to be handed to the Supervisor at the Heytesbury Gas Plant and the duplicate set returned to SABU Petroleum Engineering in Adelaide.
- 13.3. Ensure that the total liquids production is recorded and trucked away from the well site as previously arranged. Any water can be drained to the flare pit (which must be securely fenced).
- 13.4. Ensure that the lease is left in a clean and tidy state and contact the Project Leader to notify Land owner that test is complete

Preliminary

Surface Casing & Cementing Report

NOT YET AVAILABLE
Preliminary

PRODUCTION CASING & CEMENTING REPORT

NOT YET AVAILABLE
Preliminary

PROPOSED WELLHEAD SCHEMATIC

3-1/8" 5000 psi Trim 2 wellhead

NOT YET AVAILABLE
Preliminary


PROPOSED DOWNHOLE SCHEMATIC

NOT YET AVAILABLE
Preliminary

PERFORATION REQUEST ADVICE

NOT YET AVAILABLE
Preliminary

PROPOSED LEASE LAYOUT



EQUIPMENT REQUIREMENTS

1. Swab valve to fit 3-1/8" wellhead.
2. Flowline to separator
frac tank/road tanker c/w static earth lines and unloading pump
small gauge tank (2 x 55 bbl compartments)
tank piping
chiksans
line heater
choke manifold
flare line
methanol & injection equipment
3. Caravan & generator
lighting equipment
fire extinguishers
4. Slickline unit complete with:
 - running/pulling tools for perforating system
 - high rate electronic gauges
 - swabbing equipment for 3-1/2" monobore
 - dummy gun drifts.
5. Separator (1440 psi) & well test equipment
6. PVT sampling equipment, including
 - 3 x 20 litre HP gas sample bombs
 - 3 x 0.5 litre HP liquid sample bombs
7. Memory Production Logging tool for GR/CCL correlation & associated hard/software

Preliminary

CONDENSATE PRODUCTION

Generic well	FTHP (psi)	Anticipated rate (MMscf/d)	Test duration (hours)	Gas produced (MMscf)	C5+, @ CGR = 12 (bbls)	C5+, @ CGR = 18 (bbls)
Cleanup flow	1300	5.0	6	1.3	15	23
Rate determination	various	2.0	2	0.2	2	3
Shut well in for stabilisation			6			
RIH gauges			2			
Flow 1	1000	9.5	8	3.2	38	57
Shutin 1			0			
Flow 2	1300	5.5	8	1.8	22	33
Flow 2 (after sampling)	1300	5.5	2	0.5	6	8
Buildup			6			
Buildup			18			
SGS while POOH			2			
TOTAL				6.9 MMscf	83 bbls	124 bbls

Minimum rate to lift liquids for 3-1/2" tubing

Q (MMscf/d)	FTHP (psi)
3.0	1600
2.8	1450
2.6	1300
2.4	1150
2.1	1000

PRELIMINARY
 Naylor #1

EMERGENCY CONTACTS**OTWAY BASIN**

POSITION	NAME	PHONE	FAX
Aboriginal Heritage	Lionel Harridine	03 5567 1236	
Aircraft Hire	Shipwreck Coast Flights	03 5598 5441	
Ambulance, Timboon		000	
Ambulance, Warrnambool		000	
Backhoe Hire	Ian White	03 5598 6376	
CFA, Colac Region 6 Headquarters Operations Officer	Brian Brady	03 5232 1923	03 5231 1370
CFA, Colac Region 6 Headquarters Operations Manager	Mark Gunning	03 5232 1923	03 5231 1370
CFA, Timboon	Bassett	03 5598 3386	03 5598 3060
D.N.R.E.	Kaurosh Mehin	(wk) 03 9412 5082 (ah) 03 9412 1079 0419 597010	03 9412 5156
Drilling Conductor	Des Gladman	03 5562 0783	
Earth Moving	John Molan	03 5592 1261 0408 529 559	03 5592 2122
Exploration Field Service	Ray Willox	03 5598 5329 018 529 314	03 5598 5329
Fire Brigades (Fire Calls Only)	Timboon Port Campbell	03 5598 3386 03 5598 6243	
Heavy Haulage	Alan Spikin	03 5561 6111	
Helicopter Hire	Helicopter Operations Aust.	03 5561 5800 018 529 959	
Hospital, Timboon		03 5598 3000	
Hospital, Warrnambool		03 5563 1666	
Land Owner (Access)	Roland Stansfield	03 5598 5383	
Land Owner (Camp)	Wayne Thompson	03 5598 5286	
Land Owner (Penryn)	Garry Thompson Gus Thompson	03 5598 3333 03 5598 5385	
Medical Centre, Timboon		03 5598 3104	
O.D.E	Nic Hausburgh	0145 117 941	
Police, Port Campbell	B. Hair	03 5598 6310	
Police, Timboon	Russell Martin	03 5598 3026	
Police, Warrnambool		03 5562 1111	
Power Cor	Hutchins	03 5563 2512	03 5563 2511
Shire Council Corangamite	Paul Younis (Eng) Allan Kerr (Councillor)	03 5593 7100 03 5598 3240	03 5593 2695
South West Water	John Huff	03 5564 7600	
State Emergency Services Port Campbell		03 5598 6231	
Surveying	Paul Crowe	03 5561 1500 0419 515 422	03 5561 2935
Water Carting	John Molan	03 5592 1261 0408 529 559	03 5592 2122
Water Pumping	Exploration Field Service	03 5598 5329 018 529 314	03 5598 5329
Wreck Hire Warrnambool		03 5562 1411	

SANTOS

POSITION	NAME	PHONE	FAX
Gas Well Services Design Team Leader	Andrew DeGaris	(wk) 08 8224 7793 (ah) 08 8449 2610	08 8224 7755
Gas Well Services Operations Superintendent	Milt Gillies	(wk) 08 8224 7295 (ah) 08 8295 2414	08 8224 7755
Reservoir Development Eastern/Northern Gas Team Leader	John Hulme	(wk) 08 8224 7324 (ah) 08 8338 0169	08 8224 7755
Project Leader Staff Geologist	Graeme Parsons	(wk) 08 8224 7182 (ah) 08 8391 0967	
Environmental Dept.	Catriona McTaggart	(wk) 08 8224 7894 (ah) 08 8373 2961	08 8224 7141

SERVICE COMPANIES

POSITION	NAME	PHONE	FAX
Expertest Ltd	David Hawkes	08 8354 0488	08 8443 7408
Ascots Haulage	Colin Richardson David Jolley	08 8347 3449	08 8347 3414
Western District Pumping	Peter Kavanagh	018 528549	03 55611337

CFA FIRE PERMITS Rz.zz.00/01

NOT YET AVAILABLE
Preliminary

DETERMINATION OF CEMENT QUALITY

If the cementing of Naylor #1 was not problematic, and was pumped as per design to place the top of lead cement approximately 152m inside the surface casing shoe (ie. ~328m), the running of a Cement Bond Log (CBL/VDL/GR/CCL) will not be conducted for the following reasons:

- It is considered that a memory temperature log will be able to detect changes in geothermal gradient across the cement top.
- Due to the sensitivity of the location of Naylor #1, minimising the number of contractors on site will be beneficial in reducing the impact of operations on the local residents.
- A cost reduction will be realised, as mobilisation of the crews and equipment for the cement bond logging is substantial.
- Correlation to the open hole logs will be performed with the same Memory Production Logging Tool (MPLT) used for the temperature pass.
- A pressure test will be conducted on the Surface Casing to determine integrity of the pipe to withstand full shut-in wellhead pressure.

Preliminary

PE909081

This is an enclosure indicator page.
The enclosure PE909081 is enclosed within the
container PE909080 at this location in this
document.

The enclosure PE909081 has the following characteristics:

ITEM_BARCODE = PE909081
CONTAINER_BARCODE = PE909080
NAME = Enc.1 Curdie Vale 3D Depth Structure
Map
BASIN = OTWAY
ONSHORE? = Y
DATA_TYPE = SEISMIC
DATA_SUB_TYPE = HRZN_CONTR_MAP
DESCRIPTION = Encl.1 Naylor-1 Curdie Vale 3D Depth
Structure Map, Near Top Waarre Sand,
Scale 1:25000, C.I. 10m, Datum: AGD84,
Santos [BOL] Ltd, W1318, PEP154.
Enclosure 1 contained within "Naylor-1
Well Proposal Report" [PE909080].
REMARKS =
DATE_WRITTEN = 02-FEB-2001
DATE_PROCESSED =
DATE_RECEIVED =
RECEIVED_FROM = Santos (BOL) Pty Ltd
WELL_NAME = Naylor-1
CONTRACTOR =
AUTHOR =
ORIGINATOR = Santos Ltd
TOP_DEPTH =
BOTTOM_DEPTH =
ROW_CREATED_BY = CD000_SW

(Inserted by DNRE - Vic Govt Mines Dept)

PE909082

This is an enclosure indicator page.
 The enclosure PE909082 is enclosed within the
 container PE909080 at this location in this
 document.

The enclosure PE909082 has the following characteristics:

ITEM_BARCODE = PE909082
 CONTAINER_BARCODE = PE909080
 NAME = Encl.2 Naylor-1 Stratigraphic X-section
 BASIN =

OTWAY

ONSHORE? = Y
 DATA_TYPE = WELL
 DATA_SUB_TYPE = CROSS_SECTION
 DESCRIPTION = Encl.2 Naylor-1 Otway Basin
 Stratigraphic Cross-Section,
 Howmains-1, Flaxmans-1, Curdie-1, Boggy
 Creek-1,, by Santos [BOL] Ltd, W1318,
 PEP154. Enclosure 2 contained within
 "Naylor-1 Well Proposal Report"
 [PE909080].
 REMARKS =
 DATE_WRITTEN = 26-SEP-2000
 DATE_PROCESSED =
 DATE_RECEIVED =
 RECEIVED_FROM = Santos (BOL) Pty Ltd
 WELL_NAME = Naylor-1
 CONTRACTOR =
 AUTHOR =
 ORIGINATOR = Santos Ltd
 TOP_DEPTH =
 BOTTOM_DEPTH =
 ROW_CREATED_BY = CD000_SW

(Inserted by DNRE - Vic Govt Mines Dept)