



Company: **ESSO Australia Pty Ltd**

## 8.50 In. Section

Well: **SNA A19A**

Field: **SNAPPER**

Rig: ISDL 175

State:

# Victoria

**EcoScope\* Service  
1:500 Measured Depth  
Recorded Mode Log**

Rig:		ISDL 175	
Field:		SNAPPER	
Location:		Bass Strait	
Well:		SNA A19A	
Company:		ESSO Australia Pty Ltd	
<div style="text-align: right;"> <b>EcoScope* Service</b>  <b>1:500 Measured Depth</b>  <b>Recorded Mode Log</b> </div>			
Location			
Total depth:	4100.0 m		
Spud date:	27-Mar-08		
Run:	3	Elevation	K.B. Top Drive G.L. -55.0 m D.F. 41.7 m
Permanent datum:	Mean Sea Level	Elev.:	0.0 m
Log measured from:	Drill Floor	41.7 m above Perm. datum	
Depth reference:	Driller's Depth		
Service Order no. 07ASQA0023	X = E 589,787.584 m Y = N 5,772,180.379 m	Longitude	Latitude E 148° 1' 31.298" S 38° 11' 37.84"

## Bit Run Summary


Run number		3	4	5						
Bit size	in	8.5	8.5	8.5						
Bit start depth	m	4031.0	4100.0	4031.0						
Bit end depth	m	4100.0	4888.0	4848.0						
Top interval logged	m	4031.0	4089.6	4031.0						
Bottom interval logged	m	4089.6	4877.6	4842.5						
Begin log: time		9:34	15:10	15:33						
Begin log: date		15-Apr-08	19-Apr-08	27-Apr-08						
End log: time		19:07	0:23	23:06						
End log: date		15-Apr-08	23-Apr-08	27-Apr-08						
<b>Mud data</b>										
Depth	m	4099.0	4888.0	4888.0						
Type		Accolade SBM	Accolade SBM	Accolade SBM						
Mud weight	ppg	11.30	10.80	10.90						
Solids	%	15.80	15.60	15.70						
Chlorides	mg/L	46,623	50,501	50,423						
Rm	Ohm.m @ °C	n/a	n/a	n/a						
Rmf	Ohm.m @ °C	n/a	n/a	n/a						
Rmc	Ohm.m @ °C	n/a	n/a	n/a						

Potassium		n/a	n/a	n/a						
<b>Environmental data</b>										
<b>GR</b>										
Mud weight	ppg	11.30	10.80	10.90						
Bit size	in	8.5	8.5	8.5						
<b>Resistivity</b>										
<b>Neutron porosity</b>										
Hole Size	in	8.5	8.5	8.5						
Mud weight	ppg	11.30	10.80	10.90						
Temperature	°C	85	89	89						
Mud salinity	ppk	59.925	n/a	n/a						
Formation salinity		n/a	n/a	n/a						
Recording rate 1	SEC	6 (ARC) 10 (SON)	6 (ARC)	6 (ARC)						
Recording rate 2	SEC	2 (Ecoscope)	n/a	n/a						
Filtering GR		3 pts.	3 pts.	3 pts.						
Filtering density		3 pts.	n/a	n/a						
Filtering Neutron		3 pts.	n/a	n/a						
Company representative		G. Doty	R. Moore	M. Calicutt	R. Spence	D. Daniels				
Anadrill personnel		M. Amarasena	M. Sihite	M. Lu	J. Ikeda	C. Soper	D. Bui	F. Debacker		

<p style="text-align: center;"><b>DISCLAIMER</b></p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
<p><b>OTHER SERVICES FOR RUN 3</b></p> <p>Directional Drilling Directional Surveys Annular Pressure &amp; Temperature Shock &amp; Vibrations</p>	<p><b>OTHER SERVICES FOR RUN 4</b></p> <p>Directional Drilling Directional Surveys Annular Pressure &amp; Temperature Shock &amp; Vibrations</p>	<p><b>OTHER SERVICES FOR RUN 5</b></p> <p>Directional Drilling Directional Surveys Annular Pressure &amp; Temperature Shock &amp; Vibrations</p>
<p><b>REMARKS: RUN NUMBER 3</b></p> <p>Depth is referenced to Driller's depth</p> <p>Gamma ray is corrected for mud weight, tool size and bit size</p> <p>Resistivity is borehole compensated and environmentally corrected</p> <p>Neutron porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity and mud hydrogen index (a factor of mud weight, mud temperature and pressure)</p> <p>Neutron porosity is calculated by using a limestone matrix density of 2.71 g/cm<sup>3</sup></p> <p>SSn and LSn variables in the calibration are depicted as "exceeding limits" and Gamma-Gamma density calibration is depicted as "out of date". All inconsequential as operation was sourceless</p> <p>POOH to change out BHA (due to hole condition)</p>	<p><b>REMARKS: RUN NUMBER 4</b></p> <p>Depth is referenced to Driller's depth</p> <p>Gamma ray is corrected for mud weight, tool size and bit size</p> <p>Resistivity is borehole compensated and environmentally corrected</p> <p>POOH upon reaching TD of SNA A19A</p>	<p><b>REMARKS: RUN NUMBER 5</b></p> <p>Depth is referenced to Driller's depth</p> <p>Gamma ray is corrected for mud weight, tool size and bit size</p> <p>Resistivity is borehole compensated and environmentally corrected</p> <p>POOH due to completion of wiper trip.</p>

<b>EQUIPMENT DESCRIPTION</b>		
<b>RUN 3</b>	<b>RUN 4</b>	<b>RUN 5</b>


## DOWNHOLE EQUIPMENT



Maximum string diameter 8.50 in.

All lengths in Meters


## DOWNHOLE EQUIPMENT



Maximum string diameter 8.50 in.

All lengths in Meters

## DOWNHOLE EQUIPMENT



Maximum string diameter 8.50 in.

All lengths in Meters

Variable Name	Variable Description	Run Name & Value	
	Run Number		3
	General Information		
BHT_RM	Bottom Hole Temperature (RM)	DEGC	85.000
BSAL_RM	Mud Salinity (RM)	PPK	59.932
BS_RM	Bit Size (RM)	IN	8.500
COEF_M	User Defined FEXP in Clean Sand	----	1.650
C_WS	Overpressure correction to Sw and M	----	1.000
FEXP	Formation Factor Exponent (RM)	----	2.000
FNUM	Formation Factor Enumerator (RM)	----	1.000
FPHI_RM	Formation Factor Porosity Source (RM)	----	XPLOT
MST_RM	Mud Sample temperature (RM)	DEGC	24.000
MW_RM	Mud Weight (RM)	LB/G	11.300
OBMF_RM	Oil Based Mud (RM)	----	YES
RHOF_RM	Mud Filtrate Density (RM)	G/C3	1.000
RHOM_RM	Matrix density (RM)	G/C3	2.710
RMS_RM	Resistivity of Mud Sample (RM)	OHMM	1000.000
RWA_COMP_M	Rwa computation model		
RWA_DEN_AD	Rwa Density Input ADN		
RWA_DEN_CD	Rwa Density Input CDN		
RWA_DEN_IN	Rwa Density Input		
RWA_FORM_M	Rwa computation formation model		
RWA_RES_IN	Rwa computation resistivity input		
RWS_RM	Resistivity of Connate Water (RM)	OHMM	1.000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore ) (RM)	DEGC	10.000
TD_RM	Total Measured Depth (RM)	M	4100.000
TWS_RM	Temperature of Connate Water (RM)	DEGC	24.000
VF_ILLI	Fraction of illite in shales	----	0.500
VF_KAOL	Fraction of kaolinite in shales	----	0.500
VF_MONT	Fraction of montmorillonite in shales	----	0.000
XPDM_RM	Cross plot density porosity multiplier	----	0.675
XPNM_RM	Cross plot neutron porosity multiplier	----	0.325
	DVD		
-----	Parameters-----	Parameters-----	-----Sigma
-----	Parameters-----	Parameters-----	-----Sigma
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	DB	8.405
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	DB	8.370
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	DB	6.564
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	DB	6.610
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	DB	5.028
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	DB	4.983
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	DB	4.464
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	DB	4.503
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	DB	3.577
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	DB	3.541
ABNT	Abnormal Transmitter Indicator	----	No_Tx_Failed
ALPHA_DEN_OPT	Density Enhanced Vertical Resolution Processing Switch	----	NO
AM2A	ARC Air Cal Amplitude Offset at 2 MHz	----	-50000.000
ANISO_COMPUTE	Anisotropy Computation Option	----	YES
ATMP_ARC	ARC Select Temperature Channel	----	Annulus Temp
AZMF	Formation DIP Azimuth	DEG	0.000
BH_COMPUTE	Borehole Inversion Computation Option	----	YES
CDPTH_ARC	Process Start Depth	M	30.480
CHI_RM	Caliper High Limit from BS (RM)	IN	10.000
CLO_RM	Caliper Low Limit from BS (RM)	IN	-5.000
DIELEC_COMPUTE	Dielectric Computation Option	----	YES
DIPF	Formation DIP Angle	DEG	0.000
DTMUD	Delta-T for Mud (RM)	US/F	206.000
DTMUD_DH	Delta-T for Mud Downhole (RT)	US/F	230.700
DVDMHS	DVDM Down Hole Software Version	----	Karl2 (V2.2)
DVDM_DATA_LTB	DVDM: Create An DVDM LTB Data File	----	NO
DVD_DATA_FIX	DVDM: Create A Corrected DVDM Time Data File	----	NO
DYN_IMAGE_OPT	Generate Dynamic Normalized Image?	----	YES
EDPTH	Wizard Process Stop Depth	----	50000
EN_WIZARD	Enable ARC Wizard Processing	----	NO
ERRCT	Percentage Error Cutoff	----	4.500
EVRL	EVR Process averaging number of samples (RM)	----	49
FWVN	Firmware Version Number	----	2.200
GCSE	Generalized Caliper Selection	----	BS
GRSH	GR Shale (Invasion Computation Cutoff)	GAPI	1000.000
GR_CF	Gamma Ray Correction Factor	----	1.800
GR_O2COR_OPT	Enable Gamma Ray Oxygen Activation Correction	----	YES
HIGH_BLEND	High Resistivity Threshold for Blending	OHMM	2.000
IDQT	Image Derived Quality Threshold	----	2.000
IMAGE_MAX_DCRA	Image Density Caliper Right Scale	IN	8.000
IMAGE_MAX_IDDQ	Image Density Quality Right Scale	----	1.000
IMAGE_MAX_SPEF	Image PEF(Segment) Right Scale	----	6.000
IMAGE_MAX_SRHOB	Image RHOB(Segment) Right Scale	G/C3	2.650
IMAGE_MIN_DCRA	Image Density Caliper Left Scale	IN	2.000
IMAGE_MIN_IDDQ	Image Density Quality Left Scale	----	0.000
IMAGE_MIN_SPEF	Image PEF(Segment) Left Scale	----	2.000
IMAGE_MIN_SRHOB	Image RHOB(Segment) Left Scale	G/C3	2.050
INCLIN_B0	ARC Bias Constant (mg)	----	0.000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	----	0.000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	----	0.000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	----	0.000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	----	1.000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	----	0.000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	----	0.000

INCLIN_C3	ARC Scale Third-order Coefficient (mA/g/degC)	----	0.000
INVAS_COMPUTE	Invasion Computation Option	----	YES
JSD	Acquisition start date	----	14-Apr-08
JSD_ARC	ARC Acquisition start date	----	YES
LOW_BLEND	Low Resistivity Threshold for Blending	OHMM	1.000
MATR	Rock Matrix for Neutron Porosity Corrections	----	LIMESTONE
MSWS	ARC Wizard Model Switch Window	M	1.524
MULTIEFFECT_COM	Multi Effect Option	----	YES
NEU_DCOR_OPT	Density Correction Source for Neutron Processing	----	None
NEU_FTUBE_OPT	Far Thermal Tube Selection	----	Both
NEU_PRESCOR_OPT	Pressure Correction Source for Neutron Processing	----	Annulus Press
NEU_TEMPSCOR_OPT	Temperature Correction Source for Neutron Processing	----	Tool Temp
NTIK_SEL	Neutron Tick Channel Name	----	FAZ1
OACF	Oxygen Activation Correction Factor (RM)	----	8.000
P11AC_RM	ARC: Air Calibration For Phase T1 to R1	DEG	-999.250
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	DEG	-0.519
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	DEG	0.870
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	DEG	0.550
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	DEG	-0.934
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	DEG	-0.574
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	DEG	0.889
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	DEG	0.522
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	DEG	-0.927
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	DEG	-0.589
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	DEG	0.878
PMUD	Potassium Concentration in Mud	----	0.000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	----	P34B
PSOF_ADJ_T1	ARC: User Input Phase offset	DEG	0.000
RESTIK	ARC resistivity tick source	----	Phase
RSD	LWD run start date dd-mmm-yy	----	14-Apr-08
RUN_DURATION_OP	Run Duration Type ?	----	Normal
RWA_COMP_MOD	Rwa computation model	----	BASIC
RWA_DEN_ADN	Rwa Density Input	----	RHOB
RWA_DEN_CDN	Rwa Density Input	----	RHOB
RWA_DEN_INPUT	Rwa Density Input	----	RHOB
RWA_FORM_MOD	Rwa computation formation model	----	CLASTIC
RWA_RES_INPUT	Rwa computation resistivity input	----	RT
SDPTH	Wizard Process Start Depth	----	100
SIG_PCOR_OPT	Porosity Correction Source for Sigma Processing	----	Best
SPEC_CSG_DEPTH	Casing Depth for Spectroscopy Processing	M	30.480
SPEC_K_OPT	Potassium standard used during acquisition?	----	NO
SPL_CLAY_MODEL	SpectroLith Clay Model	----	SUBARKOSE
SPL_MG_OPT	Magnesium Flag Switch ?	----	OFF
SPL_SULFUR_MIN	SpectroLith Sulfur Mineral Option	----	PYRITE
STAB_SIZE	Stabilizer Size	IN	8.250
STOH	Top of Hole Sector	----	SECTOR_0
TRNO	Tool Run Number	M	3
TSIZ_ARC	ARC Tool Size	IN	6.750
TSNO	Tool Serial Number	----	808
UNIFORM_COMPUTE	Uniform Rock Option	----	YES
VERS_ARC	ARC Down hole software version Number	----	9.300
WPPV	Water Phase as Percent of Total Volume in OBM	----	25.000
WPSL	Salinity of the Water Phase Emulsified within the OBM	PPK	239.727
WRK	to Report Potassium Concentration	----	K_by_Wgt_%
WSDI	Window Size of Dynamic Normalization Image	M	4.572
ADHS	ARC Down Hole Software Version	----	v9.3b
APICG	ARC5 Gamma Ray Gain Factor	----	1.070
APIG	ARC Gamma Ray API Gain Factor	----	-1.000
ARC_DATA_FIX	ARC: Create A Corrected ARC Time Data File	----	NO
ARC_DATA_LTB	ARC: Create An ARC LTB Data File	----	NO
ATRN	ARC Tool Run Number	----	1
ATSN	ARC Tool Serial Number	----	1191
CALG	ARC Gamma Ray Cal Gain Factor	----	1.070
CALI_SLCT_ARC	ARC Caliper Selection	----	BITSIZE
KPER	Potassium Concentration (RM)	----	0.000
POFFSET_ARC	ARC: Pressure Offset	PSI	0.000
SHIG	ARC High Shock Risk Level	CPS	0.500
SMED	ARC Medium Shock Risk Level	CPS	0.330
SMIN	ARC Minimum Shock Risk Level	CPS	0.160
SUPD	ARC Real Time Shock Update Rate	S	30.000
TCODE_ARC	ARC Tool File Code	S	30.000
WRK	to Report Potassium Concentration (RM)	----	K_by_Wgt_%

Schlumberger Drilling &amp; Measurements

ID13 Parameter Insert Header Software version 3.0c

Variable Name	Variable Description	Run Name & Value		
	Run Number		4	5
	General Information			
BHT_RM	Bottom Hole Temperature (RM)	DEGC	89.000	89.000
BSAL_RM	Mud Salinity (RM)	PPK	N/A	N/A
BS_RM	Bit Size (RM)	IN	8.500	8.500
COEF_M	User Defined FEXP in Clean Sand	----	1.650	1.650
C_WS	Overpressure correction to Sw and M	----	1.000	1.000
FEXP	Formation Factor Exponent (RM)	----	2.000	2.000
FNUM	Formation Factor Enumerator (RM)	----	1.000	1.000

FPHI_RM	Formation Factor Porosity Source (RM)	----	XPLOT	XPLOT
MST_RM	Mud Sample temperature (RM)	DEGC	24.000	24.000
MW_RM	Mud Weight (RM)	LB/G	10.800	10.900
OBFM_RM	Oil Based Mud (RM)	----	YES	YES
RHOF_RM	Mud Filtrate Density (RM)	G/C3	1.000	1.000
RHOM_RM	Matrix density (RM)	G/C3	2.710	2.710
RMS_RM	Resistivity of Mud Sample (RM)	OHMM	1000.000	1000.000
RWA_COMP_M	Rwa computation model			
RWA_DEN_AD	Rwa Density Input ADN			
RWA_DEN_CD	Rwa Density Input CDN			
RWA_DEN_IN	Rwa Density Input			
RWA_FORM_M	Rwa computation formation model			
RWA_RES_IN	Rwa computation resistivity input			
RWS_RM	Resistivity of Connate Water (RM)	OHMM	1.000	1.000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore ) (RM)	DEGC	10.000	10.000
TD_RM	Total Measured Depth (RM)	M	4888.000	4888.000
TWS_RM	Temperature of Connate Water (RM)	DEGC	24.000	24.000
VF_ILLI	Fraction of illite in shales	----	0.500	0.500
VF_KAOL	Fraction of kaolinite in shales	----	0.500	0.500
VF_MONT	Fraction of montmorillonite in shales	----	0.000	0.000
XPDM_RM	Cross plot density porosity multiplier	----	0.675	0.675
XPNM_RM	Cross plot neutron porosity multiplier	----	0.325	0.325
ARC				
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	DB	8.405	8.405
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	DB	8.370	8.370
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	DB	6.564	6.564
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	DB	6.610	6.610
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	DB	5.028	5.028
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	DB	4.983	4.983
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	DB	4.464	4.464
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	DB	4.503	4.503
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	DB	3.577	3.577
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	DB	3.541	3.541
ABNT	Abnormal Transmitter Indicator	----	No_Tx_Failed	No_Tx_Failed
ADHS	ARC Down Hole Software Version	----	v9.3b	v9.3b
AM2A	ARC Air Cal Amplitude Offset at 2 MHz	----	-50000.000	-50000.000
ANISO_COMPUTE	Anisotropy Computation Option	----	YES	YES
APICG	ARC5 Gamma Ray Gain Factor	----	1.070	1.070
APIG	ARC Gamma Ray API Gain Factor	----	-1.000	-1.000
ARC_DATA_FIX	ARC: Create A Corrected ARC Time Data File	----	NO	NO
ARC_DATA_LTB	ARC: Create An ARC LTB Data File	----	NO	NO
ATMP_ARC	ARC Select Temperature Channel	----	Annulus_Temp	Annulus_Temp
ATRN	ARC Tool Run Number	----	4	5
ATSN	ARC Tool Serial Number	----	1191	1191
AZMF	Formation DIP Azimuth	DEG	0.000	0.000
BH_COMPUTE	Borehole Inversion Computation Option	----	YES	YES
CALG	ARC Gamma Ray Cal Gain Factor	----	1.070	1.070
CALI_SLCT_ARC	ARC Caliper Selection	----	BITSIZE	BITSIZE
CDPTH_ARC	Process Start Depth	M	30.480	30.480
DIELEC_COMPUTE	Dielectric Computation Option	----	YES	YES
DIPF	Formation DIP Angle	DEG	0.000	0.000
ERRCT	Percentage Error Cutoff	----	4.500	4.500
GRSH	GR Shale (Invasion Computation Cutoff)	GAPI	1000.000	1000.000
HIGH_BLEND	High Resistivity Threshold for Blending	OHMM	2.000	2.000
INCLIN_B0	ARC Bias Constant (mg)	----	0.000	0.000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	----	0.000	0.000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	----	0.000	0.000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	----	0.000	0.000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	----	1.000	1.000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	----	0.000	0.000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	----	0.000	0.000
INCLIN_C3	ARC Scale Third-order Coeeficient (mA/g/degC)	----	0.000	0.000
INVAS_COMPUTE	Invasion Computation Option	----	YES	YES
JSD_ARC	ARC Acquisition start date	----	18-Apr-08	26-Apr-08
KPER	Potassium Concentration (RM)	----	0.000	0.000
LOW_BLEND	Low Resistivity Threshold for Blending	OHMM	1.000	1.000
MSWS	ARC Wizard Model Switch Window	M	1.524	1.524
MULTIEFFECT_COM	Multi Effect Option	----	YES	YES
P11AC_RM	ARC: Air Calibration For Phase T1 to R1	DEG	-999.250	-999.250
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	DEG	-0.519	-0.519
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	DEG	0.870	0.870
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	DEG	0.550	0.550
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	DEG	-0.934	-0.934
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	DEG	-0.574	-0.574
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	DEG	0.889	0.889
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	DEG	0.522	0.522
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	DEG	-0.927	-0.927
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	DEG	-0.589	-0.589
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	DEG	0.878	0.878
POFFSET_ARC	ARC: Pressure Offset	PSI	0.000	0.000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	----	P34B	P34B
PSOF_ADJ_T1	ARC: User Input Phase offset	DEG	0.000	0.000
RESTIK	ARC resistivity tick source	----	Phase	Phase
RSD	LWD run start date dd-mmm-yy	----	18-Apr-08	26-Apr-08
RWA_COMP_MOD	Rwa computation model	----	BASIC	BASIC
RWA_DEN_ADN	Rwa Density Input	----	RHOB	RHOB
RWA_DEN_CDN	Rwa Density Input	----	RHOB	RHOB
RWA_DEN_INPUT	Rwa Density Input	----	RHOB	RHOB
RWA_FORM_MOD	Rwa computation formation model	----	CLASTIC	CLASTIC
RWA_RES_INPUT	Rwa computation resistivity input	----	RT	RT
SHIG	ARC High Shock Risk Level	CPS	0.500	0.500
SMED	ARC Medium Shock Risk Level	CPS	0.330	0.330
SMIN	ARC Minimum Shock Risk Level	CPS	0.160	0.160
SUPD	ARC Real Time Shock Update Rate	S	30.000	30.000
TCODE_ARC	ARC Tool File Code	S	30.000	30.000

TSIZ ARC ARC Tool Size  
UNIFORM\_COMPUTE Uniform Rock Option  
VERS\_ARC ARC Down hole software version Number  
WRK to Report Potassium Concentration (RM)

IN 6.750 6.750  
---- YES YES  
---- V9.3b v9.3b  
---- K\_by\_Wgt\_% K\_by\_Wgt\_%

Schlumberger Drilling & Measurements

ID13 Parameter Insert Header Software vers:

## IDEAL Version: ID13\_OC\_08

IDF

ARC6A-AA id13\_oc\_02

Format: EcoScope RM Log Vertical Scale: 1:500

Graphics File Created: 02-May-2008 19:35

### PIP SUMMARY

Gamma Ray Samples

Resistivity Samples

Neutron Samples

Rate of Penetration, Averaged over Last  
5ft (ROP5\_RM)  
200 (M/HR) 0

Ultrasonic Caliper, Vertical Diameter  
(UCVE)  
6 (IN) 16

Ultrasonic Caliper, Horizontal Diameter  
(UCHO)  
6 (IN) 16

Gamma Ray, Average (GRMA)  
0 (GAPI) 200

Collar  
Rotational  
Speed  
(CRPM)  
(RPM)  
0 200

ARC Phase Shift Resistivity 40 inch at 2  
MHz (P40H)

0.2 (OHMM) 2000

ARC Phase Shift Resistivity 34 inch at 2  
MHz (P34H)

0.2 (OHMM) 2000

ARC Phase Shift Resistivity 28 inch at 2  
MHz (P28H)

0.2 (OHMM) 2000


ARC Phase Shift Resistivity 22 inch at 2  
MHz (P22H)

0.2 (OHMM) 2000

ARC Phase Shift Resistivity 16 inch at 2  
MHz (P16H)

0.2 (OHMM) 2000











Best Thermal Neutron Porosity, Average  
(BPHI)  
(PU) 45 -15
















Master		0.8780
-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)





Master: 7-Apr-2008 5:16											
6.75-in. Array Resistivity Compensated Calibration											
Resistivity: Air											
Phase	Attenuation T1		Value	Phase	Attenuation T2		Value	Phase	Attenuation T3		Value
Master			8.405	Master			6.564	Master			5.028
	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)		4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)
Phase	Attenuation T4		Value	Phase	Attenuation T5		Value	Phase	Attenuation T1 at 400KHz		Value
Master			4.464	Master			3.577	Master			8.370
	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)		1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)		6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)
Phase	Attenuation T2 at 400KHz		Value	Phase	Attenuation T3 at 400KHz		Value	Phase	Attenuation T4 at 400KHz		Value
Master			6.610	Master			4.983	Master			4.503
	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)		2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)
Phase	Attenuation T5 at 400KHz		Value								
Master			3.541								
	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)								

Master: 20-Mar-2008 14:59											
6.75-in. Array Resistivity Compensated Calibration											
Gamma Ray: Blanket											
Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS									Value	
Master										5.134	
	2.780 (Minimum)			4.800 (Nominal)			6.000 (Maximum)				




EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch / Equipment Identification											
Primary Equipment:											
Tool Name and Serial Number											
Calibration Status											
Neutron Logging Source											
Density Logging Source											
Stabilizer Size											
ECO – 675				804							
Valid				PNG – C				2081-41299			
N/A											
8.25 – in.											




Master: 9-Apr-2008 6:30											
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration											
SSn LSn : Water Tank											
Phase	SSn Gain ----			Value	Phase	SSn Offset ----			Value		
Master				1.085	Master				317.9		
	0.6000 (Minimum)	1.000 (Nominal)	1.400 (Maximum)			-3.000 (Minimum)	0 (Nominal)	3.000 (Maximum)			
Phase	LSn Gain ----			Value	Phase	LSn Offset ----			Value		
Master				1.049	Master				37.38		
	0.6000 (Minimum)	1.000 (Nominal)	1.400 (Maximum)			-3.000 (Minimum)	0 (Nominal)	3.000 (Maximum)			

Master: 9-Apr-2008 6:30											
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration											
Neutron: Water Tank											
Phase	Far 2 Gain ----			Value	Phase	Far 2 Offset ----			Value		
Master				0.9766	Master				1.825		
	0.7000 (Minimum)	1.000 (Nominal)	1.300 (Maximum)			-3.000 (Minimum)	0 (Nominal)	3.000 (Maximum)			
Phase	Far 1 Gain ----			Value	Phase	Far 1 Offset ----			Value		
Master				1.000	Master				1.294		
	0.7000 (Minimum)	1.000 (Nominal)	1.300 (Maximum)			-3.000 (Minimum)	0 (Nominal)	3.000 (Maximum)			











Phase	Thermal Near gain -----			Value	Phase	Thermal Near offset -----			Value
Master				1.026	Master				44.00
0.7000 (Minimum)			1.000 (Nominal)	1.300 (Maximum)	-500.0 (Minimum)			0 (Nominal)	500.0 (Maximum)
Phase	Epithermal Near gain -----			Value	Phase	Epithermal Near offset -----			Value
Master				1.056	Master				85.55
0.7000 (Minimum)			1.000 (Nominal)	1.300 (Maximum)	-300.0 (Minimum)			0 (Nominal)	300.0 (Maximum)

Master: Calibration out of date 15-Sep-2007 12:07														
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration														
Gamma Density: Magnesium Block														
Phase	LS window 3 – Mg CPS			Value	Phase	SS window 1 – Mg CPS			Value	Phase	SS window 3 – Mg CPS			Value
Master	<div>EXCEEDS LIMIT</div>			1965	Master	<div></div>			4716	Master	<div></div>			11100
	2200 (Minimum)	3350 (Nominal)	4500 (Maximum)			4560 (Minimum)	6830 (Nominal)	9100 (Maximum)			11100 (Minimum)	16700 (Nominal)	22300 (Maximum)	

Master: Calibration out of date 15-Sep-2007 12:07														
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration														
Gamma Density: Aluminum Block														
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value	Phase	SS window 3 – Al CPS			Value
Master				368.8	Master				2457	Master				8183
	350.0 (Minimum)	575.0 (Nominal)	800.0 (Maximum)			2300 (Minimum)	3550 (Nominal)	4800 (Maximum)			7600 (Minimum)	11550 (Nominal)	15500 (Maximum)	

Master: Calibration out of date 15-Sep-2007 12:07														
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration														
Gamma Density: Background														
Phase	LS window 3 – Background		CPS	Value	Phase	SS window 1 – Background		CPS	Value	Phase	SS window 3 – Background		CPS	Value
Master				59.30	Master				72.40	Master				353.9
	50.00 (Minimum)	70.00 (Nominal)	90.00 (Maximum)			50.00 (Minimum)	75.00 (Nominal)	100.0 (Maximum)			270.0 (Minimum)	370.0 (Nominal)	470.0 (Maximum)	

Master: Calibration out of date 15-Sep-2007 12:07									
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration									
Gamma Density: Water Block Check									
Phase	Long spacing water density G/C3			Value	Phase	Short spacing water density G/C3			Value
Master	<div>EXCEEDS LIMIT</div>			1.024	Master	<div></div>			1.280
	1.026 (Minimum)	1.043 (Nominal)	1.059 (Maximum)			1.221 (Minimum)	1.256 (Nominal)	1.291 (Maximum)	

Master: 7-Apr-2008 12:08																	
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration																	
Resistivity: Air																	
Phase	Phase-Shift T1			Value	Phase	Phase-Shift T2			Value	Phase	Phase-Shift T3			Value			
Master				0.8622	Master				-0.9757	Master				0.8405			
-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)	-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)	-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)
Phase	Phase-Shift T4			Value	Phase	Phase-Shift T5			Value	Phase	Phase-Shift T1 at 400KHz			Value			
Master				-0.9681	Master				0.8605	Master				1.597			
-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)	-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)	-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)
Phase	Phase-Shift T2 at 400KHz			Value	Phase	Phase-Shift T3 at 400KHz			Value	Phase	Phase-Shift T4 at 400KHz			Value			
Master				-1.590	Master				1.596	Master				-1.610			
-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)	-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)	-4.000 (Minimum)				0 (Nominal)	4.000 (Maximum)
Phase	Phase-Shift T5 at 400KHz			Value													
Master				1.601													
-4.000 (Minimum)				0 (Nominal)								4.000 (Maximum)					

Master: 7-Apr-2008 12:08											
EcoScope Integrated Logging-While-Drilling Tool – 6.75 inch Calibration											
Resistivity: Air											
Phase	Attenuation T1		Value	Phase	Attenuation T2		Value	Phase	Attenuation T3		Value

Master		8.404	Master		6.020	Master		5.002
7.000 (Minimum)	9.000 (Nominal)	11.00 (Maximum)	4.000 (Minimum)	6.000 (Nominal)	8.000 (Maximum)	3.500 (Minimum)	5.500 (Nominal)	7.500 (Maximum)
Phase	Attenuation T4	Value	Phase	Attenuation T5	Value	Phase	Attenuation T1 at 400KHz	Value
Master		4.422	Master		3.556	Master		8.401
2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)	2.000 (Minimum)	4.000 (Nominal)	6.000 (Maximum)	7.000 (Minimum)	9.000 (Nominal)	11.00 (Maximum)
Phase	Attenuation T2 at 400KHz	Value	Phase	Attenuation T3 at 400KHz	Value	Phase	Attenuation T4 at 400KHz	Value
Master		6.038	Master		4.992	Master		4.434
4.000 (Minimum)	6.000 (Nominal)	8.000 (Maximum)	3.500 (Minimum)	5.500 (Nominal)	7.500 (Maximum)	2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)
Phase	Attenuation T5 at 400KHz	Value						
Master		3.549						
2.000 (Minimum)	4.000 (Nominal)	6.000 (Maximum)						

SCHLUMBERGER

Survey report

2-May-2008 03:11:54

Client.....: Esso Australia Pty. Ltd.  
Field.....: SNAPPER

Well.....: SNA A-19A  
Service Order no.....: 07ASQ0023  
Engineer.....: MA/MS/JI

Spud date.....: 27-Mar-08  
Last survey date.....: 23-Apr-08  
Total accepted surveys...: 297  
MD of first survey.....: 0.00 m  
MD of last survey.....: 4888.00 m

----- Survey calculation methods-----  
Method for positions.....: Minimum curvature  
Method for DLS.....: Mason & Taylor

----- Geomagnetic data -----  
Magnetic model.....: BGGM version 2007  
Magnetic date.....: 12-Apr-2008  
Magnetic field strength...: 1197.78 HCNT  
Magnetic dec (+E/W-).....: 13.01 degrees  
Magnetic dip.....: -68.71 degrees

----- Depth reference -----  
Permanent datum.....: GROUND LEVEL  
Depth reference.....: Driller's Depth  
GL above permanent.....: -51.00 m  
KB above permanent.....: Top Drive  
DF above permanent.....: 47.10 m

----- MWD survey Reference Criteria -----  
Reference G.....: 1000.02 mGal  
Reference H.....: 1197.78 HCNT  
Reference Dip.....: -68.71 degrees  
Tolerance of G.....: (+/-) 2.50 mGal  
Tolerance of H.....: (+/-) 6.00 HCNT  
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Vertical section origin-----  
Latitude (+N/S-).....: -4.23 m  
Departure (+E/W-).....: 0.54 m

----- Corrections -----  
Magnetic dec (+E/W-).....: 13.01 degrees  
Grid convergence (+E/W-)..: -0.63 degrees  
Total az corr (+E/W-).....: 13.64 degrees  
(Total az corr = magnetic dec - grid conv)  
Survey Correction Type ....: I, D  
I=Sag Corrected Inclination  
M=Schlumberger Magnetic Correction  
S=Shell Magnetic Correction  
F=Failed Axis Correction  
R=Magnetic Resonance Tool Correction  
D=Dmag Magnetic Correction

Azimuth from Vsect Origin to target: 222.93 degrees

[(c)2008 IDEAL ID13\_OC\_08]  
SCHLUMBERGER Survey Report

2-May-2008 03:11:54

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
1	0.00	0.00	0.00	0.00	0.00	0.00	-4.23	0.54	4.26	172.73	0.00	TIP	None
2	6.98	0.00	0.00	6.98	6.98	0.00	-4.23	0.54	4.26	172.73	0.00	MWD_M	None
3	51.98	0.57	256.84	45.00	51.98	0.19	-4.28	0.32	4.29	175.70	0.39	MWD_M	None
4	56.98	0.58	254.94	5.00	56.98	0.23	-4.29	0.27	4.30	176.36	0.13	MWD_M	None
5	61.98	0.57	255.53	5.00	61.98	0.27	-4.31	0.22	4.31	177.01	0.07	MWD_M	None
6	66.98	0.60	260.17	5.00	66.98	0.31	-4.32	0.17	4.32	177.68	0.34	MWD_M	None
7	71.98	0.62	257.38	5.00	71.98	0.36	-4.33	0.12	4.33	178.37	0.22	MWD_M	None
8	76.98	0.59	257.95	5.00	76.98	0.40	-4.34	0.07	4.34	179.06	0.19	MWD_M	None
9	81.98	0.64	260.43	5.00	81.98	0.44	-4.35	0.02	4.35	179.76	0.35	MWD_M	None
10	86.98	0.57	258.86	5.00	86.98	0.48	-4.36	-0.03	4.36	180.44	0.44	MWD_M	None
11	91.98	0.63	257.65	5.00	91.98	0.53	-4.37	-0.08	4.37	181.11	0.37	MWD_M	None
12	96.98	0.68	260.93	5.00	96.98	0.57	-4.38	-0.14	4.38	181.84	0.38	MWD_M	None

	13	101.98	0.79	266.49	5.00	101.98	0.62	-4.39	-0.20	4.39	182.66	0.67	MWD_M	None
	14	106.98	0.99	264.34	5.00	106.98	0.68	-4.40	-0.28	4.41	183.66	1.27	MWD_M	None
	15	111.98	1.17	266.07	5.00	111.97	0.75	-4.41	-0.38	4.42	184.86	1.12	MWD_M	None
	16	116.98	1.32	267.06	5.00	116.97	0.83	-4.41	-0.48	4.44	186.25	0.92	MWD_M	None
	17	121.98	1.45	265.71	5.00	121.97	0.92	-4.42	-0.60	4.46	187.78	0.82	MWD_M	None
	18	126.98	1.61	265.82	5.00	126.97	1.02	-4.43	-0.74	4.49	189.45	0.98	MWD_M	None
	19	131.98	1.87	266.12	5.00	131.97	1.13	-4.44	-0.89	4.53	191.31	1.59	MWD_M	None
	20	136.98	2.05	264.52	5.00	136.97	1.25	-4.46	-1.06	4.58	193.37	1.15	MWD_M	None
	21	141.98	2.26	263.84	5.00	141.96	1.40	-4.47	-1.25	4.65	195.56	1.29	MWD_M	None
	22	146.98	2.47	262.65	5.00	146.96	1.55	-4.50	-1.45	4.73	197.87	1.31	MWD_M	None
	23	151.98	2.63	261.25	5.00	151.95	1.73	-4.53	-1.67	4.83	200.25	1.05	MWD_M	None
	24	156.98	2.87	260.10	5.00	156.95	1.92	-4.57	-1.91	4.95	202.66	1.50	MWD_M	None
	25	161.98	3.08	259.03	5.00	161.94	2.12	-4.62	-2.16	5.10	205.11	1.32	MWD_M	None
	26	166.98	3.41	255.74	5.00	166.93	2.36	-4.68	-2.44	5.28	207.53	2.31	MWD_M	None
	27	171.98	3.82	253.42	5.00	171.92	2.63	-4.76	-2.74	5.50	209.94	2.65	MWD_M	None
	28	176.98	4.45	249.90	5.00	176.91	2.94	-4.88	-3.08	5.77	212.31	4.14	MWD_M	None
	29	181.98	5.11	247.18	5.00	181.89	3.32	-5.03	-3.47	6.11	214.62	4.25	MWD_M	None
	30	186.98	5.86	245.33	5.00	186.87	3.76	-5.22	-3.91	6.52	216.81	4.70	MWD_M	None
	31	191.98	6.71	243.55	5.00	191.84	4.27	-5.46	-4.40	7.01	218.88	5.32	MWD_M	None
	32	196.98	7.56	242.03	5.00	196.80	4.85	-5.74	-4.95	7.59	220.78	5.31	MWD_M	None
	33	201.98	8.27	240.91	5.00	201.75	5.50	-6.07	-5.56	8.23	222.47	4.43	MWD_M	None
	34	206.98	9.00	239.78	5.00	206.70	6.22	-6.44	-6.21	8.95	223.94	4.57	MWD_M	None
	35	211.98	9.60	238.89	5.00	211.63	7.00	-6.86	-6.91	9.73	225.21	3.76	MWD_M	None
	36	216.98	10.23	237.64	5.00	216.55	7.83	-7.31	-7.64	10.57	226.26	4.06	MWD_M	None
	37	221.98	10.86	236.40	5.00	221.47	8.71	-7.81	-8.41	11.47	227.11	4.08	MWD_M	None
	38	226.98	11.34	235.78	5.00	226.38	9.65	-8.35	-9.20	12.42	227.80	3.02	MWD_M	None
	39	231.98	11.80	235.08	5.00	231.28	10.63	-8.91	-10.03	13.42	228.37	2.93	MWD_M	None
	40	236.98	12.14	234.58	5.00	236.17	11.64	-9.51	-10.88	14.45	228.83	2.17	MWD_M	None
	41	241.98	12.47	234.17	5.00	241.05	12.69	-10.13	-11.74	15.51	229.21	2.08	MWD_M	None
	42	246.98	12.73	233.78	5.00	245.93	13.76	-10.77	-12.63	16.60	229.53	1.67	MWD_M	None
	43	251.98	12.99	233.25	5.00	250.81	14.85	-11.44	-13.52	17.71	229.78	1.74	MWD_M	None
	44	256.98	13.27	232.75	5.00	255.68	15.97	-12.12	-14.43	18.84	229.97	1.84	MWD_M	None
	45	261.98	13.57	232.33	5.00	260.54	17.12	-12.83	-15.35	20.00	230.12	1.92	MWD_M	None
	46	266.98	13.90	232.00	5.00	265.40	18.29	-13.55	-16.29	21.19	230.23	2.07	MWD_M	None
	47	271.98	14.27	231.60	5.00	270.25	19.49	-14.31	-17.24	22.41	230.32	2.33	MWD_M	None
	48	276.98	14.71	231.16	5.00	275.09	20.73	-15.09	-18.22	23.66	230.37	2.76	MWD_M	None
	49	281.98	15.25	230.52	5.00	279.92	22.01	-15.90	-19.22	24.95	230.40	3.44	MWD_M	None
	50	286.98	15.85	230.02	5.00	284.73	23.34	-16.76	-20.25	26.29	230.39	3.75	MWD_M	None
	51	291.98	16.57	229.56	5.00	289.53	24.72	-17.66	-21.32	27.68	230.36	4.46	MWD_M	None
	52	296.98	17.29	229.18	5.00	294.32	26.17	-18.61	-22.42	29.14	230.31	4.44	MWD_M	None
	53	301.98	17.94	229.04	5.00	299.08	27.67	-19.60	-23.57	30.65	230.25	3.97	MWD_M	None
	54	306.98	18.66	228.83	5.00	303.83	29.23	-20.63	-24.75	32.22	230.19	4.41	MWD_M	None
	55	311.98	19.37	228.65	5.00	308.56	30.86	-21.71	-25.98	33.85	230.12	4.34	MWD_M	None
	56	316.98	20.04	228.65	5.00	313.26	32.53	-22.82	-27.24	35.54	230.05	4.08	MWD_M	None
	57	321.98	20.68	228.71	5.00	317.95	34.26	-23.97	-28.55	37.28	229.98	3.90	MWD_M	None
	58	326.98	21.30	228.74	5.00	322.62	36.05	-25.15	-29.89	39.07	229.93	3.78	MWD_M	None
	59	331.98	21.91	228.78	5.00	327.27	37.88	-26.36	-31.28	40.91	229.87	3.72	MWD_M	None
	60	336.98	22.48	228.79	5.00	331.90	39.76	-27.61	-32.70	42.80	229.83	3.47	MWD_M	None
	61	341.98	23.12	228.76	5.00	336.51	41.68	-28.88	-34.16	44.73	229.78	3.90	MWD_M	None
	62	346.98	23.74	228.82	5.00	341.10	43.66	-30.19	-35.65	46.72	229.74	3.78	MWD_M	None
	63	351.98	24.36	228.85	5.00	345.66	45.69	-31.54	-37.19	48.76	229.70	3.78	MWD_M	None
	64	356.98	25.01	228.93	5.00	350.20	47.77	-32.91	-38.76	50.85	229.67	3.97	MWD_M	None
	65	361.98	25.69	228.95	5.00	354.72	49.89	-34.31	-40.37	52.99	229.64	4.15	MWD_M	None
	66	366.98	26.33	229.04	5.00	359.22	52.07	-35.75	-42.03	55.18	229.61	3.91	MWD_M	None
	67	371.98	26.95	229.13	5.00	363.69	54.30	-37.22	-43.72	57.42	229.59	3.79	MWD_M	None
	68	376.98	27.50	229.13	5.00	368.13	56.58	-38.72	-45.45	59.71	229.57	3.35	MWD_M	None
	69	381.98	28.03	229.19	5.00	372.56	58.89	-40.24	-47.21	62.04	229.56	3.24	MWD_M	None
	70	386.98	28.52	229.25	5.00	376.96	61.25	-41.79	-49.01	64.41	229.55	2.99	MWD_M	None
	71	391.98	28.98	229.40	5.00	381.34	63.64	-43.36	-50.83	66.81	229.54	2.84	MWD_M	None
	72	396.98	29.44	229.42	5.00	385.71	66.06	-44.94	-52.68	69.25	229.53	2.80	MWD_M	None
	73	401.98	29.82	229.46	5.00	390.05	68.52	-46.55	-54.56	71.72	229.53	2.32	MWD_M	None
	74	406.98	30.28	229.38	5.00	394.38	71.01	-48.18	-56.46	74.23	229.53	2.81	MWD_M	None
	75	411.98	30.75	229.34	5.00	398.69	73.53	-49.83	-58.39	76.76	229.52	2.87	MWD_M	None
	76	416.98	31.21	229.47	5.00	402.98	76.09	-51.51	-60.35	79.34	229.52	2.83	MWD_M	None
	77	421.98	31.67	229.52	5.00	407.24	78.68	-53.20	-62.33	81.95	229.52	2.81	MWD_M	None
	78	426.98	32.14	229.46	5.00	411.49	81.30	-54.92	-64.34	84.59	229.52	2.87	MWD_M	None
	79	431.98	32.64	229.45	5.00	415.71	83.96	-56.66	-66.37	87.27	229.51	3.05	MWD_M	None
	80	436.98	33.12	229.59	5.00	419.91	86.66	-58.42	-68.44	89.98	229.51	2.96	MWD_M	None
	81	441.98	33.60	229.64	5.00	424.08	89.39	-60.20	-70.53	92.73	229.52	2.93	MWD_M	None
	82	446.98	34.09	229.66	5.00	428.24	92.16	-62.01	-72.65	95.52	229.52	2.99	MWD_M	None
	83	451.98	34.63	229.69	5.00	432.36	94.96	-63.83	-74.81	98.34	229.53	3.29	MWD_M	None
	84	456.98	35.17	229.58	5.00	436.46	97.80	-65.69	-76.98	101.20	229.53	3.31	MWD_M	None
	85	461.98	35.72	229.51	5.00	440.54	100.68	-67.57	-79.19	104.10	229.53	3.36	MWD_M	None
	86	466.98	36.31	229.64	5.00	444.58	103.60	-69.47	-81.43	107.04	229.53	3.63	MWD_M	None
	87	471.98	36.92	229.73	5.00	448.60	106.56	-71.40	-83.70	110.02	229.53	3.73	MWD_M	None
	88	476.98	37.48	229.76	5.00	452.58	109.56	-73.36	-86.01	113.04	229.54	3.42	MWD_M	None
	89	481.98	37.99	229.72	5.00	456.53	112.60	-75.33	-88.35	116.10	229.55	3.11	MWD_M	None
	90	486.98	38.59	229.71	5.00	460.46	115.68	-77.34	-90.71	119.20	229.55	3.66	MWD_M	None
	91	491.98	39.34	229.64	5.00	464.34	118.80	-79.37	-93.11	122.35	229.55	4.58	MWD_M	None
	92	496.98	40.05	229.66	5.00	468.19	121.97	-81.44	-95.54	125.54	229.56	4.33	MWD_M	None

	93	501.98	40.71	229.70	5.00	472.00	125.19	-83.53	-98.01	128.78	229.56	4.03	MWD_M	None
	94	506.98	41.53	229.68	5.00	475.77	128.45	-85.66	-100.52	132.07	229.56	5.00	MWD_M	None
	95	511.98	42.30	229.73	5.00	479.49	131.77	-87.82	-103.06	135.41	229.57	4.70	MWD_M	None
	96	516.98	43.13	229.67	5.00	483.16	135.14	-90.02	-105.65	138.80	229.57	5.07	MWD_M	None
	97	521.98	43.89	229.72	5.00	486.79	138.56	-92.24	-108.28	142.24	229.57	4.64	MWD_M	None
	98	526.98	44.69	229.74	5.00	490.37	142.02	-94.50	-110.94	145.73	229.58	4.88	MWD_M	None
	99	531.98	45.45	229.77	5.00	493.90	145.54	-96.79	-113.64	149.27	229.58	4.63	MWD_M	None
	100	536.98	46.22	229.85	5.00	497.38	149.10	-99.10	-116.38	152.86	229.59	4.71	MWD_M	None
	101	541.98	46.87	229.97	5.00	500.82	152.70	-101.44	-119.16	156.49	229.59	4.00	MWD_M	None
	102	546.98	47.64	229.94	5.00	504.21	156.35	-103.80	-121.97	160.16	229.60	4.70	MWD_M	None
	103	551.98	48.34	229.87	5.00	507.56	160.03	-106.19	-124.81	163.88	229.61	4.28	MWD_M	None
	104	556.98	49.03	230.00	5.00	510.86	163.76	-108.61	-127.69	167.63	229.62	4.25	MWD_M	None
	105	561.98	49.60	230.01	5.00	514.12	167.52	-111.05	-130.59	171.42	229.62	3.48	MWD_M	None
	106	566.98	50.07	230.01	5.00	517.35	171.32	-113.50	-133.52	175.24	229.63	2.87	MWD_M	None
	107	571.98	50.38	230.08	5.00	520.54	175.13	-115.97	-136.46	179.09	229.64	1.92	MWD_M	None
	108	576.98	50.71	230.12	5.00	523.72	178.96	-118.45	-139.43	182.95	229.65	2.02	MWD_M	None
	109	581.98	51.07	230.13	5.00	526.88	182.81	-120.93	-142.40	186.83	229.66	2.20	MWD_M	None
	110	586.98	51.42	230.05	5.00	530.01	186.68	-123.44	-145.39	190.72	229.67	2.17	MWD_M	None
	111	591.98	51.74	230.02	5.00	533.11	190.56	-125.95	-148.40	194.64	229.68	1.96	MWD_M	None
	112	596.98	52.08	230.00	5.00	536.20	194.47	-128.48	-151.41	198.58	229.68	2.07	MWD_M	None
	113	601.98	52.44	229.98	5.00	539.26	198.39	-131.02	-154.44	202.53	229.69	2.20	MWD_M	None
	114	606.98	52.85	229.89	5.00	542.29	202.34	-133.58	-157.48	206.51	229.69	2.54	MWD_M	None
	115	611.98	53.20	229.98	5.00	545.30	206.30	-136.15	-160.54	210.50	229.70	2.18	MWD_M	None
	116	616.98	53.63	229.91	5.00	548.28	210.29	-138.74	-163.61	214.51	229.70	2.64	MWD_M	None
	117	621.98	54.09	229.87	5.00	551.23	214.30	-141.34	-166.70	218.55	229.71	2.81	MWD_M	None
	118	626.98	54.59	229.82	5.00	554.14	218.33	-143.96	-169.80	222.61	229.71	3.06	MWD_M	None
	119	631.98	55.15	229.71	5.00	557.02	222.39	-146.60	-172.93	226.70	229.71	3.46	MWD_M	None
	120	636.98	55.66	229.73	5.00	559.86	226.48	-149.26	-176.07	230.82	229.71	3.11	MWD_M	None
	121	641.98	56.22	229.71	5.00	562.66	230.59	-151.94	-179.23	234.96	229.71	3.42	MWD_M	None
	122	646.98	56.86	229.62	5.00	565.42	234.73	-154.64	-182.41	239.13	229.71	3.93	MWD_M	None
	123	651.98	57.51	229.47	5.00	568.13	238.91	-157.36	-185.60	243.34	229.71	4.04	MWD_M	None
	124	656.98	58.07	229.45	5.00	570.79	243.11	-160.11	-188.82	247.57	229.70	3.42	MWD_M	None
	125	661.98	58.58	229.49	5.00	573.42	247.34	-162.88	-192.05	251.82	229.70	3.12	MWD_M	None
	126	666.98	59.12	229.36	5.00	576.00	251.59	-165.66	-195.30	256.10	229.69	3.36	MWD_M	None
	127	671.98	59.65	229.20	5.00	578.55	255.86	-168.47	-198.56	260.40	229.69	3.34	MWD_M	None
	128	676.98	61.46	229.13	5.00	581.01	260.19	-171.32	-201.86	264.76	229.68	11.04	MWD_M	None
	129	681.98	62.53	228.98	5.00	583.35	264.58	-174.21	-205.19	269.17	229.67	6.57	MWD_M	None
	130	686.98	62.08	228.89	5.00	585.68	268.99	-177.12	-208.53	273.60	229.66	2.79	MWD_M	None
	131	691.98	62.38	228.87	5.00	588.01	273.39	-180.03	-211.86	278.02	229.64	1.83	MWD_M	None
	132	696.98	62.97	228.86	5.00	590.30	277.80	-182.95	-215.21	282.46	229.63	3.60	MWD_M	None
	133	701.98	63.49	228.85	5.00	592.56	282.24	-185.89	-218.57	286.93	229.62	3.17	MWD_M	None
	134	706.98	64.01	228.88	5.00	594.77	286.70	-188.84	-221.95	291.41	229.61	3.17	MWD_M	None
	135	711.98	63.74	229.00	5.00	596.97	291.17	-191.79	-225.33	295.90	229.60	1.77	MWD_M	None
	136	716.98	64.20	229.24	5.00	599.16	295.64	-194.73	-228.73	300.39	229.59	3.10	MWD_M	None
	137	721.98	66.54	229.69	5.00	601.25	300.15	-197.68	-232.18	304.94	229.59	14.48	MWD_M	None
	138	726.98	66.41	230.21	5.00	603.24	304.70	-200.63	-235.69	309.52	229.59	3.01	MWD_M	None
	139	731.98	67.11	230.69	5.00	605.21	309.26	-203.55	-239.24	314.12	229.61	5.04	MWD_M	None
	140	736.98	66.29	231.14	5.00	607.19	313.80	-206.45	-242.80	318.71	229.63	5.60	MWD_M	None
	141	741.98	66.73	231.72	5.00	609.19	318.34	-209.31	-246.39	323.29	229.65	4.21	MWD_M	None
	142	746.98	66.99	232.33	5.00	611.15	322.88	-212.14	-250.01	327.88	229.68	3.77	MWD_M	None
	143	751.98	66.05	233.16	5.00	613.14	327.40	-214.91	-253.66	332.46	229.73	7.37	MWD_M	None
	144	756.98	65.58	234.19	5.00	615.19	331.88	-217.62	-257.33	337.01	229.78	6.40	MWD_M	None
	145	761.98	63.99	235.32	5.00	617.32	336.31	-220.23	-261.03	341.52	229.85	11.52	MWD_M	None
	146	766.98	63.80	236.33	5.00	619.52	340.68	-222.75	-264.74	345.99	229.92	5.65	MWD_M	None
	147	771.98	63.66	237.08	5.00	621.73	345.04	-225.21	-268.49	350.44	230.01	4.19	MWD_M	None
	148	776.98	63.71	237.52	5.00	623.95	349.38	-227.63	-272.26	354.88	230.10	2.42	MWD_M	None
	149	781.98	63.63	237.58	5.00	626.17	353.71	-230.04	-276.04	359.33	230.19	0.59	MWD_M	None
	150	786.98	64.25	237.59	5.00	628.36	358.06	-232.44	-279.84	363.78	230.29	3.78	MWD_M	None
	151	791.98	64.09	237.61	5.00	630.54	362.41	-234.85	-283.64	368.25	230.37	0.98	MWD_M	None
	152	796.98	64.73	237.63	5.00	632.70	366.78	-237.27	-287.44	372.72	230.46	3.90	MWD_M	None
	153	801.98	65.08	237.59	5.00	634.82	371.16	-239.70	-291.27	377.21	230.55	2.14	MWD_M	None
	154	806.98	65.42	237.57	5.00	636.92	375.55	-242.13	-295.10	381.72	230.63	2.08	MWD_M	None
	155	811.98	65.16	237.55	5.00	639.01	379.94	-244.57	-298.93	386.23	230.71	1.59	MWD_M	None
	156	816.98	65.13	237.47	5.00	641.11	384.33	-247.00	-302.76	390.74	230.79	0.48	MWD_M	None
	157	818.00	65.15	237.47	1.02	641.54	385.23	-247.50	-303.54	391.66	230.81	0.60	MWD_M	None
	158	825.33	66.85	236.89	7.33	644.52	391.72	-251.13	-309.17	398.31	230.91	7.40	MWD_M	None
	159	844.01	67.54	235.57	18.68	651.76	408.48	-260.70	-323.48	415.46	231.13	2.28	MWD_M	None
	160	934.88	72.09	232.69	90.87	683.11	492.12	-310.68	-392.55	500.62	231.64	1.78	MWD_M	None
	161	964.33	73.97	231.11	29.45	691.71	519.94	-328.06	-414.71	528.78	231.65	2.50	MWD_M	None
	162	993.65	75.85	229.32	29.32	699.34	548.02	-346.18	-436.46	557.08	231.58	2.65	MWD_M	None
	163	1022.61	78.51	227.17	28.96	705.77	576.13	-364.98	-457.52	585.27	231.42	3.56	MWD_M	None
	164	1051.74	79.96	224.41	29.13	711.21	604.71	-384.94	-478.03	613.75	231.16	3.22	MWD_M	None
	165	1080.99	80.88	221.07	29.25	716.08	633.54	-406.12	-497.60	642.29	230.78	3.56	MWD_M	None
	166	1109.77	81.36	218.53	28.78	720.52	661.93	-427.96	-515.80	670.23	230.32	2.71	MWD_M	None
	167	1139.06	81.18	218.70	29.29	724.97	690.80	-450.58	-533.87	698.60	229.84	0.26	MWD_M	None
	168	1168.54	81.15	219.37	29.48	729.49	719.86	-473.21	-552.22	727.23	229.41	0.69	MWD_M	None
	169	1197.52	81.19	220.70	28.98	733.94	748.46	-495.13	-570.64	755.50	229.05	1.38	MWD_M	None
	170	1226.81	81.37	221.45	29.29	738.38	777.40	-516.96	-589.66	784.18	228.76	0.79	MWD_M	None
	171	1256.11	81.22	220.88	29.30	742.82	806.35	-538.76	-608.72	812.90	228.49	0.61	MWD_M	None
	172	1286.01	81.22	220.82	29.80	747.38	835.88	-561.11	-628.05	842.20	228.22	0.06	MWD_M	None

172	1280.01	81.22	220.82	29.50	747.38	855.88	-501.11	-828.85	842.20	228.22	0.86	MWD_M	None
173	1314.74	80.98	220.55	28.53	751.83	864.24	-582.64	-646.55	870.34	227.98	0.38	MWD_M	None
174	1342.72	81.24	219.97	27.98	756.15	891.85	-603.73	-664.42	897.75	227.74	0.69	MWD_M	None
175	1368.44	81.53	219.81	25.72	760.00	917.25	-623.24	-680.73	922.94	227.52	0.39	MWD_M	None
176	1401.74	81.16	220.34	33.30	765.02	950.13	-648.44	-701.92	955.60	227.27	0.59	MWD_M	None
177	1431.03	80.87	220.65	29.29	769.59	979.03	-670.44	-720.71	984.33	227.07	0.44	MWD_M	None
178	1458.21	81.11	220.57	27.18	773.85	1005.86	-690.82	-738.18	1011.01	226.90	0.28	MWD_M	None
179	1487.53	80.72	220.01	29.32	778.48	1034.78	-712.90	-756.90	1039.77	226.71	0.70	MWD_M	None
180	1517.39	80.23	220.32	29.86	783.42	1064.19	-735.40	-775.90	1069.04	226.53	0.59	MWD_M	None
181	1545.95	80.47	220.05	28.56	788.20	1092.31	-756.91	-794.07	1097.02	226.37	0.38	MWD_M	None
182	1576.23	80.53	219.86	30.28	793.20	1122.14	-779.81	-813.24	1126.71	226.20	0.20	MWD_M	None
183	1605.64	80.15	220.46	29.41	798.14	1151.10	-801.96	-831.94	1155.54	226.05	0.73	MWD_M	None
184	1634.87	80.32	220.54	29.23	803.09	1179.88	-823.87	-850.65	1184.22	225.92	0.20	MWD_M	None
185	1663.67	80.73	221.96	28.80	807.84	1208.27	-845.23	-869.38	1212.53	225.81	1.54	MWD_M	None
186	1693.30	80.64	221.29	29.63	812.63	1237.50	-867.08	-888.80	1241.69	225.71	0.69	MWD_M	None
187	1721.76	80.72	220.31	28.46	817.24	1265.57	-888.34	-907.15	1269.68	225.60	1.04	MWD_M	None
188	1750.85	80.65	220.10	29.09	821.95	1294.24	-910.27	-925.68	1298.26	225.48	0.23	MWD_M	None
189	1778.12	80.57	219.58	27.27	826.40	1321.11	-930.92	-942.92	1325.04	225.37	0.58	MWD_M	None
190	1808.70	80.38	219.55	30.58	831.46	1351.21	-954.17	-962.13	1355.04	225.24	0.19	MWD_M	None
191	1838.39	80.83	220.24	29.69	836.31	1380.46	-976.65	-980.92	1384.21	225.13	0.84	MWD_M	None
192	1867.48	80.28	220.10	29.09	841.08	1409.13	-998.57	-999.43	1412.80	225.02	0.59	MWD_M	None
193	1896.95	80.70	221.42	29.47	845.95	1438.17	-1020.59	-1018.40	1441.79	224.94	1.41	MWD_M	None
194	1925.66	81.13	222.12	28.71	850.48	1466.51	-1041.73	-1037.29	1470.09	224.88	0.86	MWD_M	None
195	1953.25	80.70	221.87	27.59	854.84	1493.75	-1061.98	-1055.52	1497.30	224.83	0.55	MWD_M	None
196	1983.62	81.07	221.75	30.37	859.65	1523.73	-1084.33	-1075.51	1527.25	224.77	0.39	MWD_M	None
197	2012.53	80.93	221.32	28.91	864.17	1552.28	-1105.70	-1094.44	1555.76	224.71	0.47	MWD_M	None
198	2042.33	80.87	221.97	29.80	868.89	1581.70	-1127.69	-1113.99	1585.14	224.65	0.66	MWD_M	None
199	2072.85	80.93	221.91	30.52	873.71	1611.83	-1150.11	-1134.14	1615.24	224.60	0.08	MWD_M	None
200	2101.05	80.96	222.26	28.20	878.15	1639.67	-1170.78	-1152.80	1643.07	224.56	0.37	MWD_M	None
201	2130.10	80.70	222.11	29.05	882.78	1668.35	-1192.03	-1172.06	1671.72	224.52	0.31	MWD_M	None
202	2158.30	80.73	221.62	28.20	887.33	1696.18	-1212.75	-1190.63	1699.52	224.47	0.52	MWD_M	None
203	2187.92	80.47	221.13	29.62	892.17	1725.39	-1234.68	-1209.95	1728.70	224.42	0.56	MWD_M	None
204	2216.87	80.29	220.82	28.95	897.01	1753.91	-1256.23	-1228.66	1757.19	224.36	0.37	MWD_M	None
205	2246.30	80.58	220.42	29.43	901.90	1782.91	-1278.26	-1247.56	1786.15	224.30	0.51	MWD_M	None
206	2275.82	80.41	220.26	29.52	906.77	1812.00	-1300.45	-1266.40	1815.20	224.24	0.24	MWD_M	None
207	2304.97	80.52	219.89	29.15	911.60	1840.71	-1322.45	-1284.91	1843.87	224.18	0.40	MWD_M	None
208	2334.71	80.58	220.07	29.74	916.48	1870.01	-1344.93	-1303.76	1873.13	224.11	0.19	MWD_M	None
209	2363.60	80.32	220.65	28.89	921.28	1898.47	-1366.64	-1322.21	1901.56	224.05	0.66	MWD_M	None
210	2391.27	80.31	220.78	27.67	925.93	1925.72	-1387.31	-1340.00	1928.79	224.01	0.14	MWD_M	None
211	2422.94	80.52	221.30	31.67	931.20	1956.93	-1410.86	-1360.51	1959.98	223.96	0.53	MWD_M	None
212	2450.47	80.82	221.00	27.53	935.67	1984.08	-1431.32	-1378.38	1987.11	223.92	0.47	MWD_M	None
213	2480.06	80.93	220.99	29.59	940.36	2013.28	-1453.37	-1397.55	2016.29	223.88	0.11	MWD_M	None
214	2510.37	81.02	220.91	30.31	945.11	2043.20	-1475.98	-1417.17	2046.19	223.84	0.12	MWD_M	None
215	2537.19	80.76	221.32	26.82	949.36	2069.67	-1495.93	-1434.58	2072.64	223.80	0.55	MWD_M	None
216	2567.88	80.26	221.91	30.69	954.42	2099.93	-1518.56	-1454.68	2102.89	223.77	0.76	MWD_M	None
217	2595.87	80.60	221.41	27.99	959.07	2127.52	-1539.18	-1473.03	2130.47	223.74	0.65	MWD_M	None
218	2624.74	80.58	222.25	28.87	963.79	2156.00	-1560.40	-1492.02	2158.93	223.72	0.88	MWD_M	None
219	2654.71	80.64	222.52	29.97	968.68	2185.57	-1582.24	-1511.96	2188.49	223.70	0.28	MWD_M	None
220	2683.77	80.82	222.05	29.06	973.37	2214.25	-1603.46	-1531.25	2217.17	223.68	0.52	MWD_M	None
221	2712.74	80.67	221.95	28.97	978.02	2242.83	-1624.71	-1550.38	2245.75	223.66	0.19	MWD_M	None
222	2742.20	80.67	220.94	29.46	982.80	2271.89	-1646.50	-1569.63	2274.79	223.63	1.03	MWD_M	None
223	2772.49	80.95	220.30	30.29	987.64	2301.77	-1669.20	-1589.09	2304.65	223.59	0.70	MWD_M	None
224	2800.58	80.86	220.32	28.09	992.08	2329.48	-1690.35	-1607.04	2332.35	223.55	0.10	MWD_M	None
225	2829.67	80.81	219.94	29.09	996.71	2358.16	-1712.31	-1625.55	2361.01	223.51	0.40	MWD_M	None
226	2858.19	80.90	220.73	28.52	1001.25	2386.29	-1733.77	-1643.77	2389.13	223.47	0.84	MWD_M	None
227	2887.36	80.86	220.63	29.17	1005.87	2415.07	-1755.61	-1662.54	2417.90	223.44	0.11	MWD_M	None
228	2916.76	80.84	221.21	29.40	1010.54	2444.08	-1777.54	-1681.56	2446.89	223.41	0.59	MWD_M	None
229	2945.85	80.61	221.74	29.09	1015.23	2472.78	-1799.05	-1700.57	2475.59	223.39	0.60	MWD_M	None
230	2975.36	80.16	222.19	29.51	1020.16	2501.87	-1820.69	-1720.03	2504.67	223.37	0.65	MWD_M	None
231	3003.97	80.25	221.72	28.61	1025.03	2530.06	-1841.65	-1738.87	2532.86	223.36	0.50	MWD_M	None
232	3033.50	79.77	222.24	29.53	1030.15	2559.14	-1863.27	-1758.33	2561.93	223.34	0.72	MWD_M	None
233	3062.62	79.77	221.55	29.12	1035.32	2587.79	-1884.60	-1777.46	2590.58	223.32	0.71	MWD_M	None
234	3091.61	79.54	222.28	28.99	1040.53	2616.30	-1905.83	-1796.51	2619.09	223.31	0.79	MWD_M	None
235	3120.91	79.71	222.33	29.30	1045.81	2645.12	-1927.14	-1815.91	2647.91	223.30	0.18	MWD_M	None
236	3149.93	80.58	222.12	29.02	1050.77	2673.71	-1948.31	-1835.13	2676.49	223.29	0.94	MWD_M	None
237	3178.97	80.73	222.47	29.04	1055.49	2702.36	-1969.51	-1854.41	2705.14	223.28	0.40	MWD_M	None
238	3208.02	81.60	222.14	29.05	1059.95	2731.07	-1990.74	-1873.73	2733.84	223.27	0.97	MWD_M	None
239	3237.27	81.02	221.67	29.25	1064.37	2759.98	-2012.26	-1893.04	2762.75	223.25	0.77	MWD_M	None
240	3266.58	80.75	221.14	29.31	1069.01	2788.91	-2033.96	-1912.18	2791.68	223.23	0.61	MWD_M	None
241	3295.91	80.38	220.73	29.33	1073.82	2817.82	-2055.82	-1931.14	2820.59	223.21	0.57	MWD_M	None
242	3324.75	80.81	220.45	28.84	1078.53	2846.25	-2077.43	-1949.65	2849.01	223.18	0.54	MWD_M	None
243	3354.19	80.76	220.25	29.44	1083.25	2875.28	-2099.57	-1968.47	2878.03	223.15	0.21	MWD_M	None
244	3383.34	81.16	220.52	29.15	1087.83	2904.04	-2121.50	-1987.12	2906.79	223.13	0.50	MWD_M	None
245	3411.85	80.90	220.17	28.51	1092.27	2932.17	-2142.97	-2005.35	2934.92	223.10	0.46	MWD_M	None
246	3441.10	80.72	219.86	29.25	1096.94	2961.01	-2165.08	-2023.92	2963.75	223.07	0.37	MWD_M	None
247	3471.00	80.32	220.93	29.90	1101.87	2990.47	-2187.54	-2043.03	2993.21	223.04	1.15	MWD_M	None
248	3499.53	81.08	221.49	28.53	1106.48	3018.62	-2208.72	-2061.58	3021.35	223.03	1.00	MWD_M	None
249	3526.72	80.72	221.36	27.19	1110.78	3045.45	-2228.85	-2079.34	3048.19	223.01	0.43	MWD_M	None
250	3558.23	80.67	220.79	31.51	1115.88	3076.53	-2252.29	-2099.77	3079.26	222.99	0.55	MWD_M	None
251	3586.63	80.64	221.34	28.40	1120.49	3104.54	-2273.42	-2118.18	3107.27	222.98	0.58	MWD_M	None

252	3615.78	80.57	221.37	29.15	1125.25	3133.29	-2295.01	-2137.18	3136.02	222.96	0.08	MWD_M	None
253	3645.77	80.55	221.74	29.99	1130.16	3162.86	-2317.15	-2156.81	3165.59	222.95	0.37	MWD_M	None
254	3673.81	80.08	220.61	28.04	1134.88	3190.49	-2337.95	-2175.00	3193.22	222.93	1.31	MWD_M	None
255	3704.01	76.84	220.68	30.20	1140.92	3220.05	-2360.40	-2194.27	3222.78	222.91	3.27	MWD_M	None
256	3733.39	73.53	220.93	29.38	1148.43	3248.43	-2381.90	-2212.83	3251.16	222.89	3.44	MWD_M	None
257	3762.33	71.06	220.58	28.94	1157.23	3275.98	-2402.78	-2230.83	3278.71	222.87	2.63	MWD_M	None
258	3791.82	68.62	220.92	29.49	1167.40	3303.64	-2423.75	-2248.90	3306.37	222.86	2.54	MWD_M	None
259	3821.50	66.51	220.69	29.68	1178.72	3331.05	-2444.51	-2266.82	3333.79	222.84	2.18	MWD_M	None
260	3849.31	64.23	220.95	27.81	1190.31	3356.32	-2463.64	-2283.35	3359.05	222.82	2.51	MWD_M	None
261	3878.48	61.05	220.70	29.17	1203.72	3382.20	-2483.24	-2300.28	3384.94	222.81	3.33	MWD_M	None
262	3907.65	57.84	220.86	29.17	1218.54	3407.30	-2502.26	-2316.69	3410.04	222.79	3.36	MWD_M	None
263	3936.40	54.67	221.73	28.75	1234.51	3431.19	-2520.22	-2332.46	3433.93	222.78	3.45	MWD_M	None
264	3965.37	51.73	222.11	28.97	1251.86	3454.38	-2537.48	-2347.95	3457.12	222.78	3.11	MWD_M	None
265	3995.09	48.94	222.61	29.72	1270.83	3477.26	-2554.39	-2363.37	3480.00	222.78	2.89	MWD_M	None
266	4016.94	47.73	222.56	21.85	1285.36	3493.58	-2566.41	-2374.41	3496.32	222.77	1.69	MWD_M	None
267	4041.42	47.23	222.59	24.48	1301.90	3511.62	-2579.69	-2386.62	3514.37	222.77	0.62	PUP	None
268	4067.92	45.79	221.18	26.50	1320.14	3530.84	-2594.00	-2399.45	3533.59	222.77	2.03	MWD_M	None
269	4097.13	41.11	219.89	29.21	1341.34	3550.91	-2609.26	-2412.51	3553.65	222.76	4.97	MWD_M	None
270	4126.20	39.29	219.11	29.07	1363.54	3569.64	-2623.74	-2424.45	3572.39	222.74	1.98	MWD_M	None
271	4155.65	37.03	218.71	29.45	1386.70	3587.79	-2637.89	-2435.88	3590.54	222.72	2.35	MWD_M	None
272	4184.64	35.46	219.52	28.99	1410.08	3604.89	-2651.19	-2446.69	3607.65	222.70	1.73	MWD_M	None
273	4214.31	35.68	220.61	29.67	1434.21	3622.13	-2664.40	-2457.80	3624.89	222.69	0.69	MWD_M	None
274	4243.31	35.95	221.23	29.00	1457.73	3639.08	-2677.22	-2468.91	3641.85	222.68	0.48	MWD_M	None
275	4272.77	36.06	220.84	29.46	1481.56	3656.39	-2690.29	-2480.28	3659.16	222.67	0.26	MWD_M	None
276	4301.99	36.16	220.59	29.22	1505.17	3673.60	-2703.34	-2491.52	3676.37	222.67	0.19	MWD_M	None
277	4331.45	36.23	221.07	29.46	1528.94	3690.99	-2716.50	-2502.89	3693.76	222.66	0.30	MWD_M	None
278	4360.49	35.20	221.86	29.04	1552.52	3707.93	-2729.21	-2514.12	3710.71	222.65	1.18	MWD_M	None
279	4389.93	34.64	223.09	29.44	1576.66	3724.78	-2741.64	-2525.49	3727.56	222.65	0.93	MWD_M	None
280	4419.22	34.97	222.89	29.29	1600.71	3741.50	-2753.86	-2536.89	3744.28	222.65	0.36	MWD_M	None
281	4448.36	36.43	221.56	29.14	1624.37	3758.50	-2766.46	-2548.32	3761.28	222.65	1.73	MWD_M	None
282	4477.64	37.00	220.81	29.28	1647.84	3776.00	-2779.63	-2559.84	3778.78	222.64	0.75	MWD_M	None
283	4507.15	35.14	220.89	29.51	1671.70	3793.36	-2792.77	-2571.21	3796.14	222.63	1.92	MWD_M	None
284	4536.39	34.10	223.60	29.24	1695.76	3809.97	-2805.07	-2582.37	3812.75	222.63	1.94	MWD_M	None
285	4565.71	35.32	225.42	29.32	1719.86	3826.66	-2816.97	-2594.07	3829.43	222.64	1.66	MWD_M	None
286	4595.07	35.27	225.01	29.36	1743.83	3843.61	-2828.92	-2606.12	3846.38	222.65	0.25	MWD_M	None
287	4624.34	35.73	224.75	29.27	1767.66	3860.59	-2840.97	-2618.11	3863.37	222.66	0.50	MWD_M	None
288	4653.30	34.67	224.46	28.96	1791.32	3877.28	-2852.85	-2629.83	3880.05	222.67	1.13	MWD_M	None
289	4682.94	34.47	224.25	29.64	1815.73	3894.09	-2864.88	-2641.59	3896.86	222.68	0.24	MWD_M	None
290	4712.04	36.02	222.69	29.10	1839.49	3910.88	-2877.07	-2653.14	3913.65	222.68	1.88	MWD_M	None
291	4741.51	35.33	223.07	29.47	1863.43	3928.07	-2889.66	-2664.83	3930.84	222.68	0.75	MWD_M	None
292	4771.06	35.17	223.40	29.55	1887.56	3945.12	-2902.09	-2676.51	3947.89	222.68	0.26	MWD_M	None
293	4800.37	35.36	223.75	29.31	1911.49	3962.04	-2914.35	-2688.18	3964.81	222.69	0.29	MWD_M	None
294	4829.42	35.12	224.63	29.05	1935.22	3978.80	-2926.36	-2699.86	3981.56	222.69	0.59	MWD_M	None
295	4858.67	35.48	224.20	29.25	1959.09	3995.70	-2938.44	-2711.69	3998.46	222.70	0.46	MWD_M	None
296	4868.24	35.14	223.69	9.57	1966.90	4001.23	-2942.42	-2715.53	4003.99	222.70	1.43	MWD_M	None
297	4888.00	35.13	223.85	19.76	1983.06	4012.60	-2950.63	-2723.40	4015.36	222.71	0.14	Projection to	

[(c)2008 IDEAL ID13\_OC\_08]

Company:

ESSO Australia Pty Ltd

Schlumberger

Well:

SNA A19A

Field:

SNAPPER

Rig:

ISDL 175

8.50 In. Section

State:

Victoria

EcoScope\* Service

1:500 Measured Depth

Recorded Mode Log

