

Mud type is KCL/PHPA/Glycol.

POOH for bit change.

POOH for bit change.

POOH for bit change.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

EQUIPMENT DESCRIPTION

RUN1




RUN2

RUN3

DOWNHOLE EQUIPMENT

DOWNHOLE EQUIPMENT

DOWNHOLE EQUIPMENT



6-1/2 in. PMDC S/N: 97081023 6-3/4 in. PowerPak* Motor A675XP 7850 S/N: 1437 1.5 deg. Bent Housing 8-3/8 in. Motor Sleeve REED Hycalog MT Bit OD: 8-1/2 in. XS4 S/N: 749555 Maximum string diameter 8.50 in. All lengths in Meters	7.92	6-1/2 in. PMDC S/N: 97081023 6-3/4 in. PowerPak* Motor A675XP 7850 S/N: 1437 1.5 deg. Bent Housing 8-3/8 in. Motor Sleeve REED Hycalog PDC Bit OD: 8-1/2 in. RSX192 S/N: 205899 Maximum string diameter 8.50 in. All lengths in Meters	7.88	6-1/2 in. PMDC S/N: 97081023 6-3/4 in. PowerPak* Motor A675XP 7850 S/N: 3604 0.78 deg. Bent Housing 8-3/8 in. Motor Sleeve Security TCI Bit OD: 8-1/2 in. TD51AKPRDH S/N: M16961 Maximum string diameter 8.50 in. All lengths in Meters	7.92
--	------	--	------	---	------

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN4 Directional Drilling Directional Surveys	OTHER SERVICES FOR RUN5 Directional Drilling Directional Surveys	OTHER SERVICES FOR RUN6 Directional Drilling Directional Surveys
REMARKS: RUN NUMBER 4 8-1/2 in. hole was drilled from 1744.9 m to 2073.9 m TVD. Erratic GR data removed from 1731.6 m to 1776.4 m TVD. Erratic data was due to Incorrect Surface system initialization. Depth is referenced to Driller's depth. Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight. Mud type is KCL/PHPA/Glycol. POOH for bit change.	REMARKS: RUN NUMBER 5 8-1/2 in. hole was drilled from 2073.9 m to 2409.8 m TVD. Depth is referenced to Driller's depth. Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight. Mud type is KCL/PHPA/Glycol. POOH due to PowerPak* motor failure.	REMARKS: RUN NUMBER 6 8-1/2 in. hole was drilled from 2409.8 m to 2608.9 m TVD. Depth is referenced to Driller's depth. Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight. Mud type is KCL/PHPA/Glycol. POOH for Coring run.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

EQUIPMENT DESCRIPTION

RUN4

RUN5

RUN6

DOWNHOLE EQUIPMENT

6-3/4 in. PowerPulse* 22.58
MDC: 066-AB
MEC: 212-BA
MDI: 1096-BC
MGR: 503-AA
DH Software: V7.0 C00

D&I — 18.28
GR — 17.63

6-1/2 in. PMDC 14.37
S/N: ANA98-007

6-1/2 in. NM Roller Reamer 11.61
S/N: GU2317R
Reamer OD: 8-3/8 in.

6-1/2 in. PMDC 9.42
S/N: 97081023

6-3/4 in. PowerPak* Motor 7.90
A675XP 7850
S/N: 3604
0.78 deg. Bent Housing

DOWNHOLE EQUIPMENT

6-1/2 in. PowerPulse* 22.45
MDC: 066-AB
MEC: 212-BA
MDI: 1096-BC
MGR: 503-AA
DH Software: V7.0 C00

D&I — 18.15
GR — 17.50

6-1/2 in. NM Roller Reamer 14.24
S/N: GU2298
Reamer OD: 8-3/8 in.

6-1/2 in. PDMC 12.16
S/N: ANA98-007

6-1/2 in. PMDC 9.40
S/N: 97081023

6-3/4 in. PowerPak* Motor 7.88
A675XP 7850
S/N: 3604
1.15 deg. Bent Housing

DOWNHOLE EQUIPMENT

6-3/4 in. PowerPulse* 22.49
MDC: 066-AB
MEC: 212-BA
MDI: 1096-BC
MGR: 503-AA
DH Software: V7.0 C00

D&I — 18.19
GR — 17.54

6-1/2 in. PMDC 14.28
S/N: ANA98-007

6-1/2 in. NM Roller Reamer 11.52
S/N: GU2298
Reamer OD: 8-3/8 in.

6-1/2 in. PMDC 9.44
S/N: 97081023

6-3/4 in. PowerPak* Motor 7.92
A675XP 7850
S/N: ASQ0003
0.78 deg. Bent Housing

EQUIPMENT DESCRIPTION

RUN7

RUN

RUN

DOWNHOLE EQUIPMENT

6-3/4 in. PowerPulse*
MDC: Y927-AC
MEC: 570-BA
MDI: 586-BC
MGR: 512-AA
DH Software: V7.0 C00



23.39

D&I

19.09

GR

18.44

6-1/2 in. PMDC
S/N: ANA98-700



14.94

6-1/2 in. PMDC
S/N: 97081023



12.18

6-1/2 in. NM Roller Reamer
S/N: GU2298
Reamer OD: 8-3/8 in.



10.66

Float Sub
S/N: ASQ12141




8.58

6-3/4 in. PowerPak* Motor
A675XP 7850
S/N: ASQ0003
0.0 deg. Bent Housing
8-3/8 in. Motor Sleeve



7.93




	0.00	0.24
---	------	------

[illegible]

Filtering Neutron	n/a	n/a	n/a	n/a	n/a	n/a	n/a			
Company representative	Bim Steel	Brian Davis	Roger Bain	G.Campbell	Ross Morris					
Anadrill personnel	K.Handley	D.Hastie	C.Soper	T.Auger	J.Dolan					

MLA A24A RT GR 1:500TVD

IDEAL Version: ID8_1C_01 <TVD> Vertical Scale: 1:500 Graphics File Created: 10-May-2004 17:21






Run 1


Run 2

650
TVD

700
TVD









1000
TVD

1050
TVD


1100
TVD






1150
TVD

1200
TVD







1400
TVD

1450
TVD

Run 3







1500
TVD

1550
TVD


1600
TVD






1650
TVD

1700
TVD



Erratic GR Data removed from 1731.6m to 1776.4m. Erratic data was due to incorrect Surface system initialization.





Run 4

1750
TVD

1800
TVD


1850
TVD






1900
TVD

1950
TVD







2000
TVD

2050
TVD

Run 5


2100
TVD







2150
TVD

2200
TVD









2400
TVD

Run 6

2450
TVD

2500
TVD







2550
TVD

Run 7

2600
TVD





SCHLUMBERGER

Survey report 6-May-2004 05:21:03 Page 1 of 5

Client.....: ESSO Australia Pty. Ltd.
Field.....: Turrum

Well.....: MLA A24A Spud date.....: 8-April-2004
API number.....: Last survey date.....: 05-May-04
Engineer.....: James Dolan Total accepted surveys...: 99
MD of first survey.....: 655.00 m
Rig.....: ISDL 453 MD of last survey.....: 3275.00 m
STATE.....: Victoria

----- Survey calculation methods -----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor
----- Depth reference -----
Permanent datum.....: Mean Sea Level
Depth reference.....: Driller's depth
GL above permanent.....: -59.00 m
KB above permanent.....: 27.91 m
DF above permanent.....: 27.91 m
----- Vertical section origin -----
Latitude (+N/S-).....: 0.00 m
Departure (+E/W-).....: 0.00 m
----- Geomagnetic data -----
Magnetic model.....: BGGM version 2003
Magnetic date.....: 12-Apr-2004
Magnetic field strength...: 1199.81 HCNT
Magnetic dec (+E/W-).....: 13.13 degrees
Magnetic dip.....: -68.73 degrees
----- MWD survey Reference Criteria -----
Reference G.....: 1000.03 mGal
Reference H.....: 1199.81 HCNT
Reference Dip.....: -68.73 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Platform reference point -----
Latitude (+N/S-).....: 5767927.00 m
Departure (+E/W-).....: 606840.63 m
Azimuth from rotary table to target: 172.07 degrees
----- Corrections -----
Magnetic dec (+E/W-).....: 13.13 degrees
Grid convergence (+E/W-)..: -0.76 degrees
Total az corr (+E/W-).....: 13.89 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (deg)	At Azim 100f	DLS (deg/100f)	Srvy Tool type	Tool Corr
1	655.00	33.20	210.13	0.00	633.73	96.52	-100.74	-23.64	103.48	193.21	0.00	TIP	None
2	660.00	32.99	210.13	5.00	637.92	98.66	-103.10	-25.01	106.09	193.64	1.28	GYR	None
3	665.00	33.29	210.01	5.00	642.11	100.82	-105.47	-26.38	108.72	194.04	1.87	GYR	None
4	670.00	33.73	209.91	5.00	646.27	103.00	-107.86	-27.76	111.37	194.43	2.70	GYR	None
5	675.00	34.09	209.86	5.00	650.42	105.20	-110.28	-29.15	114.06	194.81	2.20	GYR	None
6	680.00	34.69	210.12	5.00	654.55	107.43	-112.72	-30.56	116.79	195.17	3.77	GYR	None
7	685.00	35.40	210.66	5.00	658.64	109.68	-115.20	-32.01	119.56	195.53	4.72	GYR	None
8	689.10	35.51	210.76	4.10	661.98	111.54	-117.24	-33.23	121.86	195.82	0.92	GYR	None
9	717.50	34.70	205.96	28.40	685.22	124.69	-131.60	-40.99	137.84	197.30	3.09	GYR	None
10	752.43	33.40	195.32	34.93	714.19	141.79	-149.83	-47.88	157.30	197.72	5.32	MWD	None
11	780.54	33.91	186.00	28.11	737.60	156.52	-165.10	-50.75	172.73	197.09	5.62	MWD	None
12	810.03	35.97	177.85	29.49	761.79	173.13	-181.95	-51.29	189.04	195.74	5.27	MWD	None
13	838.48	36.64	170.20	28.45	784.73	189.94	-198.67	-49.53	204.75	194.00	4.90	MWD	None
14	866.83	37.47	166.76	28.35	807.36	206.98	-215.41	-46.11	220.29	192.08	2.40	MWD	None
15	895.45	37.83	165.95	28.62	830.02	224.38	-232.39	-41.99	236.16	190.24	0.65	MWD	None
16	924.14	38.25	166.46	28.69	852.61	241.96	-249.56	-37.77	252.40	188.61	0.56	MWD	None
17	952.81	39.64	166.66	28.67	874.91	259.90	-267.09	-33.58	269.19	187.17	1.48	MWD	None
18	981.60	38.22	166.49	28.79	897.30	277.91	-284.69	-29.38	286.20	185.89	1.51	MWD	None
19	1010.23	38.58	167.73	28.63	919.74	295.63	-302.02	-25.42	303.09	184.81	0.91	MWD	None
20	1039.20	38.55	167.51	28.97	942.39	313.63	-319.66	-21.55	320.39	183.86	0.15	MWD	None
21	1067.89	39.01	167.54	28.69	964.76	331.54	-337.21	-17.66	337.67	183.00	0.49	MWD	None
22	1096.72	39.89	167.06	28.83	987.02	349.80	-355.08	-13.64	355.34	182.20	0.98	MWD	None
23	1125.44	40.57	166.90	28.72	1008.95	368.27	-373.15	-9.46	373.27	181.45	0.73	MWD	None
24	1154.05	39.92	166.98	28.61	1030.78	386.68	-391.15	-5.28	391.19	180.77	0.69	MWD	None
25	1183.04	39.68	166.86	28.99	1053.06	405.17	-409.23	-1.08	409.23	180.15	0.26	MWD	None
26	1211.66	38.68	166.97	28.62	1075.24	423.17	-426.84	3.01	426.85	179.60	1.07	MWD	None
27	1240.27	38.47	166.82	28.61	1097.61	440.94	-444.21	7.06	444.27	179.09	0.24	MWD	None
28	1269.13	37.72	166.70	28.86	1120.32	458.67	-461.55	11.14	461.68	178.62	0.80	MWD	None
29	1297.80	38.60	167.43	28.67	1142.86	476.32	-478.81	15.10	479.05	178.19	1.05	MWD	None
30	1326.36	37.70	167.36	28.56	1165.32	493.90	-496.03	18.95	496.39	177.81	0.96	MWD	None

[(c)2004 IDEAL ID8_1C_01]
SCHLUMBERGER Survey Report

6-May-2004 05:21:03

Page 3 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (deg)	At Azim 100f	DLS (deg/100f)	Srvy Tool type	Tool Corr
31	1355.04	38.68	167.70	28.68	1187.86	511.58	-513.34	22.78	513.85	177.46	1.07	MWD	None
32	1384.27	37.81	167.57	29.23	1210.82	529.61	-531.02	26.65	531.68	177.13	0.91	MWD	None
33	1412.38	37.40	167.34	28.11	1233.09	546.71	-547.76	30.38	548.60	176.83	0.47	MWD	None
34	1441.17	37.84	168.07	28.79	1255.89	564.24	-564.93	34.12	565.96	176.54	0.66	MWD	None
35	1469.79	38.56	168.51	28.62	1278.39	581.90	-582.26	37.71	583.48	176.29	0.82	MWD	None
36	1498.39	37.87	168.37	28.60	1300.86	599.55	-599.59	41.26	601.01	176.06	0.74	MWD	None
37	1527.11	38.56	168.93	28.72	1323.42	617.29	-617.01	44.75	618.63	175.85	0.82	MWD	None
38	1556.02	37.65	169.12	28.91	1346.17	635.10	-634.53	48.15	636.35	175.66	0.97	MWD	None
39	1584.67	36.76	168.55	28.65	1368.99	652.40	-651.52	51.50	653.56	175.48	1.02	MWD	None
40	1613.25	38.50	168.86	28.58	1391.62	669.82	-668.63	54.92	670.89	175.30	1.87	MWD	None
41	1642.10	37.91	168.79	28.85	1414.29	687.63	-686.14	58.38	688.62	175.14	0.63	MWD	None
42	1671.05	37.92	169.06	28.95	1437.13	705.39	-703.60	61.79	706.31	174.98	0.17	MWD	None
43	1699.71	38.03	168.86	28.66	1459.72	723.00	-720.91	65.17	723.85	174.83	0.18	MWD	None
44	1727.96	37.84	169.05	28.25	1482.01	740.34	-737.95	68.50	741.12	174.70	0.24	MWD	None
45	1756.81	38.27	169.04	28.85	1504.72	758.10	-755.41	71.88	758.82	174.56	0.45	MWD	None
46	1785.62	38.00	168.66	28.81	1527.38	775.87	-772.87	75.32	776.53	174.43	0.38	MWD	None
47	1814.15	37.10	168.75	28.53	1550.00	793.22	-789.92	78.72	793.83	174.31	0.96	MWD	None
48	1842.95	38.27	167.89	28.80	1572.79	810.79	-807.16	82.29	811.34	174.18	1.36	MWD	None
49	1871.75	38.45	168.39	28.80	1595.38	828.62	-824.65	85.96	829.12	174.05	0.38	MWD	None
50	1900.47	38.71	168.39	28.72	1617.83	846.50	-842.19	89.57	846.94	173.93	0.28	MWD	None
51	1929.33	38.47	168.66	28.86	1640.39	864.46	-859.83	93.15	864.86	173.82	0.31	MWD	None
52	1958.22	37.87	169.39	28.89	1663.10	882.29	-877.36	96.55	882.66	173.72	0.79	MWD	None
53	1986.84	38.12	169.09	28.62	1685.65	899.89	-894.67	99.84	900.22	173.63	0.33	MWD	None
54	2015.48	39.37	167.94	28.64	1707.99	917.78	-912.23	103.41	918.07	173.53	1.54	MWD	None
55	2044.61	38.98	168.11	29.13	1730.57	936.13	-930.23	107.23	936.39	173.42	0.42	MWD	None
56	2071.77	38.59	168.98	27.16	1751.74	953.11	-946.91	110.61	953.34	173.34	0.75	MWD	None
57	2101.85	37.10	168.96	30.08	1775.50	971.54	-965.02	114.14	971.75	173.25	1.51	MWD	None
58	2130.54	37.51	168.59	28.69	1798.32	988.90	-982.08	117.52	989.08	173.18	0.50	MWD	None
59	2159.14	38.47	167.19	28.60	1820.86	1006.45	-999.29	121.22	1006.61	173.08	1.37	MWD	None

60 2187.44 38.03 166.74 28.30 1843.08 1023.90 -1016.35 125.17 1024.03 172.98 0.56 MWD None

[(c)2004 IDEAL ID8_1C_01]

SCHLUMBERGER Survey Report

6-May-2004 05:21:03

Page 4 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (deg)	At Azim (deg)	DLS (deg)	Srvy tool	Tool Corr
61	2216.29	38.41	166.91	28.85	1865.75	1041.68	-1033.73	129.24	1041.78	172.87	0.42	MWD	None
62	2245.08	38.93	167.52	28.79	1888.23	1059.60	-1051.28	133.22	1059.68	172.78	0.68	MWD	None
63	2273.90	38.02	167.87	28.82	1910.79	1077.48	-1068.80	137.04	1077.54	172.69	0.99	MWD	None
64	2302.68	38.81	168.30	28.78	1933.34	1095.32	-1086.29	140.73	1095.37	172.62	0.88	MWD	None
65	2331.35	38.78	168.59	28.67	1955.68	1113.25	-1103.89	144.33	1113.29	172.55	0.20	MWD	None
66	2359.88	38.33	168.94	28.53	1977.99	1131.00	-1121.33	147.79	1131.03	172.49	0.53	MWD	None
67	2388.53	38.91	168.96	28.65	2000.38	1148.85	-1138.88	151.22	1148.88	172.44	0.62	MWD	None
68	2417.21	38.59	168.82	28.68	2022.74	1166.78	-1156.50	154.68	1166.80	172.38	0.35	MWD	None
69	2445.97	39.26	168.62	28.76	2045.12	1184.82	-1174.22	158.21	1184.83	172.33	0.72	MWD	None
70	2474.75	38.92	168.19	28.78	2067.46	1202.93	-1191.99	161.86	1202.93	172.27	0.46	MWD	None
71	2503.39	39.80	167.74	28.64	2089.60	1221.04	-1209.76	165.65	1221.05	172.20	0.98	MWD	None
72	2531.95	39.39	167.17	28.56	2111.61	1239.19	-1227.53	169.60	1239.19	172.13	0.58	MWD	None
73	2560.51	40.01	166.69	28.56	2133.58	1257.36	-1245.30	173.73	1257.36	172.06	0.74	MWD	None
74	2589.43	40.85	166.60	28.92	2155.60	1276.03	-1263.54	178.06	1276.03	171.98	0.89	MWD	None
75	2617.92	41.96	167.22	28.49	2176.96	1294.79	-1281.90	182.33	1294.80	171.91	1.27	MWD	None
76	2646.67	41.96	167.88	28.75	2198.34	1313.96	-1300.67	186.47	1313.97	171.84	0.47	MWD	None
77	2675.56	41.93	168.44	28.89	2219.83	1333.22	-1319.57	190.43	1333.24	171.79	0.40	MWD	None
78	2703.70	41.03	168.90	28.14	2240.91	1351.83	-1337.84	194.10	1351.85	171.75	1.03	MWD	None
79	2732.45	40.27	169.62	28.75	2262.73	1370.53	-1356.24	197.59	1370.56	171.71	0.95	MWD	None
80	2760.98	39.81	169.96	28.53	2284.57	1388.87	-1374.31	200.84	1388.90	171.69	0.54	MWD	None
81	2789.98	38.64	171.44	29.00	2307.03	1407.20	-1392.40	203.81	1407.24	171.67	1.57	MWD	None
82	2818.82	38.83	171.71	28.84	2329.53	1425.25	-1410.25	206.45	1425.28	171.67	0.27	MWD	None
83	2847.42	38.91	171.07	28.60	2351.80	1443.20	-1428.00	209.14	1443.23	171.67	0.44	MWD	None
84	2875.94	39.73	171.25	28.52	2373.86	1461.26	-1445.85	211.91	1461.30	171.66	0.88	MWD	None
85	2904.56	40.43	171.37	28.62	2395.76	1479.69	-1464.07	214.70	1479.73	171.66	0.75	MWD	None
86	2933.12	40.91	171.26	28.56	2417.42	1498.30	-1482.47	217.51	1498.34	171.65	0.52	MWD	None
87	2961.50	41.59	171.60	28.38	2438.76	1517.01	-1500.97	220.30	1517.05	171.65	0.77	MWD	None
88	2990.42	39.85	170.94	28.92	2460.68	1535.88	-1519.62	223.16	1535.92	171.65	1.89	MWD	None
89	3019.22	39.73	171.29	28.80	2482.81	1554.30	-1537.83	226.00	1554.35	171.64	0.27	MWD	None
90	3048.40	39.90	171.55	29.18	2505.22	1572.99	-1556.30	228.79	1573.03	171.64	0.25	MWD	None

[(c)2004 IDEAL ID8_1C_01]

SCHLUMBERGER Survey Report

6-May-2004 05:21:03

Page 5 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (deg)	At Azim (deg)	DLS (deg)	Srvy tool	Tool Corr
91	3076.98	39.84	171.60	28.58	2527.16	1591.31	-1574.43	231.48	1591.35	171.64	0.07	MWD	None
92	3104.57	40.18	172.01	27.59	2548.29	1609.05	-1591.99	234.00	1609.09	171.64	0.48	MWD	None
93	3134.13	41.41	172.07	29.57	2570.67	1628.37	-1611.12	236.68	1628.41	171.64	1.27	MWD	None
94	3162.70	42.38	172.49	28.56	2591.93	1647.44	-1630.02	239.24	1647.48	171.65	1.08	MWD	None
95	3191.43	42.22	172.43	28.73	2613.18	1666.77	-1649.19	241.78	1666.81	171.66	0.18	MWD	None
96	3219.74	41.68	172.83	28.31	2634.24	1685.70	-1667.95	244.21	1685.74	171.67	0.65	MWD	None
97	3248.88	38.89	174.72	29.14	2656.46	1704.52	-1686.68	246.26	1704.56	171.69	3.19	MWD	None
98	3255.01	38.38	174.78	6.13	2661.25	1708.35	-1690.49	246.61	1708.38	171.70	2.54	MWD	None
99	3275.00	38.38	174.78	19.99	2676.92	1720.75	-1702.85	247.74	1720.78	171.72	0.00	Projection to TD	

[(c)2004 IDEAL ID8_1C_01]

Company: **ESSO Australia Pty. Ltd.**

Well: **MLA A24A**

Field: **Turrum**

Schlumberger

Field: **Purnell**

Rig: **ISDL 453**

State: **Victoria**

Gamma Ray Service
1:500 True Vertical Depth
Real Time Log