


Company: **ESSO Australia Pty. Ltd.**Well: **MLA A22A**Field: **Turrum**Rig: **ISDL 453**State: **Victoria**

PowerPulse – Gamma Ray 1:200 Measured Depth Real Time Log

PowerPulse – Gamma Ray 1:200 Measured Depth Real Time Log									
Rig: ISDL 453		Field: Turrum		Location: Bass Strait		Well: MLA A22A		Company: ESSO Australia Pty. Ltd.	
Depth logged: 1900.0 m To 3598.8 m Date logged: 27-May-04To 10-June-04		To 3598.8 m Mag decl: 13.13 deg. Mag dip: -68.73 deg.		Other services: Directional Drilling, D&I		Location			
						Total depth: 3617.00 m		K.B. Top Drive	
						Spud date: 24-May-2004		Elevation	
						Runs: 1 To 4		G.L. -59.00 m D.F. 27.91 m	
Permanent datum:		Mean Sea Level		Elev.: 0 m		27.91 m above Perm. datum			
Log measured from:		Drill Floor							
Depth reference:		Driller's Depth							
API serial no.		Y = 5767922.76 m N X = 606871.49 m E		Longitude E148°13'15.81"		Latitude S38°13'49.23"			
Bore hole record		from		to		Size		Density	
17 1/2 in.		Surface		673 m		13 3/8 in.		54.5 lb/ft	
12 1/4 in.		673 m		1891 m		9 5/8 in.		40.0 lb/ft	
8 1/2 in.		1891 m		3617 m				Surface	

<p>Depth is 1900.0 m MD.</p> <p>Mud type is KCL/PHPA/Glycol.</p> <p>POOH for bit change.</p>	<p>At 3500.0m MD, Pull inside Window to Perform Slip & Cut. Run In Hole to Resume Drilling, but BHA got Stuck at 2196.0m MD (1533.0m TVD).</p> <p>Jarring was Performed to Free the BHA.</p> <p>POOH to Inspect the BHA.</p>	<p>Unable to bypass whipstock while RIH. POOH to layout BHA and run Troubleshooting Operations.</p>
Thank You for Choosing Schlumberger.	Thank You for Choosing Schlumberger.	Thank You for Choosing Schlumberger.

EQUIPMENT DESCRIPTION					
RUN1		RUN2		RUN3	
DOWNHOLE EQUIPMENT		DOWNHOLE EQUIPMENT		DOWNHOLE EQUIPMENT	
6-3/4 in. PowerPulse*	23.24	6-3/4 in. PowerPulse*	24.84	6-3/4 in. PowerPulse*	23.17
MDC: Y927-AC		MDC: Y927-AC		MDC: V875-AE	
MEC: 570-BA		MEC: 570-BA		MEC: 212-BA	
MDI: 586-BC		MDI: 586-BC		MDI: 1096-BC	
MGR: 512-AA		MGR: 512-AA		MGR: 503-AA	
DH Software: V7.0 C00		DH Software: V7.0 C00		DH Software: V7.0 C00	
D&I	___ 18.93	D&I	___ 20.53	D&I	___ 18.82
GR	___ 18.28	GR	___ 19.88	GR	___ 18.17
6-1/2 in. PMDC	14.78	6-1/2 in. PMDC	16.38	6-1/2 in. PMDC	14.79
S/N: 9612058		S/N: 9612058		S/N: 9612058	
6-1/2 in. PMDC	12.33	6-1/2 in. PMDC	13.93	6-1/2 in. PMDC	12.34
S/N: ASS15700		S/N: ASS15700		S/N: ASS15700	
6-1/2 in. NM Roller Reamer	10.66	6-5/8 in. NM Roller Reamer	12.26	6-5/8 in. NM Roller Reamer	10.67
S/N: GU2298		S/N: GU2298		S/N: GU2298	
Reamer OD: 8-3/8 in.		Reamer OD: 8-3/8 in.		Reamer OD: 8-3/8 in.	
6-1/2 in. Float Sub		6-1/2 in. Float Sub			

 <p>6-1/2 in. Float Sub S/N: ASQ12141</p> <p>6-3/4 in. PowerPak* Motor A675XP 7:8 / 5.0 S/N: ASQ0002 1.5 deg. Bent Housing 8-3/8 in. Motor Sleeve</p> <p>Smith TCI Bit OD: 8-1/2 in. GFi11YODV S/N: MR4668</p> <p>Maximum string diameter 8.50 in. All lengths in Meters</p>	<p>S/N: ASQ12141</p> <p>8.58 7.93</p> <p>7 in. PowerPak* Motor A700GT 7:8 / 6.8 S/N: N7268 1.0 deg. Bent Housing 8-3/8 in. IB Stabilizer</p> <p>6-5/8 in. NM Rotating Stab. S/N: OSS2832-A Stabilizer OD: 8-1/2 in.</p> <p>REED-Hycalog PDC Bit OD: 8-1/2 in. RSX 163 S/N: 206165</p> <p>Maximum string diameter 8.50 in. All lengths in Meters</p>	<p>10.15 9.50</p> <p>6-1/2 in. Float Sub S/N: ASQ12141</p> <p>6-3/4 in. PowerPak* Motor A675XP 7:8 / 5.0 S/N: ASQ0002 1.15 deg. Bent Housing 8-3/8 in. Motor Sleeve</p> <p>Smith TCI Bit OD: 8-1/2 in. GFi11YODV S/N: MR4669</p> <p>Maximum string diameter 8.50 in. All lengths in Meters</p>
--	---	--

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

<p>OTHER SERVICES FOR RUN4</p> <p>Directional Drilling. Directional Surveys.</p>	<p>OTHER SERVICES FOR RUN</p>	<p>OTHER SERVICES FOR RUN</p>
<p>REMARKS: RUN NUMBER 4</p> <p>8-1/2 in. Hole was drilled from 3500.0 m to 3617.0 m MD.</p> <p>Depth is referenced to Driller's Depth.</p> <p>Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.</p> <p>Mud type is KCL/PHPA/Glycol.</p> <p>POOH due to TD of MLA A22A.</p>	<p>REMARKS: RUN NUMBER</p>	<p>REMARKS: RUN NUMBER</p>







Thank You for Choosing Schlumberger.

EQUIPMENT DESCRIPTION

RUN4

RUN

RUN

DOWNHOLE EQUIPMENT		
6-3/4 in. PowerPulse* MDC: V875-AE MEC: 212-BA MDI: 1096-BC MGR: 503-AA DH Software: 7.0 C00		23.17
6-1/2 in. PMDC S/N: 9612058		14.79
6-1/2 in. PMDC S/N: ASS15700		12.34
6-5/8 in. NM Roller Reamer S/N: GU2298 Reamer OD: 8-3/8 in.		10.67
6-1/2 in. Float Sub S/N: ASQ12141		8.59
6.75 in. PowerPak* Motor A675XP 7850		7.94

1.15 deg. Bent Housing
8-3/8 in. Motor Sleeve



Smith TCI Bit
OD: 8-1/2 in.
GF11YODV
S/N: MR4669



0.00 0.25

Maximum string diameter 8.50 in.
All lengths in Meters


[illegible]



Mud weight											
Temperature											
Mud salinity											
Formation salinity											
Update rate 1	SEC	3.7	3.7	3.7	3.7						
Update rate 2	SEC	n/a	n/a	n/a	n/a						
Filtering GR		3 pt.	3 pt.	3 pt.	3 pt.						
Filtering density		n/a	n/a	n/a	n/a						
Filtering Neutron		n/a	n/a	n/a	n/a						
Company representative		G. Campbell	B. Steel	R. Morris	B. Davis						
Anadrill personnel		K. Handley	L. Muskett	C. Soper	D. Hay						



MLA A22A RT 1:200MD



IDEAL Version: ID8_1C_01 <MD > Vertical Scale: 1:200



Graphics File Created: 11-Jun-2004 01:05

























2250



2275



















ROP5







2750



GRM1







2775































Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Displ Total (deg)	At Azim (deg)	DLS (deg)	Srvy Tool	Tool Corr
1	1900.00	60.55	200.38	0.00	1330.76	1066.41	-1100.23	-299.11	1140.16	195.21	0.00	TIP	None
2	1930.23	52.83	211.29	30.23	1347.38	1091.19	-1122.94	-309.99	1164.94	195.43	12.03	MWD	None
3	1936.70	51.80	212.54	6.47	1351.34	1096.29	-1127.29	-312.69	1169.85	195.50	6.73	GYR	None
4	1987.88	49.70	217.36	51.18	1383.73	1135.90	-1159.77	-335.37	1207.28	196.13	2.55	MWD	None
5	2015.71	49.85	217.11	27.83	1401.70	1157.14	-1176.69	-348.22	1227.13	196.49	0.27	MWD	None
6	2044.93	48.19	217.99	29.22	1420.86	1179.19	-1194.18	-361.66	1247.74	196.85	1.87	MWD	None
7	2073.54	45.40	220.16	28.61	1440.45	1200.01	-1210.37	-374.80	1267.07	197.21	3.42	MWD	None
8	2102.09	43.17	222.26	28.55	1460.89	1219.86	-1225.37	-387.93	1285.31	197.57	2.85	MWD	None
9	2130.99	40.83	227.28	28.90	1482.37	1238.95	-1239.10	-401.52	1302.53	197.95	4.32	MWD	None
10	2159.23	38.43	231.39	28.24	1504.12	1256.47	-1250.84	-415.16	1317.94	198.36	3.84	MWD	None
11	2187.94	37.96	233.27	28.71	1526.69	1273.50	-1261.69	-429.21	1332.70	198.79	1.33	MWD	None
12	2216.45	38.64	237.67	28.51	1549.06	1290.14	-1271.70	-443.77	1346.90	199.24	3.00	MWD	None
13	2245.23	38.52	238.91	28.78	1571.56	1306.74	-1281.13	-459.03	1360.89	199.71	0.83	MWD	None
14	2273.85	38.39	239.69	28.62	1593.98	1323.07	-1290.22	-474.34	1374.65	200.19	0.53	MWD	None
15	2302.70	37.97	240.56	28.85	1616.65	1339.34	-1299.10	-489.80	1388.37	200.66	0.72	MWD	None
16	2331.40	38.06	241.27	28.70	1639.27	1355.36	-1307.69	-505.25	1401.90	201.12	0.47	MWD	None
17	2360.15	37.90	239.82	28.75	1661.93	1371.44	-1316.39	-520.65	1415.61	201.58	0.96	MWD	None
18	2388.95	37.46	239.88	28.80	1684.72	1387.54	-1325.23	-535.87	1429.48	202.02	0.47	MWD	None
19	2416.70	36.76	240.80	27.75	1706.85	1402.78	-1333.52	-550.42	1442.65	202.43	0.98	MWD	None
20	2445.36	37.82	239.61	28.66	1729.65	1418.61	-1342.15	-565.49	1456.41	202.85	1.36	MWD	None
21	2474.22	37.64	239.58	28.86	1752.48	1434.79	-1351.09	-580.72	1470.60	203.26	0.19	MWD	None
22	2503.13	37.64	239.13	28.91	1775.37	1450.99	-1360.09	-595.91	1484.91	203.66	0.29	MWD	None
23	2531.94	37.11	238.98	28.81	1798.27	1467.07	-1369.08	-610.91	1499.20	204.05	0.57	MWD	None
24	2560.43	36.27	238.97	28.49	1821.11	1482.73	-1377.85	-625.50	1513.18	204.42	0.90	MWD	None
25	2589.08	36.85	239.20	28.65	1844.12	1498.42	-1386.62	-640.14	1527.25	204.78	0.63	MWD	None
26	2617.52	37.93	239.18	28.44	1866.72	1514.29	-1395.47	-654.97	1541.53	205.14	1.16	MWD	None
27	2646.36	37.60	238.86	28.84	1889.52	1530.54	-1404.56	-670.11	1556.22	205.51	0.41	MWD	None
28	2675.08	38.76	239.63	28.72	1912.09	1546.84	-1413.63	-685.37	1571.02	205.87	1.33	MWD	None
29	2703.94	39.21	239.87	28.86	1934.53	1563.45	-1422.78	-701.05	1586.12	206.23	0.50	MWD	None
30	2732.51	38.62	239.80	28.57	1956.76	1579.86	-1431.80	-716.57	1601.10	206.59	0.63	MWD	None

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Displ Total (deg)	At Azim (deg)	DLS (deg)	Srvy Tool	Tool Corr
31	2761.23	38.26	239.86	28.72	1979.25	1596.18	-1440.77	-732.01	1616.06	206.93	0.38	MWD	None
32	2789.70	37.87	240.21	28.47	2001.67	1612.20	-1449.54	-747.21	1630.79	207.27	0.48	MWD	None
33	2818.26	37.74	240.45	28.56	2024.23	1628.15	-1458.20	-762.42	1645.49	207.60	0.21	MWD	None
34	2847.05	37.96	240.04	28.79	2046.96	1644.24	-1466.97	-777.76	1660.40	207.93	0.35	MWD	None
35	2875.73	37.60	240.22	28.68	2069.63	1660.27	-1475.72	-793.00	1675.29	208.25	0.40	MWD	None
36	2904.44	37.24	240.17	28.71	2092.43	1676.18	-1484.39	-808.13	1690.12	208.56	0.38	MWD	None
37	2932.71	36.78	239.90	28.27	2115.01	1691.71	-1492.89	-822.88	1704.66	208.86	0.53	MWD	None
38	2961.62	36.54	239.37	28.91	2138.20	1707.51	-1501.62	-837.77	1719.51	209.16	0.42	MWD	None
39	2990.25	36.70	239.34	28.63	2161.18	1723.18	-1510.32	-852.46	1734.29	209.44	0.17	MWD	None
40	3019.50	36.24	239.56	29.25	2184.70	1739.12	-1519.16	-867.44	1749.37	209.73	0.50	MWD	None
41	3048.05	35.87	239.87	28.55	2207.78	1754.50	-1527.63	-881.95	1763.94	210.00	0.44	MWD	None
42	3076.53	34.95	239.44	28.48	2230.99	1769.61	-1535.97	-896.19	1778.30	210.26	1.02	MWD	None
43	3105.29	34.28	239.94	28.76	2254.66	1784.56	-1544.22	-910.29	1792.55	210.52	0.77	MWD	None
44	3133.80	33.47	240.12	28.51	2278.33	1799.07	-1552.16	-924.06	1806.40	210.77	0.87	MWD	None
45	3162.74	33.21	239.82	28.94	2302.51	1813.59	-1560.11	-937.83	1820.30	211.01	0.32	MWD	None
46	3191.46	31.81	239.57	28.72	2326.73	1827.72	-1567.90	-951.15	1833.85	211.24	1.49	MWD	None
47	3219.71	30.67	238.89	28.25	2350.88	1841.17	-1575.40	-963.74	1846.80	211.46	1.29	MWD	None
48	3248.22	29.49	238.69	28.51	2375.55	1854.34	-1582.80	-975.96	1859.51	211.66	1.27	MWD	None
49	3277.07	28.75	238.21	28.85	2400.76	1867.31	-1590.15	-987.93	1872.05	211.85	0.82	MWD	None
50	3306.00	28.14	238.44	28.93	2426.19	1880.05	-1597.38	-999.65	1884.39	212.04	0.65	MWD	None
51	3334.70	26.79	238.86	28.70	2451.66	1892.26	-1604.27	-1010.96	1896.24	212.22	1.45	MWD	None
52	3363.41	25.74	239.37	28.71	2477.40	1903.94	-1610.79	-1021.86	1907.58	212.39	1.14	MWD	None
53	3392.17	24.49	240.28	28.76	2503.44	1915.10	-1616.93	-1032.41	1918.42	212.56	1.39	MWD	None

54	3420.72	22.92	240.55	28.55	2529.58	1925.54	-1622.60	-1042.39	1928.57	212.72	1.68	MWD	None
55	3449.22	21.66	241.28	28.50	2555.95	1935.34	-1627.85	-1051.84	1938.11	212.87	1.38	MWD	None
56	3477.72	20.41	241.48	28.50	2582.55	1944.58	-1632.75	-1060.82	1947.10	213.01	1.34	MWD	None
57	3507.52	19.99	241.57	29.80	2610.52	1953.86	-1637.66	-1069.86	1956.15	213.16	0.43	MWD	None
58	3535.90	20.01	241.39	28.38	2637.19	1962.62	-1642.29	-1078.39	1964.70	213.29	0.07	MWD	None
59	3564.39	19.41	242.05	28.49	2664.01	1971.27	-1646.85	-1086.85	1973.16	213.42	0.68	MWD	None
60	3593.49	18.05	242.73	29.10	2691.57	1979.64	-1651.18	-1095.13	1981.34	213.55	1.44	MWD	None

[(c)2004 IDEAL ID8_1C_01]
SCHLUMBERGER Survey Report

10-Jun-2004 22:39:55

Page 4 of 4

```

=====
Seq Measured Incl Azimuth Course TVD Vertical Displ Displ Total At DLS Srvy Tool
# depth angle angle length depth section +N/S- +E/W- displ Azim (deg/ tool Corr
- (m) (deg) (deg) (m) (m) (m) (m) (m) (deg) 100f) type (deg)
=====
61 3617.00 16.95 243.31 23.51 2713.99 1985.93 -1654.39 -1101.43 1987.50 213.65 1.44 Projection to TD
=====

```

[(c)2004 IDEAL ID8_1C_01]

Company: **ESSO Australia Pty. Ltd.**

Schlumberger

Well: **MLA A22A**

Field: **Turrum**

Rig: **ISDL 453**

State: **Victoria**

**PowerPulse – Gamma Ray
1:200 Measured Depth
Real Time Log**