

**Input Source:** D:\OP\_Folder\Clients\Ess02008\FLA\_A20a\FLA A20a Ener\_MPBT\DLIS\Mpbt PUP Joint\_042LUP.DLIS  
**Format:** DLIS  
**Storage Set ID:** Default Storage Set

**Max Record Length:** 8192  
**Storage Unit Sequence:** 1

**File Header** File: **CCL\_042LUP** Sequence: **42**

**Defining Origin: 41**

File ID: CCL\_042LUP File Type: DEPTH LOG  
Producer Name: Schlumberger Product/Version: OP 15C0-309 File Set: 41 File Number: 43 5-FEB-2008 2:23:37  
Company Name: Esso Australia Pty Ltd.  
Well Name: A-20a  
Field Name: Flounder  
Tool String: MPEX-H405501, MPSU-CA, CCL-I  
Computations: WELLCAD, BORDYN

**Error Summary** File: **CCL\_042LUP** Sequence: **42**

No errors detected in file.

**Well Site Data** File: **CCL\_042LUP** Sequence: **42**

**Origin: 41**

**Well Data**

Company Name	Esso Australia Pty Ltd.	CN
Well Name	A-20a	WN
Field Name	Flounder	FN
Rig:	Mast	CLAB, COUN
State:	Victoria	SLAB, STAT
Nation	Australia	NATI
Field Location	Gippsland	FL
	Basin	FL1
	Bass Strait	FL2
Service Order Number	AUSL07336278	SON
Longitude	148° 26' 21.748"E	LONG
Latitude	38° 18' 39.245"S	LATI
Maximum Hole Deviation	49.0 (deg)	MHD
Elevation of Kelly Bushing	33.8 (m)	EKB
Elevation of Ground Level	-93.0 (m)	EGL
Elevation of Derrick Floor	33.8 (m)	EDF
Permanent Datum	M.S.L	PDAT, EPD
Log Measured From	K.B	LMF, APD
Drilling Measured From	K.B	DMF
	Elevation of Permanent Datum 0.0 (m)	
	Above Permanent Datum 33.8 (m)	

Absent Valued Parameters: CN1, CONT, SECT, TOWN, RANG, APIN

**Job Data**

Date as Month-Day-Year	4-Feb-2008	DATE
Run Number	1 through 6	RUN
Total Depth - Driller	2789.0 (m)	TDD
Total Depth - Logger	2747.0 (m)	TDL
Bottom Log Interval	2663.0 (m)	BLI
Top Log Interval	2658.0 (m)	TLI
Current Casing Size	7.00 (in)	CSIZ
Casing Depth From	13.8 (m)	CDF
Casing Depth To	2770.0 (m)	CADT
Casing Grade	N-80	CASG
Casing Weight	26.0 (lbm/ft)	CWEI
Bit Size	8.50 (in)	BS
Bit Size Depth From	804.0 (m)	BSDF
Bit Size Depth To	2789.0 (m)	BSDT
Date Logger At Bottom	4-Feb-2008	DLAB, TLAB
Logging Unit Number	889	LUN, LUL
Engineer's Name	S Gilbert / C.Rowand	ENGI
Witness's Name	B White / J.DiGiouanni	WITN
Service Order Number	AUSL07336278	SON
	Time Logger At Bottom 11:00	
	Logging Unit Location Prod 4 / AUSL	

**Mud Data**

## Mud Data

Drilling Fluid Type  
Maximum Recorded Temperature  
Date Logger At Bottom

Production Fluids  
230.0 (degF)  
230.0 (degF)  
4-Feb-2008

Time Logger At Bottom 11:00

DFT  
MRT  
MRT1  
DLAB, TLAB

Absent Valued Parameters: DFD, DFV, DFL, DFPH, BSAL, MSS, RMS, MST, RMFS, MFST, RMCS, MCST, RMB, RMFB, MRT2, MRT3, DCS, TCS

## PVT Data

Absent Valued Parameters: ODEN, BSAL, GGRA, BO, BW, IBG, BPP, BPT, SGOR

## Cement Data

Cement Job Type Primary

CJT

Absent Valued Parameters: CTOP, CASN, LCMT, LCVO, CDEN, CWLO, CADD, TCTY, TCV, TCDE, TCWL, TCA

## Remarks

Log correlated to ExxonMobil Solar Composite Log supplied with logging program.  
Objectives: Perforate intervals 2658–2659.7, 2661.4–2663 m MDKB using 2–1/8" 6 SPF, 45 deg phased Powerjet gun with MWPT.  
Set a 7" Posiset plug with top of seal at 2675 m MDKB then dump approximately 1m of cement on top.  
GOC @ 1677m MDKB, OWC @ 2199m MDKB. Tagged HUD @ 2747 m MDKB.  
Perforation interval: Gun#1 2658–2659.7, GUN#2 – 2661.4–2663m MDKB.  
Gun#1 CCL to top shot = 3.5 m Gun#2 CCL Top Shot = 6.8m  
Gun#1 CCL Stop Depth = 2654.6 m MDKB Gun#2 CCL Stop Depth = 2654.6m  
Before gun shot: SBHT = 230.7 degF SBHP = 3113.0 psia  
After gun shot: SBHT = 230.6 degF SBHP = 3105.3 psia  
Top of seal @ 2675 m MDKB  
CCL to top of seal = 7.07 m  
CCL Stop Depth: 2667.93m MDKB  
Dump Bailers:  
CCL to bottom of bailer = 11m  
2 cement runs were made with 1–11/16", 32ft long dump bailers.  
Schlumberger crews: P.Lawrence, Z Casey, G Martin, C Shiells

R1  
R2  
R3  
R4  
R5  
R6  
R7  
R8  
R9  
R11  
R12  
R13  
R14  
R15  
R16  
R17

## Other Services

None

OS1

## Frame Summary File: CCL\_042LUP Sequence: 42

### Origin: 41

Index Type	Start	Stop	Spacing	Channels	Index Channel	Frame Name
BOREHOLE-DEPTH	2605.28	2560.47 m	–60.0 (0.1 in) up	20	TDEP	60B
	8547.50	8400.50 ft				
BOREHOLE-DEPTH	2605.28	2560.50 m	–10.0 (0.1 in) up	12	TDEP;1	10B
	8547.50	8400.58 ft				



## Verification Listing

Listing Completed: 9-FEB-2008 12:50:16