

Input Source: D:\OP_Folder\Clients\Ess02008\FLA_A24a\GUN\FLA A24a Mwp_Ener 3-Feb-08\Diis\MwptEner Shoot_020LTP.DLIS
Format: DLIS
Storage Set ID: Default Storage Set
Max Record Length: 8192
Storage Unit Sequence: 1

File Header File: **PERFO_020LTP** Sequence: **20****Defining Origin: 64**

File ID: PERFO_020LTP File Type: STATION
Producer Name: Schlumberger Product/Version: OP 15C0-309 File Set: 41 File Number: 19 3-FEB-2008 20:38:51
Company Name: Esso Australia Pty Ltd.
Well Name: A-24a
Field Name: Flounder
Tool String: MWP_GUN, MWPT-CA, MWGT-AA
Computations: WELLCAD, BORDYN

Error Summary File: **PERFO_020LTP** Sequence: **20**

No errors detected in file.

Well Site Data File: **PERFO_020LTP** Sequence: **20****Origin: 64****Well Data**

Company Name	Esso Australia Pty Ltd.	CN
Well Name	A-24a	WN
Field Name	Flounder	FN
Rig:	Mast	CLAB, COUN
State:	Victoria	SLAB, STAT
Nation	Australia	NATI
Field Location	Gippsland	FL
	Basin	FL1
	Bass Strait	FL2
Service Order Number	AUSL07336277	SON
Longitude	148° 06' 15.10"E	LONG
Latitude	38° 18' 45.24"S	LATI
Maximum Hole Deviation	47.0 (deg)	MHD
Elevation of Kelly Bushing	33.8 (m)	EKB
Elevation of Ground Level	93.0 (m)	EGL
Elevation of Derrick Floor	33.8 (m)	EDF
Permanent Datum	M.S.L	PDAT, EPD
Log Measured From	K.B	LMF, APD
Drilling Measured From	K.B	DMF
	Elevation of Permanent Datum 0.0 (m)	
	Above Permanent Datum 33.8 (m)	

Absent Valued Parameters: CN1, CONT, SECT, TOWN, RANG, APIN

Job Data

Date as Month-Day-Year	3-Feb-2008	DATE
Run Number	1	RUN
Total Depth - Driller	3193.0 (m)	TDD
Total Depth - Logger	3128.5 (m)	TDL
Bottom Log Interval	3103.2 (m)	BLI
Top Log Interval	3102.5 (m)	TLI
Current Casing Size	7.00 (in)	CSIZ
Casing Depth From	13.5 (m)	CDF
Casing Depth To	3186.0 (m)	CADT
Casing Grade	L-80	CASG
Casing Weight	26.0 (lbm/ft)	CWEI
Bit Size	8.50 (in)	BS
Bit Size Depth From	662.0 (m)	BSDF
Bit Size Depth To	3193.0 (m)	BSDT
Date Logger At Bottom	3-Feb-2008	DLAB, TLAB
Logging Unit Number	889	LUN, LUL
Engineer's Name	S Gilbert / C.Rowand	ENGI
Witness's Name	B White / J.DiGiouanni	WITN
Service Order Number	AUSL07336277	SON
	Time Logger At Bottom 11:00	
	Logging Unit Location Prod 4 / AUSL	

Mud Data

Mud Data		DFT	
Drilling Fluid Type	Production Fluids	MRT	
Maximum Recorded Temperature	226.0 (degF)	MRT1	
	230.0 (degF)	DLAB, TLAB	
Date Logger At Bottom	3-Feb-2008	Time Logger At Bottom	11:00
Absent Valued Parameters: DFD, DFV, DFL, DFPH, BSAL, MSS, RMS, MST, RMFS, MFST, RMCS, MCST, RMB, RMFB, MRT2, MRT3, DCS, TCS			
PVT Data			
Absent Valued Parameters: ODEN, BSAL, GGRA, BO, BW, IBG, BPP, BPT, SGOR			
Cement Data			
Cement Job Type	Primary	CJT	
Absent Valued Parameters: CTOP, CASN, LCMT, LCVO, CDEN, CWLO, CADD, TCTY, TCV, TCDE, TCWL, TCA			
Remarks			
Log correlated to ExxonMobil Solar Composite Log supplied with logging program.			R1
Objectives: Perforate the well over the interval 3102.5m 3103.2m MDKB			R2
using 2-1/8" 6 SPF, 45 deg phased Powerjet gun with MWPT.			R3
Maximum Well Deviation - 47deg @ 630m MDKB			R4
Perforation interval: 3102.5m to 3103.2m MDKB.			R5
CCL to top shot = 3.50 m			R6
CCL Stop Depth = 3099.00 m MDKB			R7
Before gun shot: SBHT = 230.2 degF SBHP = 3089.4 psia			R8
After gun shot: SBHT = 231.3degF SBHP = 3090.0 psia			R9
Schlumberger crews: P.Lawrence, Z Casey, G Martin, C Shiells			R17
Other Services			
None			OS1

Channels

File: PERFO_020LTP

Sequence: 20

Origin: 64

MWPT-CA: MEASUREMENT WHILE PERFORATING TOOL

Spacing: 500.0 ms

Number of Channels: 21

CSGP_SL DPRE_SL DTEM_SL ESGP_SL FSS_SL HV_SL MTES_SL MWPS_SL PSGP_SL RCCL_SL RHV_SL RSGF_SL RSGP_SL
RSGT_SL RTEF_SL RTEMP_MWPT_SL SGPA_SL SGPT_SL SGP_SL SYNCQ_SL TEMP_MWPT_SL

Spacing: 250.0 ms

Number of Channels: 3

AGC_SL CCL_SL TAMF_SL

MWGT-AA: MEASUREMENT WHILE PERFORATING GAMMA RAY TOOL

Spacing: 500.0 ms

Number of Channels: 2

GR_SL RGR_SL

System and Miscellaneous

Spacing: 1000.0 ms

Number of Channels: 7

DEPT_SL ETIM_PL TDEP;2 TENS_SL TIME;2 TOD7 TOJ

Spacing: 500.0 ms

Number of Channels: 2

TDEP;4 TIME;4

Spacing: 250.0 ms

Number of Channels: 3

ETIM;1 TDEP;5 TIME;5

Frame Summary							File: PERFO_020LTP	Sequence: 20
Origin: 64								
<u>Index Type</u>	<u>Start</u>	<u>Stop</u>	<u>Spacing</u>	<u>Channels</u>	<u>Index Channel</u>	<u>Frame Name</u>		
TIME	4793.52	6311.52 s	2000.0 (0.5 ms)	7	TIME;2	2000T		
TIME	4793.52	6311.52 s	1000.0 (0.5 ms)	25	TIME;4	1000T		
TIME	4793.52	6311.77 s	500.0 (0.5 ms)	6	TIME;5	500T		

	Verification Listing	Listing Completed: 3-FEB-2008 23:26:09
--	-----------------------------	---