



Potassium	%	n/a	n/a								
<b>Environmental data</b>											
<b>GR</b>											
Mud weight	ppg	10.60	10.65								
Bit size	in.	8.5	8.5								
<b>Resistivity</b>											
<b>Neutron porosity</b>											
Hole Size	in.	8.5	8.5								
Mud weight	ppg	10.60	10.65								
Temperature	°C	47.0	90.0								
Mud salinity	ppk	58.368	57.942								
Formation salinity		n/a	n/a								
Recording rate 1	SEC	5 (ADN, SON)	5 (ADN, SON)								
Recording rate 2	SEC	6 (ARC)	6 (ARC)								
Filtering GR		3 pts	3 pts								
Filtering density		3 pts	3 pts								
Filtering Neutron		3 pts	3 pts								
Company representative		D. Daniels	G. Campbell								
Schlumberger D&M Personnel		M. Y. Tan	M. Amarasena	M. Lu	C. Soper	M. How					

<p style="text-align: center;"><b>DISCLAIMER</b></p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>											
<b>OTHER SERVICES FOR RUN 3</b> Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations				<b>OTHER SERVICES FOR RUN 4</b> Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations				<b>OTHER SERVICES FOR RUN</b>			
<b>REMARKS: RUN NUMBER 3</b> Depth is referenced to Driller's Depth.  Gamma ray is corrected for mud weight, tool size and bit size.  Resistivity is borehole compensated and environmentally corrected.  Neutron porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity, and mud hydrogen index (a factor of mud weight, mud temperature and pressure).  Neutron porosity is calculated using a limestone matrix density of 2.71 g/cm3.  POOH due to loss of MWD signal.				<b>REMARKS: RUN NUMBER 4</b> Depth is referenced to Driller's Depth.  Gamma ray is corrected for mud weight, tool size and bit size.  Resistivity is borehole compensated and environmentally corrected.  Neutron porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity, and mud hydrogen index (a factor of mud weight, mud temperature and pressure).  Neutron porosity is calculated using a limestone matrix density of 2.71 g/cm3  POOH due to reaching TD of FTA A17A.				<b>REMARKS: RUN NUMBER</b>			

<b>EQUIPMENT DESCRIPTION</b>											
<b>RUN 3</b>				<b>RUN 4</b>				<b>RUN</b>			

## DOWNHOLE EQUIPMENT

## DOWNHOLE EQUIPMENT

6-3/4" adnVISION\*  
DHS: 8.3A02  
Blade OD: 8-1/4"  
S/N: 373

Neutron F 35.51  
Neutron N 35.35  
Density S 34.40  
Density L 34.31  
UltraSonic 33.92  
R-O Port 33.16

37.13

6-3/4" adnVISION\*  
DHS: 8.3A02  
Blade OD: 8-1/4"  
S/N: AD41

Neutron F 35.31  
Neutron N 35.15  
Density S 34.20  
Density L 34.11  
UltraSonic 33.72  
R-O Port 32.96

37.13

6-3/4" sonicVISION\*  
DHS: 6.6B04  
S/N: 649

Delta-T 27.88  
R-O port 27.48

31.15

6-3/4" sonicVISION\*  
DHS: 6.6B04  
S/N: 630

Delta-T 27.57  
R-O port 27.17

30.94

8-3/8" ILS  
S/N: S-31746-4

23.71

8-3/8" ILS  
S/N: OSS060654C

23.35

6-3/4" TeleScope  
MDC: FA27  
MEC: AB-232  
MDI: CA-2084  
MVC: PMVC-AA-109

D&I 18.48  
MVC 17.83

22.82

6-3/4" TeleScope  
MDC: VC64  
MEC: AB-373  
MDI: CA-1841  
MVC: PMVC-AA-282

D&I 17.89  
MVC 17.24

22.24

8-3/4" ILS  
S/N: OSS0701135

R-O Port 11.51  
T5 11.41  
T3 11.10  
T1 10.80

14.82

6-3/4" arcVISION\*  
DHS: 9.3b13  
S/N: FY68

Gamma Ray 10.44  
Receiver 10.39  
T2 10.14  
T4 9.83  
ARC APRS 9.68

13.82

8-3/4" ILS  
S/N: OSS0701135

R-O Port 11.51  
T5 11.41  
T3 11.10  
T1 10.80

14.82

6-3/4" arcVISION\*  
DHS: 9.3b13  
S/N: 1191

Gamma Ray 10.44  
Receiver 10.39  
T2 10.14  
T4 9.83  
ARC APRS 9.68

13.75

6-3/4" PowerDrive Xceed\*  
S/N: 109

7.91

6-3/4" PowerDrive Xceed\*  
S/N: 111

7.91

8-1/2" Reed Hycalog PDC Bit  
S/N: 215733

0.00  
0.25

8-1/2" Reed Hycalog PDC Bit  
S/N: 215733

0.00  
0.25

Maximum string diameter 8-1/2 in.

All lengths in Meters

Maximum string diameter 8-1/2 in.

All lengths in Meters

Variable Name	Variable Description	Run Name & Value	
Run Number		3	4
General Information			
BHT_RM	Bottom Hole Temperature (RM)	47.000000	90.000000
BSAL_RM	Mud Salinity (RM)	58.367577	57.291042
BS_RM	Bit Size (RM)	8.500000	8.500000
COEF_M	User Defined FEXP in Clean Sand	1.650000	1.650000
C_WS	Overpressure correction to Sw and M	1.000000	1.000000
FEXP	Formation Factor Exponent (RM)	2.000000	2.000000
FNUM	Formation Factor Enumerator (RM)	1.000000	1.000000
FPHI_RM	Formation Factor Porosity Source (RM)	XPLOT	XPLOT
MST_RM	Mud Sample temperature (RM)	23.88889	23.88889
MW_RM	Mud Weight (RM)	10.600000	10.650000
OBFM_RM	Oil Based Mud (RM)	YES	YES
RHOF_RM	Mud Filtrate Density (RM)	1.000000	1.000000
RHOM_RM	Matrix density (RM)	2.710000	2.710000
RMS_RM	Resistivity of Mud Sample (RM)	1000.000000	1000.000000
RWA_COMP_M	Rwa computation model	BASIC	BASIC
RWA_DEN_AD	Rwa Density Input ADN	ROBB	ROBB
RWA_DEN_CD	Rwa Density Input CDN	RHOB	RHOB
RWA_DEN_IN	Rwa Density Input	ROBB	ROBB
RWA_FORM_M	Rwa computation formation model	CLASTIC	CLASTIC
RWA_RES_IN	Rwa computation resistivity input	P34H	P34H
RWS_RM	Resistivity of Connate Water (RM)	1.000000	1.000000
SHT_RM	Surface Hole Temperature (RM)	10.000000	10.000000
TD_RM	Total Measured Depth (RM)	812.000000	3036.00000
TWS_RM	Temperature of Connate Water (RM)	23.88889	23.88889
VF_ILLI	Fraction of illite in shales	0.500000	0.500000
VF_KAOL	Fraction of kaolinite in shales	0.500000	0.500000
VF_MONT	Fraction of montmorillonite in shales	0.000000	0.000000
XPDM_RM	Cross plot density porosity multiplier	0.675000	0.675000
XPNM_RM	Cross plot neutron porosity multiplier	0.325000	0.325000
ARC			
LWD_RM/STATION_FILE/	PARAMETERStation Time-frame file name	Station	Station
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	8.980860	8.459310
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	8.986440	8.437310
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	5.964700	6.484980
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	5.966310	6.515550
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	5.607090	5.085840
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	5.602970	5.054970
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	3.871990	4.389600
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	3.869330	4.413140
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	4.157310	3.635930
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	4.162690	3.617580
ABNT	Abnormal Transmitter Indicator	No_Tx_Failed	No_Tx_Failed
ADHS	ARC Down Hole Software Version	No_Tx_Failed	No_Tx_Failed
ANISO_COMP	Anisotropy Computation Option	YES	YES
APICG	ARC5 Gamma Ray Gain Factor	1.039250	1.095470
APIG	ARC Gamma Ray API Gain Factor	-1.000000	-1.000000
ATMP_ARC	ARC Select Temperature Channel	Annulus_Temp	Annulus_Temp
ATRN	ARC Tool Run Number	3	4
ATSN	ARC Tool Serial Number	Annulus_Temp	Annulus_Temp
AZMF	Formation DIP Azimuth	0.000000	0.000000
BH_COMPUTE	Borehole Inversion Computation Option	YES	YES
CALG	ARC Gamma Ray Cal Gain Factor	1.039250	1.095470
CALI_SLCT	ARC Caliper Selection	BITSIZE	BITSIZE
CDPTH_ARC	Process Start Depth	100.000000	100.000000
DIELEC_COM	Dielectric Computation Option	YES	YES
DIPF	Formation DIP Angle	0.000000	0.000000
ERRCT	Percentage Error Cutoff	4.500000	4.500000
GRSH	GR Shale (Invasion Computation Cutoff)	1000.000000	1000.000000
HIGH_BLEND	High Resistivity Threshold for Blending	2.000000	2.000000
INCLIN_B0	ARC Bias Constant (mg)	0.000000	0.000000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	0.000000	0.000000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	0.000000	0.000000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	0.000000	0.000000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	1.000000	1.000000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	0.000000	0.000000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	0.000000	0.000000
INCLIN_C3	ARC Scale Third-order Coeeficient (mA/g/degC)	0.000000	0.000000
INVAS_COMP	Invasion Computation Option	YES	YES
JSD_ARC	ARC Acquisition start date	YES	YES
KPER	Potassium Concentration (RM)	0.000000	0.000000
LOW_BLEND	Low Resistivity Threshold for Blending	1.000000	1.000000
MSWS	ARC Wizard Model Switch Window	5.000000	5.000000
MULTIEFFEC	Multi Effect Option	YES	YES
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	1.019090	1.831860
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	-0.350909	-0.359529
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	-0.927967	-1.713500
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	0.284876	0.241835
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	0.923579	1.759360
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	-0.322901	-0.329207
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	-0.977645	-1.751440
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	0.287438	0.229570
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	0.906331	1.735070
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	-0.357818	-0.326719
POFFSET_AR	ARC: Pressure Offset	0.000000	0.000000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	P34B	P34B
PSOF_ADJ_T	ARC: User Input Phase offset	0.000000	0.000000

RESTIK	ARC resistivity tick source	Phase	Phase
SHIG	ARC High Shock Risk Level	0.500000	0.500000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore ) (RM)	10.000000	10.000000
SMED	ARC Medium Shock Risk Level	0.330000	0.330000
SMIN	ARC Minimum Shock Risk Level	0.160000	0.160000
SUPD	ARC Real Time Shock Update Rate	30.000000	30.000000
TCODE_ARC	ARC Tool File Code	30.000000	30.000000
TSIZ_ARC	ARC Tool Size	6.750000	6.750000
UNIFORM_CO	Uniform Rock Option	YES	YES
VERS_ARC	ARC Down hole software version Number	9.300000	9.300000
WRK	Way to Report Potassium Concentration (RM)	K_by_Wgt_%	K_by_Wgt_%

## ISONIC

FP_SD	First Sample delay	400.00	400.00
STC_CF	Center frequency of Filter	13.00	13.00
STC_BW	Bandwidth (kHz)	Default	Default
STC_RWI	Receiver waveform ignored	None	None
PM_TOFF	Tool Time offset from surface system	0.00	0.00
DT_COH	Delta-T Coherence Cutoff Value	0.70	0.70
PPC_PF	Porosity Formula	Raymer-Hunt	Raymer-Hunt
PPC_PS	Sonic Porosity Source	DTRA	DTRA
PPC_MDT	Matrix Delta-T	47.60	47.60
PPC_FDT	Fluid Delta-T	189.00	189.00

## ADN

ADN_CHASSI	ADN Chassis Type String	ADN	ADN
ADN_COLLAR	ADN Collar Type String	ADN	ADN
ADN_STAB_S	ADN Stabilizer Type String	ADN	ADN
ALPHA_COMP	Perform Density Enhanced Vertical Resolution process ?	YES	YES
ALPHA_COMP	Perform Neutron Enhanced Vertical Resolution process ?	YES	YES
AVE_ADN	ADN/Array Channels: perform averaging(RM) :	YES	YES
A_DHS	ADN Down Hole Software Version String	YES	YES
CHI_RM	Caliper High limit from BS (RM)	3.000000	3.000000
CLO_RM	Caliper Low limit from BS (RM)	0.000000	0.000000
DEVI	Well Section Deviation	26.219999	35.270000
DTIK_SEL	ADN: Density Tick Channel Name	LSAZ	LSAZ
DTMUD	Delta-T for Mud	208.699997	210.020004
DYN_IMG_CO	Generate Dynamic Normalized Image?	YES	YES
ECC_CORR_A	Perform Eccentering Correction for TNPH?	YES	YES
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES	YES
EVRL	EVR Process averaging number of samples (RM)	49	49
FCD	Future Casing (Outer) Diameter	0.000000	0.000000
GCSE	Generalized Caliper Selection	BS	BS
HPS	ADSE-EB (High Pressure Inconel Chassis)?	NO	NO
IBS	Integral Blade Stabilizer Collar?	YES	YES
IDQT	Image Derived Quality Threshold	1.000000	1.000000
IHVS	Integrated Hole Volume Start Value(RM)	0.000000	0.000000
IMAGE_MAX_	Image SOA (Quadrant) Right Scale	2.500000	2.500000
IMAGE_MAX_	Image PEF(Segment) Right Scale	6.000000	6.000000
IMAGE_MAX_	Image RHOB(Segment) Right Scale	2.650000	2.650000
IMAGE_MIN_	Image SOA (Quadrant) Left Scale	0.000000	0.000000
IMAGE_MIN_	Image PEF(Segment) Left Scale	2.000000	2.000000
IMAGE_MIN_	Image RHOB(Segment) Left Scale	2.050000	2.050000
JSD_ADN	ADN Acquisition start date	2.050000	2.050000
LITHO_TYPE	Lithology (RM)	LIME	LIME
N1FTU_6_RM	ADN: Neutron Bank 1 Far Tubes used :	1-2-3	1-2-3
N2FTU_6_RM	ADN: Neutron Bank 2 Far Tubes used :	1-2-3	1-2-3
NNTU_RM	ADN Neutron Near Banks Used	1-2	1-2
NTIK_SEL	ADN: Neutron Tick Channel Name	FR11	FR11
SOCNL	Standoff Distance of the CNL Tool	1.000000	1.000000
SSIZ_ADN	ADN Stabilizer Size	8.250000	8.250000
STOH	ADN Density Top of Hole Sector (Left Boundary):	SECTOR_0	SECTOR_0
TRPM_RM	Average Tool Rotational Speed	20.000000	20.000000
USMIN_RM	ADN:Minimum Ultrasonic standoff (RM)	0.180000	0.180000
USWF_RM	ADN:Process Ultrasonic Waveform?	YES	YES
VERS_ADN	ADN Downhole Software Version	8.300000	8.300000
WSDI	Window Size of Dynamic Normalization Image	15.000000	15.000000

Schlumberger Drilling & Measurements

Parameter Insert Header Software version 2.0c

## IDEAL Version: ID12\_OC\_11

IDF

Format: VISION Density Neutron RM Log

Vertical Scale: 1:500

Graphics File Created: 19-Sep-2007 17:02

### PIP SUMMARY

Neutron Samples +


+ Density Samples


+ ARC Gamma Ray Samples


Rate of Penetration, Averaged over Last  
5ft (ROP5\_RM)

200 (M/HR) 0


ARC Gamma Ray (GR\_ARC)






















































Density Time After Bit (TAB_DEN) (HR)		ADN Rotational Speed (RPM_ADN) (RPM)	Photoelectric Factor, Bottom (PEB) (-----)		Bulk Density Correction, Bottom (DRHB) (G/C3)	
0	10		0	10	-0.75	0.25
Horizontal Hole Diameter (HORD) (IN)		0 250	Bulk Density, Bottom (ROBB) (G/C3)			
6	16		1.85 2.85			
Vertical Hole Diameter (VERD) (IN)			Thermal Neutron Porosity (TNPH) (PU)			
6	16		45 -15			
ARC Gamma Ray (GR_ARC) (GAPI)		0 200				
Rate of Penetration, Averaged over Last 5ft (ROP5_RM) (M/HR)		0 200				

(M/HR)

0

PIP SUMMARY

Density Samples

ARC Gamma Ray Samples

Neutron Samples

IDEAL Version: ID12\_0C\_11

IDF

6.75-in. Azimuthal Density Neutron / Equipment Identification

Primary Equipment:  
Tool Name and Serial Number  
Collar Type and Serial Number  
Chassis Type and Serial Number  
Stabilizer Type and Serial Number  
Neutron Logging Source  
Density Logging Source  
Stabilizer Size  
Calibration Status

ADN6 – CA  
ADDC – AA  
ADSE – EA  
IBS  
NSR – M  
GSR – J/Z  
8.25 – in.  
Valid

373  
  
  
  
181  
2152

Master: 6-Jul-2007 23:40									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Magnesium Block									
Phase	LS window 3 – Mg CPS			Value	Phase	SS window 1 – Mg CPS			Value
Master	<div><div></div></div>			1234	Master	<div><div></div></div>			3101
	250.0	4125	8000			700.0	9350	18000	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Phase	SS window 3 – Mg CPS			Value					
Master	<div><div></div></div>			7425					
	2500	23750	45000						
	(Minimum)	(Nominal)	(Maximum)						

Master: 6-Jul-2007 23:40									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Aluminum Block									
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value
Master	<div><div></div></div>			183.8	Master	<div><div></div></div>			1555
	50.00	725.0	1400			500.0	4250	8000	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Phase	SS window 3 – Al CPS			Value					
Master	<div><div></div></div>			4633					
	1500	15750	30000						
	(Minimum)	(Nominal)	(Maximum)						

Master: 6-Jul-2007 23:40									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Background									
Phase	LS window 3 – Background CPS			Value	Phase	SS window 1 – Background CPS			Value
Master	<div><div></div></div>			50.04	Master	<div><div></div></div>			117.0
	15.00	82.50	150.0			40.00	220.0	400.0	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Phase	SS window 3 – Background CPS			Value					
Master	<div><div></div></div>			519.0					
	150.0	825.0	1500						
	(Minimum)	(Nominal)	(Maximum)						

Master: 6-Jul-2007 23:40									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Water Block Check									
Phase	Long spacing water density G/C3			Value	Phase	Short spacing water density G/C3			Value
Master	<div><div></div></div>			1.040	Master	<div><div></div></div>			1.151
	1.024	1.039	1.054			1.096	1.126	1.156	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	

Master: 6-Jul-2007 23:40									
6.75-in. Azimuthal Density Neutron Calibration									
Neutron: 3-Point Calibration									
Phase	Far 1 tube 1 Air Point Measure CPS			Value	Phase	Far 1 tube 1 Rod Point Measure CPS			Value
Master	<div><div></div></div>			17.64	Master	<div><div></div></div>			4.361
	13.30	19.05	24.70			3.400	4.857	6.200	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Phase	Far 1 tube 1 H2O Point Measure CPS			Value	Phase	Far 1 tube 2 Air Point Measure CPS			Value
Master	<div><div></div></div>			2.045	Master	<div><div></div></div>			18.63
	1.600	2.363	3.100			13.30	19.05	24.70	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Phase	Far 1 tube 2 Rod Point Measure CPS			Value	Phase	Far 1 tube 2 H2O Point Measure CPS			Value
Master	<div><div></div></div>			4.548	Master	<div><div></div></div>			2.193
	3.400	4.857	6.200			1.600	2.363	3.100	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Phase	Far 1 tube 3 Air Point Measure CPS			Value	Phase	Far 1 tube 3 Rod Point Measure CPS			Value
Master	<div><div></div></div>			17.55	Master	<div><div></div></div>			4.417
	13.30	19.05	24.70			3.400	4.857	6.200	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Phase	Far 1 tube 3 H2O Point Measure CPS			Value					
Master	<div><div></div></div>			2.165					
	1.600	2.363	3.100						
	(Minimum)	(Nominal)	(Maximum)						

13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)	3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)
Phase Far 2 tube 1 Air Point Measure	CPS	Value	Phase Far 2 tube 1 Rod Point Measure	CPS	Value	Phase Far 2 tube 1 H2O Point Measure	CPS	Value
Master		17.33	Master		4.720	Master		2.210
13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)	3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)
Phase Far 2 tube 2 Air Point Measure	CPS	Value	Phase Far 2 tube 2 Rod Point Measure	CPS	Value	Phase Far 2 tube 2 H2O Point Measure	CPS	Value
Master		18.63	Master		4.693	Master		2.260
13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)	3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)
Phase Far 2 tube 3 Air Point Measure	CPS	Value	Phase Far 2 tube 3 Rod Point Measure	CPS	Value	Phase Far 2 tube 3 H2O Point Measure	CPS	Value
Master		17.85	Master		4.397	Master		2.199
13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)	3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)
Phase Near 1 tube 1 Air Point Measure	CPS	Value	Phase Near 1 tube 1 Rod Point Measure	CPS	Value	Phase Near 1 tube 1 H2O Point Measure	CPS	Value
Master		478.6	Master		763.5	Master		336.3
345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)	535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)	230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)
Phase Near 2 tube 1 Air Point Measure	CPS	Value	Phase Near 2 tube 1 Rod Point Measure	CPS	Value	Phase Near 2 tube 1 H2O Point Measure	CPS	Value
Master		484.6	Master		758.4	Master		337.5
345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)	535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)	230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)

Master: 6-Jul-2007 23:40		
6.75-in. Azimuthal Density Neutron Calibration		
Neutron: Water Block Check		
Phase	Far Neutron water porosity PU	Value
Master		99.51
90.00 (Minimum)	100.0 (Nominal)	125.0 (Maximum)

6.75-in. Array Resistivity Compensated / Equipment Identification		
Primary Equipment:		
Tool Name and Serial Number	ARC6 - BA	460
ARC675 Calibration Status	Valid	

Master: 6-Jul-2007 11:12											
6.75-in. Array Resistivity Compensated Calibration											
Resistivity: Air											
Phase	Phase-Shift T1		Value	Phase	Phase-Shift T2		Value	Phase	Phase-Shift T3		Value
Master			1.019	Master			-0.9280	Master			0.9236
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T4		Value	Phase	Phase-Shift T5		Value	Phase	Phase-Shift T1 at 400KHz		Value
Master			-0.9776	Master			0.9063	Master			-0.3509
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T2 at 400KHz		Value	Phase	Phase-Shift T3 at 400KHz		Value	Phase	Phase-Shift T4 at 400KHz		Value
Master			0.2849	Master			-0.3229	Master			0.2874
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T5 at 400KHz		Value								
Master			-0.3578								
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)								











Master: 6-Jul-2007 11:12



Master: 6-Jul-2007 11:12

## 6.75-in. Array Resistivity Compensated Calibration


Resistivity: Air

Phase	Attenuation T1	Value	Phase	Attenuation T2	Value	Phase	Attenuation T3	Value	
Master		8.981	Master		5.965	Master		5.607	
	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)	2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)
Phase	Attenuation T4	Value	Phase	Attenuation T5	Value	Phase	Attenuation T1 at 400KHz	Value	
Master		3.872	Master		4.157	Master		8.986	
	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)
Phase	Attenuation T2 at 400KHz	Value	Phase	Attenuation T3 at 400KHz	Value	Phase	Attenuation T4 at 400KHz	Value	
Master		5.966	Master		5.603	Master		3.869	
	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)	2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)
Phase	Attenuation T5 at 400KHz	Value							
Master		4.163							
	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)						

Master: 6-Jul-2007 11:59

## 6.75-in. Array Resistivity Compensated Calibration

Gamma Ray: Blanket

Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS			Value
Master				4.988
	2.780 (Minimum)	4.800 (Nominal)	6.000 (Maximum)	

## 6.75-in. Azimuthal Density Neutron / Equipment Identification

Primary Equipment:  
 Tool Name and Serial Number  
 Collar Type and Serial Number  
 Chassis Type and Serial Number  
 Stabilizer Type and Serial Number  
 Neutron Logging Source  
 Density Logging Source  
 Stabilizer Size  
 Calibration Status

ADN6 - CA 437  
 ADDC - AA  
 ADSE - EA  
 IBS  
 NSR - M AD41  
 GSR - J/Z A181  
 8.25-in. A2152  
 Valid

Master: 12-Aug-2007 20:19

## 6.75-in. Azimuthal Density Neutron Calibration




Density: Magnesium Block

LS window 3 – Mg CPS				SS window 1 – Mg CPS				SS window 3 – Mg CPS			
Phase	Value			Phase	Value			Phase	Value		
Master	1259			Master	3081			Master	7740		
	250.0 (Minimum)	4125 (Nominal)	8000 (Maximum)		700.0 (Minimum)	9350 (Nominal)	18000 (Maximum)		2500 (Minimum)	23750 (Nominal)	45000 (Maximum)

Master: 12-Aug-2007 20:19

## 6.75-in. Azimuthal Density Neutron Calibration




Density: Aluminum Block

Phase	LS window 3 – AI CPS			Value	Phase	SS window 1 – AI CPS			Value	Phase	SS window 3 – AI CPS			Value
Master				190.0	Master				1584	Master				4908
	50.00 (Minimum)	725.0 (Nominal)	1400 (Maximum)		500.0 (Minimum)	4250 (Nominal)	8000 (Maximum)			1500 (Minimum)	15750 (Nominal)	30000 (Maximum)		

Master: 12-Aug-2007 20:19

## 6.75-in. Azimuthal Density Neutron Calibration

Density: Background

LS window 3 – Background CPS				Value	SS window 1 – Background CPS				Value	SS window 3 – Background CPS				Value
Phase					Phase					Phase				
Master				45.83	Master				129.6	Master				558.4
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)			150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)	

Master: 12-Aug-2007 20:19

## 6.75-in. Azimuthal Density Neutron Calibration

Density: Water Block Check

Phase	Long spacing water density G/C3	Value	Phase	Short spacing water density G/C3	Value
-------	---------------------------------	-------	-------	----------------------------------	-------

Master: 13-Aug-2007 12:10	
6.75-in. Array Resistivity Compensated Calibration	
Resistivity: Air	

Phase	Phase-Shift T1		Value	Phase	Phase-Shift T2		Value	Phase	Phase-Shift T3		Value
Master			1.832	Master			-1.714	Master			1.759
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T4		Value	Phase	Phase-Shift T5		Value	Phase	Phase-Shift T1 at 400KHz		Value
Master			-1.751	Master			1.735	Master			-0.3595
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T2 at 400KHz		Value	Phase	Phase-Shift T3 at 400KHz		Value	Phase	Phase-Shift T4 at 400KHz		Value
Master			0.2418	Master			-0.3292	Master			0.2296
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T5 at 400KHz		Value								
Master			-0.3267								
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)								

Master: 13-Aug-2007 12:10											
6.75-in. Array Resistivity Compensated Calibration											
Resistivity: Air											
Phase	Attenuation T1		Value	Phase	Attenuation T2		Value	Phase	Attenuation T3		Value
Master			8.459	Master			6.485	Master			5.086
	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)		4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)
Phase	Attenuation T4		Value	Phase	Attenuation T5		Value	Phase	Attenuation T1 at 400KHz		Value
Master			4.390	Master			3.636	Master			8.437
	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)		1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)		6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)
Phase	Attenuation T2 at 400KHz		Value	Phase	Attenuation T3 at 400KHz		Value	Phase	Attenuation T4 at 400KHz		Value
Master			6.516	Master			5.055	Master			4.413
	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)		2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)
Phase	Attenuation T5 at 400KHz		Value								
Master			3.618								
	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)								

Master: 12-Aug-2007 10:43											
6.75-in. Array Resistivity Compensated Calibration											
Gamma Ray: Blanket											
Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS									Value	
Master										5.258	
	2.780 (Minimum)			4.800 (Nominal)			6.000 (Maximum)				

SCHLUMBERGER			
Survey report		15-Sep-2007 02:12:10	Page 1 of 4
Client.....: ESSO Australia Pty Ltd			
Field.....: Fortescue			
Well.....: FTA A17A			
API number.....:			
Engineer.....: MYT/MA/ML			
RIG.....: ISDL 175			
STATE.....: Victoria			
----- Survey calculation methods-----			
Method for positions.....: Minimum curvature			
Method for DLS.....: Mason & Taylor			
----- Depth reference -----			
Permanent datum.....: Mean Sea Level			
Depth reference.....: Driller's Depth			
GL above permanent.....: -69.00 m			
KB above permanent.....: Top Drive			
DF above permanent.....: 42.50 m			
----- Vertical section origin-----			
Latitude (+N/S-).....: -4.05 m			
Departure (+E/W-).....: 4.49 m			
Spud date.....: 02-Sep-07			
Last survey date.....: 15-Sep-07			
Total accepted surveys...: 85			
MD of first survey.....: 660.00 m			
MD of last survey.....: 3036.00 m			
----- Geomagnetic data -----			
Magnetic model.....: BGGM version 2007			
Magnetic date.....: 03-Sep-2007			
Magnetic field strength...: 1199.44 HCNT			
Magnetic dec (+E/W-).....: 13.21 degrees			
Magnetic dip.....: -68.86 degrees			
----- MWD survey Reference Criteria -----			
Reference G.....: 1000.04 mGal			
Reference H.....: 1199.44 HCNT			
Reference Dip.....: -68.86 degrees			
Tolerance of G.....: (+/-) 2.50 mGal			
Tolerance of H.....: (+/-) 6.00 HCNT			
Tolerance of Dip.....: (+/-) 0.45 degrees			

Departure (+E/W-).....: 14.45 m  
----- Platform reference point-----  
Latitude (+N/S-).....:  
Departure (+E/W-).....:  
  
Azimuth from Vsect Origin to target: 126.84 degrees

Distance of Dip.....: 0.45 degrees  
----- Corrections -----  
Magnetic dec (+E/W-).....: 13.21 degrees  
Grid convergence (+E/W-)..: -0.79 degrees  
Total az corr (+E/W-).....: 14.00 degrees  
(Total az corr = magnetic dec - grid conv)  
Survey Correction Type ....  
I=Sag Corrected Inclination  
M=Schlumberger Magnetic Correction  
S=Shell Magnetic Correction  
F=Failed Axis Correction  
R=Magnetic Resonance Tool Correction  
D=Dmag Magnetic Correction

[(c)2007 IDEAL ID12\_OC\_12]  
SCHLUMBERGER Survey Report

15-Sep-2007 02:12:10

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
1	660.00	43.73	170.72	0.00	612.64	133.65	-180.10	39.59	184.40	167.60	0.00	TIP	None
2	687.00	45.37	160.65	27.00	631.90	148.38	-198.40	44.28	203.28	167.42	8.18	PUP	None
3	715.14	41.29	153.00	28.14	652.38	165.05	-216.14	51.83	222.27	166.52	7.20	PUP	None
4	743.13	38.36	149.47	27.99	673.88	181.36	-231.85	60.43	239.60	165.39	4.03	PUP	None
5	771.30	38.83	149.67	28.17	695.90	197.57	-247.01	69.33	256.55	164.32	0.53	PUP	None
6	799.42	39.10	149.36	28.12	717.76	213.88	-262.24	78.30	273.69	163.37	0.36	PUP	None
7	827.52	39.46	149.08	28.10	739.51	230.33	-277.53	87.41	290.97	162.52	0.44	PUP	None
8	856.31	40.00	148.79	28.79	761.65	247.38	-293.29	96.90	308.89	161.72	0.60	PUP	None
9	884.72	40.15	144.57	28.41	783.40	264.58	-308.57	106.95	326.57	160.88	2.92	PUP	None
10	913.55	39.38	139.55	28.83	805.56	282.36	-323.10	118.27	344.07	159.89	3.49	PUP	None
11	941.59	37.91	135.61	28.04	827.47	299.55	-336.03	130.07	360.33	158.84	3.11	PUP	None
12	969.73	35.92	129.16	28.14	849.97	316.35	-347.43	142.53	375.52	157.70	4.72	PUP	None
13	998.09	35.46	124.47	28.36	873.01	332.89	-357.34	155.76	389.81	156.45	2.98	PUP	None
14	1026.34	35.73	120.07	28.25	895.99	349.27	-366.11	169.66	403.51	155.14	2.78	PUP	None
15	1055.05	36.17	115.56	28.71	919.23	365.91	-373.97	184.56	417.03	153.73	2.85	PUP	None
16	1083.06	37.35	113.45	28.01	941.67	382.28	-380.91	199.81	430.14	152.32	1.88	PUP	None
17	1111.75	38.03	114.28	28.69	964.38	399.37	-388.01	215.85	444.01	150.91	0.90	PUP	None
18	1139.82	38.02	116.07	28.07	986.49	416.30	-395.37	231.50	458.15	149.65	1.20	PUP	None
19	1168.37	38.15	117.86	28.55	1008.96	433.65	-403.35	247.19	473.07	148.50	1.19	PUP	None
20	1196.91	38.43	118.41	28.54	1031.36	451.13	-411.69	262.79	488.41	147.45	0.47	PUP	None
21	1225.68	38.08	118.17	28.77	1053.95	468.75	-420.13	278.47	504.04	146.46	0.40	PUP	None
22	1254.40	37.78	118.21	28.72	1076.61	486.20	-428.47	294.03	519.66	145.54	0.32	PUP	None
23	1282.15	37.10	118.92	27.75	1098.64	502.89	-436.54	308.85	534.75	144.72	0.88	PUP	None
24	1310.69	35.83	119.76	28.54	1121.59	519.71	-444.85	323.63	550.12	143.96	1.46	PUP	None
25	1338.31	36.07	119.61	27.62	1143.95	535.80	-452.88	337.72	564.94	143.29	0.28	PUP	None
26	1367.80	36.15	119.73	29.49	1167.78	553.04	-461.48	352.82	580.90	142.60	0.11	PUP	None
27	1396.39	36.99	119.10	28.59	1190.74	569.93	-469.85	367.66	596.60	141.96	0.98	PUP	None
28	1424.23	38.52	117.23	27.84	1212.75	586.78	-477.89	382.69	612.23	141.31	2.09	PUP	None
29	1452.46	38.59	117.40	28.23	1234.83	604.13	-485.96	398.32	628.35	140.66	0.14	PUP	None
30	1481.68	37.43	117.54	29.22	1257.85	621.89	-494.26	414.29	644.92	140.03	1.21	PUP	None

[(c)2007 IDEAL ID12\_OC\_12]  
SCHLUMBERGER Survey Report

15-Sep-2007 02:12:10

Page 3 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
31	1510.46	37.27	117.52	28.78	1280.73	639.12	-502.33	429.77	661.09	139.45	0.17	PUP	None
32	1538.73	37.53	117.80	28.27	1303.18	656.07	-510.30	444.98	677.06	138.91	0.33	PUP	None
33	1566.81	38.82	118.34	28.08	1325.26	673.22	-518.47	460.29	693.31	138.40	1.45	PUP	None
34	1595.00	39.21	118.81	28.19	1347.16	690.78	-526.96	475.88	710.03	137.92	0.53	PUP	None
35	1623.56	38.55	118.75	28.56	1369.39	708.53	-535.59	491.59	726.99	137.45	0.71	PUP	None
36	1651.81	38.21	117.82	28.25	1391.54	725.88	-543.90	507.03	743.58	137.01	0.72	PUP	None
37	1680.22	38.26	117.49	28.41	1413.86	743.23	-552.06	522.61	760.19	136.57	0.23	PUP	None
38	1708.96	38.99	116.80	28.74	1436.31	760.92	-560.25	538.57	777.13	136.13	0.90	PUP	None
39	1737.21	39.94	115.58	28.25	1458.12	778.56	-568.17	554.68	794.03	135.69	1.32	PUP	None
40	1765.70	39.99	116.13	28.49	1479.95	796.53	-576.15	571.15	811.27	135.25	0.38	PUP	None
41	1793.80	40.23	117.14	28.10	1501.44	814.34	-584.26	587.33	828.45	134.85	0.75	PUP	None
42	1822.48	40.84	117.86	28.68	1523.24	832.74	-592.87	603.87	846.26	134.47	0.82	PUP	None
43	1851.42	40.26	118.35	28.94	1545.23	851.33	-601.73	620.46	864.32	134.12	0.70	PUP	None
44	1880.34	41.14	118.01	28.92	1567.16	869.97	-610.64	637.08	882.47	133.79	0.96	PUP	None
45	1907.88	41.63	117.36	27.54	1587.82	887.95	-619.10	653.21	899.98	133.46	0.72	PUP	None
46	1935.98	42.48	116.31	28.10	1608.68	906.48	-627.59	670.00	918.03	133.13	1.20	PUP	None
47	1965.09	39.30	113.83	29.11	1630.69	925.14	-635.68	687.25	936.16	132.77	3.74	PUP	None
48	1993.68	35.90	114.81	28.59	1653.34	942.16	-642.86	703.15	952.72	132.44	3.68	PUP	None
49	2022.04	34.84	117.69	28.36	1676.46	958.29	-650.11	717.87	968.49	132.16	2.12	PUP	None
50	2050.17	36.50	119.08	28.13	1699.32	974.52	-657.91	732.30	984.43	131.94	2.00	PUP	None
51	2079.41	37.84	119.35	29.24	1722.62	992.03	-666.53	747.72	1001.67	131.71	1.41	PUP	None
52	2107.37	38.50	118.68	27.96	1744.60	1009.14	-674.91	762.83	1018.53	131.50	0.85	PUP	None
53	2136.33	38.59	118.46	28.96	1767.25	1027.00	-683.54	778.68	1036.13	131.28	0.17	PUP	None
54	2164.51	37.93	118.78	28.18	1789.37	1044.27	-691.90	793.99	1053.16	131.07	0.75	PUP	None
55	2192.55	37.27	118.25	28.04	1811.59	1061.20	-700.07	809.03	1069.87	130.87	0.80	PUP	None
56	2220.97	36.42	118.58	28.42	1834.33	1078.06	-708.18	824.01	1086.52	130.68	0.94	PUP	None
57	2249.50	36.44	119.32	28.53	1857.29	1094.84	-716.38	838.84	1103.11	130.50	0.47	PUP	None
58	2277.75	36.84	121.02	28.25	1879.96	1111.58	-724.85	853.41	1119.70	130.34	1.18	PUP	None
59	2305.75	37.44	122.32	28.00	1902.28	1128.42	-733.73	867.80	1136.41	130.21	1.08	PUP	None
60	2334.40	37.22	121.22	28.65	1925.06	1145.73	-742.88	882.57	1153.60	130.09	0.75	PUP	None

Seq # -	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
61	2362.79	36.69	117.35	28.39	1947.75	1162.64	-751.22	897.45	1170.36	129.93	2.56	PUP	None
62	2389.95	36.62	116.10	27.16	1969.54	1178.60	-758.52	911.93	1186.15	129.75	0.84	PUP	None
63	2417.94	37.08	116.97	27.99	1991.94	1195.11	-766.02	926.95	1202.50	129.57	0.76	PUP	None
64	2446.07	36.80	117.57	28.13	2014.42	1211.78	-773.76	941.97	1219.02	129.40	0.49	PUP	None
65	2474.11	36.23	117.97	28.04	2036.96	1228.26	-781.53	956.74	1235.37	129.24	0.67	PUP	None
66	2502.44	38.25	117.50	28.33	2059.51	1245.19	-789.51	971.91	1252.17	129.09	2.19	PUP	None
67	2531.37	39.64	117.87	28.93	2082.01	1263.14	-797.96	988.01	1270.00	128.93	1.48	PUP	None
68	2559.98	39.78	118.54	28.61	2104.02	1281.21	-806.60	1004.12	1287.97	128.77	0.48	PUP	None
69	2588.17	38.68	118.97	28.19	2125.85	1298.86	-815.18	1019.75	1305.53	128.64	1.23	PUP	None
70	2617.01	38.16	118.71	28.84	2148.45	1316.61	-823.82	1035.45	1323.19	128.51	0.58	PUP	None
71	2645.27	38.52	118.20	28.26	2170.61	1333.95	-832.17	1050.86	1340.46	128.38	0.52	PUP	None
72	2674.42	39.10	118.05	29.15	2193.33	1352.01	-840.78	1066.97	1358.44	128.24	0.61	PUP	None
73	2702.52	39.10	117.27	28.10	2215.14	1369.51	-849.01	1082.67	1375.86	128.10	0.53	PUP	None
74	2731.28	37.85	117.19	28.76	2237.65	1387.15	-857.20	1098.58	1393.44	127.96	1.33	PUP	None
75	2760.06	36.63	118.45	28.78	2260.56	1404.35	-865.32	1113.98	1410.58	127.84	1.52	PUP	None
76	2788.47	36.29	120.03	28.41	2283.41	1421.08	-873.57	1128.72	1427.28	127.74	1.07	PUP	None
77	2817.01	37.24	118.98	28.54	2306.28	1438.02	-881.98	1143.58	1444.19	127.64	1.22	PUP	None
78	2845.58	38.07	117.86	28.57	2328.89	1455.29	-890.29	1158.93	1461.41	127.53	1.15	PUP	None
79	2871.86	38.33	117.10	26.28	2349.55	1471.32	-897.78	1173.35	1477.42	127.42	0.62	PUP	None
80	2902.30	37.94	116.95	30.44	2373.49	1489.84	-906.33	1190.09	1495.91	127.29	0.40	PUP	None
81	2931.13	37.24	118.15	28.83	2396.33	1507.20	-914.46	1205.69	1513.25	127.18	1.07	PUP	None
82	2960.01	37.98	118.12	28.88	2419.21	1524.62	-922.77	1221.23	1530.65	127.07	0.78	PUP	None
83	2988.74	38.14	118.12	28.73	2441.83	1542.13	-931.12	1236.85	1548.15	126.97	0.17	PUP	None
84	3014.84	38.56	117.68	26.10	2462.30	1558.12	-938.69	1251.16	1564.15	126.88	0.58	PUP	None
85	3036.00	38.85	117.38	21.16	2478.81	1571.18	-944.81	1262.90	1577.20	126.80	0.50	Projected to TD	

[(c)2007 IDEAL ID12\_OC\_12]

Company: **ESSO Australia Pty Ltd**

Well: **FTA A17A**  
Field: **Fortescue**  
Rig: **ISDL 175**  
State: **Victoria**

**8.5 in. Section**

**Schlumberger**

**VISION Density Neutron**  
**1:500 Measured Depth**  
**Recorded Mode Log**