

Company: Ezzo Australia Pty Ltd.

Well: B-16

Field: Bream B

Rig: Crane / Prod # 4 Country: Australia

2-1/8" Phased Powerjet MWPT
Perforation Record
7" Posiset Plug Setting Record

Rig: Crane / Prod # 4
Field: Bream B
Location: Gippsland
Well: B-16
Company: Ezzo Australia Pty Ltd.

LOCATION			
Gippsland Basin Bass Strait		Elev.: K.B. 47.17 m G.L. 47.17 m D.F. -61 m	
Permanent Datum:	M.S.L.		
Log Measured From:	K.B.	47.2 m	above Perm. Datum
Drilling Measured From:	K.B.		
State: Victoria	Max. Well Deviation 58 deg	Longitude 148°06'15.37E	Latitude 038°35'40.34S

Logging Date	5-Mar-2008		
Run Number	1 through 6		
Depth Driller	2250 m		
Schlumberger Depth	2230 m		
Bottom Log Interval	2205 m		
Top Log Interval	1950 m		
Casing Fluid Type	Production Fluids		
Salinity			
Density			
Fluid Level	50 m		
BIT/CASING/TUBING STRING			
Bit Size	8.500 in		
From	836 m		
To	2641 m		
Casing/Tubing Size	7.000 in		
Weight	26 lbm/ft		
Grade	L-80		
From	27 m		
To	2626 m		
Maximum Recorded Temperatures	228 degF		
Logger On Bottom	5-Mar-2008	Time	11:00
Unit Number	889	Location	Prod 4 / AUSL
Recorded By	S Gilbert		
Witnessed By	G Rimmer		

Run 1			
Oil Density			
Water Salinity			
Gas Gravity			
Bo			
Bw			
1/Bg			
Bubble Point Pressure			
Bubble Point Temperature			
Solution GOR			
Maximum Deviation			
CEMENTING DATA			
Primary/Squeeze			
Casing String No			
Lead Cement Type			
Volume			
Density			
Water Loss			
Additives			
Tail Cement Type			
Volume			
Density			
Water Loss			
Additives			
Expected Cement Top			
Logging Date			
Run Number			
Depth Driller			
Schlumberger Depth			
Bottom Log Interval			
Top Log Interval			
Casing Fluid Type			
Salinity			
Density			
Fluid Level			
BIT/CASING/TUBING STRING			
Bit Size			
From			
To			
Casing/Tubing Size			
Weight			
Grade			
From			
To			
Maximum Recorded Temperatures			
Logger On Bottom			
Unit Number			
Recorded By			
Witnessed By			

DEPTH SUMMARY LISTING

Depth Control Parameters	
Log Sequence:	Subsequent Trip To the Well
Reference Log Name:	ExxonMobil Petrophysical Analysis
Reference Log Run Number:	
Reference Log Date:	.
Subsequent Trip Down Log Correction:	

DISCLAIMER















THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

REMARKS: RUN NUMBER 1	REMARKS: RUN NUMBER 2
-----------------------	-----------------------

Objectives: Perforate the well over the intervals 2191.5m to 2192.9m MDKB and 2161.8m to 2164.8m MDKB.
using 2-1/8" 6 SPF, 45 deg phased Powerjet guns with MWPT.

Maximum Deviation = 58deg @ 2045m MDKB

Gun#1	Gun#2
-------	-------

Top Shot @ 2191.5m MDKB			Top Shot @ 2161.8m MDKB			
CCL to Top Shot= 3.4 m			CCL to Top Shot= 3.4m MDKB			
CCL Stop Depth= 2188.1m MKDB			CCL Stop Depth= 2158.4 m MDKB			
7" Posiset Plug						
Top of Seal @ 2200m MDKB						
CCL to Top of Seal = 7m						
CCL Stop Depth = 2193m MDKB						
2.13 Dummy Plug Ran to ensure access for Posiset Plug.						
Schlumberger crews:J Light , C Shiells						
RUN 1						
SERVICE ORDER #: PROGRAM VERSION: FLUID LEVEL:			AUSL07336281 15C0-309 50 m			
LOGGED INTERVAL	START	STOP	LOGGED INTERVAL	START	STOP	
EQUIPMENT DESCRIPTION						
RUN 1			RUN 2			
SURFACE EQUIPMENT			SURFACE EQUIPMENT			
MWPM-AA			MPBM 81			
DOWNHOLE EQUIPMENT			DOWNHOLE EQUIPMENT			
SWBS 787		11.50	SWBS-B 785		11.53	
SWBS 785		10.81	SWBS-B 786		10.84	
SWBS 786		10.13	SWBS-B 787		10.16	
SWHS 759		9.44	SWHS-A 759		9.47	
AH-124		9.08	CCL Tachometer Cable Cur Head Volt Tension		TOOL ZERO 9.13	
MWGT-AA		8.88				CCL-L
MWPG-AA 69 MWGH-AA 69		MWPG GR 2.41				CCL-L
MWPT-CA		7.90	MPSU-CA 01102		8.67	
MWPH-AA 74 MWPS-AA 74					MPSU-CA 1011	
	CCL SMWP Pres SMWP Temp Tension	TOOL ZERO				
AH-Flex-Joint 42		5.08				
AH-Flex-Joint 42						

SAH-G
SAH-G 1035

MPD-MB
MPD-MB 268

AH-ESIC
AH-ESIC 15042003

MWP_GUN
GUN-3m 2 1/8" Phased Enerjet Gun

4.60

4.07

3.53

3.05

TOOL BOTTOM


MAXIMUM STRING DIAMETER 2.13 IN
MEASUREMENTS RELATIVE TO TOOL ZERO
ALL LENGTHS IN METERS


MPEX-7" 26lb/ft Posiset Pulg
MPEX-7" 26lb/ft Posiset Pulg

2.26

TOOL BOTTOM

MAXIMUM STRING DIAMETER 2.13 IN
MEASUREMENTS RELATIVE TO TOOL ZERO
ALL LENGTHS IN METERS

Production String	(in)		(m)	Well Schematic	(m)	(in)		Casing String
	OD	ID	MD		MD	OD	ID	
Tubing	3.500		27.6		27.0	9.625		Casing String
Tubing Hanger	7.000	3.500	25.0		27.0	20.000	9.625	Liner Hanger
					153.0	20.000		Casing Shoe
					26.0	20.000		Casing String
Shutin Valve	3.500		450.3					
Gas Lift Mandrel	3.500		526.2					
Gas Lift Mandrel	3.500		766.0		808.9	9.625		Casing Shoe
Nipple	3.500		999.6					



Job Events Summary

MAXIS Field Log

Schlumberger Job Event Summary

Time	Elapsed Time	Depth (M)	File
Log Pass (up)	5-Mar-2008 11:55	000:24	2233.6 – 1938.2 PSP_025LUP
Log Pass (up)	5-Mar-2008 14:29	000:04	2212.4 – 2176.7 PERFO_036LUP
Log Pass (up)	5-Mar-2008 14:33	000:11	2210.1 – 2165.9 PERFO_037LUP
Station Log	5-Mar-2008 14:38	000:03	2188.1 – 0.4 PERFO_038LTP
Log Pass (up)	6-Mar-2008 9:42	000:06	2177.9 – 2137.1 PERFO_047LUP
Log Pass (up)	6-Mar-2008 9:52	000:13	2178.3 – 2132.7 PERFO_048LUP
Station Log	6-Mar-2008 9:55	000:08	2158.4 – 1.0 PERFO_049LTP
Log Pass (up)	6-Mar-2008 11:51	000:02	2181.9 – 2164.1 MPBT_061LUP
Simulated Log	6-Mar-2008 12:00	000:40	MPBT_064LUP
Log Pass (up)	6-Mar-2008 12:41	000:05	2192.9 – 2148.4 MPBT_065LUP
Log Pass (up)	7-Mar-2008 9:54	000:09	2191.4 – 2148.5 PERFO_072LUP
Log Pass (up)	7-Mar-2008 11:18	000:08	2190.0 – 2149.4 PERFO_076LUP



Cement Dump Pass

MAXIS Field Log

Output DLIS Files

DEFAULT PERFO_076LUP FN:75 PRODUCER 07-Mar-2008 11:18 2190.0 M 2149.4 M


OP System Version: 15C0-309
MCM


SHM_GUN SRPC-3546-Q1_2008_OP15 CCL-L SRPC-3546-Q1_2008_OP15

PIP SUMMARY

└─ Casing Collars

Time Mark Every 60 S





PIP SUMMARY

← Casing Collars

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
CCL-L	Casing Collar Locator	
CCLD	CCL reset delay	12 IN
CCLT	CCL Detection Level	0.3 V

Format: PERFO Vertical Scale: 1:200 Graphics File Created: 07-Mar-2008 11:18

OP System Version: 15C0-309

MCM

SHM_GUN SRPC-3546-Q1_2008_OP15 CCL-L SRPC-3546-Q1_2008_OP15

Output DLIS Files

DEFAULT PERFO_076LUP FN:75 PRODUCER 07-Mar-2008 11:18

Schlumberger

Water Dump Pass

Output DLIS Files

DEFAULT PERFO_072LUP FN:71 PRODUCER 07-Mar-2008 09:54 2191.4 M 2148.5 M

OP System Version: 15C0-309



MCM


SHM_GUN SRPC-3546-Q1_2008_OP15 CCL-L SRPC-3546-Q1_2008_OP15

PIP SUMMARY

└─ Casing Collars

Time Mark Every 60 S





PIP SUMMARY

Time Mark Every 60 S

Casing Collars

Parameters		
DLIS Name	Description	Value
CCLD	CCL-L: Casing Collar Locator	12 IN
CCLT	CCL reset delay	0.3 V
	CCL Detection Level	

Format: PERFO Vertical Scale: 1:200 Graphics File Created: 07-Mar-2008 09:54

OP System Version: 15C0-309			
MCM			
SHM_GUN	SRPC-3546-Q1_2008_OP15	CCL-L	SRPC-3546-Q1_2008_OP15

Output DLIS Files			
DEFAULT	PERFO_072LUP	FN:71	PRODUCER 07-Mar-2008 09:54


Log Away From Plug Setting

MAXIS Field Log

Output DLIS Files			
DEFAULT	MPBT_065LUP	FN:64	PRODUCER 06-Mar-2008 12:41

OP System Version: 15C0-309			
MCM			
MPEX-7"	26lb/ft	MPSU-CA	SRPC-3546-Q1_2008_OP15
CCL-L	SRPC-3546-Q1_2008_OP15		

PIP SUMMARY




DLIS Name	Description	Value
CCL-L: Casing Collar Locator		
CCLD	CCL reset delay	12 IN
CCLT	CCL Detection Level	0.3 V


Format: PERFO		Vertical Scale: 1:200		Graphics File Created: 06-Mar-2008 12:41	
OP System Version: 15C0-309					
MCM					
MPEX-7"	26lb/ft	MPSU-CA	SRPC-3546-Q1_2008_OP15		
CCL-L	SRPC-3546-Q1_2008_OP15				
Output DLIS Files					
DEFAULT	MPBT_065LUP	FN:64	PRODUCER	06-Mar-2008 12:41	


<div> <div>Schlumberger</div> <div> <div>7" Posiset Plug Setting Record (TOS @ 2201m MDKB)</div> <div>MAXIS Field Log</div> </div> </div>			
---	--	--	--


<div>Output DLIS Files</div>			
DEFAULT	MPBT_064LUP	FN:63	PRODUCER 06-Mar-2008 12:00
<div>OP System Version: 15C0-309</div> <div>MCM</div>			
MPEX-7" CCL-L	26lb/ft SRPC-3546-Q1_2008_OP15	MPSU-CA	SRPC-3546-Q1_2008_OP15


<div>PIP SUMMARY</div> <div> <div>↵ MPSU Run Time Every 1 MN</div> <div>↵ MPSU Run Time Every 10 MN</div> </div>			
<div> <div>Time Mark Every 60 S</div> </div>			











Differential Tension (DTEN) (LBF)	ON/Int From D3T to STAT	MPBM Cable Current (CCUR) (MA)
-200 200	300 700	
MPSU Head Voltage (HV) (V)	MPSU Run Status (STAT)	Tension (TENS) (LBF)
200 300	0 (----10)	2000 0
	RUN Time (RTIM) (MN)	

PIP SUMMARY

- ↵ MPSU Run Time Every 1 MN
- ↵ MPSU Run Time Every 10 MN

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MPSU-CA: MECHANICAL PLUGBACK SETTING UNIT IPUMP	Intensifier Pump	TRUE

Format: MPBT Vertical Scale: 1:600 Graphics File Created: 06-Mar-2008 12:00

OP System Version: 15C0-309

MCM

MPEX-7" CCL-L	26lb/ft SRPC-3546-Q1_2008_OP15	MPSU-CA	SRPC-3546-Q1_2008_OP15
------------------	-----------------------------------	---------	------------------------

Output DLIS Files

DEFAULT	MPBT_064LUP	FN:63	PRODUCER	06-Mar-2008 12:00
---------	-------------	-------	----------	-------------------

Output DLIS Files

DEFAULT MPBT_061LUP FN:60 PRODUCER 06-Mar-2008 11:51 2181.9 M 2164.1 M


OP System Version: 15C0-309
MCM

MPEX-7" 26lb/ft MPSU-CA SRPC-3546-Q1_2008_OP15
CCL-L SRPC-3546-Q1_2008_OP15

PIP SUMMARY

Casing Collars

Time Mark Every 60 S



PIP SUMMARY

Casing Collars

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
CCL-L	Casing Collar Locator	12 IN
CCLD	CCL reset delay	0.3 V
CCLT	CCL Detection Level	

Format: PERFO Vertical Scale: 1:200 Graphics File Created: 06-Mar-2008 11:51

OP System Version: 15C0-309
MCM

MPEX-7" 26lb/ft MPSU-CA SRPC-3546-Q1_2008_OP15
CCL-L SRPC-3546-Q1_2008_OP15

Output DLIS Files



Correlate Plug to EOT.

MAXIS Field Log

Output DLIS Files

DEFAULTMPBT_059LUPFN:58PRODUCER06-Mar-2008 11:412016.3 M1983.9 M


OP System Version: 15C0-309
MCM



MPEX-7"26lb/ftMPSU-CA
CCL-LSRPC-3546-Q1_2008_OP15SRPC-3546-Q1_2008_OP15

PIP SUMMARY

└─ Casing Collars

Time Mark Every 60 S





PIP SUMMARY

Time Mark Every 60 S

Casing Collars

Parameters		
DLIS Name	Description	Value
CCL-L: Casing Collar Locator		
CCLD	CCL reset delay	12 IN
CCLT	CCL Detection Level	0.3 V

Format: PERFO Vertical Scale: 1:200 Graphics File Created: 06-Mar-2008 11:41

OP System Version: 15C0-309

MCM


MPEX-7" 26lb/ft MPSU-CA SRPC-3546-Q1_2008_OP15


CCL-L SRPC-3546-Q1_2008_OP15

Output DLIS Files		
DEFAULT	MPBT_059LUP	FN:58 PRODUCER 06-Mar-2008 11:41

Gun#2 Fired @
2261.8m to 2264.8m MDKB

MAXIS Field Log





TIME	KPA	PSIA	DEGF
1820.0	18862.3948	2735.7632	220.8580
1840.0	18887.7402	2739.4391	221.1192
1860.0	18887.5906	2739.4174	221.1226
1880.0	18890.6239	2739.8574	221.1319
1900.0	18888.0355	2739.4819	221.1251
1920.0	18887.9612	2739.4712	221.1091
1940.0	18888.1816	2739.5032	221.1260
1960.0	18863.9881	2735.9942	221.0728
1980.0	18875.2306	2737.6248	221.0593
2000.0	18875.7476	2737.6997	223.3611
2020.0	18876.5602	2737.8176	225.3153
2040.0	18886.2538	2739.2235	225.7519
2060.0	18882.1107	2738.6226	227.1453
2080.0	18879.2247	2738.2040	227.4652
2100.0	18880.0384	2738.3221	227.6777
2120.0	18889.9605	2739.7612	227.2529
2140.0	18886.8512	2739.3103	228.0005
2160.0	18887.1495	2739.3535	227.9730
2180.0	18887.5881	2739.4171	227.7302
2200.0	18881.7378	2738.5686	228.2382
2220.0	18888.0362	2739.4821	227.8810

Schlumberger

Gun#2 Shooting Pass

MAXIS Field Log

Company: Esso Australia Pty Ltd.

Well: B-16

Output DLIS Files

DEFAULT PERFO_048LUP FN:47 PRODUCER 06-Mar-2008 09:52 2178.3 M 2132.7 M


OP System Version: 15C0-309


MCM

MWP_GUN SRPC-3546-Q1_2008_OP15 MWPT-CA SRPC-3546-Q1_2008_OP15

PIP SUMMARY

Time Mark Every 60 S





PIP SUMMARY


☐ Time Mark Every 60 S

Parameters			
DLIS Name	Description	Value	
MWPT-CA: MEASUREMENT WHILE PERFORATING TOOL			
DEVI_FL_CORR	Deviation Angle for Flow Line Correction	0	DEG
FLD	Flow Line Density	1	G/C3
MWPT_NULL_SOURCE	MWPT NULL Temperature Source	TEMS	
MWPT_NULL_TEMP	MWPT NULL Temperature	0.0	DEGC

Format: MWP Vertical Scale: 1:200 Graphics File Created: 06-Mar-2008 09:52

OP System Version: 15C0-309			
MCM			
MWP_GUN	SRPC-3546-Q1_2008_OP15	MWPT-CA	SRPC-3546-Q1_2008_OP15
MWGT-AA	SRPC-3546-Q1_2008_OP15		

Output DLIS Files			
DEFAULT	PERFO_048LUP	FN:47	PRODUCER 06-Mar-2008 09:52



Gun#2 Correlation Pass

MAXIS Field Log

Company: Esso Australia Pty Ltd. Well: B-16

Output DLIS Files			
DEFAULT	PERFO_047LUP	FN:46	PRODUCER 06-Mar-2008 09:42


OP System Version: 15C0-309


MCM

PIP SUMMARY

Time Mark Every 60 S

		Pressure (SGP) (PSIA)	
Temperature (TEMP_MWPT) (DEGF)		Tension (TENS) (LBF)	
		0	2000
CCL From CCL to T1		Temperature (TEMP_MWPT) (DEGF)	
		0	2
Gamma Ray (GR) (GAPI)		Strain Gauge Pressure (SGP) (PSIA)	
0		0	20
Casing Collar Locator (CCL)		Temperature (TEMP_MWPT) (DEGF)	
-19 (----		215	225
Cable Speed (CS) (F/HR)		Strain Gauge Pressure (SGP) (PSIA)	
0		2700	2800
5000			





PIP SUMMARY

Time Mark Every 60 S

Parameters		
DLIS Name	Description	Value
MWPT-CA: MEASUREMENT WHILE PERFORATING TOOL		
DEVI_FL_CORR	Deviation Angle for Flow Line Correction	0 DEG
FLD	Flow Line Density	1 G/C3
MWPT_NULL_SOURCE	MWPT NULL Temperature Source	TEMS
MWPT_NULL_TEMP	MWPT NULL Temperature	0.0 DEGC

Format: MWP Vertical Scale: 1:200 Graphics File Created: 06-Mar-2008 09:42

OP System Version: 15C0-309
MCM

MWP_GUN	SRPC-3546-Q1_2008_OP15	MWPT-CA	SRPC-3546-Q1_2008_OP15
MWGT-AA	SRPC-3546-Q1_2008_OP15		


Output DLIS Files

DEFAULT	PERFO_047LUP	FN:46	PRODUCER	06-Mar-2008 09:42
---------	--------------	-------	----------	-------------------

Gun#1 Fired @
2291.5m to 2292.9m MDKB

MAXIS Field Log





TIME	KPA	PSIA	DEGF
1520.0	18988.6392	2754.0734	222.9583
1530.0	18990.7520	2754.3796	222.9664
1540.0	18992.6602	2754.6565	222.9634
1550.0	18990.0191	2754.2734	222.9815
1560.0	18992.9237	2754.6948	222.9896
1570.0	18990.7932	2754.3856	223.0064
1580.0	18988.4141	2754.0408	222.9840
1590.0	18988.4141	2754.0408	222.9840
1600.0	18975.8115	2752.2128	222.9178
1610.0	18971.5687	2751.5974	222.9236
1620.0	18976.1178	2752.2573	222.9234
1630.0	18982.1265	2753.1287	223.0518
1640.0	18983.1268	2753.2738	223.1004
1650.0	18981.8118	2753.0830	224.2010
1660.0	18986.6250	2753.7813	225.2490

Schlumberger

Gun#1 Shooting Pass

MAXIS Field Log

Output DLIS Files

DEFAULT

PERFO_037LUP

FN:36

PRODUCER

05-Mar-2008 14:33 2210.1 M

2165.9 M

OP System Version: 15C0-309

MCM


MWP_GUN
MWGT-AASRPC-3546-Q1_2008_OP15
SRPC-3546-Q1_2008_OP15


MWPT-CA

SRPC-3546-Q1_2008_OP15

PIP SUMMARY

Time Mark Every 60 S





Cable Speed (CS) (F/HR)		Strain Gauge Pressure (SGP) (PSIA)	
0	5000	2700	2800
Casing Collar Locator (CCL) (-----)		Temperature (TEMP_MWPT) (DEGF)	
-19	1	215	225
Gamma Ray (GR) (GAPI)		Strain Gauge Pressure (SGP) (PSIA)	
0	150	0	20
CCL From CCL to T1		Temperature (TEMP_MWPT) (DEGF)	
Temperature (TEMP_MWPT) (DEGF)		Tension (TENS) (LBF)	
		0	2000
		Pressure (SGP) (PSIA)	

PIP SUMMARY

Time Mark Every 60 S

Parameters			
DLIS Name	Description	Value	
MWPT-CA: MEASUREMENT WHILE PERFORATING TOOL			
DEVI_FL_CORR	Deviation Angle for Flow Line Correction	0	DEG
FLD	Flow Line Density	1	G/C3
MWPT_NULL_SOURCE	MWPT NULL Temperature Source	TEMS	
MWPT_NULL_TEMP	MWPT NULL Temperature	0.0	DEGC

Format: MWP Vertical Scale: 1:200 Graphics File Created: 05-Mar-2008 14:33

OP System Version: 15C0-309			
MCM			
MWP_GUN	SRPC-3546-Q1_2008_OP15	MWPT-CA	SRPC-3546-Q1_2008_OP15
MWGT-AA	SRPC-3546-Q1_2008_OP15		

Output DLIS Files			
DEFAULT	PERFO_037LUP	FN:36	PRODUCER 05-Mar-2008 14:33

Schlumberger

Gun#1 Correlation Pass

MAXIS Field Log

Output DLIS Files

DEFAULT PERFO_036LUP FN:35 PRODUCER 05-Mar-2008 14:29

OP System Version: 15C0-309


MCM


MWP_GUN SRPC-3546-Q1_2008_OP15 MWPT-CA SRPC-3546-Q1_2008_OP15
MWGT-AA SRPC-3546-Q1_2008_OP15

PIP SUMMARY

Time Mark Every 60 S

		Pressure (SGP) (PSIA)	
		Tension (TENS) (LBF)	
		0	2000
Temperature (TEMP_MWPT) (DEGF)		Temperature (TEMP_MWPT) (DEGF)	
CCL From CCL to T1		Strain Gauge Pressure (SGP) (PSIA)	
Gamma Ray (GR) (GAPI)		0	20
Casing Collar Locator (CCL)		Temperature (TEMP_MWPT) (DEGF)	
-19	(----	215	225
Cable Speed (CS) (F/HR)		Strain Gauge Pressure (SGP) (PSIA)	
0	5000	2700	2800





PIP SUMMARY


Time Mark Every 60 S

Parameters			
DLIS Name	Description	Value	
MWPT-CA: MEASUREMENT WHILE PERFORATING TOOL			
DEVI_FL_CORR	Deviation Angle for Flow Line Correction	0	DEG
FLD	Flow Line Density	1	G/C3
MWPT_NULL_SOURCE	MWPT NULL Temperature Source	TEMS	
MWPT_NULL_TEMP	MWPT NULL Temperature	0.0	DEGC

Format: MWP Vertical Scale: 1:200 Graphics File Created: 05-Mar-2008 14:29

OP System Version: 15C0-309			
MCM			
MWP_GUN	SRPC-3546-Q1_2008_OP15	MWPT-CA	SRPC-3546-Q1_2008_OP15
MWGT-AA	SRPC-3546-Q1_2008_OP15		

Output DLIS Files			
DEFAULT	PERFO_036LUP	FN:35	PRODUCER 05-Mar-2008 14:29



2.13" Dummy Plug Pass


MAXIS Field Log


Company: Esso Australia Pty Ltd. Well: B-16


Input DLIS Files					
DEFAULT	PSP_025LUP	FN:24	PRODUCER	05-Mar-2008 11:55	2233.6 M 1938.2 M
Output DLIS Files					
DEFAULT	PSP_026PUP	FN:25	PRODUCER	05-Mar-2008 12:21	2235.1 M 1933.0 M


PIP SUMMARY


Time Mark Every 60 S














Gamma Ray (GR) (GAPI)	Discriminat ed CCL (CCLD) (V)	Cable Speed (CS) (F/HR)	Tension (TENS) (LBF)
0	3	0	0
150	-1	5000	2000

Perfo Zone From PERFO_ CURVE to D3T	Well Temperature (WTEP) (DEGF)
	210
	225

	Well Pressure (WPRE) (PSIA)		Temperature (WTEP) (DEGF)
	Well Temperature (WTEP) (DEGF)		
	0		10
	Well Pressure (WPRE) (PSIA)		
	2600		2800
	Amplified Well Pressure (WPRE) (PSIA)		
	0		20

PIP SUMMARY			
Time Mark Every 60 S			
Format: PSP_1		Vertical Scale: 1:200	Graphics File Created: 05-Mar-2008 12:21

OP System Version: 15C0-309			
MCM			
PSPT-B	SRPC-3546-Q1_2008_OP15		

Parameters							
DLIS Name		Description				Value	
System and Miscellaneous							
DO		Depth Offset for Playback				1.6	M
PP		Playback Processing				NORMAL	
Input DLIS Files							
DEFAULT	PSP_025LUP	FN:24	PRODUCER	05-Mar-2008 11:55	2233.6 M	1938.2 M	
Output DLIS Files							
DEFAULT	PSP_026PUP	FN:25	PRODUCER	05-Mar-2008 12:21			

Company:	Esso Australia Pty Ltd.	Schlumberger
Well:	B-16	
Field:	Bream B	
Rig:	Crane / Prod # 4	
Country:	Australia	
2-1/8" Phased Powerjet MWPT Perforation Record 7" Posiset Plug Setting Record		