

Input Source: D:\OP_Folder\Clients\Essco_Australia_Pty_Ltd\CBA_F-1\GUN\COMP_CBA_F1_COMP_042.DLIS
Format: DLIS
Storage Set ID: Default Storage Set

Max Record Length: 8192
Storage Unit Sequence: 1

File Header File: **PERFO_036LUP** Sequence: **1**

Defining Origin: 28

File ID: PERFO_036LUP File Type: DEPTH LOG

Producer Name: Schlumberger

Product/Version: OP 16C0-147

File Set: 41

File Number: 34

15-MAR-2008 0:38:51

Company Name: Esso Australia Pty Ltd.

Well Name: CBA F-1

Field Name: Cobia

Tool String: SHM_GUN, ERS, CCL-XA

Computations: WELLCAD

Error Summary File: **PERFO_036LUP** Sequence: **1**

No errors detected in file.

Well Site Data File: **PERFO_036LUP** Sequence: **1**

Origin: 28

Well Data

Company Name	Esso Australia Pty Ltd.	CN
Well Name	CBA F-1	WN
Field Name	Cobia	FN
Rig:	ISS Rig 22	CLAB, COUN
State:	Victoria	SLAB, STAT
Nation	Australia	NATI
Field Location	Gippsland	FL
	Basin	FL1
	Bass Strait	FL2
Longitude	148° 18' 32.472"E	LONG
Latitude	38° 26' 57.528"S	LATI
Maximum Hole Deviation	61.0 (deg)	MHD
Elevation of Kelly Bushing	32.4 (m)	EKB
Elevation of Ground Level	-79.0 (m)	EGL
Elevation of Derrick Floor	32.4 (m)	EDF
Permanent Datum	Mean Sea Level	PDAT, EPD
Log Measured From	Rig Floor	LMF, APD
Drilling Measured From	Drill Floor	DMF
	Elevation of Permanent Datum	0.0 (m)
	Above Permanent Datum	32.4 (m)

Absent Valued Parameters: CN1, CONT, SECT, TOWN, RANG, APIN, SON

Job Data

Date as Month-Day-Year	14-Mar-2008	DATE
Run Number	1	RUN
Total Depth - Driller	3408.0 (m)	TDD
Total Depth - Logger	3408.0 (m)	TDL
Bottom Log Interval	3106.0 (m)	BLI
Top Log Interval	3106.0 (m)	TLI
Current Casing Size	4.50 (in)	CSIZ
Casing Depth From	3101.2 (m)	CDF
Casing Depth To	3136.4 (m)	CADT
Casing Grade	J-55	CASG
Casing Weight	12.8 (lbm/ft)	CWEI
Bit Size	9.88 (in)	BS
Bit Size Depth From	948.0 (m)	BSDF
Bit Size Depth To	3286.0 (m)	BSDT
Date Logger At Bottom	14-Mar-2008	DLAB, TLAB
Logging Unit Number	3827	LUN, LUL
Engineer's Name	R Sani / C Rowand	ENGI
Witness's Name	Mr D Broonfield / Mr B Robinson	WITN
	Time Logger At Bottom	23:55
	Logging Unit Location	AUSL

Absent Valued Parameters: SON

Mud Data

Drilling Fluid Type	Seawater		DFT
Drilling Fluid Density	1.02 (g/cm3)		DFD
Date Logger At Bottom	14-Mar-2008	Time Logger At Bottom	23:55
			DLAB, TLAB
Absent Valued Parameters: DFV, DFL, DFPH, BSAL, MSS, RMS, MST, RMFS, MFST, RMCS, MCST, RMB, RMFB, MRT, MRT1, MRT2, MRT3, DCS, TCS			
PVT Data			
Absent Valued Parameters: ODEN, BSAL, GGRA, BO, BW, IBG, BPP, BPT, SGOR			
Cement Data			
Cement Job Type	Primary		CJT
Absent Valued Parameters: CTOP, CASN, LCMT, LCVO, CDEN, CWLO, CADD, TCTY, TCV, TCDE, TCWL, TCA			
Remarks			
Log correlated to Tubing Tally provided by client.			R1
Objectives: RIH with a 3.65" Power Cutter. Cut 4-1/2" tubing joint at approximately 3106.0m MDKB.			R2
Tubing cutter is fired using SECURE.			R3
Toolstring ran with ERS.			R4
Powercutter cutting depth: 3106.0 m MDKB			R6
CCL to Top Shot: 5.25 m			R7
CCL Stop Depth: 3100.75 m MDKB			R8
Schlumberger Crews:			R12
Days: S Kiss & A Hall			R13
Nights: P Battams & C Harris			R14

Frame Summary File: PERFO_036LUP Sequence: 1						
Origin: 28						
<u>Index Type</u>	<u>Start</u>	<u>Stop</u>	<u>Spacing</u>	<u>Channels</u>	<u>Index Channel</u>	<u>Frame Name</u>
BOREHOLE-DEPTH	3119.48	3061.26 m	-60.0 (0.1 in) up	7	TDEP	60B
	10234.50	10043.50 ft				
BOREHOLE-DEPTH	3119.48	3061.28 m	-10.0 (0.1 in) up	7	TDEP;1	10B
	10234.50	10043.58 ft				

File Header		File: PERFO_038LUP	Sequence: 2
Defining Origin: 28			
File ID: PERFO_038LUP File Type: DEPTH LOG			
Producer Name: Schlumberger		Product/Version: OP 16C0-147	File Set: 41
		File Number: 36	15-MAR-2008 1:00:41
Company Name:	Esso Australia Pty Ltd.		
Well Name:	CBA F-1		
Field Name:	Cobia		
Tool String:	SHM_GUN, ERS, CCL-XA		
Computations:	WELLCAD		

Error Summary File: PERFO_038LUP Sequence: 2		
No errors detected in file.		

Well Site Data File: PERFO_038LUP Sequence: 2		
Origin: 28		
Well Data		
Company Name	Esso Australia Pty Ltd.	CN
Well Name	CBA F-1	WN
Field Name	Cobia	FN
Rig:	ISS Rig 22	CLAB, COUN
State:	Victoria	SLAB, STAT
Nation	Australia	NATI
Field Location	Gippsland	FL
	Basin	FL1
	Bass Strait	FL2
		LONG
Longitude	148° 18' 32.472"E	LATI
Latitude	38° 26' 57.528"S	MHD
Maximum Hole Deviation	61.0 (deg)	

Maximum Hole Deviation	01.0 (deg)				MINB
Elevation of Kelly Bushing	32.4 (m)				EKB
Elevation of Ground Level	-79.0 (m)				EGL
Elevation of Derrick Floor	32.4 (m)				EDF
Permanent Datum	Mean Sea Level	Elevation of Permanent Datum	0.0 (m)		PDAT, EPD
Log Measured From	Rig Floor	Above Permanent Datum	32.4 (m)		LMF, APD
Drilling Measured From	Drill Floor				DMF
Absent Valued Parameters: CN1, CONT, SECT, TOWN, RANG, APIN, SON					
Job Data					
Date as Month-Day-Year	14-Mar-2008				DATE
Run Number	1				RUN
Total Depth - Driller	3408.0 (m)				TDD
Total Depth - Logger	3408.0 (m)				TDL
Bottom Log Interval	3106.0 (m)				BLI
Top Log Interval	3106.0 (m)				TLI
Current Casing Size	4.50 (in)				CSIZ
Casing Depth From	3101.2 (m)				CDF
Casing Depth To	3136.4 (m)				CADT
Casing Grade	J-55				CASG
Casing Weight	12.8 (lbm/ft)				CWEI
Bit Size	9.88 (in)				BS
Bit Size Depth From	948.0 (m)				BSDF
Bit Size Depth To	3286.0 (m)				BSDT
Date Logger At Bottom	14-Mar-2008	Time Logger At Bottom	23:55		DLAB, TLAB
Logging Unit Number	3827	Logging Unit Location	AUSL		LUN, LUL
Engineer's Name	R Sani / C Rowand				ENGI
Witness's Name	Mr D Broonfield / Mr B Robinson				WITN
Absent Valued Parameters: SON					
Mud Data					
Drilling Fluid Type	Seawater				DFT
Drilling Fluid Density	1.02 (g/cm3)				DFD
Date Logger At Bottom	14-Mar-2008	Time Logger At Bottom	23:55		DLAB, TLAB
Absent Valued Parameters: DFV, DFL, DFPH, BSAL, MSS, RMS, MST, RMFS, MFST, RMCS, MCST, RMB, RMFB, MRT, MRT1, MRT2, MRT3, DCS, TCS					
PVT Data					
Absent Valued Parameters: ODEN, BSAL, GGRA, BO, BW, IBG, BPP, BPT, SGOR					
Cement Data					
Cement Job Type	Primary				CJT
Absent Valued Parameters: CTOP, CASN, LCMT, LCVO, CDEN, CWLO, CADD, TCTY, TCV, TCDE, TCWL, TCA					
Remarks					
Log correlated to Tubing Tally provided by client.					R1
Objectives: RIH with a 3.65" Power Cutter. Cut 4-1/2" tubing joint at approximately 3106.0m MDKB.					R2
Tubing cutter is fired using SECURE.					R3
Toolstring ran with ERS.					R4
Powercutter cutting depth: 3106.0 m MDKB					R6
CCL to Top Shot: 5.25 m					R7
CCL Stop Depth: 3100.75 m MDKB					R8
Schlumberger Crews:					R12
Days: S Kiss & A Hall					R13
Nights: P Battams & C Harris					R14

Frame Summary File: PERFO_038LUP Sequence: 2						
Origin: 28						
<u>Index Type</u>	<u>Start</u>	<u>Stop</u>	<u>Spacing</u>	<u>Channels</u>	<u>Index Channel</u>	<u>Frame Name</u>
BOREHOLE-DEPTH	3119.93	3060.34 m	-60.0 (0.1 in) up	7	TDEP	60B
	10236.00	10040.50 ft				
BOREHOLE-DEPTH	3119.93	3060.37 m	-10.0 (0.1 in) up	7	TDEP;1	10B
	10236.00	10040.58 ft				

