

Table of Contents

1. TOWING CONFIGURATION..... 2

1.1. TOWING SYSTEM LAYOUT ..... 2

2. STREAMER CONFIGURATION..... 3

2.1. STREAMER SYSTEM DESCRIPTION..... 3

2.2. STREAMER LAYOUT ..... 5

3. SOURCE CONFIGURATION..... 6

3.1. SOURCE SYSTEM DESCRIPTION ..... 6

3.2. SOURCE LAYOUT ..... 7


3.3. PULSE RESPONSE ..... 8

4. INSTRUMENTATION ROOM SYSTEM DIAGRAM..... 9

## 1. Towing Configuration

### 1.1. Towing System Layout

Towing System Layout Single vessel 2D



## 2. Streamer Configuration

### 2.1. Streamer System Description

Streamer System Parameters	
Number of Streamers	1
Type of Streamer	Seal
Streamer Length	6000 Meter
Groups per Section (150m)	12
Group Intervals	12.5 m (no overlap)
Active Group Array Length	11.7 m
Outside Diameter	50 mm
Jacket (skin type & thickness)	Polyurethane 3.3 mm
Breaking Strength	3 Ton
Ballasting Fluid (fluid-quantity)	Isopar M
Connectors (Pins)	28
Channels per Module	60 at 2 ms
Data Transmission Link	Dual twisted Quartet AWG 22
Power	+/- 175 V DC
Leakage	30 mA differential circuit breaker
Near Offset (Centre Source – Centre near Group) Seq. 001 – Seq. 013	104 m nominal
Near Offset (Centre Source – Centre near Group) Seq. 014 – Seq. 046	114 m nominal
Streamer Depth	7m +/- 1.0
Number of Front 50 m Stretch Sections	1 (85 mm diameter)
Number of Tail 50 m Stretch Sections	1 (50 mm diameter)
Number of Compasses per Streamer	22 (within digibirds)
Number of Depth Sensors per Streamer	22 (within digibirds)

Trace allocation	Near	Far	Aux
Streamer 1	1	480	481-501

### Section 3: Equipment Configuration

Hydrophone Parameters	
Hydrophone Specification	VINCI NH 95-200
No of Channels per Section	12
No of Hydrophones per Channel	16 in parallel
Active Length of Channel	11.719 m
Channel Centre Spacing	12.5 m under a 1000daN load
Hydrophone Spacing	0.781 m
Low Frequency Cut	3 Hz
Nominal Sensitivity, without electronics @ 1 bar @ 20°C	20 V/bar
Nominal Sensitivity, electronics included @ 1 bar @ 20°C	17.4 V/bar
Capacitance per Group	256 nF +/-3% at 20°C
Minimum Leakage Resistor	500 Mohm under 50 V

## 2.2. Streamer Layout



Item	Position	S/N	Bird N.O	Bird S/N	SRD N.O.	SRD S/N	Trace N.O	Weights
DCXU		686						
Slip ring		n/a						
Lead-in		n/a						
SHS		1351						
HAU		173						
HESE		1340	1	29034	1			
HESA		1333						
ALS	01	900	2	29096			1-12	5
ALS	02	918					13-24	5
ALS	03	919	3	29031	2		25-36	5
ALS	04	916					37-48	5
ALS	05	917	4	29012			49-60	5
LAUM	01	517						
ALS	06	915					61-72	5
ALS	07	914	5	29075			73-84	5
ALS	08	912					85-96	5
ALS	09	913	6	29020	3		97-108	5
ALS	10	910					109-120	5
LAUM	02	515						
ALS	11	911	7	29009			121-132	5
ALS	12	909					133-144	5
ALS	13	908	8	27490			145-156	5
ALS	14	907					157-168	5
ALS	15	1374	9	27746	4		169-180	5
LAUM	03	509						
ALS	16	905					181-192	5
ALS	17	906	10	29010			193-204	5
ALS	18	904					205-216	5
ALS	19	903	11	26502			217-228	5
ALS	20	901					229-240	5
LAUM	04	395						
ALS	21	1373	12	29002	5		241-252	5
ALS	22	1370					253-264	5
ALS	23	889	13	29037			265-276	5
ALS	24	887					277-288	5
ALS	25	897	14	27611			289-300	5
LAUM	05	513						
ALS	26	885					301-312	5
ALS	27	1369	15	26612	6		313-324	5
ALS	28	883					325-336	5
ALS	29	1381	16	29046			337-348	5
ALS	30	884					349-360	5
LAUM	06	485						
ALS	31	O898	17	26609			361-372	5
ALS	32	O899					373-384	5
ALS	33	O896	18	27772	7		385-396	5
ALS	34	O894					397-408	5
ALS	35	O902	19	29023			409-420	5
LAUM	07	473						
ALS	36	O890					421-432	5
ALS	37	O893	20	27773	8		433-444	5
ALS	38	O892					445-456	5
ALS	39	O891	21	27832			457-468	5
ALS	40	1382	22	27496			469-480	5
TAPU	1	157						
TES	1	1335						
Stic	1							
Tailbuoy	1							

### 3. Source Configuration

#### 3.1. Source System Description

Source Parameters	
Number of Sources	1
Number of Sub-arrays per Source	3
Array Length	14.7 m
Array Separation	10 m
Source Width	20 m
Source Separation	N/A
Source Volume	3040 Cubic inches
Number of Hydrophones per Source	3*3
Number of Depth Transducers per Source	3*3
Number of Guns per Source	Sub-array 1 & 3 : 9 guns Sub-array 2 : 8 guns
Number of Clusters per Source	Sub-array 1 & 3 : 3 clusters Sub-array 2 : 2 clusters
Airgun Type	Bolt, 1500 & 1900 Long Life
Operating Pressure	2000 PSI
Depth of Guns	5.0 m
Peak-to-Peak Amplitude	88.0 barm
Primary-to-Bubble Ratio	25

## 3.2. Source Layout



### 3.3. Pulse Response

