

EQUIPMENT DESCRIPTION		
RUN1	RUN	RUN
<p>DOWNHOLE E</p> <p>6-3/4 in. Pow MDC: V8 MEC: 21 MDI: 109 MGR: 50 DHS: 7.1</p> <p>D&I GR</p> <p>6-3/8 in. N S/N: 961</p> <p>6-5/8 in. NM Rc S/N: GU</p> <p>6-1/2 in. N S/N: ASS</p> <p>6-1/2 in. Fl S/N: CMF</p> <p>7 in. PowerPa A700G1 S/N: 07 1.5 deg. Bent 8-3/8 in. Mot</p>	<p>24.5</p> <p>20.2</p> <p>19.5</p> <p>16.2</p> <p>13.7</p> <p>11.6</p> <p>10.1</p> <p>9.4</p>	

6-5/8 in. Rotating l
S/N: OSS2
REED Hycalo
OD: 8-1
RSX163 S/1



0.5%
0.2%

Maximum string dia
All lengths in


Bit Run Summary


Run number		1									
Bit size	in.	8.5									
Bit start depth	m	1380.0									
Bit end depth	m	3051.0									
Top interval logged	m	1380.0									
Bottom interval logged	m	3031.9									
Begin log: time		06:00									
Begin log: date		15-Jul-04									
End log: time		14:30									
End log: date		21-Jul-04									
Mud data											
Depth	m	3042.0									
Type		KCL/PHPA/Glycol									
Mud weight	ppg	9.5									
Solids	%	5.5									
Chlorides	mg/L	38,000									
Rm											
Rmf											
Rmc											
Potassium	%	4.1									
Environmental data											
GR											
Mud weight	ppg	9.5									
Bit size	in.	8.5									
Resistivity											
Neutron porosity											
Hole Size											
Mud weight											
Temperature											
Mud salinity											
Formation salinity											
Update rate 1	SEC	3.9									
Update rate 2	SEC										
Filtering GR		3 pt.									
Filtering density											
Filtering Neutron											
Company representative		B. Steel	R. Bain								
Anadrill personnel		J. Dolan	R.Borjas	C. Soper	D. Hay	L. Johnston					

MLA-A23A RT 200TVD

IDEAL Version: ID8_1C_02 <TVD> Vertical Scale: 1:200 Graphics File Created: 29-Jul-2004 09:29

ROP*5 (ROP5) (M/HR)	GR(TM) (GRM1) (GAPI)
200	0
0	200







1250
TVD

1275
TVD

1300
TVD







TVD


1325
TVD

1350
TVD






1425
TVD





1450
TVD



1475
TVD

1500
TVD







1525
TVD

1550
TVD


1575
TVD






1600
TVD


1625
TVD






1650
TVD


1675
TVD






1700
TVD

1725
TVD







1750
TVD

1775
TVD


1800
TVD






1825
TVD


1850
TVD






1875
TVD


1900
TVD






1925
TVD

1950
TVD







1975
TVD

2000
TVD


2025
TVD







2050
TVD

2075
TVD









2150
TVD

2175
TVD







2200
TVD

2225
TVD

2250







TVD

2275
TVD


2300
TVD






2375
TVD


2400
TVD






2425
TVD

2450
TVD





SCHLUMBERGER

Survey report 21-Jul-2004 15:47:41 Page 1 of 3

Client.....: ESSO Australia Pty Ltd
Field.....: Marlin GDA 94

Well.....: MLA-A23a Spud date.....: 11-July-04
API number.....: Last survey date.....: 21-Jul-04
Engineer.....: J.Dolan, R.Borjas, L.Johnston Total accepted surveys...: 60
MD of first survey.....: 1354.00 m
Contractor.....: ISDL 453 MD of last survey.....: 3051.00 m
STATE.....: Victoria

----- Survey calculation methods ----- Geomagnetic data -----
Method for positions.....: Minimum curvature Magnetic model.....: BGGM version 2003
Method for DLS.....: Mason & Taylor Magnetic date.....: 11-Jul-2004
Magnetic field strength...: 1199.66 HCNT
----- Depth reference ----- Magnetic dec (+E/W-).....: 13.13 degrees
Permanent datum.....: Mean Sea Level Magnetic dip.....: -68.73 degrees
Depth reference.....: Driller's Depth
GL above permanent.....: -59.00 m
KB above permanent.....: 27.91 m
DF above permanent.....: 27.91 m
Reference Dip.....: -68.73 degrees
----- Vertical section origin ----- Tolerance of G.....: (+/-) 2.50 mGal
Latitude (+N/S-).....: 0.00 m Tolerance of H.....: (+/-) 6.00 HCNT
Departure (+E/W-).....: 0.00 m Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-).....: 13.13 degrees
Grid convergence (+E/W-)..: -0.76 degrees
Total az corr (+E/W-).....: 13.89 degrees
Azimuth from rotary table to target: 197.61 degrees (Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

Seq	Measured	Incl	Azimuth	Course	TVD	Vertical	Displ	Displ	Total	At	DLS	Srvy	Tool
#	depth	angle	angle	length	depth	section	+N/S-	+E/W-	displ	Azim	(deg/	tool	Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(deg)	100f)	type	(deg)	
1	1354.00	24.41	208.68	0.00	1311.29	222.48	-208.20	-79.44	222.84	200.88	0.00	TIP	None
2	1412.62	31.19	197.32	58.62	1363.15	249.59	-233.36	-89.79	250.04	201.05	4.46	MWD	None
3	1435.36	32.38	191.97	22.74	1382.48	261.54	-244.95	-92.81	261.94	200.75	4.10	MWD	None
4	1469.69	34.54	188.94	34.33	1411.12	280.32	-263.56	-96.23	280.57	200.06	2.42	MWD	None
5	1498.10	36.38	190.02	28.41	1434.26	296.63	-279.81	-98.95	296.79	199.47	2.09	MWD	None
6	1526.48	36.23	193.91	28.38	1457.14	313.35	-296.24	-102.43	313.45	199.07	2.48	MWD	None
7	1554.83	36.28	198.02	28.35	1480.00	330.10	-312.35	-107.04	330.18	198.92	2.61	MWD	None
8	1583.38	36.43	198.33	28.55	1503.00	347.02	-328.43	-112.31	347.11	198.88	0.25	MWD	None
9	1612.18	36.36	198.70	28.80	1526.18	364.11	-344.64	-117.74	364.19	198.86	0.24	MWD	None
10	1641.00	35.79	196.73	28.82	1549.47	381.07	-360.80	-122.91	381.16	198.81	1.37	MWD	None
11	1669.93	35.39	196.62	28.93	1573.00	397.91	-376.93	-127.74	397.98	198.72	0.43	MWD	None
12	1698.85	35.72	196.59	28.92	1596.53	414.72	-393.04	-132.54	414.79	198.64	0.35	MWD	None
13	1727.94	35.67	196.77	29.09	1620.15	431.69	-409.30	-137.41	431.75	198.56	0.12	MWD	None
14	1756.54	35.98	196.69	28.60	1643.34	448.43	-425.33	-142.23	448.48	198.49	0.33	MWD	None
15	1785.30	35.60	195.45	28.76	1666.67	465.24	-441.49	-146.89	465.29	198.40	0.87	MWD	None
16	1814.24	34.92	195.65	28.94	1690.30	481.94	-457.59	-151.37	481.98	198.30	0.73	MWD	None
17	1843.05	34.84	195.98	28.81	1713.94	498.41	-473.44	-155.86	498.44	198.22	0.22	MWD	None
18	1871.63	35.07	196.19	28.58	1737.36	514.78	-489.17	-160.40	514.80	198.15	0.28	MWD	None
19	1900.02	34.38	196.89	28.39	1760.69	530.94	-504.68	-165.00	530.96	198.10	0.86	MWD	None
20	1928.81	35.24	196.20	28.79	1784.33	547.38	-520.43	-169.68	547.39	198.06	1.00	MWD	None
21	1957.63	34.51	196.38	28.82	1807.97	563.85	-536.25	-174.30	563.86	198.01	0.78	MWD	None
22	1986.33	35.36	194.30	28.70	1831.50	580.27	-552.10	-178.64	580.28	197.93	1.55	MWD	None
23	2014.67	37.19	193.47	28.34	1854.35	597.00	-568.37	-182.66	597.01	197.82	2.04	MWD	None
24	2043.39	38.82	193.79	28.72	1876.98	614.64	-585.56	-186.83	614.64	197.70	1.74	MWD	None
25	2071.57	38.36	194.51	28.18	1899.01	632.19	-602.60	-191.13	632.19	197.60	0.70	MWD	None
26	2100.21	37.30	194.78	28.64	1921.63	649.73	-619.60	-195.57	649.73	197.52	1.14	MWD	None
27	2128.93	38.54	196.06	28.72	1944.28	667.36	-636.61	-200.26	667.37	197.46	1.56	MWD	None
28	2157.62	38.41	196.37	28.69	1966.74	685.21	-653.75	-205.25	685.21	197.43	0.25	MWD	None
29	2186.68	37.18	196.59	29.06	1989.71	703.01	-670.83	-210.30	703.02	197.41	1.30	MWD	None
30	2215.32	35.98	196.99	28.64	2012.70	720.08	-687.17	-215.23	720.09	197.39	1.30	MWD	None

[(c)2004 IDEAL ID8_1C_01]
SCHLUMBERGER Survey Report

21-Jul-2004 15:47:41

Page 3 of 3

Seq	Measured	Incl	Azimuth	Course	TVD	Vertical	Displ	Displ	Total	At	DLS	Srvy	Tool
#	depth	angle	angle	length	depth	section	+N/S-	+E/W-	displ	Azim	(deg/	tool	Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(deg)	100f)	type	(deg)	
31	2243.97	35.90	196.43	28.65	2035.90	736.89	-703.27	-220.06	736.90	197.38	0.36	MWD	None
32	2272.58	35.07	196.27	28.61	2059.20	753.50	-719.21	-224.74	753.51	197.35	0.89	MWD	None
33	2301.12	35.16	196.01	28.54	2082.54	769.91	-734.98	-229.30	769.92	197.33	0.19	MWD	None
34	2329.93	35.22	195.85	28.81	2106.09	786.50	-750.94	-233.86	786.52	197.30	0.12	MWD	None
35	2358.20	34.43	195.49	28.27	2129.29	802.64	-766.49	-238.22	802.65	197.27	0.88	MWD	None
36	2386.44	34.46	194.07	28.24	2152.58	818.59	-781.93	-242.30	818.61	197.22	0.87	MWD	None
37	2416.23	32.78	193.88	29.79	2177.39	835.05	-797.94	-246.28	835.08	197.15	1.72	MWD	None
38	2444.90	31.57	192.94	28.67	2201.66	850.28	-812.79	-249.82	850.31	197.09	1.39	MWD	None
39	2473.21	32.10	193.08	28.31	2225.71	865.16	-827.34	-253.18	865.21	197.02	0.58	MWD	None
40	2501.92	33.94	195.27	28.71	2249.78	880.78	-842.50	-257.02	880.83	196.97	2.33	MWD	None
41	2530.34	33.35	195.78	28.42	2273.44	896.51	-857.67	-261.24	896.57	196.94	0.70	MWD	None
42	2559.17	34.43	194.57	28.83	2297.37	912.57	-873.19	-265.44	912.64	196.91	1.35	MWD	None
43	2587.94	36.59	193.41	28.77	2320.79	929.25	-889.40	-269.48	929.33	196.86	2.40	MWD	None
44	2616.48	37.45	193.70	28.54	2343.58	946.39	-906.11	-273.50	946.48	196.80	0.94	MWD	None
45	2644.94	36.30	193.73	28.46	2366.34	963.43	-922.70	-277.55	963.54	196.74	1.23	MWD	None
46	2674.27	35.62	193.93	29.33	2390.08	980.61	-939.42	-281.67	980.74	196.69	0.72	MWD	None
47	2702.63	34.95	193.40	28.36	2413.23	996.95	-955.34	-285.54	997.10	196.64	0.79	MWD	None
48	2731.20	33.06	193.28	28.57	2436.92	1012.89	-970.88	-289.23	1013.05	196.59	2.02	MWD	None
49	2759.64	31.42	192.91	28.44	2460.97	1028.01	-985.66	-292.67	1028.19	196.54	1.77	MWD	None
50	2788.87	28.98	192.53	29.23	2486.23	1042.66	-1000.00	-295.91	1042.86	196.48	2.55	MWD	None
51	2817.54	26.43	192.98	28.67	2511.61	1055.94	-1013.00	-298.85	1056.16	196.44	2.72	MWD	None
52	2845.85	23.56	192.40	28.31	2537.27	1067.86	-1024.67	-301.48	1068.10	196.39	3.10	MWD	None
53	2874.69	21.48	191.96	28.84	2563.91	1078.85	-1035.46	-303.81	1079.11	196.35	2.21	MWD	None
54	2903.24	19.54	190.65	28.55	2590.65	1088.80	-1045.27	-305.77	1089.08	196.31	2.13	MWD	None
55	2932.26	18.69	191.29	29.02	2618.07	1098.24	-1054.60	-307.58	1098.54	196.26	0.92	MWD	None
56	2960.99	17.56	192.44	28.73	2645.37	1107.13	-1063.35	-309.42	1107.45	196.22	1.26	MWD	None
57	2990.06	16.45	192.44	29.07	2673.17	1115.59	-1071.65	-311.25	1115.93	196.20	1.16	MWD	None
58	3018.84	15.08	193.63	28.78	2700.87	1123.39	-1079.27	-313.01	1123.74	196.17	1.49	MWD	None
59	3030.18	14.67	193.43	11.34	2711.83	1126.29	-1082.10	-313.69	1126.65	196.17	1.11	MWD	None
60	3051.00	13.94	193.05	20.82	2732.00	1131.42	-1087.11	-314.87	1131.79	196.15	1.08	Projection to TD	

[(c)2004 IDEAL ID8_1C_01]

Company: **ESSO Australia Pty. Ltd.**

Schlumberger

Well: **MLA-A23A**

Field: **Marlin GDA 94**

Rig: **ISDL 453**

State: **Victoria**

Gamma Ray Service

1:200 True Vertical Depth

Real Time Log