

Jack Bates
Exploration
Otway Basin
Amrit-1
SANTOS – INPEX – UNOCAL

Location	
Total depth:	2979.0 m
Spud date:	20-Nov-2004
Runs:	1 To 4
Permanent datum:	LAT _____ Elev.: 0 m _____
Log measured from:	Rotary Table 29.0 m above Perm. datum
Depth reference:	Driller's Pipe Tally

Rig:	API serial no.	Longitude	Latitude
Field:	X = 563729.6mE		
Location:	Y =5690204.1mN	141° 44' 07.08"E	38° 56' 05.20"S
Well:			
Comp:			

Depth logged:	1425.0 m To 2763.0 m	Mag decl:	10.48 deg.	Other services:
Date logged:	20-Nov-04 To 7-Dec-04	Mag dip:	-70.25 deg.	Directional Surveys

g record

from	to	Size	Density	from	to
------	----	------	---------	------	----

1425.0 m	1835.0 m	30 in.	456.3/309 lb/ft	1425.0 m	1510.0 m
1835.0 m	2459.0 m	20 in.	133 lb/ft	1425.0 m	1822.0 m
2459.0 m	2979.0 m	13.375 in.	68 lb/ft	1425.0 m	2454.5 m

[illegible][illegible]

[illegible]

from	to	Min	Max	from	to
4,000	4,000	4,000	4,000	4,000	4,000

1423.0 m	1835.0 m	0.20 deg.	1.07 deg.	1423.0 m	1835.0 m
1835.0 m	2979.0 m	0.12 deg	0.40 deg	1835.0 m	2459.0 m

		0.00 deg.	0.07 deg.	2459.0 m	2797.0 m
--	--	-----------	-----------	----------	----------

--	--	--	--	--	--	--

Equipment	Software record
-----------	-----------------

OLU ME 0104	IDEAL wis	ID9_1C_01
-------------	-----------	-----------

Geolograph	SPM	hspm9_2c_08
------------	-----	-------------

LWD	6.0 B08
-----	---------

	MWD	7.0C00	
--	-----	--------	--

Run number		1	2	3	4						
Bit size	in	26	17.5	12.25	12.25						
Bit start depth	m	1425.0	1835.0	2459.0	2695.0						
Bit end depth	m	1835.0	2459.0	2695.0	2979.0						
Top interval logged	m	1425.0	1820.0	2444.0	2678.5						
Bottom interval logged	m	1820.0	2444.0	2678.5	2963.0						
Begin log: time		08:20:00	13:10:00	03:50:00	8:30:00						
Begin log: date		20-Nov-04	27-Nov-04	4-Dec-04	6-Dec-04						
End log: time		16:30:00	22:15:00	7:00:00	16:00:00						
End log: date		22-Nov-04	1-Dec-04	6-Dec-04	7-Dec-04						
Mud data											
Depth	m	1835.0	2459.0	2695.0	2979.0						
Type		Sea water	KCl/PHPA/Glycol	KCl/PHPA/Glycol	KCl/PHPA/Glycol						
Mud weight	ppg	8.6	9.2	9.5	9.6						
Solids	%	N/A	4.0	8.8	9.5						
Chlorides	mg/l	N/A	38500	52500	48000						
Rm	OHMM@°C	N/A	0.1192@25.1	0.078@26.3	0.0968@25.2						
Rmf	OHMM@°C	N/A	0.1087@24.9	0.0732@25.8	0.0891@24.9						
Rmc	OHMM@°C	N/A	0.1248@26.8	0.1005@25.5	0.1285@24.5						

Potassium	%	N/A	4.0	5.4	5.1						
Environmental data											
GR											
Mud weight	ppg	8.6	9.2	9.5	9.6						
Bit size	in	26	17.5	12.25	12.25						
Resistivity											
Neutron porosity											
Hole Size	in	26	17.5	12.25	12.25						
Mud weight	ppg	8.6	9.2	9.5	9.6						
Bottom Hole Temperature	°C	17.0	23.0	24.0	26.0						
Mud salinity	ppm	N/A	N/A	N/A	N/A						
Formation salinity	ppm	N/A	N/A	N/A	N/A						
Recording rate 1	SEC	6	6	6	6	GR-APWD RES					
Recording rate 2	SEC	6	6	6	6						
Filtering GR		3-Point	3-point	3-point	3-point						
Filtering density		N/A	N/A	N/A	N/A						
Filtering Neutron		N/A	N/A	N/A	N/A						
Company representative		D. Atkins	P. King	J. Young	R. Subramanian						
Anadrill personnel		D. Borges	O. Radicevic	L. Watson	B. Manjenic						

<p style="text-align: center;">DISCLAIMER</p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
OTHER SERVICES FOR RUN1 Directional Surveys Performance Drilling Annular Pressure, ECD & Temperature Internet Web Witness	OTHER SERVICES FOR RUN2 Directional Surveys Performance Drilling Annular Pressure, ECD & Temperature Internet Web Witness	OTHER SERVICES FOR RUN3 Directional Surveys Performance Drilling Annular Pressure, ECD & Temperature Multi Vibrational Chassis (MVC) Internet Web Witness
REMARKS: RUN NUMBER 1 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Jet in 30" casing & continue to drill 26" to TD. POOH: Section TD. Remarks: Low Gamma Ray readings are due to enlarged hole size.	REMARKS: RUN NUMBER 2 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Drill 17.5" section to TD. POOH: Section TD.	REMARKS: RUN NUMBER 3 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Drill 12.25" section to TD. POOH: Rate of penetration.

EQUIPMENT DESCRIPTION		
RUN1	RUN2	RUN3
DOWNHOLE F	DOWNHOLE F	DOWNHOLE F

DOWNHOLE E

DOWNHOLE E

DOWNHOLE E

PowerPl
Software ver:
s/n W4

CDR
Software ver:
s/n L96

26" WB St
s/n 536

Float S
s/n 32

A962GT Po
s/n 10
lobes
Stabilizer Sleeve

26" Mill To
Smith MSDS, Jets 2x
s/n MR3

Maximum string dian
All lengths in



28.6
— 24.3
— 20.1
— 18.4
— 15.7
— 15.0

PowerPl
Software ver:
s/n: W4

CDR
Software ver:
s/n: L96

17 1/2" String
s/n 207

Float S
s/n: 32

A962GT Po
s/n: 1C
lobes
Stabiilizer sleeve

17 1/2" Mill 1
Reed T11C, Jets
s/n: J61

Maximum string dian
All lengths in



28.8
— 24.4
— 20.3
— 18.6
— 15.8
— 15.1

PowerPl
Software ver
s/n: ED

In Line Sta
OD 12
s/n: 2132
CDR
Software ver:
OD 8

12 1/4" String
s/n: AIB

XO
s/n: X/1


Float S
s/n: 37

A962GT Po
s/n: 2C
lobes:
Stabilizer sleeve

XO
s/n: L 9

12 1/4" PI
Hughes HCH606
s/n 7003

Maximum string dian
All lengths in



30.9
— 26.7
— 26.0
— 22.0
— 21.5
— 19.4
— 16.6
— 16.1
— 14.5
— 12.5
— 11.5
— 10.5
— 0.6
— 0.3

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN4 Directional Surveys Performance Drilling Annular Pressure, ECD & Temperature Multi Vibrational Chassis (MVC) Internet Web Witness	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 4 Depth is Driller's Depth. CDR gamma ray is corrected for bit size, mud weight and tool size. CDR resistivity is borehole compensated but not environmentally corrected. Run Objective: Drill 12.25" section to TD. POOH: TD of Armit-1.	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

EQUIPMENT DESCRIPTION

RUN4	RUN	RUN
<div>DOWNHOLE E</div> <div><div>PowerPul</div><div>Software version: ED</div><div><div>D&I MVC</div><div><div></div><div>30.9</div></div><div><div></div><div>26.7</div></div><div><div></div><div>26.0</div></div></div><div><div>In Line Station</div><div>OD 12</div><div><div></div><div>22.5</div></div></div></div>		

Maximum string dian
All lengths in

Variable Name	Variable Description	Run Name & Value				
		Run #1	Run #2	Run #3	Run #4	
BHT_RM	Bottom Hole Temperature (degC)		17.000000	23.000000	24.000000	26.000000
BS_RM	Bit Size (in)	26.000000	17.500000	12.250000	12.250000	
MST_RM	Mud Sample temperature (degC)		12.000000	25.100000	26.300000	25.200000
MW_RM	Mud Weight (ppg)	8.600000	9.200000	9.500000	9.600000	
OBMF_RM	Oil Based Mud	NO	NO	NO	NO	
RMS_RM	Resistivity of Mud Sample (ohmm)		0.000000	0.119200	0.078000	0.096800
SHT_RM	Surface Hole Temperature (degC)		12.000000	15.000000	15.000000	15.000000
TD_RM	Total Measured Depth (m)	1835.000000	2459.000000	2695.000000	2979.000000	
ENV_SELECT	Res. Env. Corr. Selection	BS	BS	BS	BS	
TSIZ_CDR	CDR Tool Size (in)	9.500000	9.500000	8.250000	8.250000	
PLATEU	CDR: Plateau GR sensor	YES	YES	YES	YES	
VERS_CDR	CDR Down hole software version Number		6.0B0800	6.0B0800	6.0B0800	6.0B0800
Schlumberger Drilling & Measurements			Parameter Insert Header Software version 1.1c			


Parameters


DLIS Name	Description	Value
DO	Depth Offset	0.0 m



PIP SUMMARY


- └ CDR Gamma Ray Samples
- └ CDR Resistivity Samples


CDR Resistivity Time After Bit (TAB_ CDR_RES) (HR)		Annular Pressure (PRSA) (PSI)
0 10		0 6000
Rate of Penetration, Averaged over Last 5ft (ROP5_RM) (M/HR)	Uncorrected Phase Shift Resistivity (PSR) (OHMM)	Equivalent Circulating Density (ECD_ CDR) (LB/G)
200 0	0.2 200	5 15
CDR Gamma Ray (GR_ CDR) (GAPI)	Uncorrected Attenuation Resistivity (ATR) (OHMM)	Annular Temperature (ATMP_ CDR) (DEGC)
0 200	0.2 200	0 100
















1650



1675





















1975

2000













2150


2175















2375


2400






























2875

2900







CDR Gamma Ray (GR_CDR) (GAPI) 200			Uncorrected Attenuation Resistivity (ATR) (OHMM) 200			Annular Temperature (ATMP_CDR) (DEGC) 100		
Rate of Penetration, Averaged over Last 5ft (ROP5_RM) (M/HR) 0			Uncorrected Phase Shift Resistivity (PSR) (OHMM) 200			Equivalent Circulating Density (ECD_CDR) (LB/G) 15		
CDR Resistivity Time After Bit (TAB_CDR_RES) (HR) 10						Annular Pressure (PRSA) (PSI) 6000		

PIP SUMMARY								
└ CDR Gamma Ray Samples								
└ CDR Resistivity Samples								
IDEAL Version: ID9_1C_01								
IDF								

9.50-in. Compensated Dual Resistivity / Equipment Identification								
Primary Equipment:			RGS9 – AA			9525		
Tool Name and Serial Number			Plat – GR			–		
Gamma Ray Type								
Calibration Status								

Master: 2–Oct–2004 8:36														
9.50–in. Compensated Dual Resistivity Calibration														
Resistivity: Air														
Phase	Attenuation down DB			Value	Phase	Attenuation up DB			Value	Phase	BHC attenuation DB			Value
Master				3.705	Master				3.932	Master				3.818
	3.290 (Minimum)	3.890 (Nominal)	4.490 (Maximum)		3.290 (Minimum)	3.890 (Nominal)	4.490 (Maximum)			3.790 (Minimum)	3.890 (Nominal)	3.990 (Maximum)		

Master: 2–Oct–2004 8:36											
9.50–in. Compensated Dual Resistivity Calibration											
Resistivity: Air											
Phase	Phase shift down DEG		Value	Phase	Phase shift up DEG		Value	Phase	BHC phase shift DEG		Value
Master			0.1082	Master			0.09295	Master			0.1006
	–2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)		–2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)		–0.9000 (Minimum)	0.1000 (Nominal)	1.100 (Maximum)

Master: 2–Oct–2004 7:55									
9.50-in. Compensated Dual Resistivity Calibration									
Gamma Ray: Blanket									
Phase	Gain					Value			
Master						0.9923			
	0.8000 (Minimum) 1.000 (Nominal) 1.200 (Maximum)								

8.25-in. Compensated Dual Resistivity / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

Gamma Ray Type

Calibration Status

CDR8 – AA

8001




Plat – GR

–

Master: 3–Nov–2004 2:01

8.25-in. Compensated Dual Resistivity Calibration




Resistivity: Air

Phase	Attenuation down	DB	Value	Phase	Attenuation up	DB	Value	Phase	BHC attenuation	DB	Value
Master			4.993	Master			4.928	Master			4.960
	4.400 (Minimum)	5.000 (Nominal)	5.600 (Maximum)		4.400 (Minimum)	5.000 (Nominal)	5.600 (Maximum)		4.900 (Minimum)	5.000 (Nominal)	5.100 (Maximum)

Master: 3–Nov–2004 2:01

8.25-in. Compensated Dual Resistivity Calibration


Resistivity: Air

Phase	Phase shift down	DEG	Value	Phase	Phase shift up	DEG	Value	Phase	BHC phase shift	DEG	Value
Master			-0.2902	Master			0.6567	Master			0.1833
	-2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)		-2.400 (Minimum)	0.1000 (Nominal)	2.600 (Maximum)		-0.9000 (Minimum)	0.1000 (Nominal)	1.100 (Maximum)

Master: 3–Nov–2004 4:17

8.25-in. Compensated Dual Resistivity Calibration

Gamma Ray: Blanket

Phase	Gain	Value
Master		0.8570
	0.8000 (Minimum)1.000 (Nominal)1.200 (Maximum)	

SCHLUMBERGER

Survey report

Client..... SANTOS – INPEX – UNOCAL

Field..... Amrit

Well..... Amrit–1

Spud date..... 20–Nov–2004

API number.....

Last survey date..... 07–Dec–04

Engineer..... D.Borges, L.Watson, O.Radicevic

Total accepted surveys...: 44

MD of first survey..... 0.00 m

RIG..... Jack Bates

MD of last survey..... 2979.00 m

STATE..... Victoria

----- Survey calculation methods-----

Method for positions..... Minimum curvature

Method for DLS..... Mason & Taylor

Magnetic field strength...: 1221.99 HCNT

Permanent datum..... LAT

Depth reference..... Driller's Pipe Tally

GL above permanent..... –1396.00 m

KB above permanent..... Top Drive

DF above permanent..... 29.00 m

Reference Dip..... –70.25 degrees

Tolerance of G..... (+/–)

Latitude (+N/S–)..... 0.00 m

Departure (+E/W–)..... 0.00 m

Tolerance of H..... (+/–) 6.00 HCNT

Tolerance of Dip..... (+/–) 0.45 degrees

----- Platform reference point-----

Latitude (+N/S–)..... 0.00 m

Departure (+E/W–)..... 0.00 m

Azimuth from Vsect Origin to target: 0.00 degrees

Survey Correction Type ...:

I=Sag Corrected Inclination

M=Schlumberger Magnetic Correction

S=Shell Magnetic Correction

F=Failed Axis Correction

R=Magnetic Resonance Tool Correction

D=Dmag Magnetic Correction

----- Geomagnetic data -----

Magnetic model..... BGM version 2004

Magnetic date..... 20–Nov–2004

Magnetic dec (+E/W–).....

Magnetic dip..... –70.25 degrees

----- MWD survey Reference Criteria -----

Reference G..... 1000.09 mGal

Reference H..... 1221.99 HCNT

Reference Dip..... –70.25 degrees

Tolerance of G..... (+/–)

Tolerance of H..... (+/–) 6.00 HCNT

Tolerance of Dip..... (+/–) 0.45 degrees

----- Corrections -----

Magnetic dec (+E/W–)..... 10.48 degrees

Grid convergence (+E/W–): –0.46 degrees

Total az corr (+E/W–): 10.94 degrees

(Total az corr = magnetic dec – grid conv)

#	depth	angle	angle	length	depth	section	+N/S-	+E/W-	displ	Azim	(deg/	tool	Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(deg)	10m)	type	(deg)	
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	TIP	None	
2	1425.49	0.59	234.33	1425.49	1425.46	-4.28	-4.28	-5.96	7.34	234.33	0.00	MWD	None
3	1454.01	1.07	295.89	28.52	1453.98	-4.25	-4.25	-6.32	7.62	236.09	0.33	MWD	None
4	1487.29	0.97	129.33	33.28	1487.26	-4.29	-4.29	-6.38	7.69	236.08	0.61	MWD	None
5	1510.95	0.86	56.64	23.66	1510.92	-4.32	-4.32	-6.08	7.46	234.60	0.46	MWD	None
6	1539.34	0.80	303.78	28.39	1539.31	-4.09	-4.09	-6.07	7.32	235.99	0.49	MWD	None
7	1568.02	0.85	315.97	28.68	1567.98	-3.83	-3.83	-6.38	7.44	239.03	0.06	MWD	None
8	1595.59	0.53	308.57	27.57	1595.55	-3.60	-3.60	-6.62	7.54	241.45	0.12	MWD	None
9	1624.12	0.56	304.38	28.53	1624.08	-3.44	-3.44	-6.84	7.66	243.29	0.02	MWD	None
10	1653.18	0.34	298.89	29.06	1653.14	-3.32	-3.32	-7.03	7.78	244.73	0.08	MWD	None
11	1681.34	0.26	305.03	28.16	1681.30	-3.24	-3.24	-7.16	7.86	245.63	0.03	MWD	None
12	1709.52	0.31	319.56	28.18	1709.48	-3.15	-3.15	-7.26	7.91	246.56	0.03	MWD	None
13	1737.89	0.40	311.67	28.37	1737.85	-3.02	-3.02	-7.38	7.98	247.73	0.04	MWD	None
14	1766.33	0.35	299.78	28.44	1766.29	-2.92	-2.92	-7.53	8.08	248.85	0.03	MWD	None
15	1809.32	0.26	261.27	42.99	1809.28	-2.86	-2.86	-7.74	8.26	249.70	0.05	MWD	None
16	1849.73	0.23	231.00	40.41	1849.69	-2.93	-2.93	-7.90	8.42	249.65	0.03	MWD	None
17	1878.02	0.37	193.70	28.29	1877.98	-3.05	-3.05	-7.96	8.53	249.02	0.08	MWD	None
18	1908.10	0.34	223.98	30.08	1908.06	-3.21	-3.21	-8.05	8.67	248.24	0.06	MWD	None
19	1935.76	0.18	265.57	27.66	1935.72	-3.28	-3.28	-8.15	8.78	248.11	0.09	MWD	None
20	1963.97	0.17	252.91	28.21	1963.92	-3.29	-3.29	-8.23	8.87	248.21	0.01	MWD	None
21	1991.95	0.12	204.40	27.98	1991.90	-3.33	-3.33	-8.29	8.93	248.11	0.05	MWD	None
22	2020.87	0.20	231.00	28.92	2020.82	-3.39	-3.39	-8.34	9.00	247.88	0.04	MWD	None
23	2049.42	0.23	223.20	28.55	2049.37	-3.46	-3.46	-8.41	9.10	247.64	0.01	MWD	None
24	2077.78	0.26	214.74	28.36	2077.73	-3.56	-3.56	-8.49	9.21	247.27	0.02	MWD	None
25	2105.32	0.33	183.75	27.54	2105.27	-3.69	-3.69	-8.53	9.29	246.63	0.06	MWD	None
26	2134.71	0.29	176.46	29.39	2134.66	-3.85	-3.85	-8.53	9.36	245.74	0.02	MWD	None
27	2162.92	0.22	203.34	28.21	2162.87	-3.97	-3.97	-8.55	9.42	245.11	0.05	MWD	None
28	2192.60	0.14	180.37	29.68	2192.55	-4.06	-4.06	-8.57	9.48	244.68	0.04	MWD	None
29	2220.68	0.29	203.20	28.08	2220.63	-4.15	-4.15	-8.60	9.55	244.21	0.06	MWD	None
30	2248.46	0.15	220.05	27.78	2248.41	-4.25	-4.25	-8.65	9.64	243.85	0.05	MWD	None
31	2277.42	0.31	183.89	28.96	2277.37	-4.35	-4.35	-8.68	9.71	243.36	0.07	MWD	None
32	2306.21	0.34	216.07	28.79	2306.16	-4.50	-4.50	-8.74	9.83	242.74	0.06	MWD	None
33	2334.13	0.40	185.07	27.92	2334.08	-4.67	-4.67	-8.79	9.95	242.05	0.07	MWD	None
34	2361.66	0.37	221.08	27.53	2361.61	-4.83	-4.83	-8.86	10.09	241.42	0.09	MWD	None
35	2390.55	0.33	232.85	28.89	2390.50	-4.95	-4.95	-8.99	10.26	241.17	0.03	MWD	None
36	2419.57	0.32	200.20	29.02	2419.52	-5.08	-5.08	-9.08	10.40	240.81	0.06	MWD	None
37	2433.15	0.24	208.59	13.58	2433.10	-5.14	-5.14	-9.11	10.46	240.59	0.07	MWD	None
38	2476.28	0.50	232.35	43.13	2476.23	-5.33	-5.33	-9.30	10.72	240.19	0.07	MWD	None
39	2534.29	0.33	216.60	58.01	2534.24	-5.62	-5.62	-9.60	11.13	239.67	0.04	MWD	None
40	2649.13	0.37	195.11	114.84	2649.07	-6.24	-6.24	-9.90	11.70	237.76	0.01	MWD	None
41	2762.85	0.23	199.79	113.72	2762.79	-6.81	-6.81	-10.07	12.16	235.92	0.01	MWD	None
42	2878.16	0.23	190.81	115.31	2878.10	-7.26	-7.26	-10.19	12.51	234.55	0.00	MWD	None
43	2950.00	0.26	140.59	71.84	2949.94	-7.52	-7.52	-10.11	12.61	233.35	0.03	MWD	None
44	2979.00	0.26	140.59	29.00	2978.94	-7.63	-7.63	-10.03	12.60	232.76	0.00	Proj. to TD	

Company: **SANTOS – INPEX – UNOCAL****Schlumberger**Well: **Amrit-1**Field: **Exploration**Rig: **Jack Bates****VIC-P-52**State: **Victoria**

CDR – Resistivity
1:200 Measured Depth
Recorded Mode Data

