

Company: Anzon

Well: Basker 3

Field: Basker

Rig Ocean Patriot

Country: Australia

2-7/8" HSD Perforation

CCL Correalation Log 1:200

Suite4 ; Run2

Ocean Patriot

Basker

VIC/L26

Basker 3

Anzon

LOCATION			
VIC/L26	Elev.: K.B. 21.5 m		
Northing : 5759552.0m	G.L. -155.5 m		
Easting : 649256.8m	D.F. 21.5 m		
Permanent Datum:	Mean Sea Level		
Log Measured From:	Drill Floor		
Drilling Measured From:	Drill Floor		
State: Victoria	Max. Well Deviation 45.7 deg	Longitude 148 42' 24.94" E	Latitude 38 17' 58.97" S

Logging Date

4-Jul-2006

Run Number

2

Depth Driller

4086 m

Schlumberger Depth

4076 m

Bottom Log Interval

3547 m

Top Log Interval

3541 m

Casing Fluid Type

Well Fluid

Salinity

Density

Fluid Level

0 m

BIT/CASING/TUBING STRING

Bit Size

8.500 in

From

3520 m

To

4125 m

Casing/Tubing Size

4.500 in

Weight

12.6 lbm/ft

Grade

L-80

From

0 m

To

3555.4 m

Maximum Recorded Temperatures

Logger On Bottom

Time

Unit Number

Location

Recorded By

Witnessed By

		Run 1	Run 2	F
PVT DATA				
Oil Density				
Water Salinity				
Gas Gravity				
Bo				
Bw				
1/Bg				
Bubble Point Pressure				
Bubble Point Temperature				
Solution GOR				
Maximum Deviation		45.7 deg		
CEMENTING DATA				
Primary/Squeeze		Primary		
Casing String No				
Lead Cement Type				
Volume				
Density				
Water Loss				
Additives				
Tail Cement Type				
Volume				
Density				
Water Loss				
Additives				
Expected Cement Top				
Logging Date				
Run Number				
Depth Driller				
Schlumberger Depth				
Bottom Log Interval				
Top Log Interval				
Casing Fluid Type				
Salinity				
Density				
Fluid Level				
BIT/CASING/TUBING STRING				
Bit Size				
From				
To				
Casing/Tubing Size				
Weight				
Grade				
From				
To				
Maximum Recorded Temperatures				
Logger On Bottom		Time		
Unit Number		Location		
Recorded By				
Witnessed By				

Date Created: 7-JUL-2006 14:02:06

Logging Cable

Type:	2-32ZT
Serial Number:	24187
Length:	6499.86 M
<hr/>	
Conveyance Method:	Wireline
Rig Type:	Offshore Floater with WMC

Log Sequence:	Subsequent Log In the Well
Reference Log Name:	GR-CCL
Reference Log Run Number:	1
Reference Log Date:	4-Jul-2006


1. All Schlumberger depth control policy followed.
2. IDW used as a primary depth measurement.
3. Subsequent log in the well, Log correlated to GR-CCL dated: 4-Jul-2006
- 4.
- 5.
- 6.

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OS5:

6m of 2-7/8" HSD gun was run in order to perforate the tubing below the packer and regain the flow due to the malfunction of the fullbore Isolation Valve.

SURFACE EQUIPMENT	
SHM-EA	
DOWNHOLE EQUIPMENT	
MH-22 MH-22	6.94
CCL-L CCL-L	6.46
SHM_GUN GUN	6.00



All Depth as per driller’s depth



Correlation Pass
Scale 1:200

MAXIS Field Log

Company: Anzon Well: Basker 3

Output DLIS Files

DEFAULT	PERFO_066LUP	FN:110	PRODUCER	04-Jul-2006 17:24	3543.9 M	3463.7 M
---------	--------------	--------	----------	-------------------	----------	----------

OP System Version: 14C0-302

MCM


SHM_GUN	14C0-302	CCL-L	14C0-302
---------	----------	-------	----------


PIP SUMMARY

Time Mark Every 60 S

Casing Collars

Shifted Casing Collar Locator (SCCL)		Tension (TENS)	
-10	(----	10	10000
			(LBF)
			0





Casing Collar Locator (CCL)		DCMAIN Voltage (DCV)	
-19	(----	0	200
	1	(V)	
Raw Casing Collar Locator (RCCL)		DCMAIN Current (DCC)	
-3	(----	0	2000
	17	(MA)	
Shifted Casing Collar Locator (SCCL)		Tension (TENS)	
-10	(----	10	10000
		(LBF)	0

PIP SUMMARY

Time Mark Every 60 S

Casing Collars

Parameters		
DLIS Name	Description	Value
CCLD	CCL-L: Casing Collar Locator	12 IN
CCLT	CCL reset delay	0.3 V
	CCL Detection Level	

Format: PERFO_1 Vertical Scale: 1:200 Graphics File Created: 04-Jul-2006 17:24

OP System Version: 14C0-302

MCM

SHM_GUN 14C0-302 CCL-L 14C0-302

Output DLIS Files		
DEFAULT	PERFO_066LUP	FN:110 PRODUCER 04-Jul-2006 17:24

Company: Anzon Well: Basker 3

Output DLIS Files

DEFAULT PERFO_067LUP FN:111 PRODUCER 04-Jul-2006 17:37 3543.9 M 3466.2 M


OP System Version: 14C0-302
MCM


SHM_GUN 14C0-302 CCL-L 14C0-302

PIP SUMMARY

Casing Collars

Time Mark Every 60 S





	Shifted Casing Collar Locator (SCCL)	Tension (TENS)
-10	(----	1010000
		(LBF)
		0

PIP SUMMARY

Time Mark Every 60 S

Casing Collars

Parameters		
DLIS Name	Description	Value
CCL-L: Casing Collar Locator		
CCLD	CCL reset delay	12 IN
CCLT	CCL Detection Level	0.3 V

Format: PERFO_1

Vertical Scale: 1:200

Graphics File Created: 04-Jul-2006 17:37

OP System Version: 14C0-302

MCM

SHM_GUN

14C0-302

CCL-L

14C0-302

Output DLIS Files		
DEFAULT	PERFO_067LUP	FN:111 PRODUCER 04-Jul-2006 17:37

Company: Anzon

Well: Basker 3

Field: Basker

Rig: Ocean Patriot

Country: Australia

Schlumberger

2-7/8" HSD Perforation
CCL Correalation Log 1:200
Suite4 ; Run2