




PIP SUMMARY


Density Samples +
Gamma Ray Samples
Resistivity Samples
Neutron Samples +


Gamma Ray, Average, Real-Time, Computed Downhole (GRMA_DH_ECO_RT) (GAPI)	ARC Phase Shift Resistivity 40 inch at 2 MHz, Real-Time (P40H_ECO_RT) (OHMM)	Thermal Neutron Porosity, Average, Real-Time (TNPH_ECO_RT) (PU)	Equivalent Circulating Density, Real-Time (ECD_ECO_RT) (LB/G)
0 200	0.2 200	45 -15	10 15
Ultrasonic Caliper, Average Diameter, Real-Time, Computed Downhole (UCAV_DH_ECO_RT) (IN)	ARC Phase Shift Resistivity 28 inch at 2 MHz, Real-Time (P28H_ECO_RT) (OHMM)	Photoelectric Factor, Bottom, Real-Time, Computed Downhole (PEB_DH_ECO_RT) (G/C3)	Bulk Density Correction, Bottom, Real-Time Computed Downhole (DRHB_DH_ECO_RT) (G/C3)
6 16	0.2 200	0 10 -0.25 0.25	Downhole Annulus Pressure, Real Time, Computed Downhole (DHAP_DH_ECO_RT) (PSI)
ROP*5 (ROP5) (M/HR)	MWD Collar RPM (CRPM_RT) (RPM)	ARC Phase Shift Resistivity 16 inch at 2 MHz, Real-Time (P16H_ECO_RT) (OHMM)	Bulk Density, Bottom, Real-Time, Computed Downhole (ROBB_DH_ECO_RT) (G/C3)
200 0	0 400	0.2 200	1.85 2.85
			Downhole Annulus Temperature, Real Time, Computed Downhole (DHAT_DH_ECO_RT) (DEGC)
			0 200


























ROP*5 (ROP5) (M/HR)		MWD Collar RPM (CRPM_RT) (RPM)		ARC Phase Shift Resistivity 16 inch at 2 MHz, Real-Time (P16H_ECO_RT) (OHMM)		Bulk Density, Bottom, Real-Time, Computed Downhole (ROBB_DH_ECO_RT) (G/C3)		Downhole Annulus Temperature, Real Time, Computed Downhole (DHAT_ DH_ECO_RT) (DEGC)	
200	0	0	400	0.2	200	1.85	2.85	0	200
						Photoelectric	Bulk Density Correction		

Ultrasonic Caliper, Average Diameter, Real-Time, Computed Downhole (UCAV_DH_ECO_RT) 6 (IN) 16	ARC Phase Shift Resistivity 28 inch at 2 MHz, Real-Time (P28H_ECO_RT) 0.2 (OHMM) 200	Factor, Bottom, Real-Time, Computed Downhole (PEB_DH_ECO_RT) 0 (----- 10	Correction, Bottom, Real-Time Computed Downhole (DRHB_DH_ECO_RT) (G/C3) -0.25 0.25	Downhole Annulus Pressure, Real Time, Computed Downhole (DHAP_DH_ECO_RT) 0 (PSI) 6000
Gamma Ray, Average, Real-Time, Computed Downhole (GRMA_DH_ECO_RT) 0 (GAPI) 200	ARC Phase Shift Resistivity 40 inch at 2 MHz, Real-Time (P40H_ECO_RT) 0.2 (OHMM) 200	Thermal Neutron Porosity, Average, Real-Time (TNPH_ECO_RT) 45 (PU) -15	Equivalent Circulating Density, Real-Time (ECD_ECO_RT) 10 (LB/G) 15	
PIP SUMMARY Density Samples + Gamma Ray Samples Resistivity Samples Neutron Samples -				
IDEAL Version: ID11_0C_01 IDEAL				