


# Elver-1 EcoScope Service RT 200TVD


Format: ECO-SON-GVR\_200TVD\_RT


Vertical Scale: 1:200


Graphics File Created: 05-Jan-2009 08:37


<p><b>Ultrasonic Caliper, Average Diameter, Real-Time, Recomputed at Surface (UCAV_ECO_RT)</b></p> <p>8 (IN) 13</p>	<p><b>Shallow Button Resistivity, Real-Time (RES_BS_RT)</b></p> <p>0.2 (OHMM) 2000</p>			<p><b>Equivalent Circulating Density, Real-Time (ECD_ECO_RT)</b></p> <p>0 (G/C3) 2</p>
	<p><b>Deep Button Resistivity, Real-Time (RES_BD_RT)</b></p> <p>0.2 (OHMM) 2000</p>			
	<p><b>Ring Resistivity, Real-Time (RES_RING_RT)</b></p> <p>0.2 (OHMM) 2000</p>	<p><b>Photoelectric Factor, Bottom, Real-Time, Computed Downhole (PEB_DH_ECO_RT)</b></p> <p>0 (----) 10</p>	<p><b>Bulk Density Correction, Bottom, Real-Time Computed Downhole (DRHB_DH_ECO_RT)</b></p> <p>-0.25 (G/C3) 0.25</p>	<p><b>Delta-T Compressional, Real-Time (DTCO_RT)</b></p> <p>40 (US/F) 140</p>
	<p><b>ARC Phase Shift Resistivity 40 inch at 2 MHz, Real-Time (P40H_ECO_RT)</b></p> <p>0.2 (OHMM) 2000</p>	<p><b>Bulk Density, Bottom, Real-Time, Computed Downhole (ROBB_DH_ECO_RT)</b></p> <p>1.95 (G/C3) 2.95</p>	<p><b>Coherence at Compressional Peak, Real-Time (CHCO_RT)</b></p> <p>-9 (----) 1</p>	
<p><b>ROP*5 (ROP5)</b></p> <p>200 (M/HR) 0</p>	<p><b>MWD Collar RPM (CRPM_RT)</b></p> <p>0 400</p>	<p><b>ARC Phase Shift Resistivity 16 inch at 2 MHz, Real-Time (P16H_ECO_RT)</b></p> <p>0.2 (OHMM) 2000</p>	<p><b>Best Thermal Neutron Porosity, Average, Real-Time (BPHI_ECO_RT)</b></p> <p>45 (PU) -15</p>	<p><b>Downhole Annulus Temperature, Real Time, Computed Downhole (DHAT_DH_ECO_RT)</b></p> <p>0 (DEGC) 200</p>















2700  
TVD

2725  
TVD









<div>ROP*5 (ROP5)</div> <div>200 (M/HR) 0</div>	<div>MWD Collar RPM</div> <div>(CRPM_RT) (RPM)</div> <div>0 400</div>	<div>ARC Phase Shift Resistivity</div> <div>16 inch at 2 MHz, Real-Time</div> <div>(P16H_ECO_RT)</div> <div>0.2 (OHMM) 2000</div>	<div>Best Thermal Neutron</div> <div>Porosity, Average, Real-Time</div> <div>(BPHI_ECO_RT)</div> <div>45 (PU) -15</div>	<div>Downhole Annulus</div> <div>Temperature, Real Time,</div> <div>Computed Downhole (DHAT_</div> <div>DH_ECO_RT)</div> <div>0 (DEGC) 200</div>
<div>Gamma Ray, Average,</div> <div>Real-Time (GRMA_ECO_RT)</div> <div>0 (GAPI) 200</div>		<div>ARC Phase Shift Resistivity</div> <div>40 inch at 2 MHz, Real-Time</div> <div>(P40H_ECO_RT)</div> <div>0.2 (OHMM) 2000</div>	<div>Bulk Density, Bottom,</div> <div>Real-Time, Computed</div> <div>Downhole (ROBB_DH_ECO_</div> <div>RT)</div> <div>1.95 (G/C3) 2.95</div>	<div>Coherence at Compressional</div> <div>Peak, Real-Time (CHCO_RT)</div> <div>-9 (----) 1</div>
<div>Ultrasonic Caliper, Average</div> <div>Diameter, Real-Time,</div> <div>Recomputed at Surface</div> <div>(UCAV_ECO_RT)</div> <div>8 (IN) 13</div>		<div>Ring Resistivity, Real-Time</div> <div>(RES_RING_RT)</div> <div>0.2 (OHMM) 2000</div>	<div>Photoelectric</div> <div>Factor,</div> <div>Bottom,</div> <div>Real-Time,</div> <div>Computed</div> <div>Downhole</div> <div>(PEB_DH_</div> <div>ECO_RT)</div> <div>0 (----) 10</div> <div>Bulk Density</div> <div>Correction,</div> <div>Bottom,</div> <div>Real-Time</div> <div>Computed</div> <div>Downhole</div> <div>(DRHB_DH_</div> <div>ECO_RT)</div> <div>-0.25 (G/C3) 0.25</div>	<div>Delta-T Compressional,</div> <div>Real-Time (DTCO_RT)</div> <div>40 (US/F) 140</div>
		<div>Deep Button Resistivity,</div> <div>Real-Time (RES_BD_RT)</div> <div>0.2 (OHMM) 2000</div>		<div>Equivalent Circulating</div> <div>Density, Real-Time (ECD_</div> <div>ECO_RT)</div> <div>0 (G/C3) 2</div>



		Shallow Button Resistivity, Real-Time (RES_BS_RT)	
		0.2 (OHMM)	2000
IDEAL Version: ID13_0C_08			
IDF			
ECO6	id13_0c_02	MWD_10	id13_0c_02
RAB	id13_0c_02	SON675	id13_0c_02