



PRESSURE EVALUATION LOG



WELL : TREFOIL-2

FROM (m): 2510

TO (m): 2540

SCALE: 1/ 500

Country : AUSTRALIA
 Region : TASMANIA
 Field : TREFOIL
 Permit : T/18P
 Well Type : APPRAISAL
 Rig Name : KAN TAN 4

POSITION
 Latitude : 39 53' 07.93" S
 Longitude : 145 22' 14.62" E
 X (m) : 360690.389
 Y (m) : 5583676.588
 RT-Sealevel (m MSL) : 26
 RT-Seabed (m) : 95

CASING SHOE SIZE / DEPTH
 762mm (30") at (m MDRT) : 153.00
 340mm (13 3/8") at (m MDRT) : 930.00
 245mm (9 5/8") at (m MDRT) : 2520.00

Spud Date : 06-10-2009
 Total Depth Date :
 Total Depth (m MDRT) :
 Total Depth (m TVSS) :
 Status :

ABBREVIATIONS

MW MUD WEIGHT	NB NEW BIT
FV FUNNEL VISCOSITY	RR RERUN BIT
PV PLASTIC VISCOSITY	CB CORE BIT
YP YIELD POINT	WOB WEIGHT ON BIT
FC FILTER CAKE	RPM REVS PER MINUTE
SOL SOLIDS	FLC FLOW CHECK
CR CIRCULATE RETURNS	WL FILTRATE
SD SAND - %	PR POOR RETURNS
S SALINITY - PPM	NR NO RETURNS
RM MUD RESISTIVITY	BG BACKGROUND GAS
RMF MUD FILTRATE	TG TRIP GAS
C CARBIDE TEST	STG SHORT TRIP GAS
LAT LOGGED AFTER TRIP	CG CONNECTION GAS
DS DEVIATION SURVEY	SG SWAB GAS
	SVG SURVEY GAS

LITHOLOGY LEGEND

Dolomite	Claystone	Argil Siltstone	Calcareous
Calcurudite	Siltstone	Sandy Siltstone	Dolomitic
Calcarenite	Sandstone	Calcareous Siltstone	Fossils
Calcsiltite	Coal	Argil Sandstone	Foraminiferae
Calclutite	Intrusive Volcanics	Calcareous Sandstone	Carbonaceous
Sandy Claystone	Volcaniclastics	Dolomitic Sandstone	Chert
Silty Claystone	Tuff	Silty Sandstone	Pyrite
Calcareous Claystone	Cement		Glaucinite
Argil Calclutite			Mica

ENGINEERING

Test
FIT or LOT
Mud loss
Mud gain
Deviation survey
Core
Shoe
Calciometry



