



DIRECTIONAL SURVEY REPORT

Origin Energy Resources Ltd

Trefoll-2

Trefoll

Tasmania

Australia

AU-FE-000671414

UTM Zone 55S, GDA 1994

RT-MSL = 26.0m

Measured Depth (metres)	Inclination (degrees)	Direction (degrees)	Vertical Depth (metres)	Latitude (metres)	Departure (metres)	Vertical Section (metres)	Dogleg (deg/30m)
0.000	0.00	0.00	0.000	0.000 N	0.000 E	0.000	TIE-IN
95.000	0.00	0.00	95.000	0.000 N	0.000 E	0.000	0.00
204.920	0.58	282.17	204.918	0.117 N	0.544 W	-0.080	0.16
289.500	0.55	277.88	289.494	0.263 N	1.363 W	-0.170	0.02
376.490	0.32	238.01	376.482	0.191 N	1.982 W	-0.057	0.13
435.080	0.35	232.40	435.071	0.006 S	2.265 W	0.159	0.02
521.950	0.72	199.02	521.937	0.684 S	2.654 W	0.861	0.16
547.830	0.73	193.58	547.815	0.996 S	2.745 W	1.179	0.08
579.000	0.69	195.91	578.982	1.367 S	2.842 W	1.556	0.05
665.440	0.36	203.20	665.419	2.115 S	3.091 W	2.319	0.12
782.280	0.67	192.10	782.254	3.126 S	3.381 W	3.347	0.08
812.120	0.66	196.82	812.092	3.462 S	3.467 W	3.689	0.06
868.190	0.30	224.95	868.160	3.877 S	3.666 W	4.116	0.22
896.770	1.03	195.99	896.738	4.177 S	3.790 W	4.424	0.81
925.970	0.71	183.94	925.934	4.608 S	3.874 W	4.859	0.38
952.440	0.80	188.49	952.402	4.953 S	3.913 W	5.206	0.13
981.350	0.74	192.99	981.309	5.336 S	3.985 W	5.593	0.09
1010.200	0.83	198.72	1010.157	5.716 S	4.094 W	5.979	0.12
1067.210	0.87	190.96	1067.160	6.533 S	4.309 W	6.809	0.06
1095.870	0.84	194.49	1095.817	6.950 S	4.403 W	7.232	0.07
1153.510	1.11	191.81	1153.449	7.905 S	4.623 W	8.199	0.14
1182.360	1.27	187.06	1182.293	8.496 S	4.719 W	8.796	0.20
1211.300	0.97	182.63	1211.227	9.059 S	4.770 W	9.360	0.33
1240.320	1.00	184.76	1240.243	9.555 S	4.802 W	9.857	0.05
1269.440	0.96	179.68	1269.359	10.052 S	4.822 W	10.354	0.10
1298.710	1.13	178.12	1298.624	10.585 S	4.811 W	10.885	0.17
1327.950	1.27	184.82	1327.857	11.194 S	4.829 W	11.495	0.20
1357.120	1.31	184.97	1357.020	11.849 S	4.885 W	12.151	0.04
1385.950	1.43	187.08	1385.842	12.534 S	4.958 W	12.840	0.13
1414.800	1.33	186.15	1414.684	13.223 S	5.038 W	13.533	0.11
1443.260	1.42	189.23	1443.135	13.898 S	5.129 W	14.213	0.12
1471.760	1.41	188.55	1471.627	14.593 S	5.238 W	14.914	0.02
1500.560	1.44	186.77	1500.418	15.304 S	5.334 W	15.629	0.06
1529.740	1.02	177.87	1529.591	15.928 S	5.367 W	16.254	0.48
1559.000	1.11	183.32	1558.846	16.472 S	5.374 W	16.797	0.14
1588.150	1.05	181.86	1587.991	17.022 S	5.399 W	17.348	0.07
1617.270	1.14	175.03	1617.105	17.577 S	5.383 W	17.901	0.16
1646.320	1.17	184.16	1646.149	18.160 S	5.379 W	18.481	0.19
1675.150	1.31	182.99	1674.973	18.781 S	5.418 W	19.104	0.15
1703.610	1.02	183.90	1703.427	19.359 S	5.452 W	19.683	0.30
1731.980	1.12	176.27	1731.792	19.888 S	5.451 W	20.211	0.18
1760.710	1.20	179.48	1760.516	20.468 S	5.430 W	20.788	0.11
1790.080	1.13	181.99	1789.880	21.064 S	5.437 W	21.383	0.09
1819.450	1.17	182.73	1819.244	21.652 S	5.462 W	21.972	0.05
1848.520	1.17	190.32	1848.308	22.242 S	5.529 W	22.564	0.16

<i>Measured Depth (metres)</i>	<i>Inclination (degrees)</i>	<i>Direction (degrees)</i>	<i>Vertical Depth (metres)</i>	<i>Latitude (metres)</i>	<i>Departure (metres)</i>	<i>Vertical Section (metres)</i>	<i>Dogleg (deg/30m)</i>
1877.800	1.13	190.92	1877.582	22.820 S	5.638 W	23.149	0.04
1906.650	1.23	192.98	1906.426	23.403 S	5.761 W	23.739	0.12
1934.670	1.08	194.42	1934.440	23.953 S	5.895 W	24.296	0.17
1963.220	0.48	64.50	1962.988	24.161 S	5.853 W	24.501	1.51
1992.330	0.56	59.70	1992.097	24.036 S	5.620 W	24.361	0.09
2021.460	0.59	61.98	2021.226	23.895 S	5.366 W	24.203	0.04
2050.740	0.64	78.76	2050.504	23.793 S	5.074 W	24.081	0.19
2080.190	0.61	81.26	2079.953	23.737 S	4.760 W	24.005	0.04
2102.200	0.68	80.27	2101.961	23.697 S	4.515 W	23.948	0.10
2138.040	0.69	75.36	2137.799	23.607 S	4.096 W	23.830	0.05
2195.190	0.63	82.85	2194.945	23.481 S	3.452 W	23.660	0.06
2253.190	0.62	89.29	2252.941	23.437 S	2.823 W	23.574	0.04
2281.350	0.84	88.95	2281.099	23.432 S	2.465 W	23.545	0.24
2310.290	0.91	90.74	2310.036	23.431 S	2.023 W	23.514	0.08
2339.670	0.80	84.68	2339.412	23.415 S	1.585 W	23.468	0.15

CALCULATION BASED ON MINIMUM CURVATURE METHOD

**SURVEY COORDINATES RELATIVE TO WELL SYSTEM REFERENCE POINT
TVD VALUES GIVEN RELATIVE TO DRILLING MEASUREMENT POINT**

**VERTICAL SECTION RELATIVE TO WELL HEAD
VERTICAL SECTION IS COMPUTED ALONG A CLOSURE OF 183.87 DEGREES (GRID)
A TOTAL CORRECTION OF 11.45 DEG FROM MAGNETIC NORTH TO GRID NORTH HAS BEEN APPLIED**

**HORIZONTAL DISPLACEMENT IS RELATIVE TO THE WELL HEAD.
HORIZONTAL DISPLACEMENT(CLOSURE) AT 2339.670 METRES
IS 23.468 METRES ALONG 183.87 DEGREES (GRID)**