


SPP: 149 - 335 psi

WOB: 1.4 - 8.9 kbf

RPM: 80 - 100

SPP: 117 - 432 psi





MARL: lt gry-m gry, m gn gry-m brn gry, com-abd foss frags incl bry, shell frags, forams, v sft, v disp, n fiss

CALCARENITE: lt gry-lt brn gry, f-m gr, wk calc cmt, abd foss frag incl bry, forams, shell frags, mod argill, tr-com vf-f qtz gr, rr m gn glauc, p vis por, n fluor

CALCARENITE: lt gry-lt brn gry, f-m gr, wk calc cmt, abd foss frags incl bry, forams, shell frags, mod argill, tr-com v f-f qtz gr, rr m gn glauc, p vis por, n fluor

CALCARENITE: lt gry-lt brn gry, f-m gr, wk calc cmt, abd foss frags incl bry, forams, shell frags, mod argill, tr-com v f-f qtz gr, rr m gn glauc, p vis por, n fluor



260
270
280
290
300
310
320
330
340
350
360
370
380
390
400


CALCARENITE: lt gry-lt brn gry, rr lt gn gry, f-m gr, wk calc cmt, abd foss frags incl bry, forams, shell frags, sli argill, rr v f-f qtz gr, rr m gn glauc, p vis por, n fluor

244mm (9-5/8") casing shoe at 299mMD

CALCARENITE: lt gry-lt brn gry, rr lt gn gry, f-m gr, wk calc cmt, abd bry, forams, shell frags, mod argill, rr-com v f-f qtz gr, tr gn glauc gn glauc, p vis por, n fluor


CALCARENITE: lt gry-lt brn gry, rr lt gn gry, f-m gr, wk calc cmt, abd bry, forams, shell frags, mod argill, rr v f-f qtz gr, tr gn glauc, p vis por, n fluor

WOB: 1.4 - 12.0 klf
RPM: 80 - 120
SPP: 465 - 598 psi



410
420
430
440
450
460
470
480
490
500
510
520
530
540
550

WOB: 1.4 - 12.0 klf
RPM: 80 - 120
SPP: 311 - 798 psi




CALCARENITE: off wh-lt m gry-lt brn gry, f-m gr, wk-mod strong calc cmt, abd bry, forams, shell frags, mod argill, rr v f-f qtz gr, tr gn glauc, p vis por, n fluor

CALCARENITE: off wh-lt m gry-lt brn gry, f-m gr, wk-mod strong calc cmt, abd bry, forams, shell frags, n-mod argill, rr v f-f qtz gr, tr gn glauc, p vis por, n fluor

Survey at 472m
N25degsE
2 degs

CALCARENITE: off wh-lt m gry-lt brn gry, f-m gr, wk-mod strong calc cmt, abd bry, forams, shell frags, mod argill, rr v f-f qtz gr, tr gn glauc, p vis por, n fluor



CALCARENITE: off wh-lt m gry-lt brn gry, f-m gr, wk-strong calc cmt, com bry, tr echinoid spines, forams & shell frags, n-mod argill, rr v f-f qtz gr, tr-com gn glauc, fri, v p vis

MARL: m gry-m brn, v calc grd to CLCLT, tr foss frags, sft, stky, n fiss


CALCILUTITE: lt gry-m gry-m lt gry, sli-v argill, grd i/p to MRL, oft v f calcerenitic, grd CLCAR, tr foss frags, sft, stky, n fiss

MARL: v lt-m gry-gn gry-brn gry, v calc grd i/p to off wh argil calc CLCLT tr foss frags, sft, stky, n fiss

Survey at 687m
 N86degsE
 2 degs

WOB: 5.0 - 14.0 klb
RPM: 80 - 128
SPP: 278 - 978 psi

WOB: 3.0 - 15.0 klb
RPM: 50 - 116
SPP: 420 - 940 psi



Run Carbide at 699m
MW: 9.0ppg Vis: 41
Average hole size: 8.90inch


MARL: v lt-m gry-gn gry-brn gry, occ
lt-m brn gry, mod-v calc, tr foss frags,
sft, stky, n fiss


MARL: lt-m gn gry-lt m gry, mod-v
calc, tr foss frags, sft, stky, n fiss

MARL: lt-m gn gry-lt m gry, mod-v
calc, tr foss frags, sft, tr glauc, stky, n
fiss

COAL: m brn-blk, irreg-blky frac, ea
lstr, sli-dom v argil, frm-mod hd

SANDSTONE: lt-m brn, vf-m gr, dom
vf, ang-sbrnd, p-mod srtd, v wk sil
cmt, abd lt brn argil & slt mtrx,
quartzose w/cr-opq qtz gr, tr crs clr
mic flks, tr blk c detr, rr pyr, fri, v p inf
por, n fluor





CLAYSTONE: lt-dk brn, dom m brn, sl
 slty and f aren i/p, v sli-mod carb, tr
 blk coal flk, tr amber, sft, v disp, n fiss

SANDSTONE: lt brn gry, vf-v crs, dom
 m-crs, sbang-rnd, p-mod srtd, wk sil
 cmt, tr-com lt brn argill & slt mtrx,
 quartzose w/cr-op qtz gr w/mnr brn
 stn, tr gr gry & blk cht lit, tr blk c detr,
 fri, gd-v gd inf por, n fluor

CLAYSTONE: lt-dk brn, dom m brn, sl
 slty and f aren i/p, v sli-mod carb, tr
 blk coal flk, tr amb, sft, v disp, n fiss

Survey at 917m
 N50degsE
 3 degs

SANDSTONE: lt brn gry, vf-v crs, dom
 m-crs, sbang-rnd, p srtd, wk sil cmt,
 tr-com lt brn argill & slt mtrx,
 quartzose w/cr-op qtz gr w/mnr brn
 stn, tr gr gry & blk cht lit, tr blk c detr,
 fri, gd-v gd inf por, n fluor

CLAYSTONE: m-dk brn, sli slty & f
 aren i/p, mod-v carb, tr blk c flks, sft,
 v disp, n fiss

COAL: m brn-blk, irr-blky frac, ea lstr,
 sli-dom v argill, tr amb, frm-mod hd

WOB: 0.5 - 11.9 klf
RPM: 14 - 141
SPP: 364 - 1233 psi

WOB: 0.5 - 9.1 klf
RPM: 31 - 121
SPP: 287 - 1234 psi

1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140

CLAYSTONE: m-dk brn, sli slty & f
aren, mod-v carb, tr blk c flks, sft, v
disp, n fiss

COAL: m brn-blk, irr-blky frac, ea lstr,
sli-dom v argill, tr amb, frm-mod hd


COAL: m brn-blk, irr-blky frac, ea lstr,
sli-dom v argill, tr amb, frm-mod hd

Survey at 1079m
N88degsE
3 degs

SANDSTONE: lt brn gry, vf-pbl, dom
m-crs, sbang-rnd, v p srted, wk sil cmt,
com lt brn argill & slt mtrx, qtz
w/cr-op quartzose gr w/mnr or brn
stn, tr gn gry & blk cht lith, tr-com blk
c detr, fri, g inf por, n fluor

COAL: m brn-dom blk, irr-blky frac,
ea-sbvit lstr, sli-v argill, tr amb, mod
hd. The Coal has no natural fluor but
gives a wk dull lt yel rn crsh cut fluor.
The amb has mod bri sol lt-m yel
natural fluor and gives a wk v slo
strmg lt yell cut fluor

SANDSTONE: v lt gry-lt brn gy, v f-gt,
dom m-crs, ang-sbrnd, v p srted, wk sil
cmt, com wh-lt brn argill & slt mtrx,
quartzose w/cr-op qtz gr, tr gn gry
& blk cht lith, tr-com blk c detr, fri, gd
inf por, no fluor




CLAYSTONE: wh-m brn, v slit & v aren i/p, kao i/p, sli-mod carb, tr blk c flks, tr micrmic, frm, v disp & washing f/spl, n fiss

SANDSTONE: v lt gry-lt brn gy, v f-v crs, dom m-crs, ang-sbrnd, v p srtd, mod sil cmt, com-abd wh-lt brn argill & slit mtrx, quartzose w/clr-op qtz gr, rr gn & blk cht lith, tr blk c detr, fri-mod hd, fr-gd inf por, no fluor

CLAYSTONE: off wh-m brn, v slit & v aren, v kao i/p, sli carb, tr blk c flks, tr micrmic, frm-mod hd, v disp, n fiss

COAL: v dk brn-dom blk, blk-y-sbconch frac, ea-sli sbvit lstr, sli-m argill, mod hd.



CLAYSTONE: off wh-m brn, v slt & v f aren, v kao i/p, sli carb, tr blk c flks, tr micrmic, rr pyr, frm-mod hd, v disp, n fiss

SANDSTONE: v lt gry-lt brn gy, v f-gt, dom m, ang-sbrnd, v p strd, mod sil cmt, abd off wh-lt brn argill & slt mtrx, quartzose w/clr-op qtz gr, rr gn & blk cht lith, tr blk c detr, tr pyr, mod hd, fr inf por, no fluor

CLAYSTONE: off wh-m brn, dom lt brn, v slt & v f aren, v kao i/p, sli carb, tr blk c flks, tr micrmic, tr pyr, mod hd, v disp, sli sbfiss

CLAYSTONE: off wh-m gn gry-m brn gry, mod slty, tr vf off wh alt fspr gr, tr brn-blk carb spks, tr micmic, sft, v disp, sli sbfiss

FORMATION EVALUATION LOG

RATE OF PENETRATION		INTERPRETED LITHOLOGY	MD meters 1:500	LITHOLOGY	CORE	OIL SHOWS	TOTAL GAS		CHROMATOGRAPH					REMARKS
ROP (0-100m/hr)							%		Methane ppm					
100	90	80	70	60	50	40	30	20	10	1	Methane ppm	10000		
Backup ROP (100-200m/hr)		%						1	Ethane ppm	10000				
200	190	180	170	160	150	140	130	120	110	1	Propane ppm	10000		
WOB (klb)		%						1	iso-Butane ppm	10000				
5	10	15	20	25	30	35	40	45	50	1	n-Butane ppm	10000		
		%						1	iso-Pentane ppm	10000				
		%						1	n-Pentane ppm	10000				
		%						1			10	100	1000	10000